

HTTPBis – IETF90

HTTP Connect – Tunnel Protocol For WebRTC

draft-hutton-httpbis-connect-protocol-00

A. Hutton, J. Uberti, M. Thomson

RTCWEB Requirements.

- draft-ietf-rtcweb-use-cases-and-requirements
 - F21 The browser must be able to send streams and data to a peer in the presence of Firewalls that only allows traffic via a HTTP Proxy, when Firewall policy allows WebRTC traffic.
 - × **draft-ietf-rtcweb-transports:** Further discussion of the interaction of RTCWEB with firewalls is contained in [I-D.hutton-rtcweb-nat-firewall-considerations]. This document makes no requirements on interacting with HTTP proxies or HTTP proxy configuration methods.
NOTE IN DRAFT: This may be added.

draft-hutton-httpbis-connect-protocol-00 - Background

- RTCWEB Interim meeting – May 2014
 - Discussed the issue of WebRTC browsers using HTTP Connect for TURN and ICE-TCP traffic and how to document this in draft-ietf-rtcweb-transports.
 - Consensus was to ensure that the HTTP traffic is marked appropriately to allow the proxy to know that WebRTC traffic is being sent over it, allowing it to drop/log said traffic if desired. – Hence this draft.

draft-hutton-httpbis-connect-protocol-00 - Background

- **draft-ietf-tls-applayerprotoneg.**
 - This document describes a Transport Layer Security (TLS) extension for application layer protocol negotiation within the TLS handshake
- **draft-thomson-rtcweb-alpn-00 (Hopefully adopted by now).**
 - Web Real-Time Communications (WebRTC) uses Datagram Transport Layer Security (DTLS) to secure all peer-to-peer communications. Identifying WebRTC protocol usage with Application Layer Protocol Negotiation (ALPN) enables an endpoint to positively identify WebRTC uses and distinguish them from other DTLS uses.
- **draft-hutton-httpbis-connect-protocol-00**
 - Provides HTTP Proxies with an indication that WebRTC related real-time media is to be included in the tunnel this specification defines the Tunnel-Protocol Request header field and associated labels for use within a HTTP Connect request.
 - This allows the proxy to identify the protocol being used in the tunnel as early as possible therefore enabling the proxy to make informed policy decisions.

draft-hutton-httpbis-connect-protocol-00

Overview

- Tunnel-Protocol HTTP Request Header Field
 - The client MAY include the Tunnel-Protocol Request Header field in a HTTP Connect request to indicate the application layer protocol within the tunnel.
- Header Field Values
 - Valid values for the protocol field are taken from the registry established in [[I-D.ietf-tls-applayerprotoneg](#)]. For the purposes of WebRTC, the values "webrtc" [[I-D.thomson-rtcweb-alpn](#)] and "turn" [[I-D.patil-tram-alpn](#)] are applicable.
- The name 'Tunnel-Protocol' is open to debate. Alternatives include "Tunneled-Application".
- We need to determine which ALPN tags are valid. For instance, "turn" might not be appropriate (it's not strictly an application).
- Example:

```
CONNECT 198.51.100.0:8999 HTTP/1.1
Host: 198.51.100.0:8999
Tunnel-Protocol: webrtc
```

draft-hutton-httpbis-connect-protocol-00

Next Steps

Adopt & Bash

Bash & Adopt

Something else.