Core Protocol Spec

draft-hamilton-quic-transport-protocol-01

Draft Outline

- Overview of QUIC features
- Packet Types and Formats
- Life of a Connection
 - Describes Version Negotiation and Crypto handshake requirements
- Frame Types and Formats
- Packetization and Reliability
- Streams: QUIC's Data Structuring Abstraction
- Flow Control
- Error Codes
- Security Considerations

Current State

Draft documents QUIC version Q036, which is tethered to the current Google deployment.

- "Diversification Nonce" is for QUIC crypto; not useful with TLS 1.3
- Timestamps are in a home-grown floating-point format
- Numbers are little-endian

If adopted, based on wg discussion and consensus, the draft will move away from Q036 design.

Discussions on mailing list so far

- Packet number vs. Sequence number
 - Use "Packet number", since TCP seq num has different semantics.

Discussions on mailing list so far

- Packet number vs. Sequence number
 - Use "Packet number", since TCP seq num has different semantics.

Endian-ness

- Q034 uses little-endian numbers, since Chrome runs only on little-endian machines.
- Also, there are about 21 big-endian machines left in the world.
- However, IETF uses big-endian for everything.
- QUIC will interact with HTTP/2 and with TLS, both of which use big-endian.

- QUIC uses 32-bit version.
 - Q036 is represented by the ASCII values of the four characters
 That is, "Q036" is 0x 51 30 33 38

- QUIC uses 32-bit version.
 - Q036 is represented by the ASCII values of the four characters
 That is, "Q036" is 0x 51 30 33 38
- Martin's strawman proposal:
 - 0xffff0000-0xffffffff for experimentation
 - 0xffff5100 and up as corresponding to versions of the draft
 - (Also, ALPN label tracks QUIC version referred to by HTTP mapping doc)

- Jana's mod to Martin's strawman:
 - Reserve 0x0000001 to 0x0000ffff (16K versions) for standards
 - \bullet 0x00000001 0x0000fff (4096 versions) to QUIC standards
 - $0x00001000 0x0000ffff (\sim 60K \text{ versions})$ for draft versions
 - 0x00010000 upwards (~4 billion versions) for experimentation
 - Conveniently, "Q036" falls in this space

- Jana's mod to Martin's strawman:
 - Reserve 0x0000001 to 0x0000ffff (16K versions) for standards
 - \blacksquare 0x00000001 0x0000fff (4096 versions) to QUIC standards
 - $0x00001000 0x0000ffff (\sim 60K \text{ versions})$ for draft versions
 - 0x00010000 upwards (~4 billion versions) for experimentation
 - Conveniently, "Q036" falls in this space
- Suggestion: Wiki page for experimental versions
 - Is self-registration adequate?

Other topics for review and discussion

- Transport params format and exhaustive listing
 - List and discuss semantics of connection options
- Clean up and group error codes (editorial)
- Remove diversification nonce (editorial)

Other topics for review and discussion

- Transport params format and exhaustive listing
 - List and discuss semantics of connection options
- Clean up and group error codes (editorial)
- Remove diversification nonce (editorial)
- Reconsider ACK timestamp format
 - Currently a home-grown floating-point wire format
- Connection ID is currently client-chosen
- Addressing: Connection ID and relationship to 5-tuple
 - Relevance to QUIC mobility

Other topics for review and discussion

- Transport params format and exhaustive listing
 - List and discuss semantics of connection options
- Clean up and group error codes (editorial)
- Remove diversification nonce (editorial)
- Reconsider ACK timestamp format
 - Currently a home-grown floating-point wire format
- Extensibility: Transport feature negotiation vs. version negotiation
- Connection ID is currently client-chosen
- Addressing: Connection ID and relationship to 5-tuple
 - Relevance to QUIC mobility
- Packet size / Path MTU recommendation
- Functional API, ala RFC 793 (?)