

# Bio-inspired and and behaviour-based robotics (BBR)

Autonomous robots, TME290

---

Ola Benderius

`ola.benderius@chalmers.se`

Applied artificial intelligence

Vehicle engineering and autonomous systems

Mechanics and maritime sciences

Chalmers

# Introduction

---

# Moving around is not everything

- So far, we have looked at basic perception and navigation behaviour
- We know how to navigate in the local frame, and avoid obstacles
- We know how to plan a path and how to follow it

# Moving around is not everything

- So far, we have looked at basic perception and navigation behaviour
- We know how to navigate in the local frame, and avoid obstacles
- We know how to plan a path and how to follow it

What if the robot needs to do different things, and autonomously select what task to do?

- An **intelligent machine** has a *goal to achieve* and must be able to interact with its environment *autonomously*, i.e. without continuous human guidance

- An **intelligent machine** has a *goal to achieve* and must be able to interact with its environment *autonomously*, i.e. without continuous human guidance
- In any non-trivial robotics application, the robot must be capable of doing several things, in parallel or sequentially

- An **intelligent machine** has a *goal to achieve* and must be able to interact with its environment *autonomously*, i.e. without continuous human guidance
- In any non-trivial robotics application, the robot must be capable of doing several things, in parallel or sequentially
- In most real-world applications, *rapid reactions* and *adaptive behaviours* are needed

# Machine intelligence

---



# Machine intelligence

Main approaches to **machine intelligence**, or AI:

# Machine intelligence

Main approaches to **machine intelligence**, or AI:

- Classical artificial intelligence (AI)

Main approaches to **machine intelligence**, or AI:

- Classical artificial intelligence (AI)
  - 1950s–
  - Focused on high-level (human) reasoning

Main approaches to **machine intelligence**, or AI:

- Classical artificial intelligence (AI)
  - 1950s–
  - Focused on high-level (human) reasoning
- Behaviour-based robotics (BBR)


Main approaches to **machine intelligence**, or AI:

- Classical artificial intelligence (AI)
  - 1950s–
  - Focused on high-level (human) reasoning
- Behaviour-based robotics (BBR)
  - 1980s–
  - Focused on basic survival-related behaviours
  - Strongly influenced by (the brains of) relatively simple biological organisms (e.g. insects)

Main approaches to **machine intelligence**, or AI:


- Classical artificial intelligence (AI)
  - 1950s–
  - Focused on high-level (human) reasoning
- Behaviour-based robotics (BBR)
  - 1980s–
  - Focused on basic survival-related behaviours
  - Strongly influenced by (the brains of) relatively simple biological organisms (e.g. insects)
- In the framework of **behaviour-based robotics** (BBR) one normally defines a set of **isolated robotic behaviours** (or brain processes)

# Data flow in classic AI



- In **classical AI** intelligence is decomposed into functional modules

# Data flow in behaviour-based AI



- In **nouvelle AI**, intelligence is built from a set of *basic behaviours*, from which *intelligent behaviour* is thought to emerge: **BBR**



## **Biological background**

---

# Biological background

The **behaviour-based** approach to robotics is *strongly inspired* by the studies of **animal behaviour**

# Biological background

The **behaviour-based** approach to robotics is *strongly inspired* by the studies of **animal behaviour**

- Animals are *experts* at survival and reproduction, in their specific environments

# Biological background

The **behaviour-based** approach to robotics is *strongly inspired* by the studies of **animal behaviour**

- Animals are *experts* at survival and reproduction, in their specific environments
- They are able to **learn** and **adapt** to changes in their living conditions (i.e. adjust their behaviours)

# Biological background

The **behaviour-based** approach to robotics is *strongly inspired* by the studies of **animal behaviour**

- Animals are *experts* at survival and reproduction, in their specific environments
- They are able to **learn** and **adapt** to changes in their living conditions (i.e. adjust their behaviours)
- They are experts in **allocating time**: Eating, drinking, sleeping, foraging, mating etc.

# Biological background

The **behaviour-based** approach to robotics is *strongly inspired* by the studies of **animal behaviour**

- Animals are *experts* at survival and reproduction, in their specific environments
- They are able to **learn** and **adapt** to changes in their living conditions (i.e. adjust their behaviours)
- They are experts in **allocating time**: Eating, drinking, sleeping, foraging, mating etc.
- The overall goal is primarily survival, and secondarily self-fulfilment

# Biological background

The **behaviour-based** approach to robotics is *strongly inspired* by the studies of **animal behaviour**

- Animals are *experts* at survival and reproduction, in their specific environments
- They are able to **learn** and **adapt** to changes in their living conditions (i.e. adjust their behaviours)
- They are experts in **allocating time**: Eating, drinking, sleeping, foraging, mating etc.
- The overall goal is primarily survival, and secondarily self-fulfilment
- Thus, **biologically inspired** methods are logical

- **Ethology:** The study of animals in their *natural* environment



- **Ethology:** The study of animals in their *natural* environment
- **Comparative psychology:** Perform experiments in controlled environments (a lab)

- **Ethology:** The study of animals in their *natural* environment
- **Comparative psychology:** Perform experiments in controlled environments (a lab)
- **Phenomenological model** is a common approach:  
Describes the behaviour using a simple set of equations, i.e. without taking the detailed neural activities into account

# Behavioural layers of action

Four different kinds, or levels, of behaviours:

- Reflexes
- Taxes and kineses
- Fixed action patterns
- Complex (adaptive) behaviours

Generally good starting-points when designing AI in robotics.

- Automatic, *involuntary* reactions to external stimuli (e.g. the withdrawal reflex)

- Automatic, *involuntary* reactions to external stimuli (e.g. the withdrawal reflex)
- However, *not* completely stereotyped:

- Automatic, *involuntary* reactions to external stimuli (e.g. the withdrawal reflex)
- However, *not* completely stereotyped:
  - **Warm-up:** Maximum intensity reached only after a while  
Example: scratch reflex in dogs

- Automatic, *involuntary* reactions to external stimuli (e.g. the withdrawal reflex)
- However, *not* completely stereotyped:
  - **Warm-up:** Maximum intensity reached only after a while  
Example: scratch reflex in dogs
  - **Fatigue:** Reduced intensity even if the stimulus remains unchanged  
Possibly a result of *neurotransmitter depletion* (the synapses “run out of fuel”)

**Taxis:** Orientation of motion towards (or away from) some stimulus



**Taxis:** Orientation of motion towards (or away from) some stimulus

- *Spatial* intensity gradient, or a *temporal gradient* (requires a **short-term memory**)

**Taxis:** Orientation of motion towards (or away from) some stimulus

- *Spatial* intensity gradient, or a *temporal gradient* (requires a **short-term memory**)
- Examples:

**Taxis:** Orientation of motion towards (or away from) some stimulus

- *Spatial* intensity gradient, or a *temporal gradient* (requires a **short-term memory**)
- Examples:
  - **Phototaxis** : Moving towards or away from light (cf. Braitenberg vehicle)

**Taxis:** Orientation of motion towards (or away from) some stimulus

- *Spatial* intensity gradient, or a *temporal gradient* (requires a **short-term memory**)
- Examples:
  - **Phototaxis** : Moving towards or away from light (cf. Braitenberg vehicle)
  - **Chemotaxis**: Moving towards a higher (or lower) concentration of a chemical (example: trail-following ants)

**Taxis:** Orientation of motion towards (or away from) some stimulus

- *Spatial* intensity gradient, or a *temporal gradient* (requires a **short-term memory**)
- Examples:
  - **Phototaxis** : Moving towards or away from light (cf. Braitenberg vehicle)
  - **Chemotaxis**: Moving towards a higher (or lower) concentration of a chemical (example: trail-following ants)
  - **Thermotaxis**: Movement along a temperature gradient

**Kinesis:** *Non-directional* movement in response to a stimulus

**Kinesis:** *Non-directional* movement in response to a stimulus

- Movement rate (rather than direction) dependent on the level of the stimulus

**Kinesis:** *Non-directional* movement in response to a stimulus

- Movement rate (rather than direction) dependent on the level of the stimulus
- Purpose: Search for best conditions



**Kinesis:** *Non-directional* movement in response to a stimulus


- Movement rate (rather than direction) dependent on the level of the stimulus
- Purpose: Search for best conditions
- Example: Wood lice move less if the level of humidity is high

# Fixed action patterns (FAPs)

- A sequence of actions over time
- Temporal extension beyond that of the stimulus
- Examples of FAP: Egg-retrieval in geese

# Fixed action patterns (FAPs)

- A sequence of actions over time
- Temporal extension beyond that of the stimulus
- Examples of FAP: Egg-retrieval in geese



- Animals do not only react to immediate stimuli: They also maintain an internal state

# Complex behaviours

- Animals do not only react to immediate stimuli: They also maintain an internal state
- Motivated behaviours: depend on internal states

# Complex behaviours

- Animals do not only react to immediate stimuli: They also maintain an internal state
- Motivated behaviours: depend on internal states
- Example: Navigation of the desert ant *cataglyphis fortis*




## Desert ant navigation

- Cannot use pheromones: Would evaporate in the desert heat
- Still capable of moving long distances (100 m or more) from their nest, and then move straight back (nest=tiny hole in the ground):

# Desert ant navigation

- Cannot use pheromones: Would evaporate in the desert heat
- Still capable of moving long distances (100 m or more) from their nest, and then move straight back (nest=tiny hole in the ground):





- How do they do this?

# Desert ant navigation

- How do they do this?
- Desert ants have the ability to

# Desert ant navigation

- How do they do this?
- Desert ants have the ability to
  1. Measure distance travelled (odometry)

- How do they do this?
- Desert ants have the ability to
  1. Measure distance travelled (odometry)
  2. Measure direction (compass, based on light polarisation pattern)

- How do they do this?
- Desert ants have the ability to
  1. Measure distance travelled (odometry)
  2. Measure direction (compass, based on light polarisation pattern)
- Thus, they can maintain a vector connecting the nest to the current position

- How do they do this?
- Desert ants have the ability to
  1. Measure distance travelled (odometry)
  2. Measure direction (compass, based on light polarisation pattern)
- Thus, they can maintain a vector connecting the nest to the current position
- To return, they simply reverse the vector

- How do they do this?
- Desert ants have the ability to
  1. Measure distance travelled (odometry)
  2. Measure direction (compass, based on light polarisation pattern)
- Thus, they can maintain a vector connecting the nest to the current position
- To return, they simply reverse the vector
- Ephemeris function: Cataglyphis can also compensate for the motion of the sun in the sky

- Still, finding the nest is difficult



- Still, finding the nest is difficult
- Near the nest, the ants use pattern matching, i.e. using its eyes to match the current view to a stored snapshot taken when leaving, i.e. **landmark recognition**

- Still, finding the nest is difficult
- Near the nest, the ants use pattern matching, i.e. using its eyes to match the current view to a stored snapshot taken when leaving, i.e. **landmark recognition**
- Additional sensory modality: The ants can also use **odour recognition** to help pinpoint the entrance to the nest

- Still, finding the nest is difficult
- Near the nest, the ants use pattern matching, i.e. using its eyes to match the current view to a stored snapshot taken when leaving, i.e. **landmark recognition**
- Additional sensory modality: The ants can also use **odour recognition** to help pinpoint the entrance to the nest
- This is another example of **sensor fusion**!

# Behaviour-based robotics


---

# Behaviour isolation

- In the **behaviour-based robotics** (BBR) approach the robotic brains (control systems) are built in a *bottom-up* fashion, from simple isolated behaviours

# Behaviour isolation

- In the **behaviour-based robotics** (BBR) approach the robotic brains (control systems) are built in a *bottom-up* fashion, from simple isolated behaviours



- Robots are first provided with simple, survival-related behaviours, then more complex behaviours are added

- Robots are first provided with simple, survival-related behaviours, then more complex behaviours are added
- Isolated behaviours form a behavioural repertoire



- Robots are first provided with simple, survival-related behaviours, then more complex behaviours are added
- Isolated behaviours form a behavioural repertoire
- For a robot, survival entails, for example:
  - Avoiding collisions
  - Avoiding to run out of battery energy
  - Restore energy
- Reactive response: Quick reactions, without too much deliberation, act on input and state

- Robots are first provided with simple, survival-related behaviours, then more complex behaviours are added
- Isolated behaviours form a behavioural repertoire
- For a robot, survival entails, for example:
  - Avoiding collisions
  - Avoiding to run out of battery energy
  - Restore energy
- Reactive response: Quick reactions, without too much deliberation, act on input and state
- **Decision-making** is simply the coordination of behaviours

There are two main classes of **behavioural coordination** methods:

There are two main classes of **behavioural coordination** methods:

- Arbitration: *winner-take-all* strategy, dominating behaviour is activated (competitive methods)

There are two main classes of **behavioural coordination** methods:

- Arbitration: *winner-take-all* strategy, dominating behaviour is activated (competitive methods)
- Behavioural fusion, or blending: A combination of more than one behaviour is activated at a time (sharing actuation infrastructure)

Behavioural architectures:

Behavioural architectures:

- Examples of behaviour arbitration:
  - Finite-state machines (FSMs)
  - Artificial neural networks (ANNs)
  - Subsumption

Behavioural architectures:


- Examples of behaviour arbitration:
  - Finite-state machines (FSMs)
  - Artificial neural networks (ANNs)
  - Subsumption
- Example also capable of behaviour blending:
  - Motivation-based modelling (utility functions)



# Subsumption architecture

- Finite-state machines (FSMs), representing the behaviours, are wired together in a behaviour network
- Higher level behaviours can *suppress* the lower level behaviours for some amount of time
- Modular architecture: New behaviours can be added "on top" of existing behaviours
- However, requires extensive manual tuning, which in practice limit the number of behaviours.

# Subsumption architecture



**Figure 1:** A behaviour control program (left). The 'Escape' behaviour FSM (right).

- Subsumption was developed by Prof. Rodney Brooks at the MIT AI lab in the 1980s.

- Each behaviour is associated with a benefit
- Overall states are in general degrading over time
- To keep a positive state, continuous action is needed

# Generating behaviour structures and behaviour tuning

In the end, behavioural modelling comes down to coordination and tuning of simple isolated components.

- How can we model a behavioural system?
- How can we tune behaviours and their interaction?