



| 3 Decades of Experience in Packaging
| Multiple Country Operations

| 800⁺ Channel Partners
| 80⁺ Service Centres





HAND OPERATED SEALING MACHINES

! Ideal for sealing heat sealable poly pouches ! Hand operated Impulse (instant) sealing ! Hot bar sealers for laminated pouches ! Adjustable electronic timer ! Audio visual sealing indicators ! Suitable for packing solids, granules and powders ! Round element option for simultaneous sealing and cutting

Technical specifications

Model	Seal (mm)		Power		Dimension (mm)			Weight
	Length	Width	V	VA	L	B	H	
Impulse Sealers								
190HW	190	3	240	345	305	85	155	2.75
200 Eco	200	1.6	240	215	305	85	155	2.5
200Dv2	200	1.6	240	215	305	85	155	2.5
200HB	200	1.6	240	245	305	85	155	2.7
250D	250	1.6	240	320	350	85	155	2.85
300D	300	1.6	240	340	405	85	155	3.2
300HB	300	1.6	240	390	405	85	155	4.3
300HW	300	3	240	500	405	85	155	4.4
400D	400	1.6	240	525	535	85	155	4.6
400HB	400	1.6	240	565	535	85	155	4.7
400HW	400	3	240	600	535	85	155	5
500HB	500	1.6	240	545	630	85	155	5.6
600HB	600	1.6	240	710	720	85	155	6.5
Model	Seal (mm)		Power		Dimension (mm)			Weight
	Length	Width	V	VA	L	B	H	
Hot bar Sealers								
200 HH	200	11.5	240	180	340	85	155	2.6
300 HH	300	11.5	240	260	410	85	155	3.0

Pictures shown may vary from actual products.



FOOT OPERATED SEALING MACHINES

! Adjustable electronic timer ! Tilttable sealing jaw ! Adjustable bag rest ! Ease of operation ! High productivity ! Visual indication during sealing ! Audio indication at the end of sealing ! Hot bar sealer with energy regulator for sealing laminated pouches

Technical specifications

Model	Seal (mm)		Power		Dimension (mm)			Weight (Kg)
	Length	Width	V	VA	L	B	H	
Impulse Sealers								
QS 300 F	300	1.6	240	400	660	620	1050	19
QS 300 FE	300	5	240	600	660	620	1050	22
QS 300 FP	300	3x2	240	800	660	620	1050	24
QS 400 F	400	1.6	240	470	660	620	1050	20
QS 400 FE	400	5	240	720	660	620	1050	23
QS 500 F	500	1.6	240	560	660	620	1050	20
QS 500 FE	500	5	240	750	660	620	1050	23
QS 600 F	600	1.6	240	650	700	620	1050	23
QS 600 FE	600	5	240	920	700	620	1050	26
QS 900 F	900	1.6	240	950	1000	620	1050	30
QS 900 FE	900	5	240	1200	1000	620	1050	35
Model	Seal (mm)		Power		Dimension (mm)			Weight
	Length	Width	V	VA	L	B	H	
Hot bar Sealers								
200 FHM	200	14.5	240	340	660	620	1050	
300 FHM	300	14.5	240	500	660	620	1050	
400 FHM	400	14.5	240	650	660	620	1050	

Pictures shown may vary from actual products.



DELTA SERIES (ECONOMY)

No tilting facility; F D- Standard model,
FE D- 5mm sealing Width,
FP D- Two parallel 3mm wide seals,
FHE D- Hot bar sealers

Technical specifications

Model	Seal (mm)		Power		Dimension (mm)			Weight
	Length	Width	V	VA	L	B	H	
Impulse Sealers								
300 F D	300	1.6	240	400	500	500	1000	17
300 FE D	300	5	240	600	500	500	1000	18
300 FP D	300	3x2	240	800	500	500	1000	19
400 F D	400	1.6	240	470	500	500	1000	22
400 FE D	400	5	240	720	500	500	1000	24
Model	Seal (mm)		Power		Dimension (mm)			Weight
	Length	Width	V	VA	L	B	H	
Hot bar Sealers								
300 FHE D	300	11.5	240	260	500	530	930	17
400 FHE D	400	11.5	240	340	500	530	930	20



MOBILE SEALER

- For packing heavy bags
- Ideal for tea sacks, chemicals, spices etc.
- A mobile machine can reach to the filled bag
- Height adjustability 0.3 to 1.3m

Technical specifications

Model	Seal (mm)		Power Rating		Dimension (mm)			Weight
	Length	Width	V	VA	L	B	H	
900MSE	900	5	240	1040	1320	400	1290	56
900MSE SS	900	5	240	1040	1320	400	1200	56
900MSH	900	12	240	650	1320	400	1200	35
900MSH SS	900	12	240	650	1320	400	1200	35

*For SS model MSE/MSH only outer parts except for Castor wheel, Element Bed & Element Holder are fabricated in SS grade.



BED SEALER

- Can seal up to a length of six feet 5mm sealing width
- Reverse bend rocke arm for uniform- sealing from one end to the other
- Equipped with bearing mounted lever to achieve maximum pressure during sealing

Technical specifications

Model	Seal (mm)		Power	
	Length	Width	V	VA
1800 TM	1800	5	240	2700
1200 TM	1200	5	240	1500

Pictures shown may vary from actual products.



Foil Sealer (FS)



Foil Sealer Delta

FOIL SEALERS

- For pilfer evident and leak proof sealing of aluminum foils on cups, cans, bottles, plastic containers and trays
- Height adjustability and provision for heat control

Strong cups, cans and bottles can be sealed without extra attachments. Flimsy Cups and trays require extra support at the bottom of the neck, otherwise the cup/neck may be crushed during sealing operation. The support has to be matched with the shape of the cup to be sealed (Provide dimensional sketches or samples for design of appropriate support)

Technical specifications

Model	Head adjusting range from base	Sealing Dia Max	Power Watts	Voltage	L (mm)	B (mm)	H (mm)	Weight Kg
FS 1545	70 to 300mm	140mm	300	AC 240	560	250	650	11
FS 2045	70 to 300mm	190mm	450	AC 240	560	250	650	13.5
FSD 1545	10 to 160 mm	140mm	300	AC 240	460	170	250	4.5



SEPACK PORTABLE BAG CLOSER SBSC

TECHNICAL SPECIFICATIONS

Capacity	: 300-350 bags per hour
Stitch length	: 7.2mm
Motor	: 1/HP 230 Volts AC/DC universal single phase 8000rpm
Control	: Micro switch finger touch start



HAND WRAPPER HW 450

I Ideal for wrapping cling film I Suitable for super markets, fruit stalls, Bakeries, frozen foods etc
I Enhanced display on the shelf

Technical specifications

Model	Hand wrapper - HW 450
Voltage	240 V 1Phase
Power	50W
Film width	up to 450mm



HOT AIR GUN

The Stylish Hot Air Gun from Sepack is generally used for shrink wrapping of objects like bottles, containers, tray, hardware items & spare parts. Shrink wrapping provides an attractive pilfer proof shape hugging protection.

Technical specifications

Model	HAGP1600
Voltage	240 V/50Hz
Power	1600W
Air Flow	250/500 LPM
Temp	400°C/550°C



SEPACK SE-CODERS BATCH CODING MACHINES

Availabe Models: 4mm, 3mm & 2mm




CARTON SEALER PREMIUM

A hand held tool for dispensing BOPP adhesive tapes over boxes, containers etc.



Sepack India Pvt. Ltd., 3rd Floor, Mathewsons Square, High School Jn. Edappally, Cochin - 24, +91 - 484 - 3541000, E-mail: sepack@sepack.in | www.sepack.in

Branch & CFA: Delhi > Kolkata > Mumbai > Hyderabad > Vijayawada > Guwahati
Overseas company: Sepack Lanka Pvt. Ltd., Colombo & Khaleej Al Sharq Al Awsat Trading LLC, UAE

 Service WhatsApp Number
+918590050096.



SEPACK PORTABLE BAG CLOSER SBCS

TECHNICAL SPECIFICATIONS

Capacity	: 300-350 bags per hour
Stitch length	: 7.2mm
Motor	: 1/HP 230 Volts AC/DC universal single phase 8000rpm
Control	: Micro switch finger touch start



HAND WRAPPER HW 450

I Ideal for wrapping cling film I Suitable for super markets, fruit stalls, Bakeries, frozen foods etc
I Enhanced display on the shelf

Technical specifications

Model	Hand wrapper - HW 450
Voltage	240 V 1Phase
Power	50W
Film width	up to 450mm



HOT AIR GUN

The Stylish Hot Air Gun from Sepack is generally used for shrink wrapping of objects like bottles, containers, tray, hardware items & spare parts. Shrink wrapping provides an attractive pilfer proof shape hugging protection.

Technical specifications

Air flow	: 250/500LPM
Temp	: 400°C/550°C
Voltage	: 240V/50Hz
Power	: 1800W



SEPACK SE-CODERS BATCH CODING MACHINES

Availabe Models: 4mm, 3mm & 2mm



CARTON SEALER PREMIUM

A hand held tool for dispensing BOPP adhesive tapes over boxes, containers etc.