Best practices

General

- Chose meaningful variable and method names
- Implement as much tests as possible for a good coverage
- Tests should be robust and meaningful
- Add comments only if something is not obvious
- Do your own review before opening the pull request
- Test your implementations
- Inline implementation (for / if / ...) should be with { }

```
Example :

if (value == true) return null; ------> Wrong

if (value == true) {
    return null;
} ------> Good
```

Backend

- The backend should return DTOs
- DTO mappers should be in the controller layer
- DTO mappers should be done with MapStruct and decorator classes if required
- Use SOLID principles (***S**ingle responsibility*, ***O**pen/closed*, ***L**iskov substitution*, ***I**nterface segregation, **D**ependency inversion*)
- Use static import as much as possible
- Everything should be final when possible (variables and methods args)
- Use lombok for getters, setters and constructors

Frontend

- Imports should be formatted this way: external imports, line break then project imports
- Style sheets files should be formatted this way (surrounding empty lines when there is a child, otherwise, no empty lines):

```
.class {

  &.class-bis {
    css-attributes: value;
```

```
  }

  .child {
    css-attributes: value;
  }

}
```

- The parent selectors should be placed before the children selectors. (see above)
- Attributes should be read-only when possible
- Private attributes should start with “_”
- Methods should have an explicit return type
- Group different element (attributes, constructor, methods, event methods...) with comments above
- Comments should have only the first letter in capital

```
// Methods

myPublicMethod(): void {
}

// Private methods

_myPrivateMethod(): void {
}
```