



SF10FP

Stanilite Spitfire® recessed emergency range has been designed to be as unobtrusive as practically possible. The Spitfire® is available in two lamp head sizes of 85mm or 141mm, pre-cabled with a universal 6-way lamp head lead connector assembly that simply snaps into the remote pack.

### Features

- Power pack complete with flex and plug
- Optional protective clear dome or IP65 weatherproof enclosure lamp head wire guard
- Universal wall or ceiling mount.
- Recessed or surface mount options available
- Hi-temperature NiCad batteries for SF series, sealed lead acid for EWF series
- Surface mount electronics and 105°C rated electronic components
- Filament continuity circuit – monitors whether the lamp is present and if the filament has failed

### 10W Economy Spitfire® D10 Non Maintained Emergency

Part No.	Description
EWF10FP	10W Recessed with 141mm head, flex & plug
EWF10FPCD	10W Recessed with 141mm clear dome, flex & plug

### 7W Spitfire® D12.5 Non Maintained Emergency

SFB07	7W Surface mounted
SF07FP	7W Recessed with 85mm head, flex & plug
SF07FPCD	7W Recessed with 85mm clear dome, flex & plug
SF07FP-SS	7W Recessed with 85mm stainless steel, flex & plug
SF07FPLH	7W Recessed with 141mm head, flex & plug
SF07FPLHCD	7W Recessed with 141mm clear dome, flex & plug

### 10W Spitfire® D20 Non Maintained Emergency

SFB10	10W Surface mounted
SFB10CD	10W Surface mounted with clear dome
SFB10-BLK	10W Surface mounted black
SF10FP	10W Recessed with 85mm head, flex & plug
SF10FPCD	10W Recessed with 85mm clear dome, flex & plug
SF10FP-SS	10W Recessed with 85mm stainless steel, flex & plug
SF10FPSSCD	10W Recessed with 85mm stainless steel clear dome, flex & plug
SF10FP-BLK	10W Recessed with 85mm black head, flex & plug
SF10FP-RP	10W Recessed with 85mm rust proof head, flex & plug
SF10FP-WPH	10W Recessed with 85mm w/proof surface mount head, flex & plug
SF10FPWG	10W Recessed with 85mm head, wire guard
SF10FPLH	10W Recessed with 141mm head, flex & plug
SF10FPLHCD	10W Recessed with 141mm head, flex & plug, clear dome

### 240V AC Spitfire®

Part No.	Description
SFAC10	240V AC 10W 6V Recessed with 85mm head
SFAC10LH	240V AC 10W 6V Recessed with 141mm head

### 110V DC Spitfire® Non Maintained Emergency

SFBDC10	110V DC 10W Surface mount
SFDC10	110V DC 10W Recessed with 85mm head
SFDC10FP	110V DC 10W Recessed with 85mm head, flex & plug
SFDC10FPLH	110V DC 10W Recessed with 141mm head, flex & plug

Stanilite  
**nexusLX**®

### Non Maintained Nexus® Spitfire® Emergency

SFBNXS10	Nexus 10W Surface mount
SFBNXS10CD	Nexus 10W Surface mount 85mm clear dome
SFNXS10FP	Nexus 10W Recessed with 85mm head, flex & plug
SFNXS10FPCD	Nexus 10W Recessed with 85mm clear dome, flex & plug
SFNXS10FP-SS	Nexus 10W Recessed with 85mm stainless steel, flex & plug
SFNXS10FP-BLK	Nexus 10W Recessed with 85mm black head, flex & plug
SFNXS10FP-WPH	Nexus 10W Recessed with 85mm w/proof surface mt head, flex & plug
SFNXS10FP-RP	Nexus 10W Recessed with 85mm rust proof, round pin, flex & plug
SFNXS10FPWG	Nexus 10W Recessed with 85mm flex & plug, wire guard
SFNXS10FPLH	Nexus 10W Recessed with 141mm head, flex & plug
SFNXS10FPLHCD	Nexus 10W Recessed with 141mm head clear dome, flex & plug



EWF10FP



SFB10



SF10FP-WPH

### Technical Specifications

Photometric & Luminaires Spacings												
Product	Classification		Mounting Height in Metres									
			2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0	6.0
10W Economy Spitfire	C0	D10	10.2	10.6	10.9	11.1	11.3	11.4	11.5	11.6	11.6	11.2
	C90	D10	10.2	10.6	10.9	11.1	11.3	11.4	11.5	11.6	11.6	11.2
7W Spitfire	C0	D12.5	11.5	11.5	11.8	12.1	12.4	12.5	12.7	12.9	13.0	12.8
	C90	D12.5	11.5	11.5	11.8	12.1	12.4	12.5	12.7	12.9	13.0	12.8
10W Spitfire	C0	D20	13.1	13.6	14.1	14.5	14.8	15.1	15.5	15.8	16.1	16.4
	C90	D20	13.1	13.6	14.1	14.5	14.8	15.1	15.5	15.8	16.1	16.4
SFB10-BLK	C0	D6.3	8.6	8.8	9.0	9.1	9.2	9.2	9.2	9.0	8.7	7.7
	C90	D6.3	8.6	8.8	9.0	9.1	9.2	9.2	9.2	9.0	8.7	7.7
SF10FP-BLK	C0	D6.3	8.6	8.8	9.0	9.1	9.2	9.2	9.2	9.0	8.7	7.7
	C90	D6.3	8.6	8.8	9.0	9.1	9.2	9.2	9.2	9.0	8.7	7.7

\*Nexus versions of the above have the same data

### Power Consumption

240V AC 50HZ

• All Spitfires 8.5W

### Lamp Head Cut Out

SF07FP

• Small head 70mm

• Large head 130mm

SF10FP

• Small head 70mm

• Large head 130mm

### Construction

• Zinc Steel – White Powder Coated

• Clear Dome – polycarbonate

### Parts & Accessories

Part No.	Description
<b>7 Watt</b>	
02-SFSHD12.5	85mm head assembly
02-SFSHCD	85mm head assembly – clear dome
02-SFLHD12.5	141mm head assembly
02-SFLHCD	141mm head assembly – clear dome
02-SFLHCD-BLK	141mm head assembly black – clear dome
02-SF07FP	7W recessed with flex & plug, no head
15-00803	Lamp to suit 7W Spitfire
03-01206	Battery 10 cell sub C to suit 7W Spitfire
<b>10 Watt</b>	
02-SFSHD20	85mm head assembly
02-SFSHCD	85mm head assembly – clear dome
02-SFLHD20	141mm head assembly
02-SFLHCD	141mm head assembly – clear dome
02-SFLHCD-BLK	141mm head assembly black – clear dome
02-SF10FP	10W recessed with flex & plug, no head
15-00800	Lamp to suit 10W Spitfire
03-01017P	Battery 5 cell 4Ah NiCad to suit 10W Spitfire
<b>EWF Series</b>	
02-SFLHD10	141mm head assembly clear dome
15-00800	Lamp to suit EWF series
03-01210	Battery to suit EWF series

**Note** Rust proof, weatherproof, stainless steel and black options available upon request

Thomas & Betts emergency lighting products are tested to comply with AS2293 and meet relevant Australian EMC Standards. Due to ongoing product development, specification changes may result.