

## Related

[2 basic set implementations](#)

To implement a set in Go you can use a key-value map with boolean or empty struct values.

[yourbasic.org](#)

[Get slices of keys and values from a map](#)

You can use a range statement to extract slices of keys and values from a map in Go.

[yourbasic.org](#)

[Sort a map by key or value](#)

To sort a map (which is an unordered collection) you must maintain a separate data structure, typically a slice of keys or values.

[yourbasic.org](#)

[Hash tables explained \[step-by-step example\]](#)

Hash tables are used to implement dictionary and map data structures. They offer a combination of efficient lookup, insert and delete operations.

[yourbasic.org](#)

[Amortized time complexity](#)

Amortized analysis considers both the cheap and expensive operations performed by an algorithm. It is used for algorithms that have expensive operations that happen only rarely.

[yourbasic.org](#)

## Most Read

[Do you make these Go coding mistakes?](#)[Why Go? – Key advantages you may have overlooked](#)[Go string handling overview \[cheat sheet\]](#)[Type, value and equality of interfaces](#)[Concurrent programming](#)[See all 178 Go articles](#)

## Maps explained: create, add, get, delete

[yourbasic.org/golang](#)

Go maps are implemented by hash tables and have efficient add, get and delete operations.



- » [Create a new map](#)
- » [Add, update, get and delete keys/values](#)
- » [For-each range loop](#)
- » [Performance and implementation](#)

## Create a new map

```
var m map[string]int           // nil map of string-int pairs

m1 := make(map[string]float64) // Empty map of string-float64 pairs
m2 := make(map[string]float64, 100) // Preallocate room for 100 entries

m3 := map[string]float64{      // Map literal
    "e":  2.71828,
    "pi": 3.1416,
}
fmt.Println(len(m3))           // Size of map: 2
```

- A map (or dictionary) is an **unordered** collection of **key-value** pairs, where each key is **unique**.
- You create a new map with a **make** statement or a **map literal**.
- The default **zero value** of a map is **nil**. A nil map is equivalent to an empty map except that **elements can't be added**.
- The **len** function returns the **size** of a map, which is the number of key-value pairs.

**Warning:** If you try to add an element to an uninitialized map you get the mysterious run-time error [Assignment to entry in nil map](#).

## Add, update, get and delete keys/values

```

m := make(map[string]float64)

m["pi"] = 3.14           // Add a new key-value pair
m["pi"] = 3.1416         // Update value
fmt.Println(m)           // Print map: "map[pi:3.1416]"

v := m["pi"]             // Get value: v == 3.1416
v = m["pie"]             // Not found: v == 0 (zero value)

_, found := m["pi"]      // found == true
_, found = m["pie"]      // found == false

if x, found := m["pi"]; found {
    fmt.Println(x)
}                          // Prints "3.1416"

delete(m, "pi")          // Delete a key-value pair
fmt.Println(m)           // Print map: "map[]"

```

- When you index a map you get two return values; the second one (which is optional) is a boolean that indicates if the key exists.
- If the key doesn't exist, the first value will be the default [zero value](#).

## For-each range loop

```

m := map[string]float64{
    "pi": 3.1416,
    "e": 2.71828,
}
fmt.Println(m) // "map[e:2.71828 pi:3.1416]"

for key, value := range m { // Order not specified
    fmt.Println(key, value)
}

```

- Iteration order is not specified and may vary from iteration to iteration.
- If an entry that has not yet been reached is removed during iteration, the corresponding iteration value will not be produced.
- If an entry is created during iteration, that entry may or may not be produced during the iteration.

Starting with [Go 1.12](#), the `fmt` package prints maps in key-sorted order to ease testing.

## Performance and implementation

- Maps are backed by [hash tables](#).
- Add, get and delete operations run in **constant** expected time. The time complexity for the add operation is [amortized](#).
- The comparison operators `==` and `!=` must be defined for the key type.

*Go step by step*



Core Go concepts: [interfaces](#), [structs](#), slices, maps, [for loops](#), [switch statements](#), [packages](#).

Share this page: [!\[\]\(a03a7eb2f4046e1d3c76772003e549ea\_img.jpg\)](#) [!\[\]\(844169987a590ed8c7e31d5d18950e8d\_img.jpg\)](#) [!\[\]\(2af34e678d9364b2f32b7174f4964d2c\_img.jpg\)](#)

This work is licensed under a [CC BY 3.0 license](#).