

# Version control

## with git and GitHub

Karl Broman

Biostatistics & Medical Informatics, UW–Madison

`kbroman.org`

`github.com/kbroman`

`@kwbroman`

Course web: `kbroman.org/Tools4RR`

Slides prepared with `Sam Younkin`

# "FINAL".doc



FINAL.doc!




FINAL\_rev.2.doc



FINAL\_rev.6.COMMENTS.doc



FINAL\_rev.8.comments5.  
CORRECTIONS.doc



FINAL\_rev.18.comments7.  
corrections9.MORE.30.doc



FINAL\_rev.22.comments49.  
corrections.10. #@\$%WHYDID  
ICOMETOGRADSCHOOL?????.doc

© 2012 J. R. R. R. R.

WWW.PHDCOMICS.COM

<http://www.phdcomics.com/comics/archive.php?comiciid=1531>

# Methods for tracking versions

- ▶ Don't keep track
- ▶ Save numbered zip files
- ▶ Formal version control

# Suppose it stops working...

- ▶ Don't keep track
  - good luck!
- ▶ Save numbered zip files
  - Unzip versions and `diff`
- ▶ Formal version control
  - Easy to study changes back in time
  - Easy to jump back and test

# Why use formal version control?

- ▶ History of changes
- ▶ Able to go back
- ▶ No worries about breaking things that work
- ▶ Merging changes from multiple people

# Example repository

PUBLIC

kbroman / Talk\_MAGIC

Unwatch 1

Star 0

Fork 0

Talk for MAGIC workshop in Cambridge, UK, 12 June 2013 — Edit

97 commits

1 branch

0 releases

1 contributor

branch: master

Talk\_MAGIC

Greatly simplify the public domain stuff in the ReadMe

kbroman authored 15 days ago

latest commit f1777ef192

Figs	Add crazy table from preCC paper	4 months ago
Perf	Add lines_of_code_by_version.csv to repository	4 months ago
R	Another fix regarding map expansion in 8-way RIL by selfing at k=0	4 months ago
.gitignore	Add lines_of_code_by_version.csv to repository	4 months ago
Makefile	Revise Readme to link to version for web	4 months ago
ReadMe.md	Greatly simplify the public domain stuff in the ReadMe	15 days ago
magic.tex	Fix two slight bugs in slides:	4 months ago

ReadMe.md


## Talk for MAGIC Workshop in Cambridge, UK

These are slides for a talk I will give at the [Workshop on MAGIC-type populations](#) in Cambridge, UK, on 12 June 2013.

The PDF is [here](#).

-----

To the extent possible under law, [Karl Broman](#) has waived all copyright and related or neighboring rights to "MAGIC design and other topics". This work is published from: United States.



<> Code

Issues 0

Pull Requests 0

Wiki

Pulse

Graphs

Network

Settings

HTTPS clone URL


<https://github.com>

You can clone with HTTPS, SSH, or Subversion.

Clone in Desktop

Download ZIP

# Example repository



## Greatly simplify the public domain stuff in the ReadMe



**kbroman** authored 15 days ago


latest commit [f177ef192](#)




<a href="#">Figs</a>	Add crazy table from preCC paper	4 months ago
<a href="#">Perl</a>	Add lines_of_code_by_version.csv to repository	4 months ago
<a href="#">R</a>	Another fix regarding map expansion in 8-way RIL by selfing at k=0	4 months ago
<a href="#">.gitignore</a>	Add lines_of_code_by_version.csv to repository	4 months ago
<a href="#">Makefile</a>	Revise Readme to link to version for web	4 months ago
<a href="#">ReadMe.md</a>	Greatly simplify the public domain stuff in the ReadMe	15 days ago
<a href="#">magic.tex</a>	Fix two slight bugs in slides:	4 months ago


rights to "MAGIC design and other topics". This work is published from: United States.






# Example history




PUBLIC  **kbroman / Talk\_MAGIC**

 Unwatch 1  Star 0  Fork 0




 branch: master **Talk\_MAGIC** / Commits





Sep 27, 2013

 **Greatly simplify the public domain stuff in the ReadMe**  
kbroman authored 15 days ago f1777ef192   
[Browse code](#) 




 **Fix url in ReadMe.md file**  
kbroman authored 15 days ago o6515823f9   
[Browse code](#) 




Jun 17, 2013




 **Another fix regarding map expansion in 8-way RIL by selfing at k=0**  
kbroman authored 4 months ago 280a482f2c   
[Browse code](#) 




 **Fix two slight bugs in slides:**   
- 8-way RIL by selfing: map expansion = 1 at k=0  
- Slight repair to definition of 3-pt coincidence  
kbroman authored 4 months ago 51d4a9c9cb   
[Browse code](#) 




Jun 10, 2013




 **Change one page number**  
kbroman authored 4 months ago e8e0688615   
[Browse code](#) 




 **Add missing paren**  
kbroman authored 4 months ago f4975dee6e   
[Browse code](#) 




 **who's -> who is**  
kbroman authored 4 months ago 886f20f098   
[Browse code](#) 

 **rubblish -> bad**  
kbroman authored 4 months ago e0fbf2f647   
[Browse code](#) 

 **Add link to R/qtl page**  
kbroman authored 4 months ago 4edf3e8d76   
[Browse code](#) 

 **Revise slide re analysis issues**  
kbroman authored 4 months ago 14ebb1eeb5   
[Browse code](#) 

 **italicize 'de novo'**  
kbroman authored 4 months ago 45dda4b4c7   
[Browse code](#) 

 **replace plain right arrow with fat arrow**  
kbroman authored 4 months ago 8bbe305d6c   
[Browse code](#) 



# Example commit

PUBLIC kbroman / Talk\_MAGIC

Unwatch 1 Star 0 Fork 0

Fix two slight bugs in slides:

- 8-way RIL by selfing: map expansion = 1 at k=0
- Slight repair to definition of 3-pt coincidence

master

kbroman authored 4 months ago 1 parent e0e8608 commit 51d4aa9ceb104bbf26e0cbe105a5c7f8dc02a832

Showing 2 changed files with 5 additions and 3 deletions.

Show Diff Stats

R/map\_expansion\_func.R

View file @ 51d4aa9

```
... @@ -25,8 +25,10 @@ mesibA4 <- function(k)
25 25 #####
26 26 # Eight-way
27 27 #####
28 -mesibf8 <- function(k)
29 - 4 - (((1)/(2)))^(k-2)
+mesibf8 <- function(k) {
+  if(k==0) return(1)
+  4 - (((1)/(2)))^(k-2)
+}
30 32
31 33 mesibX8 <- function(k)
32 34 ((14)/(3)) - (((30 + 14*sqrt(5))/(15))) * (((1+sqrt(5))/(4)))^k - (((30 - 14*sqrt(5))/(15))) * (((1-s
```

magic.tex

View file @ 51d4aa9

```
... @@ -636,7 +636,7 @@
636 636
637 637 \hspace{20mm} {\color{myblue}} = $\mathsf{Pr}(\text{rec'n in 23}) \setminus
638 638 \setminus \text{rec'n in 12}) /
639 - \Pr(\text{rec'n in 12})\}$
+ \Pr(\text{rec'n in 23})\}$
640 640
641 641 \item
642 642 No interference { \color{myblue}} = 1 }
```

# What is git?

- ▶ Formal version control system
- ▶ Developed by Linus Torvalds (developer of Linux)
  - used to manage the source code for Linux
- ▶ Tracks any content (but mostly plain text files)
  - source code
  - data analysis projects
  - manuscripts
  - websites
  - presentations

# Why use git?

- ▶ It's fast
- ▶ You don't need access to a server
- ▶ Amazingly good at merging simultaneous changes
- ▶ Everyone's using it

# What is GitHub?

- ▶ A home for git repositories
- ▶ Interface for exploring git repositories
- ▶ **Real** open source
  - immediate, easy access to the code
- ▶ Like facebook for programmers
- ▶ Free 2-year "micro" account for students
  - [education.github.com](https://education.github.com)
- ▶ (Bitbucket.org is an alternative)
  - free private repositories

# Why use GitHub?

- ▶ It takes care of the server aspects of git
- ▶ Graphical user interface for git
  - Exploring code and its history
  - Tracking issues
- ▶ Facilitates:
  - Learning from others
  - Seeing what people are up to
  - Contributing to others' code
- ▶ Lowers the barrier to collaboration
  - "There's a typo in your documentation." vs.  
"Here's a correction for your documentation."

# Basic use

- ▶ Change some files
- ▶ See what you've changed

```
git status
```

```
git diff
```

```
git log
```

- ▶ Indicate what changes to save

```
git add
```

- ▶ Commit to those changes

```
git commit
```

# Basic use

- ▶ Change some files
- ▶ See what you've changed

```
git status
```

```
git diff
```

```
git log
```

- ▶ Indicate what changes to save

```
git add
```

- ▶ Commit to those changes

```
git commit
```

- ▶ Push the changes to GitHub

```
git push
```

# Basic use

- ▶ Change some files
- ▶ See what you've changed

```
git status  
git diff  
git log
```

- ▶ Indicate what changes to save

```
git add
```

- ▶ Commit to those changes

```
git commit
```

- ▶ Push the changes to GitHub

```
git push
```

- ▶ Pull changes from your collaborator

```
git pull
```



# Basic use

- ▶ Change some files
- ▶ See what you've changed

```
git status
```

```
git diff
```

```
git log
```

- ▶ Indicate what changes to save

```
git add
```

- ▶ Commit to those changes

```
git commit
```

- ▶ Push the changes to GitHub

```
git push
```

- ▶ Pull changes from your collaborator

```
git fetch
```

```
git merge
```

# Initialize repository

- ▶ Create (and `cd` to) a working directory
  - For example, `~/Docs/Talks/Graphs`
- ▶ Initialize it to be a git repository
  - `git init`
  - Creates subdirectory `~/Docs/Talks/Graphs/.git`

```
$ mkdir ~/Docs/Talks/Graphs
$ cd ~/Docs/Talks/Graphs
$ git init
Initialized empty Git repository in ~/Docs/Talks/Graphs/.git/
```

# Produce content

## ► Create a README.md file

```
## Talk on "How to display data badly";

These are slides for a talk that I give as often as possible,
because it's fun.

This was inspired by Howard Wainer's article, whose title I
stole: H Wainer (1984) How to display data badly.
American Statistician 38:137-147

A recent PDF is
[here](
http://www.biostat.wisc.edu/~kbroman/talks/graphs2013.pdf).

```

# Incorporate into repository

- ▶ Stage the changes using `git add`

```
$ git add README.md
```

# Incorporate into repository

- ▶ Now commit using `git commit`

```
$ git commit -m "Initial commit of README.md file"
[master (root-commit) 32c9d01] Initial commit of README.md file
1 file changed, 14 insertions(+)
create mode 100644 README.md
```

- ▶ The `-m` argument allows one to enter a message
- ▶ Without `-m`, `git` will spawn a text editor
- ▶ Use a meaningful message
- ▶ Message can have multiple lines, but make 1st line an overview

# A few points on commits

- ▶ Use frequent, small commits
- ▶ Don't get out of sync with your collaborators
- ▶ Commit the sources, not the derived files  
(R code not images)
- ▶ Use a `.gitignore` file to indicate files to be ignored

```
*~  
manuscript.pdf  
Figs/*.pdf  
.RData  
.RHistory  
*.Rout  
*.aux  
*.log  
*.out
```

# Using git on an existing project

- ▶ `git init`
- ▶ Set up `.gitignore` file
- ▶ `git status` (did you miss any?)
- ▶ `git add .` (or name files individually)
- ▶ `git status` (did you miss any?)
- ▶ `git commit`

# Removing/moving files

For files that are being tracked by git:

Use `git rm` instead of just `rm`

Use `git mv` instead of just `mv`

```
$ git rm myfile  
$ git mv myfile newname  
$ git mv myfile SubDir/  
$ git commit
```



# First use of git

```
$ git config --global user.name "Jane Doe"
$ git config --global user.email "janedoe@wisc.edu"

$ git config --global color.ui true

$ git config --global core.editor emacs


$ git config --global core.excludesfile ~/.gitignore_global
```

# Set up GitHub repository





- ▶ Get a GitHub account
- ▶ Click the "Create a new repo" button
- ▶ Give it a **name** and description
- ▶ Click the "Create repository" button
- ▶ Back at the command line:


```
git remote add origin  
https://github.com/username/repo  
git push -u origin master
```


# Set up GitHub repository



[Explore](#) [Gist](#) [Blog](#) [Help](#)

 kbroman   


PUBLIC 


 kbroman /

Great repository names are short and memorable. Need inspiration? How about [scaling-octo-wookie](#).

**Description** (optional)

---

☒  **Public**  
Anyone can see this repository. You choose who can commit.

☐  **Private**  
You choose who can see and commit to this repository.

---

☐ **Initialize this repository with a README**  
This will allow you to `git clone` the repository immediately.


Add .gitignore: **None**

Add a license: **None** ⓘ

---


Create repository

# Set up GitHub repository



The screenshot shows the GitHub interface for a repository named 'repo' by user 'kbroman'. The top navigation bar includes the GitHub logo, a dropdown for 'This repository', a search bar, and links for 'Explore', 'Gist', 'Blog', and 'Help'. The repository header shows 'kbroman / repo' with 'Unwatch' and 'Star' buttons. The main content area features a 'Quick setup' section with a 'Set up in Desktop' button and a text input field containing the SSH URL 'https://github.com/kbroman/repo.git'. Below this, a recommendation states that every repository should include a README, LICENSE, and .gitignore. The 'Create a new repository on the command line' section provides a list of terminal commands to initialize a new repository. The 'Push an existing repository from the command line' section provides commands to add a remote and push to the master branch.

**Quick setup** — if you've done this kind of thing before

 **Set up in Desktop** or **HTTP** **SSH**

We recommend every repository include a [README](#), [LICENSE](#), and [.gitignore](#).

## Create a new repository on the command line

```
touch README.md
git init
git add README.md
git commit -m "first commit"
git remote add origin https://github.com/kbroman/repo.git
git push -u origin master
```

## Push an existing repository from the command line

```
git remote add origin https://github.com/kbroman/repo.git
git push -u origin master
```

# Configuration file

Part of a .git/config file:

```
[remote "origin"]
  url = https://github.com/kbroman/ctl.git
  fetch = +refs/heads/*:refs/remotes/origin/*

[branch "master"]
  remote = origin
  merge = refs/heads/master

[remote "brian"]
  url = git://github.com/byandell/ctl.git
  fetch = +refs/heads/*:refs/remotes/brian/*
```

# Branching and merging

- ▶ Use branches to test out new features without breaking the working code.

```
git branch devel  
git branch  
git checkout devel
```

- ▶ When you're happy with the work, merge it back into your master branch.

```
git checkout master  
git merge devel
```

# Issues and pull requests

- ▶ Problem with or suggestion for someone's code?
  - Point it out as an Issue
- ▶ Even better: Provide a fix
  - Fork
  - Clone
  - Modify
  - Commit
  - Push
  - Submit a Pull Request

# Suggest a change to a repo

- ▶ Go to the repository:

`http://github.com/someone/repo`

- ▶ Fork the repository

Click the "Fork" button

- ▶ Clone your version of it

`git clone https://github.com/username/repo`

- ▶ Change things locally, `git add`, `git commit`

- ▶ Push your changes to *your* GitHub repository

`git push`

- ▶ Go to *your* GitHub repository

- ▶ Click "Pull Requests" and "New pull request"



# Pulling a friend's changes

- ▶ Add a connection

```
git remote add friend git://github.com/friend/repo
```

- ▶ If you trust them, just pull the changes

```
git pull friend master
```

- ▶ Alternatively, fetch the changes, test them, and *then* merge them.

```
git fetch friend master
git branch -a
git checkout remotes/friend/master
git checkout -b friend
git checkout master
git merge friend
```

- ▶ Push them back to your GitHub repo

```
git push
```

# Merge conflicts

Sometimes after `git pull friend master`


```
Auto-merging README.md
CONFLICT (content): Merge conflict in README.md
Automatic merge failed; fix conflicts and then commit the result.
```

Inside the file you'll see:

```
<<<<<< HEAD
A line in my file.
=====
A line in my friend's file
>>>>>> 031389f2cd2acde08e32f0beb084b2f7c3257fff
```

Edit, add, commit, push, submit pull request.

# git/GitHub with RStudio



See [GitPrimer.pdf](#) or [RStudio page](#)

# Delete GitHub repo

The screenshot shows the GitHub repository settings page for 'kbroman / RStudioTest'. The page is divided into several sections:

- Options:** A sidebar menu with links to 'Collaborators', 'Service Hooks', and 'Deploy Keys'.
- Settings:** The main content area, which includes:
  - Repository Name:** A text input field containing 'RStudioTest' and a 'Rename' button.
  - Default Branch:** A dropdown menu showing 'master'.
  - Features:** A section with three checkboxes:
    - ☒ **Wikis:** GitHub Wikis are the simplest way to let others contribute content. Any GitHub user can create and edit pages to use for documentation, examples, support or anything you wish.
    - ☐ **Restrict edits to Collaborators only:** Public Wikis will still be readable by everyone.
    - ☒ **Issues:** GitHub Issues adds lightweight issue tracking tightly integrated with your repository. Add issues to milestones, label issues, and close & reference issues from commit messages.
  - GitHub Pages:** A section with a description of the GitHub Pages generator, a 'Publish' button, and an 'Automatic Page Generator' button.
- Danger Zone™:** A red banner at the bottom with the following options:
  - Make this repository private:** A link to 'upgrade your plan' to make the repository private.
  - Transfer Ownership:** A section with a description of transferring the repository and a 'Transfer' button.
  - Delete this repository:** A section with a description of deleting the repository and a 'Delete this repository' button.

# Git at Statistics, UW-Madison

- ▶ Easy to use, free infinite private repositories.
- ▶ Not as nice of interface to review code: Rely on GUI or private web page.
- ▶ When your ssh account expires, your access to them expires.

# Git at Statistics, UW-Madison

Setup (on server):

- ▶ Connect to server

```
ssh bigmem01.stat.wisc.edu
```

Consider using kinit + aklog if logging on frequently

- ▶ Make Folder

```
cd Repositories
```

```
mkdir NewRepository
```

- ▶ Initialize Server Repository

```
cd NewRepository
```

```
git init
```

# Git at Statistics, UW-Madison

Usage (on client, e.g. laptop):

- ▶ Clone/Pull onto other systems

```
git clone ssh:\\bigmem01.stat.wisc.edu\~[user]\Repositories\NewRepository
```

- ▶ Make changes, and commit

```
git add -i
```

```
git commit -m 'An informative message here.'
```

- ▶ Push changes back

```
git push origin
```

Open source means everyone can see my stupid mistakes.

Version control means everyone can see every stupid mistake I've ever made.