References

Untagged PDF derivative | HTML reader

References

The bibliography lives in project bibliography source and is read by Pandoc during rendering. The combined PDF path invokes `--natbib`, so citation markers become LaTeX citation commands resolved against the bib file. HTML, reveal.js, and other non-LaTeX reader surfaces use `--citeproc` against that same file.

Untagged PDF derivative | HTML reader

References (part 2)

This is one bibliography with format-specific consumers, not two metadata sources. Titles retain the source's original spelling.

The standalone checkout provides a local cross-reference gate for citation labels and all manuscript references:

Untagged PDF derivative | HTML reader

References (part 3)

```
uv run --locked pytest
tests/test_xref_integrity.py -q
```

Untagged PDF derivative | HTML reader

References (part 4)

To validate that `references.bib` is syntactically clean and contains the required fields per entry type, the stricter citation validator is available when the project is checked out under the template monorepo's `projects/working/` (it is not on the standalone repo's own dependency graph),

References (part 5)

invoked from the monorepo root with a monorepo-relative path:

References (part 6)

```
p=projects/working/\
active_fedference
b=$p/manuscript/references.bib
uv run python -m \
infrastructure.reference.\
citation.cli validate "$b" --strict
```

Untagged PDF derivative | HTML reader