Acuant Android SDK API Documentation

Last updated on – 10/19/2015

Contents

1   Introduction

The AcuantAndroidMobileSDK is designed to simplify your development efforts. The processing of the captured images takes place via Acuant's Web Services. Our Web Services offer fast data extraction and zero maintenance as software is looked after by Acuant on our optimized cloud infrastructure.

Benefits:
- ❖ Process Enhancement: Faster data extraction and process images via Acuant's Web Services.
- ❖ Easy to set up and deploy.
- ❖ No maintenance and support: All maintenance and updates are done on Acuant servers.
- ❖ Secured Connection: Secured via SSL and HTTPS AES 256-bit encryption.

Acuant Web Services supports processing of drivers licenses, state IDs, other govt issued IDs, custom IDs, driver's license barcodes, passports, medical insurance cards etc. It also supports address verification, identity verification and personal verification.

For IDs from Asia, Australia, Europe, South America, Africa – we are support dd-mm-yyyy date format.
For IDs from Canada, USA – we are support mm-dd-yyyy date format.

For a complete list of regions, states, and countries supported for ID processing, please see Appendix F of ScanW document - http://www.id-reader.com/ftp/applications/sdk/docs/ScanW.pdf

To execute any Acuant Android Mobile SDK method, a valid license key is required. Please contact sales@acuantcorp.com to obtain a license key.

This Acuant Android Mobile SDK API documentation document has the detailed description of all the important functions a developer would need to write integration with Acuant Android Mobile SDK.

2   Requirements

- AndroidSDK Version 16 or later.
- 5 MP camera resolution or higher.
- The card image must be taken in an acceptable light conditions to avoid glare and overhead lights for example.
- The card must preferably be fitted with in the brackets on the camera screen, to allow the picture to be taken at a maximum resolution.

3 Integration

A   Add AcuantAndroidMobileSDK SDK

a   Using Gradle
In order to add the framework to your project, add the AcuantAndroidMobileSDK.aar dependencies

a.1   Local file
Add the following code in your build.gradle to avoid file collision.

```
dependencies {
      configurations.create("default")
      artifacts.add("default", file('acuantMobileSDK.aar'))
}
android{
   packagingOptions {
      exclude 'META-INF/NOTICE'
      exclude 'META-INF/LICENSE'
      exclude 'META-INF/DEPENDENCIES'
      exclude 'META-INF/DEPENDENCIES.txt'
      exclude 'META-INF/LICENSE.txt'
      exclude 'META-INF/NOTICE.txt'
   }
}
```


a.2   JCenter repositories
In order to add the framework to your project, add the AcuantAndroidMobileSDK dependencies from JCenter

```
>repositories {
>    jcenter ()
>}
>dependencies {
>    compile 'com.acuant.mobilesdk:acuantMobileSDK:2.7.0'
>}
```

Add the following code in your build.gradle to avoid some file collision
```
>android{
>    packagingOptions {
>       exclude 'META-INF/NOTICE'
>       exclude 'META-INF/LICENSE'
>       exclude 'META-INF/DEPENDENCIES'
>       exclude 'META-INF/DEPENDENCIES.txt'
>       exclude 'META-INF/LICENSE.txt'
```

```
>      exclude 'META-INF/NOTICE.txt'
>    }
>}
```

b   Manually

In order to add the framework to your project, drag the AcuantAndroidMobileSDK.jar file into your project's lib folder.

Libraries

Add the following libraries to use the framework:

- httpclient-4.2.5.jar
- httpmime-4.2.5.jar
- android-support-v4.jar
- gson-2.2.4.jar
- Pdf417MobiSdk.jar

Add a folder named 'armeabi' inside the 'libs' folder. Inside the 'armeabi' folder add the .so files and also the following files:

- libcvlibbase.so.
- libzpassport.so.
- libzcardany.so
- libBlinkBarcode.so

Add a folder named 'armeabi-v7a' inside the 'libs' folder. Inside the 'armeabi-v7a' folder add the .so files and also the following files:

- libcvlibbase.so.
- libzpassport.so.
- libzcardany.so
- libBlinkBarcode.so

Add a folder named 'arm64-v8a' inside the 'libs' folder. Inside the 'arm64-v8a' folder add the .so files and also the following files:

- libcvlibbase.so.
- libzpassport.so.
- libzcardany.so
- libBlinkBarcode.so

Add a folder named 'mips' inside the 'libs' folder. Inside the 'mips' folder add the .so files and also the following files:

- libBlinkBarcode.so

Add a folder named 'mips64' inside the 'libs' folder. Inside the 'mips64' folder add the .so files and also the following files:

- libBlinkBarcode.so

Add a folder named 'x86' inside the 'libs' folder. Inside the 'x86' folder add the .so files and also the following files:

- libBlinkBarcode.so

Add a folder named 'x86_64' inside the 'libs' folder. Inside the 'x86_64' folder add the .so files and also the following files:

- libBlinkBarcode.so

B   Add views into manifest

Add the followings activities into manifest.xml file:

```
<uses-permission android:name="android.permission.CAMERA"/>
<uses-permission android:name="android.permission.WRITE_EXTERNAL_STORAGE"/>
<uses-permission android:name="android.permission.READ_EXTERNAL_STORAGE"/>
<uses-permission android:name="android.permission.READ_PHONE_STATE"/>
<uses-permission android:name="android.permission.ACCESS_NETWORK_STATE"/>
<uses-permission android:name="android.permission.INTERNET"/>

<uses-feature android:name="android.hardware.camera"/>
<uses-feature android:name="android.hardware.camera.autofocus"/>
<uses-feature android:name="android.hardware.camera.front" android:required="true"/>

<activity android:name="com.acuant.mobilesdk.detect.CameraCardDetectAuto" />
<activity android:name="com.acuant.mobilesdk.detect.CameraCardDetectManual" />
<activity
        android:name="com.acuant.mobilesdk.detect.PDF417.CameraPDF417"
android:label="CameraDetect"
        android:screenOrientation="portrait"
android:theme="@android:style/Theme.Black.NoTitleBar.Fullscreen">
</activity>
```

C   Add XML to values folder.
- values.xml

D   Add raw folder.
-    device_list.json

E   Create and initialize the controller instance in your implementation class.

a   With activity, cloud address. And license Key
Pass an activity to initialize the AcuantAndroidMobileSDKController class, the cloud
address and the license key. The cloud Address must not contain "https://". Ex:
"https://cloud.myAddress.com/" must be written "cloud.myAddress.com". Note:
Only set cloud address if you are hosting Acuant web services in your own data
center. By default, Android MobileSDK communicates with the Acuant data center.

```
AcuantAndroidMobileSDKController.getInstance(activity,
"cloud.myAddress.com", licenseKey);
```

b   With activity and license key.
Pass an activity to initialize the AcuantAndroidMobileSDKController class, and the
license key.

```
AcuantAndroidMobileSDKController.getInstance(activity,
licenseKey);
```

c   With activity.
Pass an activity to initialize the AcuantAndroidMobileSDKController class, the entry
point to the library:

```
AcuantAndroidMobileSDKController.getInstance(activity);
```

d   If your instance was created previously.

Once the controller was created, you can obtain it through:

```
AcuantAndroidMobileSDKController.getInstance();
```

4   Validating a license key

A   Activating and validating a license key.

You need to activate and validate the license key before you can start using the library.

- The activation process enables you to use the license key. Activation process is only done
  once. To activate a license, set the callback for the web service methods:

```
AcuantAndroidMobileSDKControllerInstance.setWebServiceListener(th
is);
```

then, call the web service:

```
AcuantAndroidMobileSDKControllerInstance.callActivateLicenseKeySe
rvice(key);
```

the callback method `activateLicenseKeyCompleted` in the listener will be called when the activation finishes.

- The validation process implies the use of a web service process which retrieves permissions to use the library. It must be done every time you create a `AcuantAndroidMobileSDKController` instance to use the library.

  To validate, first set the callback for the web service methods like before:

  ```
  AcuantAndroidMobileSDKControllerInstance.setWebServiceListener(th
  is);
  ```

  then, set the license key to the controller:

  ```
  AcuantAndroidMobileSDKControllerInstance.setLicensekey(licenseKey
  );
  ```

  the callback method `validateLicenseKeyCompleted` in the listener will be called when the validation will finish.

For the first time use, you must activate and then validate the license key. After the license is activated, you only need to validate the license key every time you create an instance of the library on any Android device.

5   Capturing and cropping a card

A   Add the card capture method.

In order to show the camera interface, you need to know the card type that you want to capture.

If you need to capture passports, then you need to use the auto capture camera interface. If you need to capture driver's license or medical card you will need to use the manual camera interfaces.

If you need to capture Driver's License, you need to call 2 times: for the front side card and for the back side card.

a   Show the camera interface

```
AcuantAndroidMobileSDKControllerInstance.setWidth(myWidth);

AcuantAndroidMobileSDKControllerInstance.setPdf417BarcodeImageDrawable(getResources()
.getDrawable(R.drawable.barcode));

AcuantAndroidMobileSDKControllerInstance.showCameraInterface(this, currentOptionType,
cardRegion, isBarcodeSide);
```

b   Validating a license key and show the camera interface

```
AcuantAndroidMobileSDKControllerInstance.setWidth(myWidth);

AcuantAndroidMobileSDKControllerInstance.setPdf417BarcodeImageDrawable(getResources()
.getDrawable(R.drawable.barcode));

AcuantAndroidMobileSDKControllerInstance.
getInstanceAndShowCameraInterface(contextActivity, license, activity, cardType,
region, isBarcodeSide);
```

The width values are mandatory, they are set to indicate the width and height of the cropped cardimage.
A Drawable can be provided before calling showCameraInterface method in order to be displayed in the barcode scanning functionality. If not, no image will be shown.
`currentOptionType` is one of the AcuantCardType possibilities: Driver License, Medical Insurance or Passport.
`stringMessage`Message to show.
`currentOptionType` is one of the AcuantCardType possibilities: passport.

c   Retrieve the cropped card image from auto camera interface

After the user taps the screen, the cropping process begins. There are two callback methods:

- **public void** onCardCroppedStart(Activity activity);

    `activity:` the activity of the full screen Window, or the activity owner of the modal dialog (in case of Passport and Tablet for example)

- **public void** onCardCroppedFinish(final Bitmap bitmap);

    `bitmap:` the image card result
    On this function call, cropped card image is returned.

d   Retrieve the cropped card image from manual camera interface

After the user taps the screen, the cropping process begins, there are two callback methods:

- **public void** onCardCroppedStart(Activity activity);

activity: the activity of the full screen Window, or the activity owner of the modal dialog (in case of Passport and Tablet for example)

- **public void** onCardCroppedFinish(Bitmap bitmap);

  bitmap: the image card result
  On this function call, cropped card image is returned.

- **public void** onCardCroppedFinish(final Bitmap bitmap, boolean scanBackSide);

  bitmap: the image card result
  On this function call, cropped card image is returned.
  scanBackSide: A flag to alert the user to capture the back side of the card.

e   Retrieve the PDF417

After the user opens the camera, the detection process begins, there are only one callback methods:

- **public void** onPDF417Finish (String result);

  result: the barcode string result

B   Optional, Add the following methods to customize.

setWatermarkText: method to see the watermark on your camera
AcuantAndroidMobileSDKController.setWatermarkText("Powered By Acuant",0,0,30,0);

setPdf417 BarcodeDialogWaitingBarcode: method to customize dialog that shows if card is unable to scan.
setPdf417BarcodeDialogWaitingBarcode("IdScan GO", "Unable to scan the barcode?", 10, "Try Again", "Yes");

setInitialMessageDescriptor: Customize the initial message, default implementation says "Align and Tap" or "Tap to Focus".
setInitialMessageDescriptor(R.layout.hold_steady);

setInitialMessageDescriptor(message, red, green, blue, alpha);

setFinalMessageDescriptor : Customize the capturing message, default implementation says "hold steady".
setFinalMessageDescriptor(R.layout.align_and_tap);
setFinalMessageDescriptor(message, red, green, blue, alpha);

setFlashlight: Enable or disable the flashlight, by default is false.
setFlashlight(showFlashlight);
setFlashlight(left, top, right, bottom);

setCropBarcode: Enable or disable the barcode image cropping. By default is false.
setCropBarcode(canCropBarcode);

setShowActionBar: Enable or disable the action bar. By default is false.
setShowActionBar (false);

setShowStatusBar: Enable or disable the status bar. By default is false.
setShowStatusBar (false);

C Add the following methods to set the size of the card.

If the proper card size is not set, MobileSDK will not be able to process the card.

For Driver's License Cards
```
AcuantAndroidMobileSDKControllerInstance.setWidth(1009);
```

For Medical Insurance Cards
```
AcuantAndroidMobileSDKControllerInstance.setWidth(1009);
```

For Passport Documents
```
AcuantAndroidMobileSDKControllerInstance.setWidth(1478);
```

6 Processing a card

After the captureand the crop process, you can retrieve information through processing of the cropped image.

A Add a callback for the web service.

```
AcuantAndroidMobileSDKControllerInstance.setWebServiceListener(callback);
```

B Call the web service to process the card image

a For Driver's License Cards

```
ProcessImageRequestOptions options =
```

```
ProcessImageRequestOptions.getInstance();
options.autoDetectState = true;
options.stateID = -1;
options.reformatImage = true;
options.reformatImageColor = 0;
options.DPI = 150;
options.cropImage = false;
options.faceDetec = true;
options.signDetec = true;
options.iRegion = 0;
options.imageSource = 101;
options.acuantCardType = cardType;


AcuantAndroidMobileSDKControllerInstance.callProcessImageServices(frontSideCa
rdImage, backSideCardImage, barcodeString,callerActivity, options);
```

Explanation of the parameters:

region - Integer parameter for the Region ID. Parameter value -
United States – 0
Australia – 4
Asia – 5
Canada – 1
America – 2
Europe – 3
Africa – 7
General Documents – 6

autoDetectState- Boolean value. True – SDK will auto detect the state of the ID. False – SDK wont auto detect the state of the ID and will use the value of ProcState integer.

stateID - Integer value of the state to which ID belongs to. If AutoDetectState is true, SDK automatically detects the state of the ID and stateID value is ignored. If AutoDetectState is false, SDK uses stateID integer value for processing. For a complete list of the different countries supported by the SDK and their different State integer values, please see Appendix F of ScanW document - http://www.id-reader.com/ftp/applications/sdk/docs/ScanW.pdf

faceDetec - Boolean value. True - Return face image. False – Won't return face image.

signDetec - Boolean value. True – Return signature image. False – Won't return signature image.

reformatImage - Boolean value. True – Return formatted processed image. False – Won't return formatted image. Values of ReformatImageColor and ReformatImageDpi will be ignored.

reformatImageColor - Integer value specifying the color value to reformat the image. Values –
Image same color – 0
Black and White – 1
Grayscale 256 – 2

Smart from the start

Color 256 – 3
True color – 4
Enhanced Image – 5

DPI - Integer value up to 600. Reformats the image to the provided DPI value. Size of the image will depend on the DPI value. Lower value (150) is recommended to get a smaller image.

cropImage – Boolean value. When true, cloud will crop the RAW image. Boolean value. Since MobileSDK crops the image, leave this flag to false.

imageSource – To identify the source of the image. 101 is the value for MobileSDK.

b   For Medical Insurance Cards

```
ProcessImageRequestOptions options
=ProcessImageRequestOptions.getInstance();
options.reformatImage = true;
options.reformatImageColor = 0;
options.DPI = 150;
options.cropImage = false;
options.acuantCardType = cardType;

AcuantAndroidMobileSDKControllerInstance.callProcessImageServices(frontSideCa
rdImage, backSideCardImage, null, callerActivity, options);
```

Explanation of the parameters:

reformatImage - Boolean value. True – Return formatted processed image. False – Won't return formatted image. Values of ReformatImageColor and ReformatImageDpi will be ignored.

reformatImageColor - Integer value specifying the color value to reformat the image. Values –
Image same color – 0
Black and White – 1
Grayscale 256 – 2
Color 256 – 3
True color – 4
Enhanced Image – 5

DPI - Integer value up to 600. Reformats the image to the provided DPI value. Size of the image will depend on the DPI value. Lower value (150) is recommended to get a smaller image.

cropImage – Boolean value. When true, cloud will crop the RAW image. Boolean value. Since MobileSDK crops the image, leave this flag to false.

c   For Passport Cards

```
ProcessImageRequestOptions options =
ProcessImageRequestOptions.getInstance();
```

```
options.reformatImage = true;
options.reformatImageColor = 0;
options.DPI = 150;
options.cropImage = false;
options.faceDetec = true;
options.signDetec = true;
options.acuantCardType = cardType;
```

```
AcuantAndroidMobileSDKControllerInstance.callProcessImageServices(frontSideCa
rdImage, null, null, callerActivity, options);
```

Explanation of the parameters:

faceDetec - Boolean value. True - Return face image. False – Won't return face image.

signDetec- Boolean value. True – Return signature image. False – Won't return signature image.

reformatImage - Boolean value. True – Return formatted processed image. False – Won't return formatted image. Values of ReformatImageColor and ReformatImageDpi will be ignored.

reformatImageColor - Integer value specifying the color value to reformat the image. Values –
Image same color – 0
Black and White – 1
Grayscale 256 – 2
Color 256 – 3
True color – 4
Enhanced Image – 5

DPI - Integer value up to 600. Reformats the image to the provided DPI value. Size of the image will depend on the DPI value. Lower value (150) is recommended to get a smaller image.

cropImage – Boolean value. When true, cloud will crop the RAW image. Boolean value. Since MobileSDK crops the image, leave this flag to false.

C   Finally, do your post-processing of the card information

The callback method:

processImageServiceCompleted(AcuantCard card, int status, String message)

`card`: a 'card ' object with the scanned information
`status`: one of the constants of AcuantErrorType
`message`: error message from the server

is called when the web service completes. A 'card' with the card information is returned. It will be an instance of DRIVERS_LICENSE, PASSPORT, MEDICAL_INSURANCE according to

the original card type you passed to the web service. You can retrieve state, signature, name, etc. from this class, for example for license driver's card, these are some properties:

```
String name;
String licenceID;
String address;
String city;
String zip;
String state;
String idCountry;
String eyeColor;
String hair;
String height;
String weight;
String licenceClass;
String restriction;
String sex;
String county;
String dateOfBirth;
String expirationDate;
String nameLast;
String nationality;
String placeOfBirth;

Bitmap faceImage;
Bitmap signImage;
Bitmap reformatImage;
```

You can retrieve the name through:

card.getName()

also, you can check all the properties for all the card types in the API doc.

This is the implementation in the Sample project:

```
/**
    *
    */
@Override
publicvoid processImageServiceCompleted(AcuantCard card, int status, String
errorMessage)
    {
        Util.dismissDialog(progressDialog);

        String dialogMessage = null;
```

```java
try
    {

DataContext.getInstance().setCardType(mainActivityModel.getCurrentOptionType());

if (status == AcuantErrorType.AcuantNoneError)
        {
if (card == null || card.isEmpty())
            {
                dialogMessage = "No data found for this license card!";
            } else
            {

switch (mainActivityModel.getCurrentOptionType())
                {
caseCardType.DRIVERS_LICENSE:

                    DataContext.getInstance().setProcessedLicenseCard((Drivers
                    LicenseCard) card);
break;

caseCardType.MEDICAL_INSURANCE:

                    DataContext.getInstance().setProcessedMedicalCard((AcuantM
                    edicalCard) card);
break;

caseCardType.PASSPORT:

                    DataContext.getInstance().setProcessedPassportCard((Acuant
                    PassportCard) card);
break;

default:
thrownew IllegalStateException("There is not implementation for processing the card
type '"
                                + mainActivityModel.getCurrentOptionType() +
"'");
                }

                Util.unLockScreen(MainActivity.this);

                Intent showDataActivityIntent = new Intent(this,
ShowDataActivity.class);
this.startActivity(showDataActivityIntent);
                }
            } else
            {
                Log.v(TAG, "processImageServiceCompleted, webService returns an
error: " + errorMessage);
                dialogMessage = "" + errorMessage;
            }

        } catch (Exception e)
        {
```

```
            Log.v(TAG, e.getMessage(), e);
            dialogMessage = "Sorry! Internal error has occurred, please contact us!";

        }

if (dialogMessage != null)
        {
            Util.showDialog(this, dialogMessage);
}
    }
```

7 Error Types

public final static int *AcuantErrorCouldNotReachServer* = 0; //check internet connection
public final static int *AcuantErrorUnableToAuthenticate* = 1; //keyLicense are incorrect
public final static int *AcuantErrorUnableToProcess* = 2; //image received by the server was unreadable, take a new one
public final static int *AcuantErrorInternalServerError* = 3; //there was an error in our server, try again later
public final static int *AcuantErrorUnknown* = 4; //there was an error but we were unable to determine the reason, try again later
public final static int *AcuantErrorTimedOut* = 5; //request timed out, may be because internet connection is too slow
public final static int *AcuantErrorAutoDetectState* = 6; //Error when try to detect the state
public final static int *AcuantErrorWebResponse* = 7; //the json was received by the server contain error
public final static int *AcuantErrorUnableToCrop* = 8; //the received image can't be cropped.
public final static int *AcuantErrorInvalidLicenseKey* = 9; //Is an invalid license key.
public final static int *AcuantErrorInactiveLicenseKey* = 10; //Is an inative license key.
public final static int *AcuantErrorAccountDisabled* = 11; //Is an account disabled.
public final static int *AcuantErrorOnActiveLicenseKey* = 12; //there was an error on activation key.
public final static int *AcuantErrorValidatingLicensekey* = 13; //The validation is still in process.
public final static int *AcuantErrorCameraUnauthorized* = 14; //The privacy settings are preventing us from accessing your camera.
public final static int *AcuantNoneError* = 200; //The privacy settings are preventing us from accessing your camera.

8 Change Log

Gradle support added in version 2.7.