

Acuant iOS SDK API Documentation

Last updated on – 10/13/2016

Contents

1	Introduction	3
2	Requirements	3
3	Integration.....	4
4	Activate the license key	6
5	Initialize and create the SDK's instance.....	7
6	Capturing a card.....	8
7	Processing a card	16
8	Facial Recognition and Match Feature	28
9	Error Types	31
10	Miscellaneous	32
11	Change Log.....	32

1 Introduction

The AcuantMobileSDK.framework is a Cocoa Framework. Processing of the captured images takes place via Acuant's Web Services. Acuant's Web Services offer fast data extraction and authentication with zero downtime.

Benefits:

- ❖ Process Enhancement: Faster data extraction and authentication process images via Acuant's Web Services.
- ❖ Easy to set up and deploy.
- ❖ No maintenance and support: All maintenance and updates are done on Acuant servers.
- ❖ Secured Connection: Secured via SSL and HTTPS AES 256-bit encryption.

Acuant Web Services supports data extraction from of drivers licenses, state IDs, other govt issued IDs, custom IDs, driver's license barcodes, passports, medical insurance cards etc. It also supports document authentication and facial recognition to verify and authenticate the identity.

For IDs from Asia, Australia, Europe, South America, Africa – we are support dd-mm-yyyy date format.

For IDs from Canada, USA – we are support mm-dd-yyyy date format.

For a complete list of regions, states, and countries supported for ID processing, please see Appendix F of ScanW document - <http://www.id-reader.com/ftp/applications/sdk/docs/ScanW.pdf>

To execute any Acuant iOS Mobile SDK method, a valid license key is required. Please contact sales@acuantcorp.com to obtain a license key.

This Acuant iOS Mobile SDK API documentation has the detailed description of all the important functions a developer would need to write integration with Acuant iOS Mobile SDK.

Note: The Framework will not modify the Status bar of the app.

2 Requirements

- iOS 8.0 or later is required.
- iPhone 4S and above.
- iPad 3 and above.
- iPad mini.
- iPod Touch 5G and above.
- The card image must be taken in an acceptable light conditions to avoid glare and overhead lights for example.
- The card must preferably be fitted with in the brackets on the camera screen, to allow the picture to be taken at a maximum resolution.

3 Integration

A Installation with CocoaPods

Acuant iOS Mobile SDK can be installed using CocoaPods. CocoaPods is a dependency manager for Objective-C, which automates and simplifies the process of using 3rd-party libraries like Acuant iOS Mobile SDK in your projects.

Note : GitHub has recently changed the versioning for large files. To be able to download large files while cloning from GitHub or CocoaPods repositories please make sure git-lfs is installed in the build machine. More information for git-lfs is available at <https://git-lfs.github.com/>. Please clone/update our SDK repository only after the git-lfs is installed.

After cloning the repository execute the following command to make sure all files are pulled.

```
git lfs pull
```

Common Error:

If git-lfs is not setup, then GitHub doesn't download of large files. Therefore, if the following build error appears while building the iOS app, that means some of the files are missing.

```
ld: warning: ignoring file
../com.acuant.plugin.AcuantMobileSDK/AcuantMobileSDK.framework/AcuantMobileSDK, file
was built for unsupported file format ( 0x76 0x65 0x72 0x73 0x69 0x6F 0x6E 0x20 0x68 0x74
0x74 0x70 0x73 0x3A 0x2F 0x2F ) which is not the architecture being linked (armv7):
../com.acuant.plugin.AcuantMobileSDK/AcuantMobileSDK.framework/AcuantMobileSDK
Undefined symbols for architecture armv7:
```

```
"_OBJC_CLASS_$_AcuantCardProcessRequestOptions", referenced from:
```

```
objc-class-ref in AcuantMobileSDK.o
```

```
"_OBJC_CLASS_$_AcuantMobileSDKController", referenced from:
```

```
objc-class-ref in AcuantMobileSDK.o
```

```
ld: symbol(s) not found for architecture armv7
```

```
clang: error: linker command failed with exit code 1 (use -v to see invocation)
```

a Podfile

- Create a Podfile with following lines

```
platform :ios, '8.0'
```

```
pod 'AcuantMobileSDK', '~> <version number>'
(example pod 'AcuantMobileSDK', '~> 4.9.5.1')
```

- Execute 'Pod install' to add the AcuantMobileSDK
- If it is a Swift project then add the following imports in the Objective-C bridging file

```
#import <Foundation/Foundation.h>
#import <UIKit/UIKit.h>
#import "AcuantMobileSDK/AcuantCardProcessRequestOptions.h"
#import "AcuantMobileSDK/AcuantCardRegion.h"
#import "AcuantMobileSDK/AcuantCardResult.h"
#import "AcuantMobileSDK/AcuantCardType.h"
#import "AcuantMobileSDK/AcuantDriversLicenseCard.h"
#import "AcuantMobileSDK/AcuantError.h"
#import "AcuantMobileSDK/AcuantFacialCaptureDelegate.h"
#import "AcuantMobileSDK/AcuantFacialData.h"
#import "AcuantMobileSDK/AcuantFacialRecognitionViewController.h"
#import "AcuantMobileSDK/AcuantMedicalInsuranceCard.h"
#import "AcuantMobileSDK/AcuantMobileSDKController.h"
#import "AcuantMobileSDK/AcuantPassportCard.h"
```

B Add AcuantMobileSDK.embeddedframework on each project

If you are not using CocoaPods for Acuant iOS Mobile SDK installation, then you would have to add the AcuantMobileSDK.embeddedframework into your project. You can download the Acuant iOS Mobile SDK and embeddedframework from GitHub - <https://github.com/Acuant/AcuantiOSMobileSDK>.

In order to add the framework to your project, drag the AcuantMobileSDK.embeddedframework folder into your project's file structure.

a Natives frameworks and libraries

Go to the target.

Click on "Build Phases".

Expand "Link binary with libraries".

Click on plus to add frameworks and libraries.

Add following frameworks.

- AssetsLibrary.framework
- SystemConfiguration.framework.
- AudioToolbox.framework
- AVFoundation.framework.
- CoreMedia.framework.
- CoreVideo.framework.
- CoreGraphics.framework
- QuartzCore.framework.
- CoreMotion.framework

Add following libraries

Smart from the start

- libc++.tdb.
- libconv.tdb.
- libz.tdb.

Note: For Xcode 7.0 and below, use .dylib

- libc++.dylib.
- libconv.dylib.
- libz.dylib.

b Targets

Go to the target.

Click on “Build Settings”.

b.1 Change following targets

Set “C Language Dialect” with GNU99

Set “C++ Language Dialect” with Compiler Default

Set “C++ Standard Library” with Compiler Default

b.2 Change following flags

Add on “GCC_PREPROCESSOR_DEFINITIONS” = CVLIB_IMG_NOCODEC

C Integration with Objective-C.

Add the import header in your AppDelegate’s header file.

```
#import <AcuantMobileSDK/AcuantMobileSDKController.h>
```

D Integration with Swift.

In order to integrate our SDK on a Swift project you just need to create an Objective-C bridging header to expose those files to Swift.

Create this bridge is very simple, after you add an Objective-C file, the Xcode propts an alert suggesting to create the header file.

Apple Reference:

<https://developer.apple.com/library/ios/documentation/Swift/Conceptual/BuildingCocoaApps/MixandMatch.html>

4 Activate the license key

In order to activate the license key, use the following method:

```
- (IBAction)activateAction:(id)sender {
    [_instance activateLicenseKey:_licenseKeyText.text];
}
```

Note: The license key only needs to be activated once. Execute this method only one time. Some licensees are issued by Acuant pre-activated and don't need further actions.

5 Initialize and create the SDK's instance

A Initialize with license key

In the below call, license key is validated and instance is created.

```
//Obtain the main controller instance
_instance = [AcuantMobileSDKController initAcuantMobileSDKWithLicenseKey:@"MyLicensekey"
andDelegate:self];
```

Note: This method verifies if the license key is valid and it returns an instance that can be used to reference the methods. We recommend that you create one instance per session in order to optimize your resources.

B With license key and cloud address.

In the below call, license key is validated, the instance is created with the specified cloud address if you are hosting Acuant web services in your own data center. By default, iOS MobileSDK communicates with the Acuant data center.

```
//Obtain the main controller instance
_instance = [AcuantMobileSDKController initAcuantMobileSDKWithLicenseKey:@"MyLicensekey"
delegate:self andCloudAddress:@"cloud.myAddress.com"];
```

The cloud Address must not contain "https://"

Ex: "https://cloud.myAddress.com/" must be written "cloud.myAddress.com"

Note: This method verifies if the license key is valid and it returns an instance that can be used to reference the methods. We recommend that you create one instance per session in order to optimize your resources.

C If your instance was created previously

```
//Obtain the main controller instance
_instance = [AcuantMobileSDKController initAcuantMobileSDK];
```

- D Check if the license key validation was successful or not.
In order to know if the license key validation has finished or to know if it was successful, use the method below. This method is called after the instance of the MobileSDK has been created.

```
-(void)mobileSDKWasValidated:(BOOL)wasValidated {
    _wasValidated = wasValidated;
}
```

6 Capturing a card

A SDK Configuration for card capture interface.

In order to show the camera interface choose between manual capture interface or barcode capture interface depending on the card type.(AcuantCardTypeMedicalInsuranceCard, AcuantCardTypeDriversLicenseCard, AcuantCardTypePassportCard).

For AcuantCardTypeMedicalInsuranceCard and AcuantCardTypePassportCard you can only use the manual capture interface.

For AcuantCardTypeDriversLicenseCard, depending on the region, you can only use the manual capture interface and the barcode capture interface.

For IDs from USA and Canada, use manual capture interface for the front side and use barcode capture or manual capture interface for backside.

For IDs from South America, Europe, Asia, Australia, Africa region use manual capture interface for both front and backside.

- a In the header file where you'll be doing the parsing, add the following import.
`#import <AcuantMobileSDK/AcuantMobileSDKController.h>`

- b In the same header file, implement the
`AcuantMobileSDKControllerCapturingDelegate`.

```
@interface ISGViewController () <AcuantMobileSDKControllerCapturingDelegate,
AcuantMobileSDKControllerProcessingDelegate>
```

B Card capture interface methods.

- a Card capture interface with SDK initializations

In order to initialize the SDK and show the camera interface in the same step you must use the following method:

```
[AcuantMobileSDKController initAcuantMobileSDKWithLicenseKey:licenseKey
AndShowCardCaptureInterfaceInViewController:self delegate:self typeCard:_cardType region:_region
isBarcodeSide:_isBarcodeSide];
```

Note: if you are going to use any customization method, then you should create a previous instance of the SDK in order to set the camera customization.

Ex:

```
[_instance = [AcuantMobileSDKController initWithAcuantMobileSDK];
[_instance setWidth:1250];
[AcuantMobileSDKController initWithAcuantMobileSDKWithLicenseKey:licenseKey
AndShowCardCaptureInterfaceInViewController:self delegate:self typeCard:_cardType
region:_region isBarcodeSide:_isBarcodeSide];
```

b Manual Card capture interface without initialization

In order to call this function, you will need to initialize the SDK first and create an instance of the SDK to call the function (see point 4)

```
[_instance showManualCameraInterfaceInViewController:self delegate:self cardType:_cardType
region:_region andBackSide:YES];
```

c Barcode capture interface without initialization

In order to call this function, you will need to initialize the SDK first and create an instance of the SDK to call the function (see point 4)

```
[_instance showBarcodeCameraInterfaceInViewController:self delegate:self cardType:_cardType region:
_region];
```

d Methods to set the size of the card.

If the proper card size is not set, MobileSDK will not be able to process the card.

For Driver's License Cards

```
-(void)showCameraInterface{
    if(_instance.isAssureIDAllowed){ //If AssureId is enabled
        [_instance setWidth:2024];
    }else{
        [_instance setWidth:1250]; //If AssureId is not enabled
    }
}
```

For Medical Insurance Cards

```
-(void)showCameraInterface{
    [_instance setWidth:1500];
}
```

For Passport Documents

```
-(void)showCameraInterface{
    [_instance setWidth:1478];
}
```

e Optional methods to customize the appearance and final message on the camera screen. Customize the initial message, default implementation says "Align and Tap" or "Tap to Focus". For Driver License Front side, Driver License Back side, Medical Insurance and Passport

```
[_instance setInitialMessage:@"Initial Message" frame:CGRectMake(0, 0, 0, 0)
backgroundColor:[UIColor blueColor] duration:5.0 orientation:AcuantHUDLandscape];
```

Customize the capturing message, default implementation says "hold steady".
For Driver License Front Side and Medical Insurance

```
[_instance setCapturingMessage:@"Capturing Message" frame:CGRectMake(0, 0, 0, 0)
backgroundColor:[UIColor blueColor] duration:5.0 orientation:AcuantHUDLandscape];
```

f Optional method to enable cropping of the barcode image.
By default it is disabled.

```
[_instance setCanCropBarcode:YES];
```

Note: The barcode cropped image will be received with the didCaptureImage delegate method.

g Optional method to enable the initial message on the barcode camera interface.
By default it is disabled.

```
[_instance setCanShowMessage:YES];
```

i Optional method to pause the scanning of the barcode camera

```
[_instance pauseScanningBarcodeCamera];
```

j Optional method to resume the scanning of the barcode camera
[_instance resumeScanningBarcodeCamera];

C AcuantMobileSDKControllerCapturingDelegate protocol to handle the capturing.

a Required delegate method

a.1 didCaptureCropImage

In order to retrieve the cropped image captured by all card capture interface must use the following method:

```
-(void)didCaptureCropImage:(UIImage *)cardImage scanBackSide:(BOOL)scanBackSide{
    _isCameraTouched = NO;
    [_instance dismissCardCaptureInterface];
    _isBarcodeSide = scanBackSide;
    switch (_sideTouch) {
        case FrontSide:
            [_frontImage setImage:cardImage];
            break;
        case BackSide:
            [_backImage setImage:cardImage];
            [_frontImageLabel setText:@""];
    }
}
```

```

[_backImageLabel setText:@""];
[self cardHolderPositions];
_frontImage.layer.masksToBounds = YES;
_frontImage.layer.cornerRadius = 10.0f;
_frontImage.layer.borderWidth = 1.0f;

_backImage.layer.masksToBounds = YES;
_backImage.layer.cornerRadius = 10.0f;
_backImage.layer.borderWidth = 1.0f;
[_backImage setUserInteractionEnabled:YES];
break;
default:
break;
}
[_sendRequestButton setEnabled:YES];
[_sendRequestButton setHidden:NO];
if (scanBackSide) {
_sideTouch = BackSide;
[UIAlertController showSimpleAlertWithTitle:@"AcuantiOSMobileSDKSample"
Message:@"Scan the backside of the license."
FirstButton:ButtonOK
SecondButton:nil
FirstHandler:^(UIAlertAction *action) {
_sideTouch = BackSide;
_isCameraTouched = YES;
[self showCameraInterface];
}
SecondHandler:nil
Tag:1
ViewController:self];
}
}
}

```

Note: For AcuantCardTypeMedicalInsuranceCard capturing backside is optional but for AcuantCardTypeDriverLicenseCard capturing backside is a must.

a.2 didCaptureOriginalImage

In order to retrieve the original image captured by all card capture interfaces please use the following method:

```

-(void)didCaptureOriginalImage:(UIImage *)cardImage{
    _originalImage = cardImage;
}

```

a.3 didCaptureData delegate method

In order to retrieve the barcode string by the barcode capture interface for AcuantCardTypeDriverLicenseCard you must use the following method:

```
-(void) didCaptureData:(NSString *)data{
    self.barcodeString = data;
}
```

a.4 didCaptureCropImage:andData:scanBackSide: delegate method

In order to retrieve the barcode string and the backside image by the barcode capture interface for AcuantCardTypeDriverLicenseCard you must use the following method:

```
-(void)didCaptureCropImage:(UIImage *)cardImage andData:(NSString *)data
scanBackSide:(BOOL)scanBackSide{
}
```

Note:

- 1) This delegate will be called only if canCropBarcode is set to YES (e.g [self.instance setCanCropBarcode:YES];)
- 2) Don't implement both delegates, didCaptureData and didCaptureCropImage:andData:scanBackSide:

a.5 didFailWithError delegate method

In order to inform that the scan or the process failed. You must use the following method:

```
-(void)didFailWithError:(AcuantError *)error{
    NSString *message;
    switch (error.errorType) {
        case AcuantErrorTimedOut:
            message = error.errorMessage;
            break;
        case AcuantErrorUnknown:
            message = error.errorMessage;
            break;
        case AcuantErrorUnableToProcess:
            message = error.errorMessage;
            break;
        case AcuantErrorInternalServerError:
            message = error.errorMessage;
            break;
        case AcuantErrorCouldNotReachServer:
            message = error.errorMessage;
            if (_isCameraTouched) {
                showAlert = NO;
            }
    }
}
```

```

    }
    break;
case AcuantErrorUnableToAuthenticate:
    message = error.errorMessage;
    break;
case AcuantErrorAutoDetectState:
    message = error.errorMessage;
    break;
case AcuantErrorWebResponse:
    message = error.errorMessage;
    break;
case AcuantErrorUnableToCrop:
    message = error.errorMessage;
    break;
case AcuantErrorInvalidLicenseKey:
    message = error.errorMessage;
    break;
case AcuantErrorInactiveLicenseKey:
    message = error.errorMessage;
    break;
case AcuantErrorAccountDisabled:
    message = error.errorMessage;
    break;
case AcuantErrorOnActiveLicenseKey:
    message = error.errorMessage;
    break;
case AcuantErrorValidatingLicensekey:
    message = error.errorMessage;
    break;
case AcuantErrorCameraUnauthorized:
    message = error.errorMessage;
    break;
default:
    break;
}
if (showAlert) {
    [UIAlertController showSimpleAlertWithTitle:@"AcuantiOSMobileSDK"
                     Message:message
                     FirstButton:ButtonOK
                     SecondButton:nil
                     FirstHandler:^(UIAlertAction *action) {
                         if (tag == 1) {
                             _sideTouch = BackSide;
                             _isCameraTouched = YES;
                             [self showCameraInterface];
                         } else if (tag == 7388467) {
                             [[UIApplication sharedApplication] openURL:[NSURL
                             URLWithString:UIApplicationOpenSettingsURLString]];
                         }
                     }
                     SecondHandler:nil];
}

```

Smart from the start

acuantcorp.com

6167 Bristol Parkway
Suite 200

Culver City, California
90230

213.867.2625

```

        Tag:tag
        ViewController:self];
    }
}

```

b Optional delegate methods

Call to inform the delegate that the time of the barcode scan expired

```

- (void)barcodeScanTimeout {
    [self showSimpleAlertWithMessage:message];
}

```

Call to show or not show the iPad brackets on the card capture interface

```

- (BOOL)showiPadBrackets {
    return YES;
}

```

Call to inform the delegate that the user pressed the back button

```

- (void)didPressBackButton {
    [_instance dismissCardCaptureInterface];
}

```

Call to obtain the back button image displayed in the card capture interface

```

- (UIImage*)imageForBackButton {
    UIImage *image = [UIImage imageNamed:@"BackButton.png"];
    return image;
}

```

Call to obtain the back button position in the screen.

```

- (CGRect)frameForBackButton {
    return CGRectZero;
}

```

Call to show or not show the back button in the card capture interface

```

- (BOOL)showBackButton {
    return YES;
}

```

These methods control the attributes of the status bar when this view controller is shown.

```

- (BOOL)cameraPrefersStatusBarHidden {
    return YES;
}

```

Call to show or not show the flashlight button in the card capture interface

```

- (BOOL)showFlashlightButton {
    return YES;
}

```

Call to obtain the flashlight button position in the screen.

```

- (CGRect)frameForFlashlightButton {

```

```
    return CGRectZero;
}
```

Call to obtain the flashlight button image displayed in the card capture interface when camera flash is turned on.

```
-(UIImage*)imageForFlashlightButton{
    UIImage *image = [UIImage imageNamed:@"FlashlightButton.png"];
    return image;
}
```

Call to obtain the flashlight button image displayed in the card capture interface when camera flash is turned off.

```
-(UIImage*)imageForFlashlightOffButton{
    UIImage *image = [UIImage imageNamed:@"FlashlightOffButton.png"];
    return image;
}
```

Call to obtain the help image displayed in the card capture interface

```
-(UIImage*)imageForHelpImageView{
    UIImage *image = [UIImage imageNamed:@"PDF417"];
    return [image imageByApplyingAlpha:0.7];
}
```

Call to obtain the help image position in the screen.

```
-(CGRect)frameForHelpImageView{
    UIImage *image = [UIImage imageNamed:@"PDF417"];
    CGRect frame = CGRectMake(self.view.frame.size.width/2 - image.size.width/2,
self.view.frame.size.height/2 - image.size.height/3 , image.size.width, image.size.height);
    return frame;
}
```

Call to obtain the watermark Message displayed in the card capture interface

```
-(NSString *)stringForWatermarkLabel{
    NSString *string = @"Powered by Acuant";
    return string;
}
```

Call to obtain the watermark label position in the screen.

```
-(CGRect)frameForWatermarkImageView{
    UIImage *image = [UIImage imageNamed:@"Logo.png"];
    CGRect frame = CGRectMake(self.view.frame.size.width/2 - image.size.width/2,
self.view.frame.size.height/2 - image.size.height/2 + 20 , image.size.width, image.size.height);

    return frame;
}
```

Call to obtain the barcode error message displayed in the barcode capture interface

```
-(UIDeviceOrientation)orientationForBarcodeErrorMessage{
    return UIDeviceOrientationPortrait;
}
```

Smart from the start

```
}
```

Call to obtain the barcode error message displayed in the barcode capture interface

```
- (NSString *)stringForBarcodeErrorMessage{
    NSString *string = @"Unable to scan the barcode?";
    return string;
}
```

Call to obtain the barcode title error displayed in the barcode capture interface

```
- (NSString *)stringForBarcodeTitleError{
    NSString *string = @"Title Sample";
    return string;
}
```

Call to obtain the time elapse to appear in the barcode capture interface

```
- (int)timeForBarcodeErrorMessage{
    return 10;
}
```

Call to set if the error message is hidden or not.

```
- (BOOL)isHiddenBarcodeErrorMessage{
    return YES;
}
```

Call to obtain the barcode button text for the second button displayed in the barcode alert.

```
- (NSString *)stringForBarcodeFirstButton{
    NSString *string = @"Yes";
    return string;
}
```

Call to obtain the barcode button text for the second button displayed in the barcode alert.

```
-(NSString *)stringForBarcodeSecondButton{
    NSString *string = @"Try Again";
    return string;
}
```

7 Processing a card

A SDK Configuration for card capture interface.

a In the header file where you'll be doing the parsing, add the following import.

```
#import <AcuantMobileSDK/AcuantMobileSDKController.h>
```


- b In the same header file, implement the `AcuantMobileSDKControllerProcessingDelegate`.

```
@interface ISGViewController () <AcuantMobileSDKControllerCapturingDelegate,
AcuantMobileSDKControllerProcessingDelegate>
```

B Card processing method.

- a For Driver's License Cards

In order to setup `AcuantCardTypeDriverLicenseCard`, set the following values.

```
- (IBAction)sendRequest:(id)sender {
    self.view.userInteractionEnabled = NO;
    [SVProgressHUD showWithStatus:@"Sending Request"];

    //Obtain the front side of the card image
    UIImage *frontSideImage = [self frontSideCardImage];
    //Obtain the back side of the card image
    UIImage *backSideImage =[self backSideCardImage];

    //Obtain the default AcuantCardProcessRequestOptions object for the type of card you want to process
    (Driver's License card for this example)
    AcuantCardProcessRequestOptions *options = [AcuantCardProcessRequestOptions
defaultRequestOptionsForCardType: AcuantCardTypeDriversLicenseCard];

    //Optionally, configure the options to the desired value
    options.autoDetectState = YES;
    options.stateID = -1;
    options.reformatImage = YES;
    options.reformatImageColor = 0;
    options.DPI = 150.0f;
    options.cropImage = NO;
    options.faceDetection = YES;
    options.signatureDetection = YES;
    options.region = _regionID;
    options.sourceImage = 101;

    // Now, perform the request
    [_instance processFrontCardImage:frontSideImage
BackCardImage:backSideImage
andStringData:_barcodeString
withDelegate:self
withOptions:options];
}
```

Explanation of the parameters:

region - Integer parameter for the Region ID. Parameter value -

United States – 0
 Australia – 4
 Asia – 5
 Canada – 1
 America – 2
 Europe – 3
 Africa – 7
 General Documents – 6

autoDetectState - Boolean value. True – SDK will auto detect the state of the ID. False – SDK wont auto detect the state of the ID and will use the value of ProcState integer.

stateID - Integer value of the state to which ID belongs to. If AutoDetectState is true, SDK automatically detects the state of the ID and stateID value is ignored. If AutoDetectState is false, SDK uses stateID integer value for processing. For a complete list of the different countries supported by the SDK and their different State integer values, please see Appendix F of ScanW document - <http://www.id-reader.com/ftp/applications/sdk/docs/ScanW.pdf>

faceDetection - Boolean value. True - Return face image. False – Won't return face image.

signatureDetection - Boolean value. True – Return signature image. False – Won't return signature image.

reformatImage - Boolean value. True – Return formatted processed image. False – Won't return formatted image. Values of ReformatImageColor and ReformatImageDpi will be ignored.

reformatImageColor - Integer value specifying the color value to reformat the image. Values –
 Image same color – 0
 Black and White – 1
 Gray scale 256 – 2
 Color 256 – 3
 True color – 4
 Enhanced Image – 5

DPI - Integer value up to 600. Reformats the image to the provided DPI value. Size of the image will depend on the DPI value. Lower value (150) is recommended to get a smaller image.

cropImage – Boolean value. When true, cloud will crop the RAW image. Boolean value. Since MobileSDK crops the image, leave this flag to false.

sourceImage – Define the source or type of image.
 MobileSDK – 101

b For Medical Insurance Cards

In order to setup AcuantCardTypeMedicalInsuranceCard, just set the following values.

```
- (IBAction)sendRequest:(id)sender {
    self.view.userInteractionEnabled = NO;
    [SVProgressHUD showWithStatus:@"Sending Request"];
```

```
//Obtain the front side of the card image
UIImage *frontSideImage = [self frontSideCardImage];
//Optionally, Obtain the back side of the image
UIImage *backSideImage =[self backSideCardImage];

//Obtain the default AcuantCardProcessRequestOptions object for the type of card you want to process
(Medical Insurance card for this example)
AcuantCardProcessRequestOptions *options = [AcuantCardProcessRequestOptions
defaultRequestOptionsForCardType: AcuantCardTypeMedicalInsuranceCard];

//Optionally, configure the options to the desired value
options.reformatImage = YES;
options.reformatImageColor = 0;
options.DPI = 150.0f;
options.cropImage = NO;

// Now, perform the request
[_instance processFrontCardImage:frontSideImage
BackCardImage:backSideImage
andStringData:nil
withDelegate:self
withOptions:options];
}
```

Explanation of the parameters:

reformatImage - Boolean value. True – Return formatted processed image. False – Won't return formatted image. Values of ReformatImageColor and ReformatImageDpi will be ignored.

reformatImageColor - Integer value specifying the color value to reformat the image. Values –
Image same color – 0
Black and White – 1
Gray scale 256 – 2
Color 256 – 3
True color – 4
Enhanced Image – 5

DPI - Integer value up to 600. Reformats the image to the provided DPI value. Size of the image will depend on the DPI value. Lower value (150) is recommended to get a smaller image.

cropImage – Boolean value. When true, cloud will crop the RAW image. Boolean value. Since MobileSDK crops the image, leave this flag to false.

c For Passport

In order to setup AcuantCardTypePassportCard, just set the following values.

```
- (IBAction)sendRequest:(id)sender {
self.view.userInteractionEnabled = NO;
[SVProgressHUD showWithStatus:@"Sending Request"];
```

Smart from the start

```
//Obtain the front side of the card image
UIImage *frontSideImage = [self frontSideCardImage];

//Obtain the default AcuantCardProcessRequestOptions object for the type of card you want to process
(Passport card for this example)
AcuantCardProcessRequestOptions *options = [AcuantCardProcessRequestOptions
defaultRequestOptionsForCardType: AcuantCardTypePasssपोर्टCard];

//Optionally, configure the options to the desired value
options.reformatImage = YES;
options.reformatImageColor = 0;
options.DPI = 150.0f;
options.cropImage = NO;
options.faceDetection = YES;
options.signatureDetection = YES;
options.sourceImage = 101;

// Now, perform the request
[_instance processFrontCardImage:frontSideImage
BackCardImage:nil
andStringData:nil
withDelegate:self
withOptions:options];
}
```

Explanation of the parameters:

faceDetection - Boolean value. True - Return face image. False – Won't return face image.

signatureDetection - Boolean value. True – Return signature image. False – Won't return signature image.

reformatImage - Boolean value. True – Return formatted processed image. False – Won't return formatted image. Values of ReformatImageColor and ReformatImageDpi will be ignored.

reformatImageColor - Integer value specifying the color value to reformat the image. Values –
Image same color – 0
Black and White – 1
Gray scale 256 – 2
Color 256 – 3
True color – 4
Enhanced Image – 5

DPI - Integer value up to 600. Reformats the image to the provided DPI value. Size of the image will depend on the DPI value. Lower value (150) is recommended to get a smaller image.

cropImage – Boolean value. When true, cloud will crop the RAW image. Boolean value. Since MobileSDK crops the image, leave this flag to false.

Smart from the start

sourceImage – Define the source or type of image.
MobileSDK – 101

C AcuantMobileSDKControllerProcessingDelegate protocol to handle the processing.

a For Driver's License Cards

If using the AcuantCardTypeDriversLicenseCard, add the following code:

```
#pragma mark -
#pragma mark CardProcessing Delegate
-(void)didFinishProcessingCardWithResult:(AcuantCardResult *)result{
    self.view.userInteractionEnabled = YES;
    [SVProgressHUD dismiss];
    NSString *message;
    UIImage *faceimage;
    UIImage *signatureImage;
    UIImage *frontImage;
    UIImage *backImage;
    AcuantDriversLicenseCard *data = (AcuantDriversLicenseCard*)result;
    message [NSString stringWithFormat:@"First Name - %@ \nMiddle Name - %@ \nLast Name - %@ \nName Suffix - %@ \nAuthentication Result - %@ \nAuthentication Summary - %@ \nID - %@ \nLicense - %@ \nDOB Long - %@ \nDOB Short - %@ \nDate Of Birth Local - %@ \nIssue Date Long - %@ \nIssue Date Short - %@ \nIssue Date Local - %@ \nExpiration Date Long - %@ \nExpiration Date Short - %@ \nEye Color - %@ \nHair Color - %@ \nHeight - %@ \nWeight - %@ \nAddress - %@ \nAddress 2 - %@ \nAddress 3 - %@ \nAddress 4 - %@ \nAddress 5 - %@ \nAddress 6 - %@ \nCity - %@ \nZip - %@ \nState - %@ \nCounty - %@ \nCountry Short - %@ \nCountry Long - %@ \nClass - %@ \nRestriction - %@ \nSex - %@ \nAudit - %@ \nEndorsements - %@ \nFee - %@ \nCSC - %@ \nSigNum - %@ \nText1 - %@ \nText2 - %@ \nText3 - %@ \nType - %@ \nDoc Type - %@ \nFather Name - %@ \nMother Name - %@ \nNameFirst_NonMRZ - %@ \nNameLast_NonMRZ - %@ \nNameLast1 - %@ \nNameLast2 - %@ \nNameMiddle_NonMRZ - %@ \nNameSuffix_NonMRZ - %@ \nDocument Detected Name - %@ \nDocument Detected Name Short - %@ \nNationality - %@ \nOriginal - %@ \nPlaceOfBirth - %@ \nPlaceOfIssue - %@ \nSocial Security - %@ \nIsAddressCorrected - %d \nIsAddressVerified - %d", data.nameFirst, data.nameMiddle, data.nameLast, data.nameSuffix, data.authenticationResult, [self arrayToString:data.authenticationResultSummaryList], data.licenceId, data.license, data.dateOfBirth4, data.dateOfBirth, data.dateOfBirthLocal, data.issueDate4, data.issueDate, data.issueDateLocal, data.expirationDate4, data.expirationDate, data.eyeColor, data.hairColor, data.height, data.weight, data.address, data.address2, data.address3, data.address4, data.address5, data.address6, data.city, data.zip, data.state, data.county, data.countryShort, data.idCountry, data.licenceClass, data.restriction, data.sex, data.audit, data.endorsements, data.fee, data.CSC, data.sigNum, data.text1, data.text2, data.text3, data.type, data.docType, data.fatherName, data.motherName, data.nameFirst_NonMRZ, data.nameLast_NonMRZ, data.nameLast1, data.nameLast2, data.nameMiddle_NonMRZ, data.nameSuffix_NonMRZ, data.documentDetectedName, data.documentDetectedNameShort, data.nationality, data.original, data.placeOfBirth, data.placeOfIssue, data.socialSecurity, data.isAddressCorrected, data.isAddressVerified];
}
```

```
if (_region == AcuantCardRegionUnitedStates || _region == AcuantCardRegionCanada) {
```

```

        message = [NSString stringWithFormat:@"%s@ \nIsBarcodeRead - %hhd \nIsIDVerified - %hhd \nIsOcrRead - %hhd", message, data.isBarcodeRead, data.isIDVerified, data.isOcrRead];
    }

```

```

    faceimage = [UIImage imageWithData:data.faceImage];
    signatureImage = [UIImage imageWithData:data.signatureImage];
    frontImage = [UIImage imageWithData:data.licenceImage];
    backImage = [UIImage imageWithData:data.licenceImageTwo];
-(void)didFailWithError:(AcuantError *)error{
    self.view.userInteractionEnabled = YES;
    [SVProgressHUD dismiss];
    NSString *message;
    switch (error.errorType) {
        case AcuantErrorTimedOut:
            message = error.errorMessage;
            break;
        case AcuantErrorUnknown:
            message = error.errorMessage;
            break;
        case AcuantErrorUnableToProcess:
            message = error.errorMessage;
            break;
        case AcuantErrorInternalServerError:
            message = error.errorMessage;
            break;
        case AcuantErrorCouldNotReachServer:
            message = error.errorMessage;
            break;
        case AcuantErrorUnableToAuthenticate:
            message = error.errorMessage;
            break;
        case AcuantErrorAutoDetectState:
            message = error.errorMessage;
            break;
        case AcuantErrorWebResponse:
            message = error.errorMessage;
            break;
        case AcuantErrorUnableToCrop:
            message = error.errorMessage;
            break;
        case AcuantErrorInvalidLicenseKey:
            message = error.errorMessage;
            break;
        case AcuantErrorInactiveLicenseKey:
            message = error.errorMessage;
            break;
        case AcuantErrorAccountDisabled:
            message = error.errorMessage;
            break;
        case AcuantErrorOnActiveLicenseKey:
            message = error.errorMessage;

```

Smart from the start

acuantcorp.com

6167 Bristol Parkway Culver City, California 213.867.2625
 Suite 220 90030

```

        break;
    case AcuantErrorValidatingLicensekey:
        message = error.errorMessage;
        break;
    case AcuantErrorCameraUnauthorized:
        message = error.errorMessage;
        break;
    default:
        break;
}
[UIAlertController showSimpleAlertWithTitle:@"AcuantiOSMobileSDK"
                 Message:message
                 FirstButton:ButtonOK
                 SecondButton:nil
                 FirstHandler:^(UIAlertAction *action) {
    if (tag == 1) {
        _sideTouch = BackSide;
        _isCameraTouched = YES;
        [self showCameraInterface];
    } else if (tag == 7388467) {
        [[UIApplication sharedApplication] openURL:[NSURL
URLWithString:UIApplicationOpenSettingsURLString]];
    }
}
                 SecondHandler:nil
                 Tag:tag
                 ViewController:self];
}

```

b For Medical Insurance Cards

If using the AcuantCardTypeMedicalInsuranceCard, add the following code:

```

#pragma mark -
#pragma mark CardProcessing Delegate
-(void)didFinishProcessingCardWithResult:(AcuantCardResult *)result{
    self.view.userInteractionEnabled = YES;
    [SVProgressHUD dismiss];
    NSString *message;
    UIImage *faceimage;
    UIImage *signatureImage;
    UIImage *frontImage;
    UIImage *backImage;
    AcuantMedicalInsuranceCard *data = (AcuantMedicalInsuranceCard*)result;
    message=[NSString stringWithFormat:@"First Name - %@ \nLast Name - %@ \nMiddle Name - %@
\nMemberID - %@ \nGroup No. - %@ \nContract Code - %@ \nCopay ER - %@ \nCopay OV - %@
\nCopay SP - %@ \nCopay UC - %@ \nCoverage - %@ \nDate of Birth - %@ \nDeductible - %@
\nEffective Date - %@ \nEmployer - %@ \nExpire Date - %@ \nGroup Name - %@ \nIssuer Number -
%@ \nOther - %@ \nPayer ID - %@ \nPlan Admin - %@ \nPlan Provider - %@ \nPlan Type - %@ \nRX

```

```
Bin - %@ \nRX Group - %@ \nRX ID - %@ \nRX PCN - %@ \nTelephone - %@ \nWeb - %@ \nEmail
- %@ \nAddress - %@ \nCity - %@ \nZip - %@ \nState - %@" data.firstName, data.lastName,
data.middleName, data.memberId, data.groupNumber, data.contractCode, data.copayEr, data.copayOv,
data.copaySp, data.copayUc, data.coverage, data.dateOfBirth, data.deductible, data.effectiveDate,
data.employer, data.expirationDate, data.groupName, data.issuerNumber, data.other, data.payerId,
data.planAdmin, data.planProvider, data.planType, data.rxBin, data.rxGroup, data.rxD, data.rxDcn,
data.phoneNumber, data.webAddress, data.email, data.fullAddress, data.city, data.zip, data.state];
```

```
frontImage = [UIImage imageWithData:data.reformattedImage];
backImage = [UIImage imageWithData:data.reformattedImageTwo];
```

```
-(void)didFailWithError:(AcuantError *)error {
    self.view.userInteractionEnabled = YES;
    [SVProgressHUD dismiss];
    NSString *message;
    switch (error.errorType) {
        case AcuantErrorTimedOut:
            message = error.errorMessage;
            break;
        case AcuantErrorUnknown:
            message = error.errorMessage;
            break;
        case AcuantErrorUnableToProcess:
            message = error.errorMessage;
            break;
        case AcuantErrorInternalServerError:
            message = error.errorMessage;
            break;
        case AcuantErrorCouldNotReachServer:
            message = error.errorMessage;
            break;
        case AcuantErrorUnableToAuthenticate:
            message = error.errorMessage;
            break;
        case AcuantErrorAutoDetectState:
            message = error.errorMessage;
            break;
        case AcuantErrorWebResponse:
            message = error.errorMessage;
            break;
        case AcuantErrorUnableToCrop:
            message = error.errorMessage;
            break;
        case AcuantErrorInvalidLicenseKey:
            message = error.errorMessage;
            break;
        case AcuantErrorInactiveLicenseKey:
            message = error.errorMessage;
            break;
        case AcuantErrorAccountDisabled:
```

Smart from the start


```

        message = error.errorMessage;
        break;
    case AcuantErrorOnActiveLicenseKey:
        message = error.errorMessage;
        break;
    case AcuantErrorValidatingLicensekey:
        message = error.errorMessage;
        break;
    case AcuantErrorCameraUnauthorized:
        message = error.errorMessage;
        break;

    default:
        break;
}
[UIAlertController showSimpleAlertWithTitle:@"AcuantiOSMobileSDK"
                    Message:message
                    FirstButton:ButtonOK
                    SecondButton:nil
                    FirstHandler:^(UIAlertAction *action) {
                        if (tag == 1) {
                            _sideTouch = BackSide;
                            _isCameraTouched = YES;
                            [self showCameraInterface];
                        } else if (tag == 7388467) {
                            [[UIApplication sharedApplication] openURL:[NSURL
                                URLWithString:UIApplicationOpenSettingsURLString]];
                        }
                    }
                    SecondHandler:nil
                    Tag:tag
                    ViewController:self];
}

```

c For Passport.

If using the `AcuantCardTypePassportCard`, add the following code:

```

#pragma mark -
#pragma mark CardProcessing Delegate
-(void)didFinishProcessingCardWithResult:(AcuantCardResult *)result{
    self.view.userInteractionEnabled = YES;
    [SVProgressHUD dismiss];
    NSString *message;
    UIImage *faceimage;
    UIImage *signatureImage;
    UIImage *frontImage;
    UIImage *backImage;
    AcuantPassaportCard *data = (AcuantPassaportCard*)result;
    message=[NSString stringWithFormat:@"First Name - %@ \nMiddle Name - %@ \nLast Name - %@ \nAuthentication Result - %@ \nAnunthentication Summary - %@ \nPassport Number - %@ \nPersonal

```

Smart from the start

```
Number - %@ \nSex - %@ \nCountry Long - %@ \nNationality Long - %@ \nDOB Long - %@ \nIssue
Date Long - %@ \nExpiration Date Long - %@ \nPlace of Birth - %@", data.nameFirst,
data.nameMiddle, data.nameLast, data.authenticationResult, [self
arrayToString: data.authenticationResultSummaryList], data.passportNumber, data.personalNumber,
data.sex, data.countryLong, data.nationalityLong, data.dateOfBirth4, data.issueDate4,
data.expirationDate4, data.end_POB];
```

```
faceimage = [UIImage imageWithData: data.faceImage];
frontImage = [UIImage imageWithData: data.passportImage];
```

```
-(void)didFailWithError:(AcuantError *)error {
    self.view.userInteractionEnabled = YES;
    [SVProgressHUD dismiss];
    NSString *message;
    switch (error.errorType) {
        case AcuantErrorTimedOut:
            message = error.errorMessage;
            break;
        case AcuantErrorUnknown:
            message = error.errorMessage;
            break;
        case AcuantErrorUnableToProcess:
            message = error.errorMessage;
            break;
        case AcuantErrorInternalServerError:
            message = error.errorMessage;
            break;
        case AcuantErrorCouldNotReachServer:
            message = error.errorMessage;
            break;
        case AcuantErrorUnableToAuthenticate:
            message = error.errorMessage;
            break;
        case AcuantErrorAutoDetectState:
            message = error.errorMessage;
            break;
        case AcuantErrorWebResponse:
            message = error.errorMessage;
            break;
        case AcuantErrorUnableToCrop:
            message = error.errorMessage;
            break;
        case AcuantErrorInvalidLicenseKey:
            message = error.errorMessage;
            break;
        case AcuantErrorInactiveLicenseKey:
            message = error.errorMessage;
            break;
        case AcuantErrorAccountDisabled:
            message = error.errorMessage;
```

Smart from the start

```

        break;
    case AcuantErrorOnActiveLicenseKey:
        message = error.errorMessage;
        break;
    case AcuantErrorValidatingLicensekey:
        message = error.errorMessage;
        break;
    case AcuantErrorCameraUnauthorized:
        message = error.errorMessage;
        break;
    default:
        break;
}
[UIAlertController showSimpleAlertWithTitle:@"AcuantiOSMobileSDK"
                    Message:message
                    FirstButton:ButtonOK
                    SecondButton:nil
                    FirstHandler:^(UIAlertAction *action) {
                        if (tag == 1) {
                            _sideTouch = BackSide;
                            _isCameraTouched = YES;
                            [self showCameraInterface];
                        } else if (tag == 7388467) {
                            [[UIApplication sharedApplication] openURL:[NSURL
URLWithString:UIApplicationOpenSettingsURLString]];
                        }
                    }
                    SecondHandler:nil
                    Tag:tag
                    ViewController:self];
}

//Function to convert Authentication Summary list to a single NSString object
-(NSString*)arrayToString:(NSArray*)array {
    NSString* retStr = @"";
    for(NSString* str in array){
        if([retStr isEqualToString:@""]){
            retStr = str;
        } else {
            retStr = [NSString stringWithFormat:@"%s,%s",retStr,str];
        }
    }
    return retStr;
}

```

Note : For Driving license and Passport , in order to see AssureID results, please look for these two fields : “AuthenticationResult”, “AuthenticationResultSummary”.

“AuthenticationResult” can have either of the following values: Success , Failed ,Attention

“AuthenticationResultSummary” will be empty for Success and Failed results. When “AuthenticationResult” will have value “Attention”, “AuthenticationResultSummary” will contain the reason for “attention”.

8 Facial Recognition and Match Feature

Acuant FRM (Facial Recognition Match) is a person authentication solution for mobile devices based on biometric face recognition.

Acuant FRM

- Opens the front camera
- Ensures the user is correctly placed in front of the camera
- Detects a live person
- Detects spoofing attacks by presenting eye blink challenge
- Acquires biometric samples
- Verifies the identity of a user
- All the steps are done in real time.

Benefits of Acuant FRM

- Helps in reducing fraud by matching the face biometrics to the face image on the driver’s license or passport.
- Easy to integrate
- Secure
- Fast and convenient
- Real time checks and processing within seconds

The Acuant FRM performs following checks to recognize a live face and match face biometrics to the face picture on the driver’s license or passport.

- 1) Face position checks: check that the face is well detected, correctly centered and in a good distance from the camera.
 - a) Distance to person algorithm ensures that person’s face is at optimal distance from the front camera.
 - b) Ensures that person is only presenting frontal face (Side faces are rejected).
- 2) Tracks eye blinks as an added layer to check for face liveness and avoid spoofing attacks.
- 3) Captures face biometrics and matches it to the face picture on the driver’s license or passport.

Following are the APIs/Classes to use the Facial Match feature.

a. AcuantFacialCaptureDelegate

This is the delegate to be used to get the call back from the SDK interface. It has two protocols

- i. `-(void)didFinishFacialRecognition:(UIImage*)image;`
This is called when a live face is successfully recognized. The parameter “image” contains the face image recognized by facial recognition.
- ii. `-(void)didCancelFacialRecognition`
This is called when the user cancels facial recognition.
- iii. `-(int)facialRecognitionTimeout{
 return 20;
}`

Sets the Facial recognition timeout in seconds.
- iv. `-(void)didTimeoutFacialRecognition:(UIImage*)lastImage`
Control comes here when user taps on “Yes” on the facial timeout alert. The argument “lastImage” is the last frame image before timeout
- v. `-(UIImage*)imageForFacialBackButton`
API to provide custom image for Facial screen “Back” button
- vi. `-(NSAttributedString*) messageToBeShownAfterFaceRectangleAppears;`
API to display custom message after red rectangle appears.
- vii. `-(CGRect)frameWhereMessageToBeShownAfterFaceRectangleAppears;`
API to specify where messageToBeShownAfterFaceRectangleAppears appears on the camera screen.

b. AcuantFacialRecognitionViewController

This class has the following utility method which can be called to present the facial recognition interface.

- i. `+(id)presentFacialCaptureInterfaceWithDelegate:(id<AcuantFacialCaptureDelegate>)delegate withSDK:(AcuantMobileSDKController*)sdkController
inViewController:(UIViewController*)parentVC
withCancelButton:(BOOL)cancelVisible withWaterMark:(NSString*)watermarkText
withBlinkMessage:(NSAttributedString*)message
inRect:(CGRect)rect;`

Following are the input parameters:

- (id<AcuantFacialCaptureDelegate>)delegate : Delegate where the control to be returned.
- :(AcuantMobileSDKController*)sdkController : The SDK controller.
- (UIViewController*)parentVC : The parent view controller which presents the camera interface.
- (BOOL)cancelVisible : Whether to show cancel button or not
- (NSString*)watermarkText : Brand watermark text
- (NSAttributedString*)message : Instruction message (For example “Blink Slowly.”)
- (CGRect)rect : Frame in which instruction to be shown within the camera interface.

c. Facial Match function call

```
/**
Use this method to do facial match.
@param selfieImage The captured selfie Image.
@param IDFaceImage Face Image from ID or Passport card
@param delegate the delegate of the process request
@param options the options of the process request.
@discussion you must always provide a selfieImage and a face image to match
        @discussion use the options object to indicate the type as AcuantCardTypeFacial.
Processing will fail if you don't provide this parameter.
        @discussion you're encourage to provide a delegate to be informed about what happened
with your processing request. You can change the delegate using the
cardProcessingDelegate property of this class.
        @discussion you should call this method only once and wait until your delegate is
informed. If you call this method while we're already processing a card, we'll ignore your
second call.
*/
```

```
-(void)validatePhotoOne:(UIImage *)selfieImage
    withImage:(NSData *) IDFaceImage
    withDelegate:(id<AcuantMobileSDKControllerProcessingDelegate>)delegate
    withOptions:(AcuantCardProcessRequestOptions*)option;
```

Below is an example of facial match function call :

```
//Face Image
UIImage *selfImage = image;
//DL/Passport Photo
NSData *faceImageData = _resultViewController.faceImageData;

//Obtain the default AcuantCardProcessRequestOptions object for the type of card you
want to process (License card for this example)
AcuantCardProcessRequestOptions *options = [AcuantCardProcessRequestOptions
```

```
defaultRequestOptionsForCardType:AcuantCardTypeFacial];
```

```
[self.instance validatePhotoOne:selfieImage withImage:faceImageData  
withDelegate:<Delegate the control should come back> withOptions:options];
```

- i. The first parameter is the selfie image returned in the callback -
(void)didFinishFacialRecognition:(UIImage*)image;
- ii. The second parameter is the face image from the ID/Passport against which the face image needs to be matched.
- iii. Delegate is the web service delegate where the control will be after the function call returns.
- iv. AcuantCardProcessRequestOptions is the last argument which is initialized with card type as AcuantCardTypeFacial as shown above.

The following delegate method will be called after the function call returns

```
- (void)didFinishValidatingImageWithResult:(AcuantCardResult*)cardResult {  
    AcuantFacialData* result =(AcuantFacialData*)cardResult;  
}
```

- d. AcuantFacialData
Following are the parameters.

```
@property (nonatomic, assign) BOOL isMatch ; // If both images matched.
```

```
@property (nonatomic, assign) BOOL isFacialEnabled; // If facial feature is enabled.
```

```
@property (nonatomic, assign) BOOL faceLivelinessDetection; // If a live face was  
detected.
```

```
@property (nonatomic, strong) NSString *transactionId; // Facial match transaction id
```

```
@property (nonatomic, strong) NSString *facialMatchConfidenceRating; // Confidence  
level out of 100
```

```
@property (nonatomic, strong) NSString *errorMessage; // Any service error description.  
If the transaction has gone through successfully then this field will be nil.
```

9 Error Types

```
AcuantErrorCouldNotReachServer = 0, //check internet connection
```

```
AcuantErrorUnableToAuthenticate = 1, //keyLicense are incorrect
```

```
AcuantErrorUnableToProcess = 2, //image received by the server was unreadable, take a new one
```

```
AcuantErrorInternalServerError = 3, //there was an error in our server, try again later
```

Smart from the start

AcuantErrorUnknown = 4, //there was an error but we were unable to determine the reason, try again later
 AcuantErrorTimedOut = 5, //request timed out, may be because internet connection is too slow
 AcuantErrorAutoDetectState = 6, //Error when try to detect the state
 AcuantErrorWebResponse = 7, //the json was received by the server contain error
 AcuantErrorUnableToCrop = 8, //the received image can't be cropped.
 AcuantErrorInvalidLicenseKey = 9, //Is an invalid license key.
 AcuantErrorInactiveLicenseKey = 10, //Is an inactive license key.
 AcuantErrorAccountDisabled = 11, //Is an account disabled.
 AcuantErrorOnActiveLicenseKey = 12, //there was an error on activation key.
 AcuantErrorValidatingLicensekey = 13, //The validation is still in process.
 AcuantErrorCameraUnauthorized = 14, //The privacy settings are preventing us from accessing your camera.
 AcuantErrorOpenCamera = 15 //There are an error when the camera is opened.

10 Miscellaneous

A How to check version of the SDK.

Open the AcuantMobileSDK.framework
 Open the Version folder.
 Open the folder with number version.
 Open the Resources folder
 Open the Info.plist file inside you can find the version number

11 Change Log

Acuant iOS MobileSDK version 4.9.5.1

Changes:

- Modified API signature
 - +(id)presentFacialCaptureInterfaceWithDelegate
 (id<AcuantFacialCaptureDelegate>)delegate withSDK:
 (AcuantMobileSDKController*)sdkController inViewController:
 (UIViewController*)parentVC
 withCancelButton:(BOOL)cancelVisible
 withWaterMark:(NSString*)watermarkText withBlinkMessage:
 (NSAttributedString*)message inRect:(CGRect)rect;
- Made the following barcode delegate method optional
 - (void)didCaptureCropImage:(UIImage *)cardImage
 andData:(NSString*)data scanBackSide:(BOOL)scanBackSide