BASES DE DATOS

FES Aragón ICO

Dr. Omar Mendoza González

LMD - Sentencias de selección o consultas

```
SELECT
  [ALL | DISTINCT | DISTINCTROW ]
   [HIGH PRIORITY]
   [STRAIGHT JOIN]
   [SQL SMALL RESULT] [SQL BIG RESULT] [SQL BUFFER RESULT]
   [SQL CACHE | SQL NO CACHE] [SQL CALC FOUND ROWS]
  select expr[, select expr...]
  [FROM table references
  [WHERE where condition]
  [GROUP BY {col_name | expr | position}]
   [ASC | DESC], ... [WITH ROLLUP]]
  [HAVING where condition]
  [ORDER BY {col_name | expr | position}
   [ASC | DESC], ...]
  [LIMIT {[offset,] row count | row count OFFSET offset}]
  [PROCEDURE procedure name(argument list)]
  [INTO OUTFILE 'file_name' export_options
   | INTO DUMPFILE 'file name'
   | INTO var name [, var name]]
  [FOR UPDATE | LOCK IN SHARE MODE]]
```

Select Básico

SELECT * FROM alumnos;

- Clausulas del comando SELECT
 - DISTINCT
 - FROM
 - WHERE
 - GROUP BY
 - HAVING
 - ORDER BY
 - LIMIT

Seleccionar renglones (SELECCION)

```
SELECT * FROM alumnos WHERE status_alu = 'BA';
```

SELECT * FROM alumnos WHERE status_alu = 'BA' AND sexo = 'F';

Seleccionar columnas (PROYECCION)

SELECT clave_alu, ap_paterno, ap_materno, nombre, curp

FROM alumnos;

SELECT clave_alu, status_alu FROM alumnos;

Seleccionar columnas y renglones (PROYECCION y PROYECCION)

SELECT clave_alu, ap_paterno, ap_materno, nombre, curp

FROM alumnos

WHERE curp = "AND status_alu = 'BA';

Ordenar Resultados

SELECT clave_alu, ap_paterno, ap_materno, nombre, status_alu

FROM alumnos

ORDER BY ap_paterno, ap_materno, nombre;

Ordenar Resultados Descendente

SELECT clave_alu, ap_paterno, ap_materno, nombre, status_alu

FROM alumnos

ORDER BY status_alu DESC, ap_paterno, ap_materno, nombre;

DISTINCT

SELECT nombre FROM alumnos ORDER BY 1;

SELECT DISTINCT nombre FROM alumnos ORDER BY 1;

DISTINCT

SELECT nombre, ap_paterno FROM alumnos ORDER BY 1;

SELECT DISTINCT nombre, ap_paterno FROM alumnos ORDER BY 1;

Resultados a Archivos

```
SELECT clave alu, nombre
INTO OUTFILE '/tmp/resultF.txt'
     FIELDS TERMINATED BY ','
OPTIONALLY
     ENCLOSED BY ""
     LINES TERMINATED BY '\n'
FROM alumnos
WHERE sexo = 'F';
```

LIMIT

SELECT * FROM alumnos LIMIT 1,10;

SELECT clave_alu, ap_paterno, ap_materno, nombre, curp

FROM alumnos

WHERE curp = "AND status_alu <> 'BA'
ORDER BY 1

LIMIT 100, 10;

Agrupamientos

SELECT ciudad, COUNT(*) FROM alumnos GROUP BY ciudad;

SELECT sexo, COUNT(*) FROM alumnos GROUP BY sexo;

Agrupamientos

SELECT sexo, ciudad, COUNT(*)
FROM alumnos
GROUP BY sexo, ciudad;

Selección de resultados de Agrupamientos

SELECT sexo, ciudad, COUNT(*)
FROM alumnos
GROUP BY sexo, ciudad
HAVING COUNT(*) >= 10;