

AdBuster 2.0 PRO

A prototype for local TV volume stabilization

AdBuster 2.0 PRO is a Windows prototype exploring how audio analysis can be combined with automatic TV volume control. It detects loudness patterns through a microphone and, when a Broadlink device is configured, can send infrared commands to the TV.

How does it work?

1. A microphone picks up the TV's audio for real-time analysis.
2. AdBuster analyzes loudness and changes in the audio, then decides whether to respond.
3. With a configured Broadlink device, the application can send a volume-down command.
4. When the audio returns to its usual level, the application can restore the volume.

The PC and Broadlink device must be connected to the same local network. The PC can use Wi-Fi or Ethernet.

What does the prototype explore?

The project brings together:

- real-time microphone audio analysis,
- CEPA logic for interpreting audio patterns,
- machine-learning components,
- infrared control through Broadlink.

Models can be trained offline using data collected during or after a session. Training does not take place in real time during audio monitoring.

Data and privacy

AdBuster does not save raw microphone recordings, such as WAV files. Derived audio measurements may be collected locally for model development; these measurements are not audio recordings. Data is not uploaded to the cloud.

Project status

AdBuster 2.0 PRO is a prototype released for testing and evaluation. Feedback and suggestions for improvement are welcome. Results may depend on the microphone, TV, configuration, and Broadlink device.

The public PRO package contains compiled application files and supporting resources. The source code is not included. Use of the package is subject to the PRO license.

Project and documentation: [GitHub — AdBuster WinApp](#)

Contact: [Contact form](#)