

Parallel & Distributed Computing: Lecture 12

Alberto Paoluzzi

November 14, 2017

Project: Add-ons modules to LARLIB.jl

Example of Python to Julia conversion

- 1 Step one: removal of dependencies from `larlib.largrid.py`
- 2 Step two: syntactic translation of functions
- 3 Step three: integration test
- 4 Step four: Debug, debug, debug

Step one: removal of dependencies from
`larlib.largrid.py`

Look for function definitions

Get the significant subset

```
def larModelProduct(twoModels):  
def grid_0(n):  
def grid_1(n):  
def larGrid(n):  
def index2addr (shape):  
def binaryRange(n):  
def larVertProd(vertLists):  
def filterByOrder(n):  
def larCellProd(cellLists):  
def larGridSkeleton(shape):  
def larImageVerts(shape):  
def larCuboids(shape, full=False):  
def mergeSkeletons(larSkeletons):
```

From largrid.py To largrid-test.py 1/5

Original code

```
def grid0(n):  
    cells = AA(LIST)(range(n+1))  
    return cells  
  
def grid1(n):  
    ints = range(n+1)  
    cells = TRANS([ints[:-1],ints[1:]])  
    return cells
```

From largrid.py To largrid-test.py 1/5

Original code

```
def grid0(n):
    cells = AA(LIST)(range(n+1))
    return cells

def grid1(n):
    ints = range(n+1)
    cells = TRANS([ints[:-1],ints[1:]])
    return cells
```

Removed dependencies in python

```
def grid_0(n):
    return [[i] for i in xrange(n+1)]

def grid_1(n):
    return [[i,i+1] for i in xrange(n)]
```

From largrid.py To largrid-test.py 2/5

Original code

```
def index2addr (shape):  
    n = len(shape)  
    shape = shape[1:]+[1]  
    weights = [PROD(shape[k:]) for k in range(n)]  
    def index2addr0 (multindex):  
        return INNERPROD([multindex, weights])  
    return index2addr0
```


From `largrid.py` To `largrid-test.py` 2/5

Original code

```
def index2addr (shape):
    n = len(shape)
    shape = shape[1:]+[1]
    weights = [PROD(shape[k:]) for k in range(n)]
    def index2addr0 (multindex):
        return INNERPROD([multindex, weights])
    return index2addr0
```

Removed dependencies

```
def index2addr (shape):
    n = len(shape)
    theShape = shape[1:]+[1]
    weights = [prod(theShape[k:]) for k in xrange(n)]
    def index2addr0 (multiIndex):
        return dot(multiIndex, weights)
    return index2addr0
```

From `largrid.py` To `largrid-test.py` 3/5

Original code

```
def larVertProd(vertLists):  
    return AA(CAT)(CART(vertLists))
```

From `largrid.py` To `largrid-test.py` 3/5

Original code

```
def larVertProd(vertLists):  
    return AA(CAT)(CART(vertLists))
```

Removed dependencies

```
using IterTools
```

```
def larVertProd(vertLists):  
    return [[x[0] for x in v] for v in itertools.product(*vertLists)]
```

From largrid.py To largrid-test.py 4/5

Original code

```
def binaryRange(n):
def larCellProd(cellLists):
    shapes = [len(item) for item in cellLists]
    indices = CART([range(shape) for shape in shapes])
    jointCells = [CART([cells[k] for k, cells in zip(index, cellLists)])
                  for index in indices]
    convert = index2addr([ shape+1 if (len(cellLists[k][0]) > 1) else shape
                          for k, shape in enumerate(shapes) ])
    return [AA(convert)(cell) for cell in jointCells]
```

From largrid.py To largrid-test.py 4/5

Original code

```
def binaryRange(n):
def larCellProd(cellLists):
    shapes = [len(item) for item in cellLists]
    indices = CART([range(shape) for shape in shapes])
    jointCells = [CART([cells[k] for k, cells in zip(index, cellLists)])
                  for index in indices]
    convert = index2addr([ shape+1 if (len(cellLists[k][0]) > 1) else shape
                          for k, shape in enumerate(shapes) ])
    return [AA(convert)(cell) for cell in jointCells]
```

Removed dependencies

```
def larCellProd(cellLists):
    shapes = [len(item) for item in cellLists]
    indices = itertools.product(*[xrange(shape) for shape in shapes])
    def assemblies(index):
        return itertools.product(*[cells[k] for k, cells in zip(index, cellLists)])
    jointCells = [list(assemblies(index)) for index in indices]
    convert = index2addr([ shape+1 if (len(cellLists[k][0]) > 1) else shape
                          for k, shape in enumerate(shapes) ])
    return [map(convert, cell) for cell in jointCells]
```

From largrid.py To largrid-test.py 5/5

Original code

```
def larGridSkeleton(shape):
    n = len(shape)
    def larGridSkeleton0(d):
        components = filterByOrder(n)[d]
        componentCellLists = [AA(APPLY)(zip( AA(larGrid)(shape), (component) ))
                               for component in components]
        return CAT([ larCellProd(cellLists) for cellLists in componentCellLists ])
    return larGridSkeleton0
```

From largrid.py To largrid-test.py 5/5

Original code

```
def larGridSkeleton(shape):
    n = len(shape)
    def larGridSkeleton0(d):
        components = filterByOrder(n)[d]
        componentCellLists = [AA(APPLY)(zip( AA(larGrid)(shape),(component) ))
                                for component in components]
        return CAT([ larCellProd(cellLists) for cellLists in componentCellLists ])
    return larGridSkeleton0
```

Removed dependencies

```
def larGridSkeleton(shape):
    n = len(shape)
    def larGridSkeleton0(d):
        components = filterByOrder(n)[d]
        componentCellLists = [ [apply(f,[x]) for f,x in zip( [larGrid(dim) for dim
                                                                for component in components] ]
        print "componentCellLists =",componentCellLists
        out = [ larCellProd(cellLists) for cellLists in componentCellLists ]
        return list(itertools.chain(*out))
    return larGridSkeleton0
```

Step two: syntactic translation of functions

Language translation 1/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def grid_0(n):  
    return [[i] for i in xrange(n+1)]  
def grid_1(n):  
    return [[i,i+1] for i in xrange(n)]  
def larGrid(n):  
    def larGrid1(d):  
        if d==0: return grid_0(n)  
        elif d==1: return grid_1(n)  
    return larGrid1
```

Language translation 1/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def grid_0(n):
    return [[i] for i in xrange(n+1)]
def grid_1(n):
    return [[i,i+1] for i in xrange(n)]
def larGrid(n):
    def larGrid1(d):
        if d==0: return grid_0(n)
        elif d==1: return grid_1(n)
    return larGrid1
```

Julia translation

```
function grid_0(n)
    return hcat([[i] for i in range(0,n+1)]...) end
function grid_1(n)
    return hcat([[i,i+1] for i in range(0,n)]...) end
function larGrid(n)
    function larGrid1(d)
        if d==0
            return grid_0(n)
        elseif d==1
            return grid_1(n)
        end end
    return larGrid1 end
```

Language translation 1/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def grid_0(n):
    return [[i] for i in xrange(n+1)]
def grid_1(n):
    return [[i,i+1] for i in xrange(n)]
def larGrid(n):
    def larGrid1(d):
        if d==0: return grid_0(n)
        elif d==1: return grid_1(n)
    return larGrid1
```

Julia translation

```
function grid_0(n)
    return hcat([[i] for i in range(0,n+1)]...) end
function grid_1(n)
    return hcat([[i,i+1] for i in range(0,n)]...) end
function larGrid(n)
    function larGrid1(d)
        if d==0
            return grid_0(n)
        elseif d==1
            return grid_1(n)
        end end
    return larGrid1 end
```

Language translation 2/7

[largrid.py-test.py](#) → [largrid-test.jl](#)

transformed code

```
def index2addr (shape):  
    n = len(shape)  
    theShape = shape[1:]+[1]  
    weights = [prod(theShape[k:]) for k in xrange(n)]  
    def index2addr0 (multiIndex):  
        return dot(multiIndex, weights)  
    return index2addr0
```

Language translation 2/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def index2addr (shape):
    n = len(shape)
    theShape = shape[1:]+[1]
    weights = [prod(theShape[k:]) for k in xrange(n)]
    def index2addr0 (multiIndex):
        return dot(multiIndex, weights)
    return index2addr0
```

Julia translation

```
function index2addr(shape)
    n = length(shape)
    theShape = append!(shape[2:end], 1)
    weights = [prod(theShape[k:end]) for k in range(1,n)]
    function index2addr0(multiIndex)
        return dot(collect(multiIndex), weights) + 1
    end
    return index2addr0
end
```

Language translation 3/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def binaryRange(n):
    return ['{0:0'+str(n)+'b}'.format(k) for k in xrange(2**n)]
def larVertProd(vertLists):
    return [[x[0] for x in v] for v in itertools.product(*vertLists)]
def filterByOrder(n):
    terms = [[int(elem) for elem in list(term)] for term in binaryRange(n)]
    return [term for term in terms if sum(term) == k] for k in xrange(n+1)]
```

Language translation 3/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def binaryRange(n):
    return ['{0:0'+str(n)+'b}'.format(k) for k in xrange(2**n)]
def larVertProd(vertLists):
    return [[x[0] for x in v] for v in itertools.product(*vertLists)]
def filterByOrder(n):
    terms = [[int(elem) for elem in list(term)] for term in binaryRange(n)]
    return [[term for term in terms if sum(term) == k] for k in xrange(n+1)]
```

Julia translation

```
using IterTools
function binaryRange(n)
    return [bin(k,n) for k in range(0,2^n)] end
function larVertProd(vertLists)
    coords = [[x[1] for x in v] for v in IterTools.product(vertLists...)]
    return sortcols(hcat(coords...)) end
function filterByOrder(n)
    terms = [[parse{Int8,bit} for bit in convert{Array{Char,1},term}]
              for term in binaryRange(n)]
    return [[term for term in terms if sum(term) == k] for k in range(0,n+1)] end
```

Language translation 4/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def larCellProd(cellLists):
    shapes = [len(item) for item in cellLists]
    indices = itertools.product(*[xrange(shape) for shape in shapes])
    def assemblies(index):
        return itertools.product(*[cells[k] for k, cells in zip(index, cellLists)])
    jointCells = [assemblies(index) for index in indices]
    convert = index2addr([ shape+1 if (len(cellLists[k][0]) > 1) else shape
                          for k, shape in enumerate(shapes) ])
    return [map(convert, cell) for cell in jointCells]
```


Language translation 4/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def larCellProd(cellLists):
    shapes = [len(item) for item in cellLists]
    indices = itertools.product(*[xrange(shape) for shape in shapes])
    def assemblies(index):
        return itertools.product(*[cells[k] for k, cells in zip(index, cellLists)])
    jointCells = [assemblies(index) for index in indices]
    convert = index2addr([ shape+1 if (len(cellLists[k][0]) > 1) else shape
                          for k, shape in enumerate(shapes) ])
    return [map(convert, cell) for cell in jointCells]
```

Julia translation

```
function larCellProd(cellLists)
    shapes = [length(item) for item in cellLists]
    cart = IterTools.product([range(0, shape) for shape in shapes]...)
    indices = hcat([collect(tuple) for tuple in sort(collect(cart))])...
    h = 1
    index = indices[:, h]
    inCart = [collect(cells[k+1]) for (k, cells) in collect(zip(index, cellLists))]
    jointCells = sort(collect(IterTools.product(inCart...)))
    for h in range(2, size(indices, 2))
        index = indices[:, h]
        inCart = [collect(cells[k+1]) for (k, cells) in collect(zip(index, cellLists))]
        jointCells = hcat( jointCells, sort(collect(IterTools.product(inCart...))) )
    end
    convertIt = index2addr([ shape+1 for shape in shapes ])
    [hcat(map(convertIt, jointCells[:, j])...) for j in range(1, size(jointCells, 2))]
```

Language translation 5/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def larImageVerts(shape):  
    def vertexDomain(n):  
        return [[k] for k in xrange(n)]  
    vertLists = [vertexDomain(k+1) for k in shape]  
    vertGrid = larVertProd(vertLists)  
    return vertGrid
```

Language translation 5/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def larImageVerts(shape):
    def vertexDomain(n):
        return [[k] for k in xrange(n)]
    vertLists = [vertexDomain(k+1) for k in shape]
    vertGrid = larVertProd(vertLists)
    return vertGrid
```

Julia translation

```
function larImageVerts(shape)
    function vertexDomain(n)
        return [[k] for k in range(0,n)]
    end
    vertLists = [vertexDomain(k+1) for k in shape]
    vertGrid = larVertProd(vertLists)
    return vertGrid
end
```

Language translation 6/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def larGridSkeleton(shape):
    n = len(shape)
    def larGridSkeleton0(d):
        components = filterByOrder(n)[d]
        componentCellLists = [ [apply(f,[x]) for f,x in zip( [larGrid(dim) for dim
                                                                for component in components ]
                                                                )
                                ]
                                for component in components ]
        print "componentCellLists =",componentCellLists
        out = [ larCellProd(cellLists) for cellLists in componentCellLists ]
        return list(itertools.chain(*out))
    return larGridSkeleton0
```

Language translation 6/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def larGridSkeleton(shape):
    n = len(shape)
    def larGridSkeleton0(d):
        components = filterByOrder(n)[d]
        componentCellLists = [ [apply(f,[x]) for f,x in zip( [larGrid(dim) for dim
                                                                for component in components ]
                                                                )
                                ]
                                for component in components ]
        print "componentCellLists =",componentCellLists
        out = [ larCellProd(cellLists) for cellLists in componentCellLists ]
        return list(itertools.chain(*out))
    return larGridSkeleton0
```

Julia translation

```
function larGridSkeleton(shape)
    n = length(shape)
    function larGridSkeleton0(d)
        components = filterByOrder(n)[d]
        mymap(arr) = [arr[:,k] for k in range(1,size(arr,2))]
        componentCellLists = [ [ mymap(f(x)) for (f,x) in zip( [larGrid(dim) for dim
                                                                for component in components ]
                                                                )
                                ]
                                for component in components ]
        out = [ larCellProd(cellLists) for cellLists in componentCellLists ]
```

Language translation 7/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def larCuboids(shape, full=False):  
    vertGrid = larImageVerts(shape)  
    gridMap = larGridSkeleton(shape)  
    if not full:  
        cells = gridMap(len(shape))  
    else:  
        skeletonIds = xrange(len(shape)+1)  
        cells = [ gridMap(id) for id in skeletonIds ]  
    return vertGrid, cells
```

Language translation 7/7

largrid.py-test.py → largrid-test.jl

transformed code

```
def larCuboids(shape, full=False):
    vertGrid = larImageVerts(shape)
    gridMap = larGridSkeleton(shape)
    if not full:
        cells = gridMap(len(shape))
    else:
        skeletonIds = xrange(len(shape)+1)
        cells = [ gridMap(id) for id in skeletonIds ]
    return vertGrid, cells
```

Julia translation

```
function larCuboids(shape, full=false)
    vertGrid = larImageVerts(shape)
    gridMap = larGridSkeleton(shape)
    if ! full
        cells = gridMap(length(shape)+1)
    else
        skeletonIds = range(1,length(shape)+1)
        cells = [ gridMap(id) for id in skeletonIds ]
    end
```

Step three: integration test

Execute the functions to be exported (API)

```
print(larCuboids(shape, true})
```

Step four: Debug, debug, debug