



# P2

March 27, 2017

## 1 2 Positive Semidefinite Matrix

### 1.1 2-1

Example:

$$\begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix}$$

## 1.2 2-2

Proof:

Let  $M$  be a psd matrix and  $v$  be one of the eigenvector of  $M$  with eigenvalue  $\lambda$ .

By definition of psd we must have  $v^T M v \geq 0$ . Let  $v^T M v = c$ . By definition of eigenvector, we have:

$$v^T (Mv) = c$$

$$v^T \lambda v = c$$

$$\lambda v^T v = c$$

$$\lambda = \frac{c}{||v||}$$

Since  $c \geq 0$  and  $||v|| = 0$  ( $v$  is eigenvector), we must have  $\lambda \geq 0$ .

### 1.3 2-3

Proof:

If  $M = BB^T$  where  $B \in \mathbf{R}^{n \times d}$ . Let  $x \in \mathbf{R}^n$ , then we must have:

$$\begin{aligned}x^T M x &= x^T (BB^T) x \\&= (x^T B)(B^T x) \\&= (B^T x)^T (B^T x) \\&= \|B^T x\|^2 \geq 0.\end{aligned}$$

Then  $M$  is psd.

If  $M$  is psd, then it is real and symmetric. By Spectual Theorem,  $M = Q\Sigma Q^T$ , where  $\Sigma$  is a diagonal matrix of the corresponding eigenvalues of  $M$ . By part 2-2, we proved that all eigenvalues are positive. Thus we can always write  $\Sigma = RR^T$  where  $R$  is a diagonal matrix whose values is the square root of eigenvalues. Let  $B = QS$ ,  $M = BB^T$

In [ ]:

# P3

March 27, 2017

## 1 3 Positive Definite Matrix

### 1.1 3-1

Let  $M$  be a positive definite matrix and  $v$  be one of the eigenvector of  $M$  with eigenvalue  $\lambda$ .

By definition of psd we must have  $v^T M v > 0$ . Let  $v^T M v = c$ . By definition of eigenvector, we have:

$$\begin{aligned}v^T (Mv) &= c \\v^T \lambda v &= c \\ \lambda v^T v &= c \\ \lambda &= \frac{c}{||v||}\end{aligned}$$

Since  $c > 0$  and  $||v|| = 1$  ( $v$  is eigenvector), we must have  $\lambda > 0$ .

## 1.2 3-2

Proof:

Since  $Q$  is orthogonal matrix, we have  $Q^T Q = I$ , therefore:

$$M(Q\Sigma^{-1}Q^T) = (Q\Sigma Q^T)(Q\Sigma^{-1}Q^T) = Q\Sigma\Sigma^{-1}Q^T = QQ^T = I$$

### 1.3 3-3

Proof: Let  $x \in \mathbf{R}^n$  be any vector. Since  $M$  is symmetric positive definite matrix we must have  $x^T M x > 0$

$$\begin{aligned} x^T (M + \lambda I) x &= x^T (M x + \lambda I x) \\ &= x^T M x + \lambda x^T I x \\ &= x^T M x + \lambda \|x\|^2 \geq x^T M x > 0. \end{aligned}$$

Hence  $x^T (M + \lambda I) x$  is symmetric positive definite matrix.

Let  $v$  be an eigen vector of  $M$  and  $\lambda_v$  be its corresponding eigenvalue. Observe that  $(M + \lambda I)v = (\lambda_v + \lambda)v$ . Hence  $v$  is also an eigenvector of  $M + \lambda I$  with eigenvalue  $\lambda_v + \lambda$ .

Since  $M + \lambda I$  is a positive definite matrix, by our result of 3-2, its inverse has form  $Q(\Sigma + \lambda I)^{-1}Q^T$  where  $\Sigma^{-1} = \text{diag}((\sigma_1 + \lambda)^{-1}, (\sigma_2 + \lambda)^{-1}, \dots, (\sigma_n + \lambda)^{-1})$ .

#### 1.4 3-4

Proof: Let  $x \in \mathbf{R}$  be any vector. We have:

$$x^T(M + N)x = x^T Mx + x^T N x > 0$$

In [ ]:



# P4

March 27, 2017

## 1 4 Kernel Matrix

### 1.1 4-1

By the definition of  $K$ ,  $K_{ij} = x_i^T x_j = x_j^T x_i$ . We also have  $K_{ii} = x_i^T x_i = \|x_i\|^2$ . Using these informations we can calculate  $x_1^T x_1 - x_2^T x_1 - x_1^T x_2 + x_2^T x_2 = (x_1 - x_2)^T (x_1 - x_2) = \|x_1 - x_2\|^2$ . There fore  $K$  contains pairwise distances information of  $X$ .

In [ ]:

March 27, 2017

## 1 5 Kernel Ridge Regression

### 1.1 5-1

If  $w$  is a minimizer of  $J(w)$ , we must have  $\frac{dJ(w)}{dw} = 0$ . Therefore:

$$\begin{aligned}\frac{dJ(w)}{dw} &= 2X^T(Xw - y) + 2\lambda Iw = 0 \\ 2X^T Xw - 2X^T y + 2\lambda Iw &= 0 \\ X^T Xw + \lambda Iw &= X^T y \\ (X^T X + \lambda I)w &= X^T y.\end{aligned}$$

By our conclusion from 2-3,  $X^T X$  is a psd Matrix and from 3-3  $X^T X + \lambda I$  is positive definite for any  $\lambda > 0$  and is invertible. Then we have  $w = (X^T X + \lambda I)^{-1} X^T y$ .

## 1.2 5-2

Since  $w = \frac{1}{\lambda}(X^T y - X^T X w) = \frac{1}{\lambda} X^T (y - X w)$ . We have  $w = X \alpha$  where  $\alpha = \frac{1}{\lambda}(y - X w)$

### 1.3 5-3

$w = \sum_{i=1}^n \alpha_i x_i$ . Hence  $w$  must lie in the span of  $x_i$ , this is what we described as “in the span of data”.

**1.4 5-4**

$$\alpha = \frac{1}{\alpha}(y - Xw)$$

$$\lambda I \alpha = y - XX^T \alpha$$

$$(\lambda I - XX^T) \alpha = y$$

$$\alpha = (\lambda I - XX^T)^{-1} y$$

## 1.5 5-5

Let  $K = XX^T$

$$\begin{aligned}Xw &= XX^T\alpha \\&= XX^T(\lambda I - XX^T)^{-1}y \\&= K(\lambda I - K)^{-1}y\end{aligned}$$

**1.6 5-6**

$$\begin{aligned}x^T w &= x^T X^T \alpha \\ &= k_x^T (\lambda I - XX^T)^{-1} y\end{aligned}$$

In [ ]:

P7

March 27, 2017

## **1 7 Kernelized Pegasos**



## 1.1 7-1

The margin of SVM is  $y_i w^T x_i$ . By Representer's theorem,  $w = \sum_{i=1}^n$ . Therefore:

$$\begin{aligned} y_j w^T x_j &= y_j \sum_{i=1}^n \alpha_i^{(t)} x_i x_j \\ &= y_j \sum_{i=1}^n \alpha_i^{(t)} \langle x_i, x_j \rangle \\ &= y_j K_j^T \alpha^{(t)} \end{aligned}$$

## 1.2 7-2

By Pegaso Algorithm, If  $t+1$  step does not violate margin:

$$\begin{aligned}w^{(t+1)} &= (1 - \eta^{(t)}\lambda)w^{(t)} \\X^T\alpha^{(t+1)} &= (1 - \eta^{(t)}\lambda)X^T\alpha^{(t)} \\ \alpha^{(t+1)} &= (1 - \eta^{(t)}\lambda)\alpha^{(t)}\end{aligned}$$

Algorithm step: If  $t+1$  step does not violate margin, then  $\alpha_i^{(t+1)} = (1 - \eta_t\lambda)\alpha_i^{(t)}$

### 1.3 7-3

Define  $(0, 0, \dots, 1, \dots, 0)$  as a vector of dimension  $n$  where  $j^{th}$  element is 1 and other elements are zeros. If  $t+1$  step, the prediction on point  $x_j$  does violate margin:

$$\begin{aligned} w^{(t+1)} &= (1 - \eta^{(t)}\lambda)w^{(t)} + \eta_t y_j x_j \\ X^T \alpha^{(t+1)} &= (1 - \eta^{(t)}\lambda)X^T \alpha^{(t)} + \eta_t y_j X^T (0, 0, \dots, 1, \dots, 0) \\ \alpha^{(t+1)} &= (1 - \eta^{(t)}\lambda)\alpha^{(t)} + \eta_t y_j (0, 0, \dots, 1, \dots, 0) \end{aligned}$$

Algorithm step: If  $t+1$  step, the prediction on point  $x_j$  does violate margin, then first update  $\alpha_i^{(t+1)} = (1 - \eta_t \lambda) \alpha_i^{(t)}$  Then we add the  $j^{th}$  element of  $\alpha_t$  with  $y_j x_j$

Pseudo Code:

---

#### Algorithm 2: Kernelized Pegasos Algorithm

---

```

input: Kernel Matrix  $K$  labels  $y_1, \dots, y_n \in \{-1, 1\}$  and  $\lambda > 0$ .
 $\alpha^{(1)} = (0, \dots, 0) \in \mathbf{R}^d$ 
 $t = 0$  # step number
repeat
   $t = t + 1$ 
   $\eta^{(t)} = 1/(t\lambda)$  # step multiplier
  randomly choose  $j$  in  $1, \dots, n$ 
  if  $y_j K_j^T \alpha^{(t)} < 1$ 
     $\alpha^{(t+1)} = (1 - \eta^{(t)}\lambda)\alpha^{(t)}$ 
     $\alpha^{(t+1)}[j] = \alpha^{(t+1)}[j] + \eta^{(t)} y_j$ 
  else
     $\alpha^{(t+1)} = (1 - \eta^{(t)}\lambda)\alpha^{(t)}$ 
until bored
return  $\alpha^{(t)}$ 

```

---

## 7.4 (Optional) Efficient Kernelized Pegasos

---

**Algorithm 2:** Kernelized Pegasos Algorithm

---

```
input: Kernel Matrix  $K$  labels  $y_1, \dots, y_n \in \{-1, 1\}$  and  $\lambda > 0$ .  
 $\alpha^{(1)} = (0, \dots, 0) \in \mathbf{R}^d$   
 $s^{(0)} = 1$   
 $t = 0$  # step number  
repeat  
     $t = t + 1$   
     $\eta^{(t)} = 1/(t\lambda)$  # step multiplier  
     $s^{(t+1)} = (1 - \eta^{(t)}\lambda)s^{(t)}$   
    randomly choose  $j$  in  $1, \dots, n$   
    if  $y_j K_j^T \alpha^{(t)} < 1$   
         $\alpha^{(t+1)} = \alpha^{(t)}$   
         $\alpha^{(t+1)}[j] = \alpha^{(t+1)}[j] + \frac{1}{s^{(t+1)}} \eta^{(t)} y_j$   
until bored  
 $\alpha^{(t)} = \alpha^{(t)} s^{(t)}$   
return  $\alpha^{(t)}$ 
```

---

# P8

March 27, 2017

```
In [1]: import numpy as np
import matplotlib.pyplot as plt
import sklearn
import scipy.spatial
import functools
from scipy.spatial.distance import cdist
```

# 1 8-2 Kernel and Kernel Machine

## 1.1 8-2-1

```
In [173]: #Kernel test W,X,sigma
import numpy as np
W_test = np.array([[1,2,3],[4,5,6]])
X_test = np.array([[2,3,4],[5,6,7]])
sigma = 1

In [174]: from scipy.spatial.distance import cdist
def linear_kernel(W, X):
    """
    Computes the linear kernel between two sets of vectors.
    Args:
        W, X - two matrices of dimensions n1xd and n2xd
    Returns:
        matrix of size n1xn2, with  $w_i^T x_j$  in position i,j
    """
    return np.dot(W, np.transpose(X))

def RBF_kernel(W, X, sigma):
    """
    Computes the RBF kernel between two sets of vectors
    Args:
        W, X - two matrices of dimensions n1xd and n2xd
        sigma - the bandwidth (i.e. standard deviation) for the RBF/Gaussian
    Returns:
        matrix of size n1xn2, with  $\exp(-||w_i - x_j||^2 / (2 \sigma^2))$  in position i,j
    """
    #TODO
    diff_mat = cdist(W, X, 'sqeuclidean')
    return np.exp(-(diff_mat) / (2 * sigma ** 2))

def polynomial_kernel(W, X, offset, degree):
    """
    Computes the inhomogeneous polynomial kernel between two sets of vectors
    Args:
        W, X - two matrices of dimensions n1xd and n2xd
        offset, degree - two parameters for the kernel
    Returns:
        matrix of size n1xn2, with  $(\text{offset} + \langle w_i, x_j \rangle)^{\text{degree}}$  in position i,j
    """
    #TODO
    return (offset + linear_kernel(W, X)) ** degree
```


## 1.2 8-2-2

```
In [175]: def linear_kernel(W, X):  
    """  
    Computes the linear kernel between two sets of vectors.  
    Args:  
        W, X - two matrices of dimensions n1xd and n2xd  
    Returns:  
        matrix of size n1xn2, with  $w_i^T x_j$  in position i,j  
    """  
    return np.dot(W, np.transpose(X))  
X0=[ [-4], [-1], [0], [2]]  
linear_kernel(X0,X0)  
  
Out[175]: array([[16,  4,  0, -8],  
                 [ 4,  1,  0, -2],  
                 [ 0,  0,  0,  0],  
                 [-8, -2,  0,  4]])
```

### 1.3 8-2-3


```
In [176]: import matplotlib.pyplot as plt
plot_step = .01
xpts = np.arange(-5.0, 6, plot_step).reshape(-1,1)
prototypes = np.array([-4,-1,0,2]).reshape(-1,1)

# Linear kernel
y = linear_kernel(prototypes, xpts)
for i in range(len(prototypes)):
    label = "Linear@"+str(prototypes[i,:])
    plt.plot(xpts, y[i,:], label=label)
plt.legend(loc = 'best')
plt.show()
```




```
In [177]: # Poly Kernel
y = polynomial_kernel(prototypes, xpts, 1, 3)
for i in range(len(prototypes)):
    label = "Polynomial@"+str(prototypes[i,:])
    plt.plot(xpts, y[i,:], label=label)
plt.legend(loc = 'best')
plt.show()
```





```
In [178]: # RBF Kernel
y = RBF_kernel(prototypes, xpts, 1)
for i in range(len(prototypes)):
    label = "RBF@" + str(prototypes[i,:])
    plt.plot(xpts, y[i,:], label=label)
plt.legend(loc = 'best')
plt.show()
```



## 1.4 8-2-4

```
In [179]: class Kernel_Machine(object):
    def __init__(self, kernel, prototype_points, weights):
        """
        Args:
            kernel(W,X) - a function return the cross-kernel matrix between
            prototype_points - an Rxd matrix with rows  $\mu_1, \dots, \mu_R$ 
            weights - a vector of length R
        """

        self.kernel = kernel
        self.prototype_points = prototype_points
        self.weights = weights


    def predict(self, X):
        """
        Evaluates the kernel machine on the points given by the rows of X
        Args:
            X - an nxd matrix with inputs  $x_1, \dots, x_n$  in the rows
        Returns:
            Vector of kernel machine evaluations on the n points in X.  $S = \sum_{i=1}^R w_i k(x_j, \mu_i)$ 
        """
        # TODO
        xX = self.kernel(X, self.prototype_points)
        return np.dot(xX, self.weights)

In [180]: from functools import partial
    prototype_points = np.array([-1, 0, 1]).reshape(-1, 1)
    weights = np.array([1, -1, 1]).reshape(-1, 1)
    x = np.array([-4, -1, 0, 2]).reshape(-1, 1)
    k = partial(RBF_kernel, sigma=1)
    machine = Kernel_Machine(k, prototype_points, weights)

In [181]: machine.predict(x)

Out[181]: array([[ 0.01077726],
                  [ 0.52880462],
                  [ 0.21306132],
                  [ 0.48230437]])


In [182]: #Plot the result function
    plot_step = .001
    xpts = np.arange(-6, 6, plot_step).reshape(-1, 1)
    plt.plot(xpts, machine.predict(xpts), label='x')
    plt.xlabel('x')
    plt.ylabel('Predicted y')
    plt.show()
```



## 2 8-3 Kernel Ridge Regression

### 2.1 8-3-1 Show data

```
In [183]: data_train, data_test = np.loadtxt("../krr-train.txt"), np.loadtxt("../krr-  
x_train, y_train = data_train[:,0].reshape(-1,1), data_train[:,1].reshape(-1,1)  
x_test, y_test = data_test[:,0].reshape(-1,1), data_test[:,1].reshape(-1,1)  
  
In [184]: plt.scatter(x_train, y_train)  
plt.xlabel('X')  
plt.ylabel('Y')  
plt.show()
```




As we seen X and Y are non lienar and there is a clear twist at x=0.5

## 2.2 8-3-2

```
In [185]: def train_kernel_ridge_regression(X, y, kernel, l2reg):  
    # TODO  
    K = kernel(X,X)  
    dim_K = K.shape[0]  
    alpha = np.linalg.inv((np.identity(dim_K)*l2reg+K)).dot(y)  
    return Kernel_Machine(kernel, X, alpha)
```

## 2.3 8-3-3


```
In [186]: plot_step = .001
xpts = np.arange(0 , 1, plot_step).reshape(-1,1)
plt.plot(x_train,y_train,'o')
l2reg = 0.0001
for sigma in [.01,.1,1]:
    k = functools.partial(RBF_kernel, sigma=sigma)
    f = train_kernel_ridge_regression(x_train, y_train, k, l2reg=l2reg)
    label = "Sigma="+str(sigma)+",L2Reg="+str(l2reg)
    plt.plot(xpts, f.predict(xpts), label=label)
plt.legend(loc = 'best')
plt.ylim(-1,1.5)
plt.show()
```



When  $\sigma = 0.01$  RBF kernel tends to overfit, because it assigns huge inner product to the neighbours of training data. When  $\sigma = 1$  RBF kernel does not overfit, but it could be under fit.

## 2.4 8-3-4

```
In [187]: plot_step = .001
xpts = np.arange(0 , 1, plot_step).reshape(-1,1)
plt.plot(x_train,y_train,'o')
sigma= .02
for l2reg in [.0001,.01,.1,2,10000]:
    k = functools.partial(RBF_kernel, sigma=sigma)
    f = train_kernel_ridge_regression(x_train, y_train, k, l2reg=l2reg)
    label = "Sigma="+str(sigma)+",L2Reg="+str(l2reg)
    plt.plot(xpts, f.predict(xpts), label=label)
plt.legend(loc = 'best')
plt.ylim(-1,1.5)
plt.show()
```



The prediction function will become a constant prediction of 0 as  $\lambda \rightarrow \infty$ .



## 2.5 8-3-5

```
In [17]: from sklearn.base import BaseEstimator, RegressorMixin, ClassifierMixin

class KernelRidgeRegression(BaseEstimator, RegressorMixin):
    """sklearn wrapper for our kernel ridge regression"""

    def __init__(self, kernel="RBF", sigma=1, degree=2, offset=1, l2reg=1):
        self.kernel = kernel
        self.sigma = sigma
        self.degree = degree
        self.offset = offset
        self.l2reg = l2reg

    def fit(self, X, y=None):
        """
        This should fit classifier. All the "work" should be done here.
        """
        if (self.kernel == "linear"):
            self.k = linear_kernel
        elif (self.kernel == "RBF"):
            self.k = functools.partial(RBF_kernel, sigma=self.sigma)
        elif (self.kernel == "polynomial"):
            self.k = functools.partial(polynomial_kernel, offset=self.offset)
        else:
            raise ValueError('Unrecognized kernel type requested.')

        self.kernel_machine_ = train_kernel_ridge_regression(X, y, self.k, self.l2reg)

        return self

    def predict(self, X, y=None):
        try:
            getattr(self, "kernel_machine_")
        except AttributeError:
            raise RuntimeError("You must train classifier before predicting")

        return (self.kernel_machine_.predict(X))

    def score(self, X, y=None):
        # get the average square error
        return ((self.predict(X) - y).mean())

In [18]: from sklearn.model_selection import GridSearchCV, PredefinedSplit
from sklearn.model_selection import ParameterGrid
from sklearn.metrics import mean_squared_error, make_scorer
import pandas as pd
```

```

test_fold = [-1]*len(x_train) + [0]*len(x_test)    #0 corresponds to test,
predefined_split = PredefinedSplit(test_fold=test_fold)

In [135]: param_grid = [{'kernel': ['RBF'], 'sigma': np.exp2(-np.arange(-5, 5, 0.1)), 'deg
                {'kernel': ['polynomial'], 'offset': np.arange(-10, 10, 1), 'deg
                {'kernel': ['linear'], 'l2reg': [10, 1, .01]}]
kernel_ridge_regression_estimator = KernelRidgeRegression()
grid = GridSearchCV(kernel_ridge_regression_estimator,
                    param_grid,
                    cv = predefined_split,
                    scoring = make_scorer(mean_squared_error, greater_is_b
                    # n_jobs = -1 #should allow parallelism, but crashes L
                    )
grid.fit(np.vstack((x_train, x_test)), np.vstack((y_train, y_test)))

Out[135]: GridSearchCV(cv=PredefinedSplit(test_fold=array([-1, -1, ..., 0, 0])),
    error_score='raise',
    estimator=KernelRidgeRegression(degree=2, kernel='RBF', l2reg=1, c
    fit_params={}, iid=True, n_jobs=1,
    param_grid=[{'kernel': ['RBF'], 'sigma': array([ 32.        , 29.857
    3,  4,  5,  6,  7,  8,  9])}, {'kernel': ['linear'], 'l2re
    pre_dispatch='2*n_jobs', refit=True, return_train_score=True,
    scoring=make_scorer(mean_squared_error, greater_is_better=False),
    verbose=0)

In [136]: pd.set_option('display.max_rows', 20)
df = pd.DataFrame(grid.cv_results_)
# Flip sign of score back, because GridSearchCV likes to maximize,
# so it flips the sign of the score if "greater_is_better=False"
df['mean_test_score'] = -df['mean_test_score']
df['mean_train_score'] = -df['mean_train_score']
cols_to_keep = ["param_degree", "param_kernel", "param_l2reg", "param_offs
                "mean_test_score", "mean_train_score"]
df_toshow = df[cols_to_keep].fillna('-')
#df_toshow.sort_values(by=["mean_test_score"])
df_RBF = df_toshow[df_toshow['param_kernel']=='RBF']
df_RBF = df_RBF.sort_values(by=["mean_test_score"])

In [137]: df_poly = df_toshow[df_toshow['param_kernel']=='polynomial']
df_poly = df_poly.sort_values(by=["mean_test_score"])

```

## 2.5.1 Print out best settings

```

In [138]: #Store best parameter settings from the sorted parameters grid generated
best_pm_poly = df_poly.iloc[0]
best_pm_RBF = df_RBF.iloc[0]
print('Polynomial Kernel best parameter settings')
print(best_pm_poly)
print('')

```

```
print('RBF Kernel best parameter settings')
print(best_pm_RBF)
```

Polynomial Kernel best parameter settings

```
param_degree      16
param_kernel      polynomial
param_l2reg        0.0473661
param_offset       -6
param_sigma        -
mean_test_score    0.0240397
mean_train_score   0.0339528
Name: 39884, dtype: object
```

RBF Kernel best parameter settings


```
param_degree      -
param_kernel      RBF
param_l2reg        0.133972
param_offset       -
param_sigma        0.0625
mean_test_score    0.0138071
mean_train_score   0.014427
Name: 7990, dtype: object
```

## 2.5.2 Print out neighbours of best settings

As we can see these settings are at local minimums. Changing in any parameters to both direction can lead to a increase in test score.


```
In [172]: # Hold param_l2reg and degree compare changes in param_offset
df_poly_neighbours_offset = df_poly[(df_poly['param_l2reg']==best_pm_poly
                                     & (df_poly['param_degree']==best_pm_poly
                                     .sort_values(by=['param_offset']).head(6)

In [146]: plt.plot(df_poly_neighbours_offset['param_offset'],df_poly_neighbours_offset['mean_test_score'])
plt.axvline(x=best_pm_poly['param_offset'],label='Best Settings',ls='dashed')
plt.title('Model: Polynomial Neighbour parameters:offset')
plt.xlabel('Offset')
plt.ylabel('Mean Test Score')
plt.legend(loc='best')
plt.show()
```




```
In [153]: # Hold param_l2reg and offset compare changes in param_degree
df_poly_neighbours_degree = df_poly[(df_poly['param_l2reg']==best_pm_poly
                                     & (df_poly['param_offset']==best_pm_poly
                                     .sort_values(by=['param_degree'])

In [159]: plt.plot(df_poly_neighbours_degree['param_degree'],df_poly_neighbours_deg
plt.axvline(x=best_pm_poly['param_degree'],label='Best Settings',ls='dash
plt.title('Model: Polynomial Neighbour parameters:degree')
plt.xlabel('degree')
plt.ylabel('Mean Test Score')
plt.legend(loc='best')
plt.show()
```




```
In [169]: # Hold param_degree and offset compare changes in param_degree
df_poly_neighbours_l2reg = df_poly[(df_poly['param_degree']==best_pm_poly
                                     & (df_poly['param_offset']==best_pm_poly
                                     .sort_values(by=['param_l2reg']).head(20)

In [171]: plt.plot(df_poly_neighbours_l2reg['param_l2reg'],df_poly_neighbours_l2reg
plt.axvline(x=best_pm_poly['param_l2reg'],label='Best Settings',ls='dashed')
plt.title('Model: Polynomial Neighbour parameters:l2reg')
plt.xlabel('l2reg')
plt.ylabel('Mean Test Score')
plt.legend(loc='best')
plt.show()
plt.savefig('test.png')
```




```
In [77]: df_RBF_neighbours_sigma = df_RBF[df_RBF['param_l2reg']==best_pm_RBF['param_l2reg']]

In [88]: plt.plot(df_RBF_neighbours_sigma['param_sigma'],df_RBF_neighbours_sigma['mean_test_score'])
plt.axvline(x=best_pm_RBF['param_sigma'],label='Best Settings',ls='dashed')
plt.title('Model: RBF Neighbour parameters:Sigma')
plt.xlabel('Sigma')
plt.ylabel('Mean Test Score')
plt.legend(loc='best')
plt.show()
```




```
In [102]: df_RBF_neighbours_l2reg = df_RBF[df_RBF['param_sigma']==best_pm_RBF['para
In [103]: plt.plot(df_RBF_neighbours_l2reg['param_l2reg'],df_RBF_neighbours_l2reg['
plt.axvline(x=best_pm_RBF['param_l2reg'],label='Best Settings',ls='dashed')
plt.title('Model: RBF Neighbour parameters:l2reg')
plt.xlabel('l2reg')
plt.ylabel('Mean Test Score')
plt.legend(loc='best')
plt.show()
```





## 2.6 8-3-6

```
In [23]: #Best setting polynomial kernel
plot_step = .001
xpts = np.arange(-0.5 , 1.5, plot_step).reshape(-1,1)
plt.plot(x_train,y_train,'o')
degree=best_pm_poly['param_degree']
offset=best_pm_poly['param_offset']
sigma= best_pm_RBF['param_sigma']
score_RBF = best_pm_RBF['mean_test_score']
score_poly = best_pm_poly['mean_test_score']
for l2reg in [best_pm_poly['param_l2reg']]:
    k = functools.partial(polynomial_kernel,degree=degree,offset=offset)
    f = train_kernel_ridge_regression(x_train, y_train, k, l2reg=l2reg)
    label = "Polynomial(score:%.3f)"%(score_poly)
    plt.plot(xpts, f.predict(xpts), label=label)
    k = functools.partial(RBF_kernel, sigma=sigma)
    f = train_kernel_ridge_regression(x_train, y_train, k, l2reg=l2reg)
    label = 'RBF(score:%.3f)'%(score_RBF)
    plt.plot(xpts, f.predict(xpts), label=label)
plt.legend(loc = 'best')
plt.ylim(-0.5,1.5)
plt.show()
```



### **2.6.1 Comment**

We observed that RBF kernel provides stronger fitting to training data than Polynomial kernel since RBF can model infinite dimensional features mapping.

## 2.7 8-3-7

As we have derived in Assignment 1, the bayes decision function for square loss for given  $X$   $Y$  is  $E[y|x]$ . In this case  $E[y|x] = E[f(x) + \epsilon|x] = f(x)$ . Also we derived that the associated bayes risk is  $var(y|x)$ . In this case, since  $f(x)$  is uncorrelated with  $\epsilon$ ,  $var(y|x) = var(f(x) + \epsilon|x) = var(f(x)|x) + var(\epsilon|x) = var(\epsilon) = 0.1$