Robótica Móvel e Inteligente

Path Planning and Obstacle Avoidance

Artur Pereira <artur@ua.pt>

DETI / Universidade de Aveiro

Outline

Navigation
Definition

- “Given partial knowledge about its environment and a goal position or series of positions, navigation encompasses the ability of the robot to act based on its knowledge and sensor values so as to reach its goal positions as efficiently and as reliably as possible.”

  [Siegwart, `http://www.cs.cmu.edu/~rasc/Download/AMRobots6.pdf`]
- In mobile robotics the knowledge about the environment and situation is usually only partially and uncertain



Navigation
Issues in navigation

- Where am I?
  - localization
- Where have I been?
  - mapping
- Where should I go?
  - decision
- **What’s the best way to get there?**
  - **Path planning**
- How do I get there?
  - Path following and obstacle avoidance (Motion)

Path planning
Definition

- Path planning – the task of computing a path for the robot such that it can reach the desired goal without colliding with known obstacles
- Optimal paths can be hard to compute, specially for robots that can not move in arbitrary directions (i.e. non-holonomic robots)

- Path and trajectory are often used with the same meaning
  - But one can distinguish them
- Path – only geometric considerations
  - a way from a start position/pose/configuration to a goal one
- Trajectory – includes geometric and time considerations
  - the dynamics is also considered
- Another term is motion, applied to mobile robots or manipulators
  - considers other constraints, like collision avoidance (of dynamic obstacles)

[2] Peter Corke, `https://robotacademy.net.au/masterclass/paths-and-trajectories/`

Path planning
Some concepts

- Configuration space (C-Space) – set of possible valid configurations (poses) of the robot
  - Defines the search space and the set of allowable paths
- Free space (F-Space) – set of valid configurations that do not intercept obstacles in the environment
  - Depends on the robot shape
- Cases to be considered:
  - Point robot
  - Symmetric robot
  - Non-symmetric robot



Path planning
Some assumptions

- Assumption 1:
  - Often, path planning methods assume that the robot is symmetric and holonomic, and treat it simply as a point
  - If the robot is treated as a point, the obstacles must be "inflated" in order to compensate the robot radius
  - This approach greatly simplifies path planning
- Assumption 2:
  - there exists a good enough estimatation of the robot's pose
- Assumption 3:
  - there exists a good enough representation (map) of the environment that can be used to compute a path

Environment representation
Possible representations

- There are different ways to represent the environment
- Two common ones are geometric maps and topological maps
- Geometric maps may represent a continuous geometric description
- Topological representations are formally graphs where:
  - nodes denote areas/points/sections in the environment
  - arcs denote adjacency between nodes

Environment representation
Example of metric and topological maps



Figure from Meyer, “Map-based navigation in mobile robotics”. 2003

Environment representation
Another example of metric and topological maps







Environment representation
Mapping approaches

- Path-planning algorithms often are only applicable to discrete maps
- Transforming a possibly continuous environment into a discrete representation suitable for the chosen path-planning algorithm is a must
- Path planner approaches differ in how they perform this decomposition

- General strategies for decomposition:
  - Road map – identify routes within the free space
    - Transforming the free space into a network of 1-D curves or lines, called road-map
  - Cell decomposition – divide space into cells that are discriminated between free and occupied cells
    - Transforming the free space into a connectivity graph of free cells, based on adjacency
  - Potential field – apply a mathematical function over the space
    - Transforming the free space into a field, or gradient, that directs the robot to the goal position

Path planning approaches
Visibility graph



- Obstacles are treated as polygons
  - for every obstacle, a polygon including it is defined
- Then, a graph is defined, where:
  - q_{init}, q_{goal}, and all polygons' vertices are the nodes
  - for every pair of nodes which can be connected by a line segment, not passing through an obstacle, there is an edge
    - such pair of nodes can "see" each other)

- With the detected nodes and edges, a connectivity graph (visibility graph) is then generated
  - every edge can be labelled with some cost function value (for example, the Euclidian distance)

Path planning approaches
Visibility graph (2)



- A graph search algorithm can be used to find the shortest path along the "roads" defined by the visibility graph
- Efficient method for sparse environments

- Problem – may cause the robot to move too close to obstacles
  - little margin for errors in motion
- Solution – grow obstacles (even more), giving more clear space between robot and obstacles

Path planning approaches
Voronoi diagrams



- For each point in free space its distance to the nearest obstacle is computed
- Then, the set of points equidistant from the nearest two or more obstacle boundaries are selected

- The Voronoi diagram is obtained by linking these points, from where the shortest path can be computed
- The result is a path of maximum distance from obstacles
  - usually far from optimal, in the sense of total path length

Path planning approaches
Cell decomposition

- Divide space into simple, connected regions called cells
  - cells can be either free, occupied or partially occupied
- Discretize the space by constructing an adjacency graph of the free cells
- Adjacency graph
  - Nodes – free cells
  - Edges – there is an edge between every pair of nodes whose corresponding cells are adjacent
- Locate “goal” and “start” cells and search for the shortest path in the adjacency graph that join them
- Typically paths are assumed to pass through the mid-points of the cells

Path planning approaches
Cell decomposition (2)



- Given an environment, how to decompose it?

- Two possible cell decomposition methods
  - Exact cell decomposition and approximate cell decomposition
- Exact cell decomposition
  - Free cells correspond exactly to free space
    - There is no partially occupied cells
- Approximate cell decomposition
  - Some free space is included in partially occupied cells
    - the partially occupied cells are considered as occupied
- Cells may or may not differ on size or shape

Path planning approaches
Exact cell decomposition

- The free space F is divided into a set of non-overlapping convex cells whose union is exactly F
- Examples of convex shapes: trapezoids, triangles
- The basic abstraction behind this method is that the position of the robot within each cell does not matter, only the ability to travel to another free cell





Path planning approaches
Exact cell decomposition (2)



- A connectivity graph can be constructed, where:
  - nodes represent the free cells
  - every adjacent pair of cells is connected by an edge
- Result can be complex if the world is complex
  - Good for sparse environments



Path planning approaches
Approximate cell decomposition



- Free space F is represented by a set of non-overlapping cells whose union is contained in F
- Cells usually have simple, regular shapes, like rectangles, squares, hexagons

- Two approaches:
  - Variable-size cell decomposition
  - Fixed-size cell decomposition

Path planning approaches
Variable-size cell decomposition

- Decomposing using variable-size cells
  - with a rectangular shape
- Grey areas are free space considered as occupied



Path planning approaches
Fixed-size cell decomposition

- Decomposing using fixed-size cells
  - with a square shape
- Grey areas are free space considered as occupied
- Cell size is not dependent on the obstacle size in the environment
  - narrow passage ways can be lost
- Low computational complexity of path planning



Path planning approaches
Quad-tree cell decomposition

- Decomposing using variable-size cells
  - with a square shape
- Partially occupied cells are subdivided until a given granularity
- At each level of resolution only the cells whose interiors lie entirely in the free space are used to construct the connectivity graph
- Efficient representation, adapted to the complexity of the environment
  - sparse environments contain fewer cells thus consuming less memory



Search algorithms
Methods

- Once a graph is obtained, finding the shortest path between start node and goal node can be done using graph search algorithms
- Many graph search algorithms require visiting each node in the graph to determine the shortest path
  - Computationally tractable for sparsely connected graphs
  - Computationally expensive for highly connected graphs (e.g., regular grid)
- Covered methods:
  - Wavefront expansion
  - Dijkstra's algorithm
  - A* algorithm

Search algorithms
Wavefront expansion

- Wavefront expansion (aka NF1 or grassfire), useful to find paths in fixed-size cell arrays
- Starting at the goal, mark in each adjacent cell its distance to the goal (here using Manhattan distance)
- This process continues until the cell corresponding to the start position is reached
- The planner calculate a path to reach the goal by linking together cells that are adjacent and closer to the goal



Search algorithms
Dijkstra's algorithm – cell environment

- Beginning at the start node, the algorithm marks all adjacent neighbors with the cost to get there
- It then proceeds to the node with the lowest cost marking all of its adjacent nodes with the lowest cost to reach them
- Once all adjacent neighbors of a node have been marked, the algorithm proceeds to the node with the next lowest cost not visited yet
- Once the algorithm visits the goal node, it terminates
- The path to goal may be obtained starting from the goal node and following the edges pointing towards the lowest node cost



Search algorithms
Dijkstra's algorithm – graph example



Taken from https://en.wikipedia.org/wiki/Dijkstra's_algorithm

Search algorithms
A* search algorithm

- The idea is to use a cost function to rank the choices, choose the best one first, and try it
- Cost function:
  - f*(n) = g(n) + h*(n) – ('*' means they are estimates)
  - where:
    - g(n) is the cost of going from the start to node n
    - h*(n) is an estimated cost of going from node n to the goal
- h* is a "heuristic function" – (a way of guessing the cost of going from node n to goal
  - the robot can't "see" the path between node n and the goal
  - h*(n) should never be greater than h(n): h*(n) $\leq$ h(n)
  - Must always underestimate remaining cost to reach goal
  - The Euclidian (straight line) distance is often a good choice

Search algorithms
A* search algorithm (2)



Potential field path planning
Main idea

- Think the robot as a particle in a potential field
- Define a potential function over the free space that has a global minimum at the goal
- Define high potentials for the obstacles
- The robot follow the steepest descent of the potential function



Potential field path planning
Rolling down the hill

- The goal location generates an attractive potential, pulling the robot towards the goal
- The obstacles generate a repulsive potential, pushing the robot far away from the obstacles
- The negative gradient of the total potential is treated as an artificial force applied to the robot
- Generated robot movement is similar to a ball rolling down the hill



Potential field path planning
Problems



- Often leads to oscillating motion
- Trapped in local minima in the potential field
- Parameter tuning problems



Navigation
Issues in navigation

- Where am I?
  - localization
- Where have I been?
  - mapping
- Where should I going?
  - decision
- What's the best way to get there?
  - Path planning
- **How do I get there?**
  - Path following and **obstacle avoidance** (Motion)

Obstacle avoidance
Purpose

- In general, the environment is not fully modeled
  - Some obstacles (chairs, for example) may not be represented
- The environment might also change dynamically
  - for example, people moving around
- In such cases, to navigate, the robot may need to modify the planned path
  - reacting, re-planning

- The purpose of the obstacle avoidance algorithms is to avoid collisions with obstacles, while pursuing the goal/plan
- Obstacle avoidance relies on
  - Information about the goal (position, plan)
  - current pose (on the map)
  - Recent sensory information (a local map)

Obstacle avoidance
Methods

- Efficient obstacle avoidance should be optimal with respect to
  - The overall goal
  - The actual speed and kinematics of the robot
  - The on-board sensors
  - The current and future risk of collision

- Covered methods:
  - Bug1
  - Bug2
  - Vector field histogram

Obstacle avoidance
Bug1 algorithm

- Algorithm:
  - Go in direction to the goal until reach it or hit an obstacle
  - If goal reached, finish
  - Do a full tour around the obstacle, storing the closest point to the goal
  - Go to that point
  - Repeat
- Comment:
  - Inefficient but does the job



Obstacle avoidance
Bug2 algorithm

- Algorithm:
  - Go in direction to the goal until reach it or hit an obstacle
  - If goal reached, finish
  - Contour the obstacle, from left or right, until reach the line between start and goal
  - Repeat, keeping the same side (left or right) as before
- Comment:
  - More efficient but can fail



Obstacle avoidance
Vector field histogram (VFH)

- Creates a local map of the environment around the robot
- Environment is represented as an occupancy grid (2D Cartesian grid called the histogram grid)
- Each grid cell (i, j) value holds the confidence that there is an obstacle at that location
- The grid is updated by relatively recent sensor data



Obstacle avoidance
Vector field histogram (VFH) – 2

- Information in the histogram grid is converted to a simpler representation, called the polar histogram
- The polar histogram retains the statistical information but reduces the amount of data that needs to be handled in real-time
- A threshold transforms the polar histogram in a binary diagram with passable regions
- A sector with low obstacle density (below threshold) is a candidate to travel away from obstacle
- The one chosen depends on the target point





Bibliography

- “Introduction to Autonomous Mobile Robots”, Second Edition, Roland Siegwart et al., MIT Press, 2011
- “Principles of Robot Motion: Theory, Algorithms, and Implementations”, Howie Choset et al., MIT Press, Boston, 2005
- “Artificial Intelligence: A Modern Approach”, 3rd edition, Russel and Norvig, Pearson, 2009
- “Introduction to Autonomous Mobile Robots”, R. Siegwart, I. Nourbakhsh, D. Scaramuzza
- “The Vector Field Histogram - Fast Obstacle Avoidance for Mobile Robots”, J. Borenstein and Y. Koren
- “VFH+: Reliable Obstacle Avoidance for Fast Mobile Robots”, I. Ulrich and J. Borenstein