RETRIEVAL-AUGMENTED GENERATION FOR HIGH-PERFORMANCE COMPUTING SUPPORT

A DISSERTATION SUBMITTED TO THE UNIVERSITY OF MANCHESTER
FOR THE DEGREE OF BACHELOR OF SCIENCE
IN THE FACULTY OF SCIENCE AND ENGINEERING

2026

Student id: 11006713

Department of Computer Science

Contents

List of Abbreviations **7**

Abstract **8**

Declaration **9**

Copyright **10**

Acknowledgements **11**

1 Introduction **12**

1.1 Project Context and Motivation 12
1.2 Problem Definition and Scope 14
1.3 Research Questions and Hypotheses 14
1.4 Aim, Objectives, and Success Criteria 15
1.5 Overview of Evaluation Strategy 17
1.6 Report Structure 18

2 Background and Related Work **19**

2.1 HPC Support as an Information Retrieval and Question Answering Problem 19
2.2 Retrieval-Augmented Generation 21
2.3 Heterogeneous Support Corpora: Documentation and Tickets 23
2.4 Authority, Freshness, and Validity in Retrieval 25
2.5 Evaluation of RAG Systems 27
2.6 Gap Analysis and Research Positioning 28

3 Problem Formulation and Requirements **30**

3.1 Task Definition 30

3.2 Data Sources and Knowledge Characteristics 31
3.3 Benchmark and Query Taxonomy 33
3.4 Requirements and Constraints 35
3.5 Success Criteria and Requirement-to-Evaluation Mapping 36
3.6 Ethical, Privacy, and Data-Governance Considerations 38

4 System Design and Implementation 40
4.1 System Overview 40
4.2 Baseline Systems 40
4.3 Corpus Ingestion and Representation 40
4.4 Authority Registry and Metadata Extraction 40
4.5 Validity-Aware Retrieval and Reranking Design 40
4.6 Prompt and Generation Design 40
4.7 API, Tooling, and Observability 40
4.8 User Interface and Interaction Design 40
4.9 Verification and Software Testing 40
4.10 Design Trade-offs 40

5 Experimental Methodology 41
5.1 Evaluation Goals 42
5.2 Development and Test Split Discipline 42
5.3 Benchmark Construction and Characterisation 42
5.4 Frozen Backbone Decisions 42
5.5 Metric Hierarchy and Decision Rules 42
5.6 Development-Phase Tuning Protocol 42
5.6.1 Generator Selection 42
5.6.2 Chunking Tuning 42
5.6.3 Retrieval-Mode Pilot 42
5.6.4 Shared Retrieval Budget Tuning 42
5.6.5 Validity-Reranker Tuning 42
5.7 Final Test-Set Experiments 42
5.7.1 Source Ablation 42
5.7.2 Validity-Signal Ablation 42
5.7.3 External-Document Scope Ablation 42
5.7.4 Tuned-Finalist Comparison 42
5.8 Manual Evaluation Protocol 42

5.9 Error Analysis Protocol 42
5.10 Reproducibility and Stability Controls 42

6 Results **43**
6.1 Development-Phase Selection Results 43
6.2 Overview of Main Test-Set Results 43
6.3 Controlled Ablation Results 43
6.3.1 Source Ablation 43
6.3.2 Validity-Signal Ablation 43
6.3.3 External-Document Scope Ablation 43
6.4 Practical Comparison Results 43
6.4.1 Tuned-Finalist Comparison 43
6.5 Manual Evaluation Results 43
6.6 Error Analysis Results 43
6.7 Stability and Robustness Results 43

7 Discussion and Critical Appraisal **44**
7.1 Answers to the Research Questions 44
7.2 What Improved and Why 44
7.3 Comparison with Prior Work 44
7.4 Where the System Still Fails 44
7.5 Threats to Validity 44
7.6 Review of the Project Plan 44

8 Conclusion and Future Work **45**
8.1 Summary of Contributions 45
8.2 Main Findings Against Objectives 45
8.3 Limitations 45
8.4 Future Work 45

A Approved External Documentation Sources **50**

B Benchmark Taxonomy Label Definitions **52**

Word Count: 0

List of Tables

2.1 The retrieval-control strategies most relevant to validity-aware support retrieval. 22
2.2 Comparison of the evidential roles, risks, and retrieval implications of the three source types in the Cambridge Service for Data Driven Discovery (CSD3) support setting. 23

3.1 Operational summary of the three source classes included in the project corpus. Counts and date bounds refer to the frozen corpus snapshot used for parameter tuning and final evaluation. The full external source list is given in Appendix A. 32
3.2 Functional requirements, quality requirements, and scope constraints derived from the project task definition and benchmark design. 35
3.3 Success-criteria and requirement-to-evaluation mapping for the project. 37

A.1 Approved external documentation source families included in the frozen external documentation snapshot used for parameter tuning and final evaluation. 50

B.1 Benchmark taxonomy label definitions and allowed values. 52

List of Figures

1.1 Annual number of resolved CSD3 helpdesk tickets from 2017 to 2025. Data sourced from RCS support ticket records. 13

List of Abbreviations

RAG	Retrieval-Augmented Generation
LLM	Large Language Model
LM	Language Model
HPC	High-Performance Computing
CSD3	Cambridge Service for Data Driven Discovery
RCS	Research Computing Services
EPSRC	Engineering and Physical Sciences Research Council
QA	Question Answering
IR	Information Retrieval
RAGAs	Retrieval Augmented Generation Assessment
RGB	Retrieval-Augmented Generation Benchmark

Abstract

RETRIEVAL-AUGMENTED GENERATION FOR HIGH-PERFORMANCE COMPUTING SUPPORT
Adam Calleja
A dissertation submitted to The University of Manchester
for the degree of Bachelor of Science, 2026

Declaration

No portion of the work referred to in this dissertation has been submitted in support of an application for another degree or qualification of this or any other university or other institute of learning.

Copyright

i. The author of this thesis (including any appendices and/or schedules to this thesis) owns certain copyright or related rights in it (the "Copyright") and s/he has given The University of Manchester certain rights to use such Copyright, including for administrative purposes.

ii. Copies of this thesis, either in full or in extracts and whether in hard or electronic copy, may be made **only** in accordance with the Copyright, Designs and Patents Act 1988 (as amended) and regulations issued under it or, where appropriate, in accordance with licensing agreements which the University has from time to time. This page must form part of any such copies made.

iii. The ownership of certain Copyright, patents, designs, trade marks and other intellectual property (the "Intellectual Property") and any reproductions of copyright works in the thesis, for example graphs and tables ("Reproductions"), which may be described in this thesis, may not be owned by the author and may be owned by third parties. Such Intellectual Property and Reproductions cannot and must not be made available for use without the prior written permission of the owner(s) of the relevant Intellectual Property and/or Reproductions.

iv. Further information on the conditions under which disclosure, publication and commercialisation of this thesis, the Copyright and any Intellectual Property and/or Reproductions described in it may take place is available in the University IP Policy (see `http://documents.manchester.ac.uk/DocuInfo.aspx?DocID=24420`), in any relevant Thesis restriction declarations deposited in the University Library, The University Library's regulations (see `http://www.library.manchester.ac.uk/about/regulations/`) and in The University's policy on presentation of Theses

Acknowledgements

Chapter 1

Introduction

1.1 Project Context and Motivation

The CSD3 is an Engineering and Physical Sciences Research Council (EPSRC) Tier-2 national High-Performance Computing (HPC) service hosted by the University of Cambridge Research Computing Services (RCS), supporting computationally intensive research across a wide range of scientific disciplines [1]. Effective use of such systems requires users to be able to follow and understand detailed documentation. These resources are often scattered across multiple sources, ranging from local CSD3 documentation [1] to external resources such as package documentation, creating a barrier for new users [2].

As a result of this complexity, users frequently turn to the RCS helpdesk for support. Figure 1.1 shows that there has been a steady increase in the yearly number of resolved CSD3 helpdesk tickets from 2017 to 2025. This growth indicates not only sustained support demand, but also an expanding archive of operational support knowledge that could be reused to improve user support [3].

Recent studies have investigated the use of Large Language Model (LLM)-based assistants for technical support and question answering, including domain-specific systems for HPC user support [2]. In particular, Retrieval-Augmented Generation (RAG)-based systems, which combine the generative capabilities of LLMs with a retrieval mechanism to access relevant information from a knowledge base, have been shown to produce more specific and factual responses than non-retrieval-augmented LLMs. This makes them a promising solution for evidence-grounded HPC support Question Answering (QA) [4].

However, the generation quality of RAG is highly dependent on the quality of the



Figure 1.1: Annual number of resolved CSD3 helpdesk tickets from 2017 to 2025. Data sourced from RCS support ticket records.

retrieved information. Recent work has shown that RAG systems can generate incorrect answers when they are provided with documents of weak relevance [5]. Furthermore, semantically relevant retrieved evidence can still be unusable if it comes from an unreliable source [6] or if it reflects outdated information [5].

In the CSD3 setting, these risks are amplified by the heterogeneous nature of the available evidence. Local CSD3 documentation is typically the primary source for currently supported usage [1], while external package documentation can provide additional context [2]. Historical support tickets, by contrast, capture concrete prior issue-resolution cases [3], but these may not remain applicable after later system or software changes [7].

The challenge is therefore not only to retrieve topically relevant information, but to prioritise evidence that is appropriate for the current CSD3 context. The next section formalises this challenge by defining the problem addressed in the dissertation and clarifying its scope.

1.2 Problem Definition and Scope

This dissertation addresses the problem of answering CSD3 user support queries using retrieved evidence from multiple information sources. The task is not only to retrieve semantically similar information, but also to prioritise evidence that is appropriate for the current CSD3 context. In this setting, answer correctness depends not only on relevance, but also on the authoritativeness, freshness, and applicability of the retrieved evidence to the current system state [5, 6].

The difficulty arises from the heterogeneous evidence base available to the system. Local CSD3 documentation provides the primary record of currently supported local usage [1]; curated external documentation provides further software-specific guidance that may not be covered by the local documentation [2]; and historical support tickets capture concrete prior issue-resolution cases [3]. These sources therefore serve different evidential roles and should not be treated as interchangeable. In particular, historical tickets may become unreliable after changes to system configuration, software versions, or local policy [3, 7]. This project therefore treats HPC support QA as a retrieval problem in which source validity, authority, and freshness must be considered alongside semantic relevance [5, 6].

This project is scoped to evidence-grounded first response assistance for CSD3 user support queries within a supervised internal support workflow, rather than a fully autonomous public-facing application. The present system is restricted to text-accessible evidence, using documentation text and visible ticket content rather than attachments, screenshots, log files, or other non-text artefacts. The study is further scoped to single-hop support queries, excluding more complex tasks that require multiple intermediate retrieval steps. On this basis, the following sections derive the research questions, objectives, success criteria, and evaluation strategy used in the remainder of the report.

1.3 Research Questions and Hypotheses

To investigate the problems introduced by the heterogeneous evidence base, this project addresses the following research questions (RQ), along with the associated hypotheses (H):

- **RQ1:** Does combining local CSD3 documentation with historical support-ticket evidence improve the factual correctness of answers, relative to single-source retrieval?

  - **H1:** Combined retrieval will outperform documentation-only and ticket-only baselines in factual correctness, particularly for case-specific troubleshooting queries for which local documentation and historical resolutions provide complementary evidence.

- **RQ2:** Does validity-aware reranking improve the factual correctness and faithfulness of answers, relative to source-agnostic relevance-based retrieval over the same heterogeneous corpus?

  - **H2:** Validity-aware reranking will outperform source-agnostic retrieval by reducing the selection of outdated, weakly authoritative, or locally inapplicable evidence, with the largest gains on version-sensitive and current-policy queries.

A secondary analysis also examines whether curated external documentation provides incremental benefit for software-specific queries beyond the core local evidence base, while treating such sources as supplementary rather than authoritative for local CSD3 policy or configuration.

These questions, along with their associated hypotheses, are evaluated later through held-out test-set comparisons of source ablations and validity-aware reranking, with paired statistical analysis where appropriate.

1.4 Aim, Objectives, and Success Criteria

The principal aim of this project is to design and evaluate an end-to-end RAG assistant for use in a supervised CSD3 support workflow. Within the scope of single-hop, text-accessible user support queries, the project investigates whether combining heterogeneous support evidence with validity-aware retrieval improves the factual correctness and faithfulness of grounded first-response answers. To achieve this aim, the project pursues the following objectives:

- **O1:** To construct a reproducible, queryable support corpus from local CSD3 documentation, historical support tickets, and selected external documentation, using source-specific preprocessing, chunking, and metadata enrichment.

- **O2:** To implement an end-to-end RAG assistant and baseline retrieval configurations for CSD3 support queries, capable of producing grounded first-response answers from retrieved evidence.

- **O3:** To design and integrate a validity-aware retrieval and reranking strategy that uses authority, scope, freshness, version, and status signals to prioritise evidence appropriate to the current CSD3 environment.
- **O4:** To develop a benchmark and experimental framework for single-hop CSD3 support queries, including a fixed development and test split and manually verified benchmark annotations for source requirements and validity sensitivity.
- **O5:** To evaluate whether heterogeneous-source retrieval and validity-aware reranking improve factual correctness over relevant baselines through controlled ablations, finalist comparisons, manual evaluation, and error analysis.

The success of these objectives will be determined by the following success criteria:

Primary Research Success Criteria

- **SC1:** The project provides a convincing held-out test-set answer to whether combining local documentation and historical support tickets improves factual correctness over single-source baselines.
- **SC2:** The project produces a convincing held-out test-set answer to whether validity-aware reranking improves over naive combined retrieval, judged primarily by factual correctness and checked against faithfulness.
- **SC3:** The project reaches a justified conclusion about the role of external documentation for software-specific queries, including the possibility that any benefit is limited or conditional.

Supporting Implementation and Validity Success Criteria

- **SC4:** A working end-to-end RAG assistant is implemented for the scoped task of supervised, single-hop, text-accessible CSD3 support QA.
- **SC5:** The system can ingest and retrieve from heterogeneous support sources, with local documentation, historical support tickets, and external documentation represented in a reproducible and source-distinct way.
- **SC6:** A fixed benchmark, validated and manually verified annotations, and a frozen development and test evaluation protocol are produced for the in-scope query class, supporting subgroup analysis of source requirements and validity sensitivity.

- **SC7:** The final conclusions are supported by controlled experiments, reproducible artefacts, and honest failure analysis, so that the strengths, limitations, and practical value of the approach can be assessed clearly.

These success criteria distinguish the core research questions from the supporting implementation requirements and provide the basis for the evaluation strategy outlined in the next section.

1.5 Overview of Evaluation Strategy

The evaluation strategy for this project was designed to test whether heterogeneous-source, validity-aware retrieval improved HPC support answer quality.

The curated benchmark was split into development and held-out test partitions so that model selection and tuning could be performed separately from final evaluation, reducing selection bias in the reported results [8]. The development set was used for generator selection and hyperparameter tuning, while the held-out test set was reserved for final comparisons.

A separate ablation was performed to investigate:

- whether combining documentation and tickets outperformed single-source retrieval,
- whether validity-aware reranking outperformed naive combined retrieval, and
- whether external documentation provided additional benefit on software-specific queries.

This allowed the contribution of each experimental factor to be assessed more directly and reduced confounding relative to a single aggregate comparison.

Retrieval Augmented Generation Assessment (RAGAs) was used as the primary evaluation framework for all ablations, because it provides scalable LLM-based scoring across both retrieval and generation [9]. Factual correctness was the primary metric for all comparisons because the central aim of the project is to improve the correctness of support answers. Faithfulness was used as a guardrail metric since RAG systems must ensure that generated answers are grounded in the retrieved evidence and not make unsupported claims [9]. Additionally, context precision and context recall were used for retrieval ablations as diagnostic metrics to assess whether changes to retrieval improve the focus and coverage of the retrieved evidence [9].

Manual evaluation complemented automated scoring, because automated judge-based metrics could miss some user-relevant response qualities [10]. Error analysis was also used to identify specific failure modes of the system and support critical evaluation beyond metric scores. A different model family was used for the evaluation and generation LLMs to reduce the risk of self-preference bias in LLM-as-a-judge evaluations [11].

The full experimental protocol is further described in Chapter 5, with results presented in Chapters 6 and 7.

1.6 Report Structure

This report is structured with each subsequent chapter building on the previous, providing further background and context for the project. Chapter 2 reviews relevant literature on HPC user support, RAG systems, evidence quality in retrieval, and the evaluation of RAG systems. Chapter 3 formalises the problem definition, requirements, success criteria, and ethical considerations for the project. Chapter 4 describes the design and implementation of the system, including the corpus construction, retrieval design, and overall system architecture. Chapter 5 outlines the experimental methodology used to evaluate the research questions. Chapter 6 presents the results of the experiments, while Chapter 7 provides an analysis of the findings, their implications, and limitations. Finally, Chapter 8 summarises the contributions of the project and suggests directions for future work.

Chapter 2

Background and Related Work

This chapter introduces the relevant background and related work for this project, structured around its key design decisions. It starts by framing HPC support as an information retrieval and question answering problem, then introduces the concept of RAG and its relevance to this domain. The chapter also discusses the heterogeneous nature of support corpora, including documentation and tickets, and the challenges of authority, freshness, and validity in retrieval. Finally, it reviews existing evaluation methodologies for RAG systems, and positions this research within the broader landscape of related work.

2.1 HPC Support as an Information Retrieval and Question Answering Problem

Current user support for HPC systems such as CSD3 is typically delivered through a combination of documentation, helpdesk systems, and direct communication with support staff and HPC experts [2]. User documentation is a central component of HPC support and often serves as the first point of reference for users [2]. Bondapalli et al. [2] show that this guidance is often fragmented across multimodal sources, making relevant information difficult and time-consuming to locate. As HPC systems and software stacks continue to grow in complexity, even experienced users may need to integrate guidance from multiple sources, creating barriers to usability and increasing reliance on support channels [2]. This is particularly important in the context of HPC support, where incorrect guidance can result in misconfigurations, failed computations, wasted computational resources, or even violations of facility policies [2].

These characteristics make HPC support a natural Information Retrieval (IR) and QA problem [2, 12]. In the technical support setting, answering a user's query is a two-stage process: the system must first retrieve the relevant documents or support artefacts, and the retrieved information must then be read to identify the answer [12]. Specifically, the retrieved information must not only be semantically similar to the user's query, but it must also contain the required information to answer the question [12]. This is particularly important for procedural and troubleshooting questions, for which the answer is non-factoid and often requires actionable guidance rather than a memorised fact [12, 13]. The task is further complicated because the required documentation may be missing or difficult to locate in fragmented support environments [2, 12].

Technical support QA differs from general open-domain QA in several key ways [12]. First, it is grounded in real user queries that often refer to products, versions, configurations, commands, error messages, and stack traces [13]. Second, Yu et al. [12] argue that, in contrast to general open-domain QA, technical support QA often contains a weak lexical overlap between the question and the answer. Therefore, documents that appear semantically relevant may fail to contain the actual resolution. Straightforward retrieve-then-read pipelines may return such documents, making them more error-prone in technical settings [12]. Third, technical QA is constrained by relatively small labelled datasets, since annotation requires domain expertise and is significantly more expensive than crowd-sourced open-domain annotation [12, 13]. Taken together, these characteristics make direct transfer from methods trained on open-domain corpora more difficult and can lead to weaker performance in technical settings [12, 13].

In addition to local documentation, historical support tickets provide another source of operational support knowledge in HPC settings [14]. TicketHub shows that historical support tickets can help staff identify prior issues and resolutions, improving the efficiency of support responses [14]. The authors further show that improved access to archival tickets helps preserve operational knowledge and reduces the learning burden on newer staff, especially when institutional systems or workflows change. Therefore, HPC support depends not only on access to documentation, but also on access to prior support interactions and their resolutions [14].

Overall, the literature supports treating HPC support as a specialised form of technical QA in which answers depend on retrieving operationally usable evidence rather than recalling isolated facts [2, 12, 13].

2.2 Retrieval-Augmented Generation

As discussed in 2.1, technical support QA is evidence-dependent: answering a query requires retrieving the relevant external information and identifying an answer within it [12, 13]. For this reason, parametric-only Language Model (LM)s are a weak fit for knowledge-intensive support tasks, because they rely on knowledge stored in model parameters rather than directly verifiable external evidence [4]. As Lewis et al. [4] note, such models are difficult to update, provide limited provenance for their predictions, and can hallucinate on knowledge-intensive tasks. Retrieval-augmented generation (RAG) addresses this limitation by combining language generation with retrieval from an external knowledge source [4].

Lewis et al. [4] define RAG as a hybrid architecture that combines parametric memory in a pre-trained sequence-to-sequence generator model with non-parametric memory in a dense document index. At inference time, a neural retriever selects the most relevant passages for a given input query and the generator produces a response using these passages as additional context. RAG is therefore a retrieval-grounded generation framework intended to improve factual performance while making the evidential basis of an answer more inspectable [4].

Lewis et al. [4] report strong empirical results on open-domain QA, knowledge-intensive generation, and fact verification benchmarks. Their models outperform parametric-only baselines on several open-domain QA tasks and generate more factual, specific, and diverse responses than BART in generation settings [4]. Additionally, because knowledge is stored partly in an external document index, that knowledge can be updated by replacing or rebuilding the index rather than retraining the generator. Related work further shows that retrieval-augmented generation can reduce hallucination in grounded conversation settings [15].

However, the original RAG architecture does not by itself ensure that retrieval is necessary, that the retrieved material is trustworthy, or that the generator will faithfully use it in the final answer [5, 6, 16]. Asai et al. [16] argue that fixed-k retrieval can be wasteful or harmful when retrieval is unnecessary or when the retrieved passages are weakly grounded. Li et al. [5] show that RAG quality depends on query-knowledge relevance, and that it degrades when the underlying corpus is out of scope or out of date. Hwang et al. [6] further show that relevance alone is insufficient in multi-source settings, because source reliability affects whether retrieved evidence should be trusted. For technical support, this means that semantically relevant material may still be unusable if it is outdated or if it comes from a less reliable source [5, 6].

Approach	Control signal	What it improves	What remains unresolved for CSD3 support
Self-RAG [16]	Retrieval necessity and passage support	Avoids indiscriminate fixed-k retrieval; enables retrieval on demand	Does not model heterogeneous source roles, local authority, or temporal validity across support sources
Li et al. [5]	Query–knowledge relevance / corpus scope	Detects when queries fall outside the effective scope of the corpus or when the corpus is outdated	Does not rank competing sources by authority or local applicability once retrieval proceeds
Hwang et al. [6]	Source reliability	Prioritises reliable and relevant sources in multi-source RAG	Does not directly address support-specific temporal drift or the distinct evidential roles of documentation versus tickets

Table 2.1: The retrieval-control strategies most relevant to validity-aware support retrieval.

Taken together, these studies show that the key design problem is no longer whether to retrieve, but how retrieval should be controlled and which evidence should be prioritised [5, 6, 16]. These control strategies operate at different points in the pipeline: Self-RAG controls whether retrieval is necessary at all [16], Li et al. [5] assess whether the corpus is capable of supporting a query, and Hwang et al. [6] control which sources should be trusted once retrieval occurs. Together they suggest that reliable support RAG requires more than stronger semantic matching. It also requires explicit control over retrieval necessity, corpus scope, and source reliability. Table 2.1 summarises the retrieval-control strategies most relevant to this project, and highlights what each one leaves unresolved for heterogeneous CSD3 support.

The comparison shows that prior work addresses retrieval necessity, corpus scope, and source reliability as separate problems, but does not by itself resolve how these concerns should be combined for heterogeneous support evidence.

Applied support-oriented RAG systems also suggest that retrieval design remains domain-specific. AskHPC, for example, combines curated HPC documentation with specialised parsing [2], while customer-service systems have incorporated structured knowledge graphs to improve retrieval [17]. For HPC support, the implication is that a useful RAG system must not only retrieve semantically relevant information, but must also prioritise evidence that is current, trustworthy, and operationally valid [2, 5, 6].

Source type	Typical authority	Main strength	Main risk	Retrieval implication
Local documentation	Primary authority for site-specific practice	Records supported local workflows, constraints, and policy-relevant configuration [1, 2]	May omit low-level tool detail and edge-case troubleshooting [2]	Prefer for site-specific questions about access, authentication, job submission, permissions, and supported configuration.
External technical documentation	Secondary for local operational truth; strong on tool semantics	Provides tool behaviour, syntax, and configuration detail beyond local guides [2]	Can be relevant yet out-of-scope, out-of-date, or less reliable for local operational decisions [5, 6]	Use as supplementary evidence for software-specific questions; do not treat as decisive for local policy or permissions.
Historical support tickets	Variable: high for prior-case retrieval, weaker for current policy	Preserves concrete problem reports, diagnostic context, and prior resolutions [3, 14]	Lagging, noisy, and privacy-sensitive; may contain stale or user-specific content [3, 14]	Use with freshness controls and access restrictions; strongest for troubleshooting analogies and prior-case retrieval.

Table 2.2: Comparison of the evidential roles, risks, and retrieval implications of the three source types in the CSD3 support setting.

This motivates this project's focus on evidence prioritisation over heterogeneous support sources, rather than treating generation quality as the primary research problem.

2.3 Heterogeneous Support Corpora: Documentation and Tickets

HPC user support draws on a heterogeneous evidence base that includes local facility documentation, external technical documentation, and historical support tickets rather than a single uniform corpus [2, 3, 14]. In this context, heterogeneity means that these sources differ not only in topic coverage, but also in their evidential role, authority, update cycle, and temporal stability [2, 5, 6]. In multi-source retrieval settings, these differences affect whether apparently relevant evidence is still trustworthy, locally applicable, and suitable for the current system state [5, 6]. Source selection is therefore an important part of the retrieval problem [5, 6]. Table 2.2 presents the main evidential strengths, risks, and retrieval implications of the three source types considered in this project.

For facility-specific support, local documentation is the primary documentary source because it records the workflows, constraints, and configurations that are actually supported on the target system [1, 2]. AskHPC describes user documentation as the first point of reference for HPC users, which makes the quality, coverage, and maintenance of local documentation central to scalable support [2]. In the case of CSD3, the local documentation covers access, authentication, job submission, software environments, and site policies [1]. It is therefore the best available source for questions about permitted or supported local practice.

External technical documentation has a complementary evidential role because it can extend local support coverage without displacing local authority [2]. In multi-source RAG, however, such material still raises source-reliability and local-applicability questions [5, 6]. It is most useful when a query depends on tool behaviour, syntax, API usage, or configuration detail that local documentation omits, summarises only briefly, or abstracts away [2]. Bondapalli et al. [2] illustrate this multi-source setting clearly by combining facility guides with scheduler manuals and programming-model documentation to answer queries whose evidence requirements span multiple sources. However, general software documentation cannot by itself establish local operational truth, because current local practice may differ from the general case [2, 5, 6]. As a result, this project treats external documentation as supplementary evidence for CSD3-specific queries rather than as the deciding source on local policy, permissions, or configuration.

Historical support tickets perform a different evidential role to documentation, because they preserve concrete user problems, diagnostic context, troubleshooting paths, and prior resolutions in a way that formal documentation often does not [3, 14]. Rodenbeck and Suk Uhr [14] show that archival ticket analysis can help staff identify common issues, retrieve previous resolutions, and reduce the steep learning curve faced by new staff by making prior cases easier to search. Joslin et al. [3] further show that HPC tickets can be normalised into structured issue-resolution pairs and used to generate FAQ-style support knowledge from recurring support patterns. They also note that ticket corpora are difficult to prepare cleanly because they contain domain-specific terminology, cryptic error messages, inconsistent wording, and user-specific artefacts, all of which complicate normalisation, summarisation, and retrieval. Tickets are also a risky evidence source because they are a lagging indicator of system state. While a closed ticket may preserve a useful resolution, that resolution may no longer be valid after later changes to documentation, software versions, or local policy [5, 14]. Joslin

et al. [3] additionally highlight the privacy and governance constraints of ticket data, since personally identifying and user-specific content may persist even after redaction. Accordingly, ticket evidence often requires stronger access control, heavier preprocessing, and more careful freshness checks that documentation sources [3, 14].

The same passage may be relevant across documentation, external manuals, and historical tickets, but its evidential status changes with source role, local applicability, and temporal currency. For this project, this means indexing and ranking account for source type, local applicability, freshness, and evidential risk alongside semantic relevance [5, 6]. This motivates the validity-aware retrieval design developed in the next section.

2.4 Authority, Freshness, and Validity in Retrieval

Accordingly, the central retrieval question in this project is not simply whether a passage is semantically related to a query, but whether it should be treated as usable evidence for an answer [5, 6]. In a multi-source support corpus, relevance-only retrieval is inadequate because a highly relevant document may come from an unreliable source, or a seemingly appropriate corpus may still fail if the query lies beyond its effective scope or depends on outdated knowledge [5, 6]. This is especially problematic in operational support settings, where outdated information can reduce response accuracy and even steer generation towards harmful answers despite the simultaneous presence of current evidence [18]. Here, authority refers to the trustworthiness of a source, freshness to the temporal currency of its information, and validity to the suitability of retrieved evidence for the current local support context.

Authority becomes a retrieval variable once the corpus varies not only in topic coverage but also in evidential trustworthiness [6]. Hwang et al. [6] show that standard multi-source RAG can retrieve incorrect information because it relies on relevance alone while overlooking source reliability. This can allow unreliable sources to dominate the retrieval process. As discussed in Section 2.3, this is especially important for operational support questions about local policy, permissions, and supported configuration, where generic software documentation cannot by itself establish local operational truth. Authority is therefore a retrieval problem, not just a post-hoc verification problem: if authoritative evidence is not prioritised before generation, the model may still ground its answer in semantically relevant but less trustworthy material [6].

Freshness is important because the evidential value of a retrieved document can

decay over time, even when its semantic relevance remains high [5, 18]. Li et al. [5] show that RAG performance degrades when the underlying corpus is out of date or no longer adequately supports the active query distribution. Ouyang et al. [18] further demonstrate that the presence of outdated information in retrieved context can substantially reduce answer accuracy despite the simultaneous presence of current evidence. In HPC support, this temporal risk is amplified because the operational environment itself changes over time, as software stacks, documentation, policies, and even the available hardware evolve, meaning that older resolutions may no longer reflect the current system state [3, 7, 14]. Therefore, freshness is not only a useful ranking heuristic, but also a condition on whether retrieved evidence can still be safely used to answer present-focused operational queries [5, 18].

In this dissertation, validity is used as an operational term for retrieved evidence that is not only semantically relevant, but also authoritative, current, and locally applicable. This means that a passage can be topically relevant yet still be invalid if it comes from a less trustworthy source, reflects an outdated system state, or does not establish the correct local operational truth [5, 6]. This suggests that temporal validity should not be reduced to a simple age threshold alone, since the usability of support evidence depends on whether it still reflects the current local operational context. It also explains why indiscriminate fixed-k retrieval is risky in this setting: adding more semantically related context does not guarantee better grounding, and the generator is not guaranteed to follow the retrieved evidence faithfully [16]. Validity-aware retrieval should therefore prefer evidence that is jointly relevant, reliable, current, and applicable to the local support context, rather than treating semantic similarity alone as sufficient ranking criteria [5, 6, 16].

Taken together, these studies imply that retrieval for HPC support should not be organised as a relevance-only search over a flattened corpus. Instead, it should incorporate source-aware preferences, freshness-sensitive controls, and local applicability constraints so that generation is grounded primarily in evidence that is defensible in the current support context [5, 6, 18]. They also suggest that when retrieved evidence is weak, stale, or conflicting, conservative response behaviour is preferable to forced resolution [5, 16]. Therefore, this project treats validity-aware retrieval as a prerequisite for trustworthy support generation, which motivates the retrieval and reranking design developed in Chapter 4.

2.5 Evaluation of RAG Systems

Evaluating RAG systems is more complex than evaluating standalone LMs because quality depends both on what evidence is retrieved and on how faithfully the generator uses that evidence [9, 19]. A single end-to-end score is therefore insufficient because a poor final answer could be caused by retrieval failure, incomplete evidence, or weak use of otherwise valid context [19]. As a result, recent work treats RAG evaluation as a multi-dimensional problem that separates retrieval quality from grounded generation quality [9, 20]. This is typically operationalised through measures such as context relevance, answer faithfulness, and answer relevance [9].

RAGAS provides a scalable, reference-free framework for evaluating RAG systems using three core dimensions: faithfulness, answer relevance, and context relevance [9]. This decomposition is especially useful during system development, because it enables rapid comparison of RAG systems even when human-annotated references are unavailable [9]. ARES challenges the assumption that prompt-based judge frameworks are automatically reliable, showing that evaluation improves when judges are tailored to the target setting and calibrated with a small human-annotated validation set [20]. Automated metrics are therefore valuable for scalable iteration, but they still require scrutiny over judge design and validation before they should be trusted for strong comparative claims [9, 20].

Even when automated frameworks report several quality dimensions, evaluation still remains too coarse if it only produces overall scores without showing where failure arose [19]. Ru et al. [19] therefore argue that RAG evaluation should serve both user-facing comparison and developer-facing diagnosis, because errors may originate in retrieval, generation, or in the interaction between the two. RAGChecker extends this line of work by moving from response-level assessment to claim-level entailment checking and by separating overall metrics from diagnostic retriever and generator metrics [19]. This is particularly important for system development, since fine-grained evaluation can expose trade-offs that aggregate scores hide, such as retrieval improvements that also introduce noise or generators that appear strong overall but still produce unsupported claims [19].

Metric choice alone does not make RAG evaluation convincing. In particular, the benchmark must also expose the retrieval conditions under which the systems fail [21]. Ben [21] address this directly in their Retrieval-Augmented Generation Benchmark (RGB) benchmark by organising evaluation around four fundamental abilities for RAG: noise robustness, negative rejection, information integration, and counterfactual

robustness. This choice of evaluation cases is especially valuable since it tests not only whether a model can answer when helpful evidence is present, but also whether it can refuse when evidence is missing, combine evidence across documents, and resist misleading retrieved content [21].

Taken together, the literature supports that strong RAG evaluation should combine scalable automated scoring with smaller amounts of human-grounded validation and targeted diagnostic analysis, rather than relying on any single framework or headline metric alone [9, 19, 20]. Automated frameworks remain valuable because they make the iterative comparison of RAG configurations practical at development time, especially when large-scale human annotation is unavailable [9, 20]. However, both the limitations of LLM-as-a-judge methods and the importance of diagnostic analysis indicate that automated scores should be interpreted with caution and complemented by human judgement and failure analysis when drawing stronger comparative conclusions [9, 19, 20]. These studies justify the evaluation design developed in Chapter 5, which uses automated metrics for scalable ablation and comparison, while retaining manual evaluation and error analysis to assess response quality and identify failure modes.

2.6 Gap Analysis and Research Positioning

The reviewed literature positions HPC support as a specialised retrieval-grounded QA problem rather than a generic chatbot task [2, 12]. AskHPC show that HPC support information is scattered across multiple sources [2], while Yu et al. [12] frame technical support QA as a retrieve-then-read process in which relevant evidence must be found before an answer can be identified. This is important because answer quality depends on appropriate external evidence, while technical-support datasets are often limited by the cost of expert annotation [12, 13].

This chapter has also shown that the support evidence base is heterogeneous rather than uniform, with each source contributing a different type of information [2, 3, 14]. In particular, local documentation, external technical documentation, and historical support tickets provide current site-specific guidance, supplementary software detail, and prior issue-resolution experience respectively [2, 3, 14]. Furthermore, since these sources differ in authority, temporal stability, and local applicability, they cannot be treated as interchangeable [3, 5, 6].

The heterogeneity of the underlying support corpus exposes a limitation in baseline RAG architectures. Although baseline RAG improves knowledge-intensive generation

by grounding outputs in external knowledge [4], later work shows that reliable RAG also depends on whether retrieved evidence is in scope, current, and trustworthy [5, 6, 18]. In particular, Li et al. [5] show that degradation occurs when the underlying corpus is out of scope or out of date, Hwang et al. [6] show that relevance-only retrieval overlooks source reliability, and [18] show that outdated evidence can reduce accuracy and mislead generation even when valid evidence is present.

The resulting literature gap is therefore not that HPC support has never been addressed using retrieval-augmented generation. AskHPC, for example, demonstrates the value of documentation-grounded RAG for HPC user support, and ticket-focused studies highlight the value of historical support interactions [2, 3, 14]. This review did not identify prior work that jointly evaluates retrieval-time evidence prioritisation across documentation and tickets when those sources differ in freshness, authority, and local validity [5, 6, 18]. More specifically, this review did not identify prior work that tests whether answer quality improves when heterogeneous support sources are combined with validity-aware reranking rather than source-agnostic semantic retrieval.

The dissertation is therefore positioned against a narrow gap defined by the intersection of heterogeneous support evidence, validity-aware prioritisation, and supervised first-response assistance for CSD3. Within this scope, the project tests whether combining documentation and tickets improves factual correctness over single-source baselines, and whether validity-aware reranking improves over naive combined retrieval.

The literature further implies that evaluation must mirror the structure of the problem. Es et al. [9] argue that RAG quality cannot be reduced to a single end-to-end score, while Ru et al. [19] show that useful diagnosis requires separating retriever and generator failure modes. As a result, the later chapters evaluate retrieval quality, faithfulness, factual correctness, and error patterns rather than relying on one headline metric.

Chapter 3

Problem Formulation and Requirements

3.1 Task Definition

This section formulates CSD3 user support as a single-hop, evidence-grounded question-answering task within a supervised internal support workflow. Given a natural-language support query and a heterogeneous evidence base consisting of local documentation, selected external documentation, and historical support tickets, the system must retrieve evidence passages that are not only semantically relevant, but also sufficiently authoritative, current, and locally applicable to the present CSD3 environment. It must then generate a first-response answer suitable for staff-assisted use: factually correct, faithful to the retrieved evidence, and appropriately qualified for the local operational context. This framing is consistent with retrieval-augmented generation for knowledge-intensive tasks, where answer quality depends on access to external evidence rather than parametric memory alone [4], and with technical support QA, which is naturally structured as a retrieve-then-read problem [12]. It also reflects recent findings that apparently relevant evidence may still be unsuitable if it is out of scope, out of date, or drawn from less reliable sources [5, 6].

In this dissertation, a query is treated as single-hop when it can be answered from one passage, or a small set of closely related passages, retrieved in a single retrieval step, without subsequent query reformulation, multi-stage decomposition, or chained intermediate retrieval. The task is further scoped to documentation text and visible ticket text. Uploaded attachments and embedded media, including screenshots and log files, are excluded from retrieval even where they contain text. This is a methodological

restriction that was chosen to reduce confounding from evidence-composition failures and multimodal interpretation errors, so that performance differences can be attributed more cleanly to heterogeneous-source retrieval and validity-aware reranking. It also keeps the benchmark reproducible by ensuring that all evaluated conditions operate over the same visible textual evidence.

The intended output of the system is not an autonomous final resolution, but evidence-grounded first-response assistance for realistic CSD3 support queries. The system is therefore designed for use within a supervised workflow, where retrieved evidence and generated answers can be reviewed by support staff before action is taken. Within this setting, the system should prefer cautious, qualified assistance when the available evidence is incomplete, conflicting, stale, or otherwise uncertain, rather than forcing an overconfident resolution. This operational framing aligns the task with the practical requirements of internal HPC support while preserving a controlled scope for later evaluation.

3.2 Data Sources and Knowledge Characteristics

The evidence base for this project consists of three heterogeneous source classes: local documentation, selected external documentation, and historical support tickets. These sources were indexed as source-distinct corpora rather than flattened into a single undifferentiated text pool, because they differ in evidential role, authority, temporal stability, and local applicability. Table 3.1 summarises the operational role and retrieval implications of each source class.

Local CSD3 documentation formed the primary documentary source in the system, since it records the workflows, policies, access conditions, and locally supported configurations that define current site-specific practice [1, 2]. Operationally, the local corpus was restricted to internal HTML pages reachable from the CSD3 documentation homepage within the `docs.hpc.cam.ac.uk/hpc/` subtree. This restriction prioritised pages that directly express current local operational guidance and excluded loosely related material outside the core documentation boundary. The resulting frozen local documentation snapshot used in parameter tuning and final evaluation contained 44 pages. In retrieval terms, this source acts as the default authority for questions about what is currently supported on CSD3.

Selected external documentation formed a supplementary documentary source, extending coverage when queries depended on software-specific detail not fully captured

Source class	Evidential role	Inclusion basis and scale	Main exclusions	Retrieval implication
Local documentation	Primary record of current site-specific practice	Internal HTML pages within the core CSD3 documentation subtree; 44 pages	Out-of-subtree and non-HTML material	Highest local authority; should dominate questions about supported workflows, policy, access, and configuration
Selected external documentation	Supplementary software and toolchain detail	Stable official manuals relevant to the CSD3 support domain; 13 sources, 662 pages	Community-managed, non-official, overly broad, or misaligned subtrees	Useful for software behaviour, syntax, and APIs, but should not override local policy or configuration evidence
Historical support tickets	Prior-case troubleshooting evidence from resolved interactions	Resolved CSD3 support tickets from November 2017 to 1 April 2026 inclusive; 89,905 tickets	Unresolved tickets and attachment/media contents as retrievable evidence	High coverage for recurring issues and diagnostic context, but noisier, more privacy-sensitive, and more temporally fragile than documentation

Table 3.1: Operational summary of the three source classes included in the project corpus. Counts and date bounds refer to the frozen corpus snapshot used for parameter tuning and final evaluation. The full external source list is given in Appendix A.

in the local documentation [2]. Sources were included only when they were stable official manuals for software or toolchains relevant to the CSD3 support domain and likely to contribute detail on software behaviour, syntax, APIs, or configuration beyond the local corpus. Community-managed, non-official, overly broad, or otherwise misaligned documentation subtrees were excluded. The approved set was defined in an external source registry and the frozen external documentation snapshot used for parameter tuning and final evaluation contained 13 sources, with a total of 662 pages. The full approved source list is provided in Appendix A. While these documents expand technical coverage, they do not displace local documentation as the deciding source on site-specific policy, permissions, or configuration.

Historical support tickets formed the third source class, providing prior-case evidence from past support interactions that may contain diagnostic context, troubleshooting paths, and previously successful resolutions [3, 14]. This project considered all resolved CSD3 support tickets from November 2017 to 1 April 2026 inclusive. Only tickets with the Jira status `Resolved` were ingested. Attachment and embedded media content were not semantically interpreted during ingestion. Instead, media references were converted into textual placeholders indicating that an attachment was present without treating its contents as retrievable evidence. This preserved ticket conversation context while keeping the corpus within the text-accessible scope defined in Section 3.1. The resulting frozen ticket snapshot used for parameter tuning and final evaluation contained 89,905 tickets. Compared with documentation, tickets provide richer prior-case detail, but are also noisier, more lexically variable, more privacy-sensitive, and more vulnerable to temporal decay [3, 14].

Taken together, these source classes were deliberately retained as distinct evidential categories rather than being merged into a single homogeneous corpus. Source identity, temporal fields, and authority-related metadata therefore needed to be preserved so that later retrieval and reranking could prefer current local documentation for site-specific questions, use external manuals as supplementary software evidence, and exploit historical tickets primarily as prior-case troubleshooting support.

3.3 Benchmark and Query Taxonomy

This section describes the construction of the benchmark dataset used for parameter tuning and final evaluation, along with the query taxonomy used for later performance analysis. This benchmark was designed to reflect realistic CSD3 support queries while remaining within the single-hop, text-accessible scope defined in Section 3.1.

To ground the benchmark in realistic operational demand, the Head of HPC Services at the University of Cambridge Research Computing Services was consulted to identify a comprehensive set of realistic user-support topics. This consultation resulted in a set of 47 representative support-topic keywords spanning a broad range of common CSD3 support themes. These keywords were used as seed topics for benchmark construction, rather than for the final query taxonomy. The 47 keywords were queried through the Jira API to retrieve candidate tickets, ordered by resolution date with the most recent first. For each keyword, candidate tickets were screened manually, with duplicates across keyword searches removed before final selection. Candidate tickets

were then manually reviewed for inclusion based on realism, relevance to CSD3 support, diversity of query types, and alignment with the scoped task definition. Recently resolved tickets were prioritised to ensure that the benchmark reflected current support demand and could be answered from the frozen evidence snapshot. Tickets were excluded if they were duplicative, clearly out of scope, dependent on unseen attachments, or required additional information that would not be available to the system at inference time. The final benchmark size of 100 queries was chosen to preserve broad topical coverage while keeping later evaluation tractable.

The resulting benchmark dataset contained 100 standalone evaluation queries, each derived from the initial user-facing query of a selected support ticket. This prevented trivial retrieval of the original ticket and reduced benchmark contamination, ensuring that system performance reflected generalisation over the remaining evidence base rather than recovery of a near-duplicate source instance. This benchmark therefore follows the general logic of test-collection-based IR evaluation, in which a fixed query set is evaluated against a fixed evidence corpus [22]. However, it is not a full Cranfield-style collection, since no exhaustive relevance judgements or fixed gold contexts were identified for each query. No fixed reference passage set was attached to each query, since in the heterogeneous support setting there may be multiple valid evidence combinations that could support a correct answer. Pre-specifying a single target context would therefore impose an artificially narrow notion of retrieval success.

To support later subgroup analysis, the benchmark taxonomy was implemented as a multi-label annotation scheme rather than as a single topic label. Each query was annotated across seven categories: the minimum evidence source needed for a correct answer; the required documentary scope; whether correctness depends on current local operational truth; whether unseen attachments materially affected the response; the broad query family; whether the query was explicitly version-sensitive; and whether the answer depended on a particular system, service, partition, or platform. The full label definitions and allowed values are provided in Appendix B. All taxonomy labels were assigned manually by the author. However, this benchmarks remains subject to several limitations: topic labels were curated from a single expert rather than through a consensus process; keyword-based candidate retrieval may miss differently phrased tickets, and manual curation and annotation introduce researcher bias.

3.4 Requirements and Constraints

This section formalises the practical requirements and constraints that follow from the task definition, heterogeneous evidence setting, and benchmark methodology developed in Sections 3.1 to 3.3. It translates the problem formulation into explicit system requirements against which later design and evaluation decisions can be judged. To support a more rigorous methodology, the requirements are grouped into three classes: functional requirements, which define what the system must do; quality requirements, which define the standard the system should achieve; and constraints, which define the intended scope and limits of the project. These requirements and constraints are summarised in Table 3.2, which also provides the rationale needed for direct mapping into the success criteria defined in Section 3.5.

Table 3.2: Functional requirements, quality requirements, and scope constraints derived from the project task definition and benchmark design.

ID	Requirement	Type	Rationale
R1	The system must retrieve candidate evidence from all three source classes: local documentation, selected external documentation, and historical support tickets.	Functional	The task is defined over a heterogeneous evidence base, so retrieval must not assume a single uniform corpus.
R2	The system must rank retrieved evidence using source-aware validity criteria rather than semantic relevance alone.	Functional	In this setting, relevant evidence may still be outdated, non-authoritative, or locally inapplicable.
R3	The system must generate an evidence-grounded first-response answer rather than an unsupported free-form response.	Functional	The project concerns staff-assisted support, not general conversational helpfulness.
R4	The system must support supervised use by producing outputs that can be reviewed by support staff.	Functional	The intended deployment setting is assistive rather than autonomous.
Q1	Answers should be factually faithful to the retrieved evidence.	Quality	Hallucinated or weakly grounded answers are especially harmful in technical support.
Q2	The system should prioritise locally authoritative and current evidence when these conflict with more generic or outdated sources.	Quality	Local operational truth has priority over generic or outdated documentation.

Continued on next page

Table 3.2 continued from previous page

ID	Requirement	Type	Rationale
Q3	The system should avoid overconfident resolution when the available evidence is incomplete, conflicting, or uncertain.	Quality	Overconfident but incorrect support guidance is operationally risky.
Q4	The benchmarked system configuration should be reproducible from frozen corpora and benchmark definitions.	Quality	Evaluation claims are only defensible if the setup is stable and auditable.
C1	The task is restricted to single-hop support queries.	Constraint	This keeps the problem controlled and avoids confounding from multi-stage reasoning.
C2	The task is restricted to evidence available in document text and visible ticket text.	Constraint	This keeps all evaluated conditions within the same visible evidence space.
C3	Attachments and embedded media are excluded from semantic interpretation.	Constraint	This avoids introducing multimodal processing as an uncontrolled source of variance.
C4	The evaluation does not assume exhaustive gold retrieval contexts for benchmark queries.	Constraint	In this heterogeneous setting, multiple valid evidence paths may support a correct answer, making a single exhaustive target context inappropriate.
C5	The system is not required to autonomously resolve out-of-scope, multi-stage, or attachment-dependent cases.	Constraint	These cases fall outside the project's controlled task definition.

These requirements define the formal contract for the project rather than a broad statement of aspiration. They specify both the intended capabilities of the system and the conditions under which its evaluation claims can be considered valid. Section 3.5 will later map each requirement into corresponding success criteria and evaluation conditions.

3.5 Success Criteria and Requirement-to-Evaluation Mapping

This section translates the functional requirements, quality requirements, and constraints defined in Section 3.4 into explicit success criteria and defines how each of these criteria will be evaluated. It formalises the success criteria already stated in

Chapter 1 by mapping `SC1` to `SC7` onto the requirements of the project. Table 3.3 summarises this mapping, together with the evaluation method and decision bases used to judge whether each criterion has been met. All comparative claims are made under a frozen development and test protocol in which development data is used for tuning and design decisions, while final conclusions are based on held-out test results.

Table 3.3: Success-criteria and requirement-to-evaluation mapping for the project.

SC	Req. IDs	Success criterion	Evaluation method	Decision basis
SC1	R1, R3, Q1	The project provides a convincing held-out test-set answer to whether combining local documentation and historical support tickets improves factual correctness over single-source baselines.	Comparative benchmark runs under a frozen development/test protocol, with development data used for tuning and held-out test data used for final comparison.	Met if held-out test results support a clear comparative conclusion about combined retrieval versus single-source baselines, judged primarily by answer correctness and checked against faithfulness.
SC2	R2, Q1, Q2	The project provides a convincing held-out test-set answer to whether validity-aware reranking improves over naive combined retrieval.	Comparative ablation runs on the held-out benchmark, including subgroup analysis of validity-sensitive queries.	Met if held-out results support a justified conclusion about the effect of validity-aware reranking, whether the observed effect is positive, neutral, or conditional.
SC3	R1, Q2	The project reaches a justified conclusion about the role of external documentation for software-specific queries.	Source-ablation subgroup analysis on benchmark subsets requiring external or mixed documentary scope.	Met if the evaluation shows, on held-out queries, whether external documentation is beneficial, unnecessary, or only conditionally useful for the scoped query class.
SC4	R3, R4, C1, C2, C3, C5	A working end-to-end RAG assistant is implemented for supervised, single-hop, text-accessible CSD3 support QA.	End-to-end system demonstration and benchmark execution on in-scope queries.	Met if the system can execute the full pipeline, produce reviewable first-response answers, and remain within the scoped task definition.

Continued on next page

Table 3.3 continued from previous page

SC	Req. IDs	Success criterion	Evaluation method	Decision basis
SC5	R1, Q4	The system can ingest and retrieve from heterogeneous support sources in a reproducible and source-distinct way.	Corpus audit, metadata inspection, and source-specific retrieval runs under common system settings.	Met if local documentation, external documentation, and historical tickets can each be indexed, retrieved, and analysed separately and in combination, with source identity preserved.
SC6	Q4, C1, C2, C3, C4	A fixed benchmark, verified annotations, and a frozen development/test evaluation protocol are produced for the in-scope query class.	Audit of benchmark files, split definitions, annotation codebook, and review-status controls.	Met if final experiments use the frozen benchmark artefacts and only manually verified annotations, with no post hoc change to test queries or evaluation protocol.
SC7	Q1, Q3, Q4, C4, C5	The final conclusions are supported by controlled experiments, reproducible artefacts, and honest failure analysis.	Review of experimental controls, frozen artefacts, held-out test results, and structured error analysis.	Met if the final claims are tied directly to the held-out evaluation, reproducible inputs, and explicit analysis of limitations, uncertainty, and failure cases.

Not all success criteria in Table 3.3 are evaluated in the same way. Some are primarily comparative and quantitative, particularly those concerning source combination, validity-aware reranking, and the role of external documentation. Others are primarily compliance or quality criteria, assessed through corpus audits, benchmark controls, faithfulness judgments, and structured error analysis. Therefore, success does not require perfect performance on every benchmark query. Instead, it requires that the held-out evaluation provides a justified answer to the project's research questions, that the system behaves credibly within the scoped task definition, and that the final conclusions are supported by reproducible artefacts and honest analysis of limitations and failure cases.

3.6 Ethical, Privacy, and Data-Governance Considerations

This project uses real internal support tickets as a primary data source. As a result, its main ethical concerns are privacy, confidentiality, and the risk of unsafe operational

advice. Historical tickets were not anonymised before ingestion, however this is justified by the intended development setting: the system is designed only for internal use within the CSD3 support service, where authorised staff already handle these records as part of normal support operations. Preserving the original ticket text also avoids distorting the operational context needed for realistic retrieval and evaluation. However, although the internal ticket corpus was not anonymised for system development, any ticket excerpts or illustrative examples included in the dissertation will be anonymised and minimised to avoid disclosing unecessary personal or operationally sensitive information. Risk was further reduced through governance and scope control: access was limited to internal project use, frozen corpora and benchmark artefacts were not intended for public release, attachment contents were excluded from semantic interpretation, and the system was framed as supervised first-response assistance rather than autonomous resolution. Residual risks remain. In particular, retrieved ticket text may contain personal information or incomplete context, and that generated answers may still be wrong. Furthermore, personally identifiable information present in retrieved ticket text could be reproduced unnecessarily in generated answers. These risks are acknowledged explicitly and mitigated through restricted access, staff oversight, and evaluation focused on faithfulness and cautious behaviour.

Chapter 4

System Design and Implementation

4.1 System Overview

4.2 Baseline Systems

4.3 Corpus Ingestion and Representation

4.4 Authority Registry and Metadata Extraction

4.5 Validity-Aware Retrieval and Reranking Design

4.6 Prompt and Generation Design

4.7 API, Tooling, and Observability

4.8 User Interface and Interaction Design

4.9 Verification and Software Testing

4.10 Design Trade-offs

Chapter 5

Experimental Methodology

5.1 Evaluation Goals

5.2 Development and Test Split Discipline

5.3 Benchmark Construction and Characterisation

5.4 Frozen Backbone Decisions

5.5 Metric Hierarchy and Decision Rules

5.6 Development-Phase Tuning Protocol

5.6.1 Generator Selection

5.6.2 Chunking Tuning

5.6.3 Retrieval-Mode Pilot

5.6.4 Shared Retrieval Budget Tuning

5.6.5 Validity-Reranker Tuning

5.7 Final Test-Set Experiments

5.7.1 Source Ablation

5.7.2 Validity-Signal Ablation

5.7.3 External-Document Scope Ablation

5.7.4 Tuned Final-Set Comparison

Chapter 6

Results

6.1 Development-Phase Selection Results

6.2 Overview of Main Test-Set Results

6.3 Controlled Ablation Results

6.3.1 Source Ablation

6.3.2 Validity-Signal Ablation

6.3.3 External-Document Scope Ablation

6.4 Practical Comparison Results

6.4.1 Tuned-Finalist Comparison

6.5 Manual Evaluation Results

6.6 Error Analysis Results

6.7 Stability and Robustness Results

Chapter 7

Discussion and Critical Appraisal

7.1 Answers to the Research Questions

7.2 What Improved and Why

7.3 Comparison with Prior Work

7.4 Where the System Still Fails

7.5 Threats to Validity

7.6 Review of the Project Plan

Chapter 8

Conclusion and Future Work

8.1 Summary of Contributions

8.2 Main Findings Against Objectives

8.3 Limitations

8.4 Future Work

Bibliography

[1] "Research Computing Services HPC Documentation — CSD3 1.0 documentation," https://docs.hpc.cam.ac.uk/hpc/index.html.

[2] A. Bondapalli, H. Zheng, O. T. Ajayi, M. Keceli, H. Siddabathuni Som, T. Childers, L. Childers, Y. Ghadar, M. Papka, V. Vishwanath, and R. Ge, "Askhpc: A chatbot for high performance computing user support," in *Proceedings of the SC '25 Workshops of the International Conference for High Performance Computing, Networking, Storage and Analysis*, ser. SC Workshops '25. New York, NY, USA: Association for Computing Machinery, 2025, p. 727–739. [Online]. Available: https://doi.org/10.1145/3731599.3767433

[3] C. Joslin, D. Burns, F. Ashish, and E. Sarbijan, "Generating Frequently Asked Questions from Technical Support Tickets using Large Language Models," in *Proceedings of the SC '25 Workshops of the International Conference for High Performance Computing, Networking, Storage and Analysis*, ser. SC Workshops '25. New York, NY, USA: Association for Computing Machinery, Nov. 2025, pp. 715–726.

[4] P. Lewis, E. Perez, A. Piktus, F. Petroni, V. Karpukhin, N. Goyal, H. Küttler, M. Lewis, W.-t. Yih, T. Rocktäschel, S. Riedel, and D. Kiela, "Retrieval-augmented generation for knowledge-intensive NLP tasks," in *Proceedings of the 34th International Conference on Neural Information Processing Systems*, ser. NIPS '20. Red Hook, NY, USA: Curran Associates Inc., Dec. 2020, pp. 9459–9474.

[5] Z. Li, J. Zhang, C. Yan, K. Das, S. Kumar, M. Kantarcioglu, and B. A. Malin, "Do You Know What You Are Talking About? Characterizing Query-Knowledge Relevance For Reliable Retrieval Augmented Generation," in *Proceedings of the*

2024 Conference on Empirical Methods in Natural Language Processing, Y. Al-Onaizan, M. Bansal, and Y.-N. Chen, Eds. Miami, Florida, USA: Association for Computational Linguistics, Nov. 2024, pp. 6130–6151.

[6] J. Hwang, J. Park, H. Park, D. Kim, S. Park, and J. Ok, "Retrieval-Augmented Generation with Estimation of Source Reliability," in *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, C. Christodoulopoulos, T. Chakraborty, C. Rose, and V. Peng, Eds. Suzhou, China: Association for Computational Linguistics, Nov. 2025, pp. 34 279–34 303.

[7] "CSD3 Upgrade October 2021 — CSD3 1.0 documentation," https://docs.hpc.cam.ac.uk/hpc/user-guide/upgrade2021.html.

[8] M. Westphal and W. Brannath, "Improving Model Selection by Employing the Test Data," in *Proceedings of the 36th International Conference on Machine Learning*. PMLR, May 2019, pp. 6747–6756.

[9] S. Es, J. James, L. Espinosa-Anke, and S. Schockaert, "RAGAS: Automated Evaluation of Retrieval Augmented Generation."

[10] M. Gritta, G. Lampouras, and I. Iacobacci, "HumanRankEval: Automatic Evaluation of LMs as Conversational Assistants," in *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, K. Duh, H. Gomez, and S. Bethard, Eds. Mexico City, Mexico: Association for Computational Linguistics, Jun. 2024, pp. 8237–8249.

[11] Z.-Y. Chen, H. Wang, X. Zhang, E. Hu, and Y. Lin, "Beyond the Surface: Measuring Self-Preference in LLM Judgments," in *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, C. Christodoulopoulos, T. Chakraborty, C. Rose, and V. Peng, Eds. Suzhou, China: Association for Computational Linguistics, Nov. 2025, pp. 1653–1672.

[12] W. Yu, L. Wu, Y. Deng, Q. Zeng, R. Mahindru, S. Guven, and M. Jiang, "Technical Question Answering across Tasks and Domains," in *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies: Industry Papers*, Y.-b. Kim, Y. Li,

and O. Rambow, Eds. Online: Association for Computational Linguistics, Jun. 2021, pp. 178–186.

[13] V. Castelli, R. Chakravarti, S. Dana, A. Ferritto, R. Florian, M. Franz, D. Garg, D. Khandelwal, S. McCarley, M. McCawley, M. Nasr, L. Pan, C. Pendus, J. Pitrelli, S. Pujar, S. Roukos, A. Sakrajda, A. Sil, R. Uceda-Sosa, T. Ward, and R. Zhang, "The TechQA Dataset," in *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, D. Jurafsky, J. Chai, N. Schluter, and J. Tetreault, Eds. Online: Association for Computational Linguistics, Jul. 2020, pp. 1269–1278.

[14] S. Rodenbeck and Y. Suk Uhr, "TicketHub: Enabling Actionable Analysis of Support Requests With NLP," in *Practice and Experience in Advanced Research Computing 2023: Computing for the Common Good*, ser. PEARC '23. New York, NY, USA: Association for Computing Machinery, Sep. 2023, pp. 109–116.

[15] K. Shuster, S. Poff, M. Chen, D. Kiela, and J. Weston, "Retrieval Augmentation Reduces Hallucination in Conversation," in *Findings of the Association for Computational Linguistics: EMNLP 2021*, M.-F. Moens, X. Huang, L. Specia, and S. W.-t. Yih, Eds. Punta Cana, Dominican Republic: Association for Computational Linguistics, Nov. 2021, pp. 3784–3803.

[16] A. Asai, Z. Wu, Y. Wang, A. Sil, and H. Hajishirzi, "Self-RAG: Learning to Retrieve, Generate, and Critique through Self-Reflection," Oct. 2023.

[17] Z. Xu, M. J. Cruz, M. Guevara, T. Wang, M. Deshpande, X. Wang, and Z. Li, "Retrieval-Augmented Generation with Knowledge Graphs for Customer Service Question Answering," in *Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval*. Washington DC USA: ACM, Jul. 2024, pp. 2905–2909.

[18] J. Ouyang, T. Pan, M. Cheng, R. Yan, Y. Luo, J. Lin, and Q. Liu, "HoH: A Dynamic Benchmark for Evaluating the Impact of Outdated Information on Retrieval-Augmented Generation," in *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, W. Che, J. Nabende, E. Shutova, and M. T. Pilehvar, Eds. Vienna, Austria: Association for Computational Linguistics, Jul. 2025, pp. 6036–6063.

[19] D. Ru, L. Qiu, X. Hu, T. Zhang, P. Shi, S. Chang, C. Jiayang, C. Wang, S. Sun, H. Li, Z. Zhang, B. Wang, J. Jiang, T. He, Z. Wang, P. Liu, Y. Zhang, and Z. Zhang, "RAGChecker: A Fine-grained Framework for Diagnosing Retrieval-Augmented Generation," in *The Thirty-eight Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, Nov. 2024.

[20] J. Saad-Falcon, O. Khattab, C. Potts, and M. Zaharia, "ARES: An Automated Evaluation Framework for Retrieval-Augmented Generation Systems," in *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, K. Duh, H. Gomez, and S. Bethard, Eds. Mexico City, Mexico: Association for Computational Linguistics, Jun. 2024, pp. 338–354.

[21] "Benchmarking Large Language Models in Retrieval-Augmented Generation | Proceedings of the AAAI Conference on Artificial Intelligence," https://ojs.aaai.org/index.php/AAAI/article/view/29728.

[22] M. Sanderson, "Test Collection Based Evaluation of Information Retrieval Systems," *Foundations and Trends in Information Retrieval*, vol. 4, pp. 247–375, Jun. 2010.

Appendix A

Approved External Documentation Sources

This appendix lists the approved external documentation source families included in the frozen external documentation snapshot used for parameter tuning and final evaluation. These sources were selected as stable, official documentation sources relevant to the CSD3 support domain. The list documents the approved source boundaries used for corpus construction.

Table A.1: Approved external documentation source families included in the frozen external documentation snapshot used for parameter tuning and final evaluation.

Source	Approved scope	Support relevance
Slurm (software)	`https://slurm.schedmd.com/`	Scheduler usage, job submission, resource requests, and runtime behaviour.
CUDA (toolchain)	`https://docs.nvidia.com/cuda/`	GPU programming, CUDA runtime, and accelerator-specific software issues.
Intel oneAPI (toolchain)	`https://www.intel.com/content/www/us/en/docs/oneapi/`	Intel compilers, build configuration, optimisation, and environment setup.
Open MPI (toolchain)	`https://docs.open-mpi.org/en/main/`; `https://docs.open-mpi.org/en/v5.0.x/`	MPI execution, communication behaviour, and version-sensitive runtime detail.
PyTorch (software)	`https://docs.pytorch.org/docs/stable/`	Distributed training, GPU use, Python environments, and framework-specific queries.

Continued on next page

Table A.1 continued from previous page

Source	Approved scope	Support relevance
TensorFlow (software)	https://www.tensorflow.org/api_docs; https://www.tensorflow.org/guide	Framework APIs, environment setup, and model-execution issues.
GROMACS (software)	https://manual.gromacs.org/documentation/current/	Molecular simulation usage, command syntax, and software-specific troubleshooting.
LAMMPS (software)	https://docs.lammps.org/stable/	Input syntax, package behaviour, and software-specific execution detail.
OpenFOAM (software)	https://doc.cfd.direct/openfoam/user-guide-v13/	Solver usage, case setup, and computational fluid dynamics support issues.
OpenMM (software)	https://docs.openmm.org/latest/userguide/	GPU-accelerated molecular simulation, software usage, and configuration questions.
Intel MPI (toolchain)	https://www.intel.com/content/www/us/en/docs/mpi-library/developer-guide-linux/2021-16/	MPI runtime behaviour, communication libraries, and parallel-execution troubleshooting.
SingularityCE (software)	https://docs.sylabs.io/guides/latest/user-guide/	Container execution, bind mounts, and software-environment portability on HPC systems.
Spack (software)	https://spack.readthedocs.io/en/latest/	Package installation, environment composition, and reproducible build workflows.

The approved scope for each source was controlled through the external source registry by restricting crawls to specified domains and included URL prefixes, while excluding archive, release-note, API, PDF, or otherwise misaligned subtrees where appropriate. This ensures that the external corpus remained focused on stable, official, and support-relevant documentation rather than becoming an unrestricted crawl of general web content.

Appendix B

Benchmark Taxonomy Label Definitions

This appendix defines the multi-label taxonomy used to annotate benchmark queries for later subgroup analysis. Each field captures a distinct property of the query or of the minimum evidence conditions required for a correct answer.

Table B.1: Benchmark taxonomy label definitions and allowed values.

Field	What it captures	Allowed values	Annotation rule

`source_needed`	The minimum evidence class needed for a correct answer	`docs`
		`tickets`
		`both`
			Labels describe the task, not the current retrieval result or the current vector-store contents. Assign the minimum evidence class required for a correct answer.

`docs_scope_needed`	Which class of official documentation is authoritative when documentary evidence is needed	`local_official`
		`external_official`
		`local_and_external`
		`none`
			Use `none` only when `source_needed=tickets`. Queries with `source_needed=docs` or `both` must not use `none`.

`validity_sensitive`	Whether correctness depends on current system, partition, service, workflow, or compatibility truth	`yes` `no`	Mark `yes` when current local operational truth is central to correctness; mark `no` when the answer is sufficiently stable.

Continued on next page

Table B.1 continued from previous page

Field	What it captures	Allowed values	Annotation rule
`attachment_dependent`	Whether visible text alone is sufficient, or whether unseen attachments materially determine correct handling	`yes` `no`	Mark `yes` when screenshots, logs, uploaded documents, or other unseen attachments materially affect the correct first response.

`query_type`	The broad problem family represented by the query	`local_operational`
		`software_version`
		`general_how_to`
			Assign the dominant problem family: local service truth, version-sensitive software or toolchain issues, or stable procedural guidance.

`version_sensitive`	Whether correctness depends materially on a software or toolchain version	`yes` `no`	Mark `yes` when version differences could change the correct guidance or resolution.
`system_scope_required`	Whether correctness depends on a particular system, service, partition, or platform	`yes` `no`	Mark `yes` when the answer would differ materially across systems or execution environments.

Where multiple interpretations were possible, labels were assigned according to the minimum evidence needed for a correct and locally applicable first-response answer.