Plik dockerfile

```
FROM scratch AS stage1

ADD alpine-minirootfs-3.21.3-aarch64.tar.gz /

RUN apk add --no-cache go

ARG VERSION="1.0.0"
ENV VERSION=${VERSION}

WORKDIR /src
COPY main.go .
RUN CGO_ENABLED=0 go build -a -installsuffix cgo -o /server main.go

FROM nginx:alpine

ARG VERSION="1.0.0"
ENV VERSION=${VERSION}

COPY default.conf /etc/nginx/conf.d/default.conf

COPY --from=stage1 /server /app/server

RUN echo '#!/bin/sh' > /docker-entrypoint.d/99-start-go.sh && \
  echo '/app/server &' >> /docker-entrypoint.d/99-start-go.sh && \
  chmod +x /docker-entrypoint.d/99-start-go.sh

HEALTHCHECK --interval=30s --timeout=5s --retries=3 \
  CMD curl -f http://localhost:8080/ || exit 1

EXPOSE 80
```

Budowa obrazu

```
adam@Adams-MacBook-Pro Docker_files % docker build -t server --build-arg VERSION=1.2.3 .

[+] Building 60.0s (15/15) FINISHED
 => [internal] load build definition from dockerfile
 => => transferring dockerfile: 1.96kB
 => [internal] load metadata for docker.io/library/nginx:alpine
 => [auth] library/nginx:pull token for registry-1.docker.io
 => [internal] load .dockerignore
 => => transferring context: 2B
 => [stage-1 1/4] FROM docker.io/library/nginx:alpine@sha256:e7257f1ef28ba17cf7c248cb8ccf6f0c6e0228ab9c315c152f9c203cd34cf6d1
 => => resolve docker.io/library/nginx:alpine@sha256:e7257f1ef28ba17cf7c248cb8ccf6f0c6e0228ab9c315c152f9c203cd34cf6d1
 => => sha256:e7257f1ef28ba17cf7c248cb8ccf6f0c6e0228ab9c315c152f9c203cd34cf6d1 10.33kB / 10.33kB
 => => sha256:d70d63a8de139d41315d23b75cefcc12b718a3b29d23862676474b7e8875628e 2.50kB / 2.50kB
 => => sha256:d8ad8cd72600f46cc068e16c39046ebc76526e41051f43a8c249884b200936c0 4.20MB / 4.20MB
 => => sha256:e7b8033f1661e1939b4b796ed059b388e193039947dc4b9a99c56881d3a700c5 12.34kB / 12.34kB
 => => sha256:5c54475b17070123dd69a8fc46181de574bd18862ff89af42ef5cdad9b6c7ab6 1.89MB / 1.89MB
 => => sha256:f3cd139bc09d96a99d569b31d5c1b3b08060b63cfc112e36b7cb9616ea141b9c 627B / 627B
 => => sha256:25adace5af65f8b0af0f205c133d7408912c2272e69edc3d577f6ed470fad8bc 952B / 952B
 => => sha256:8653d9094a720cf27760bfcc013cf847d30e3939681a5586ec504bffd2685707 401B / 401B
 => => sha256:c31eed8447fd3e8eb306b1f9335d432eabd6c3a10d3391454b4504617227a542 1.21kB / 1.21kB
 => => sha256:3dbfa89fa4bb25071a7889312fba60d046f22b6afc0d9425959570b86ad7ed51 1.39kB / 1.39kB
 => => sha256:2286bacaa097480a5e197288c73d3f00d4ba2a1f7083216a70a28ada3066876f 19.72MB / 19.72MB
 => => extracting sha256:d8ad8cd72600f46cc068e16c39046ebc76526e41051f43a8c249884b200936c0
 => => extracting sha256:5c54475b17070123dd69a8fc46181de574bd18862ff89af42ef5cdad9b6c7ab6
 => => extracting sha256:f3cd139bc09d96a99d569b31d5c1b3b08060b63cfc112e36b7cb9616ea141b9c
 => => extracting sha256:25adace5af65f8b0af0f205c133d7408912c2272e69edc3d577f6ed470fad8bc
 => => extracting sha256:8653d9094a720cf27760bfcc013cf847d30e3939681a5586ec504bffd2685707
 => => extracting sha256:c31eed8447fd3e8eb306b1f9335d432eabd6c3a10d3391454b4504617227a542
 => => extracting sha256:3dbfa89fa4bb25071a7889312fba60d046f22b6afc0d9425959570b86ad7ed51
 => => extracting sha256:2286bacaa097480a5e197288c73d3f00d4ba2a1f7083216a70a28ada3066876f
 => [internal] load build context
 => => transferring context: 3.85MB
 => [stage1 1/5] ADD alpine-minirootfs-3.21.3-aarch64.tar.gz /
 => [stage1 2/5] RUN apk add --no-cache go
 => [stage-1 2/4] COPY default.conf /etc/nginx/conf.d/default.conf
 => [stage1 3/5] WORKDIR /src
 => [stage1 4/5] COPY main.go .
 => [stage1 5/5] RUN CGO_ENABLED=0 go build -a -installsuffix cgo -o /server main.go
 => [stage-1 3/4] COPY --from=stage1 /server /app/server
 => [stage-1 4/4] RUN echo '#!/bin/sh' > /docker-entrypoint.d/99-start-go.sh &&     echo '/app/server &' >> /docker-entrypoint.d/99-start-go.sh &&     chmod +x /docker-entrypoint.d/99-start-go.sh
 => exporting to image
 => => exporting layers
 => => writing image sha256:466fe2e6f8297b2aafd71a8ea98ca72949b36d0643c2c826abd5e1ecfdc081e5
 => => naming to docker.io/library/server

View build details: docker-desktop://dashboard/build/desktop-linux/desktop-linux/r1mjottagy1x4x0rf37pl7zq8
```

Uruchomienie serwera

```
adam@Adams-MacBook-Pro ~ % docker run -d --rm -p 80:80 server
27966f6be69e20a2fc2086a2e819f1ef7c3fac20a665688355f9e8db46070bdf
```

Sprawdzenie działania

```
adam@Adams-MacBook-Pro ~ % docker container ls
CONTAINER ID   IMAGE     COMMAND                  CREATED          STATUS                             PORTS                                    NAMES
27966f6be69e   server    "/docker-entrypoint.…"   24 seconds ago   Up 23 seconds (health: starting)   0.0.0.0:80->80/tcp, [::]:80->80/tcp      funny_brown
adam@Adams-MacBook-Pro ~ % docker exec 27966f6be69e20a2fc2086a2e819f1ef7c3fac20a665688355f9e8db46070bdf ps
PID   USER     TIME  COMMAND
    1 root      0:00 nginx: master process nginx -g daemon off;
   30 root      0:00 /app/server
   35 nginx     0:00 nginx: worker process
   36 nginx     0:00 nginx: worker process
   37 nginx     0:00 nginx: worker process
   38 nginx     0:00 nginx: worker process
   39 nginx     0:00 nginx: worker process
   40 nginx     0:00 nginx: worker process
   41 nginx     0:00 nginx: worker process
   42 nginx     0:00 nginx: worker process
   43 nginx     0:00 nginx: worker process
   44 nginx     0:00 nginx: worker process
   52 root      0:00 ps
```

Zrzut ekranu, potwierdzający realizację wymaganych funkcjonalności