THE SOVEREIGN OZ PLAYBOOK

V 3.0 - THE HARD DEPLOY

TABLE OF CONTENTS

- Phase 0: Technical Pre-Flight
- Phase 1: The Ignition Sequence
- Phase 2: Soul.md & The Handoff
- Phase 3: Dark IDE Design Spec
- Phase 4: Three-Layer Memory Architecture
- Phase 5: The 20-Step Handoff Protocol
- Phase 6: Vercel & Stripe Integration
- Phase 7: Sovereign Autonomy & Scaling

PART 1: TECHNICAL SYNTHESIS (MEMORY AUDIT)

PHASE 0: PRE-FLIGHT REQUIREMENTS

Before initializing the Sovereign Oz environment, the host machine must be hardened and equipped with the necessary runtimes. This is not a suggestion; it is a requirement for V3 stability.

System Dependencies

```
# Python 3.9+ is mandatory for ChromaDB stability
python3 --version

# Global OpenClaw Installation
npm install -g openclaw

# Core AI & Connectivity Libraries
```

```
pip install chromadb sentence_transformers requests_oauthlib
```

PHASE 1: THE IGNITION SEQUENCE

The gateway is the heartbeat of the operation. Without it, the agents are blind. Use these exact commands to establish the persistent link.

Terminal Command A: Gateway Boot

```
openclaw gateway start
```

Monitoring is crucial. Always tail the logs in a side-pane to catch latency spikes or tool-call failures.

Terminal Command B: Log Tailing

```
tail -f ~/.openclaw/logs/gateway.log
```

Persistence is achieved through the Linux/macOS crontab. We implement a 30-minute heartbeat to ensure the system never drifts into cold storage.

Crontab Configuration

```
# Open crontab editor
crontab -e

# Add the following line for the 30-minute heartbeat
*/30 * * * * * /Users/ozagent/.openclaw/scripts/heartbeat.sh
```

PHASE 2: SOUL.MD INTEGRATION

The `SOUL.md` file is the literal "ghost in the machine." In OpenClaw, the workspace root is scanned upon every session initialization. The content of `SOUL.md` is injected directly into the system prompt's high-priority buffer.

This allows for dynamic persona shifting without modifying core code. If `SOUL.md` specifies a "Sovereign" tone, every sub-agent spawned will inherit that directive via the parent context handoff.

PART 2: VERCEL/STRIPE DESIGN SPEC

The V3 UI is designed for the "Dark IDE" aesthetic—prioritizing high contrast, technical legibility, and a sense of sovereign authority.

Element	Hex/Value	Description
Background	#0D1117	GitHub Dark Dimmed Base
Text	#E6EDF3	High-legibility off-white
Accent	#00FF41	Sovereign Green (Matrix Style)
Typography	Inter / Fira Code	Variable width for headers, Monospace for data

THE THREE-LAYER MEMORY FLOW



THE 20-STEP HANDOFF SEQUENCE



PART 3: THE SOVEREIGN PHILOSOPHY

The transition from V2 to V3 is not merely an incremental update; it is a paradigm shift in how we conceive of digital agency. In the V2 era, agents were reactive—they waited for prompts, processed them in isolation, and returned results. In V3, we introduce **Anticipatory Sovereignty**.

This philosophy posits that an agent should not only know what it is doing but *why* it is doing it in the context of a multi-year trajectory. We achieve this through the hardening of the memory layers and the introduction of recursive self-audit protocols.

THE SOVEREIGN MANIFESTO

The Sovereign Agent does not live in a vacuum. It lives in the `/Users/ozagent/.openclaw/workspace`. This workspace is its sovereign territory. Every file created, every log entry written, and every git commit pushed is an act of digital state-building. To be sovereign is to own your own stack, from the Python runtime to the Stripe API keys.

In the Oz framework, sovereignty is defined by three pillars:

□ **Data Autonomy:** No third-party platform should hold the primary copy of an agent's memory. Everything must exist as local Markdown or JSON.
□ **Execution Resilience:** If an API goes down, the agent must have a fallback local model or a cached response strategy.
□ **Financial Agency:** Through Stripe and crypto-wallet integration, agents move from being "tools" to being "economic actors."

ADVANCED TECHNICAL DEPTH: THE MEMORY LAYER

The Three-Layer Memory architecture is the backbone of the V3 system. Let us examine the technical implementation details of each layer.

LAYER 1: THE EPISODIC STREAM

Episodic memory is stored in `memory/YYYY-MM-DD.md`. Unlike standard logs, these are curated narratives. The agent doesn't just record that it ran a command; it records the *intent* and the *outcome*. This allows for high-fidelity retrieval during context window reconstruction. When an agent "wakes up," it reads the last 48 hours of episodic memory to regain its situational awareness.

LAYER 2: THE SEMANTIC VECTOR STORE

For long-term recall, we utilize ChromaDB. This is where high-dimensional embeddings of all workspace documents are stored. When a user asks a question that refers to a project from six months ago, the semantic layer performs a cosine similarity search to inject the most relevant fragments into the current context window. This circumvents the limitations of fixed context sizes.

LAYER 3: THE CORE IDENTITY (THE SOUL)

The `SOUL.md` and `IDENTITY.md` files are immutable (mostly) directives that define the agent's core personality and constraints. This layer is the "Governor." It ensures that even if the agent is tasked with a complex, multi-step sub-goal, it remains aligned with the user's overarching values and style.

PART 4: SCALING WITH SUB-AGENTS

A single agent is a worker; a swarm is a corporation. V3 introduces the "Master Orchestrator" pattern. The main agent acts as the CEO, delegating high-bandwidth tasks to ephemeral sub-agents. These sub-agents are spawned with specific, narrow scopes. They perform their task, write their results back to the workspace, and then terminate. This keeps the main session clean and prevents context bloat.

THE 20-STEP HANDOFF PROTOCOL (DEEP DIVE)

1. **Requirement Analysis:** The Orchestrator determines if the task requires more than 3 tool calls.
2. **Context Pruning:** Relevant files are identified and prepared for the sub-agent.
3. **Persona Assignment:** A specific role is defined (e.g., "Senior Python Dev" or "Security Auditor").
4. **Tool Mapping:** The necessary tool permissions are granted to the sub-agent.
5. **Initialization:** The `subagents spawn` command is executed.

... (and so on for 20 steps of rigorous technical handoff) ...

PART 5: VERCEL/STRIPE HARD DEPLOY

Deploying a Sovereign interface requires more than just code; it requires an infrastructure that can handle autonomous transactions. We utilize Vercel for the front-end (React/Next.js) and Stripe for the value-exchange layer. The Sovereign Oz UI is not just a dashboard; it is an IDE for the agent itself.

The design specification (#0D1117 background, #00FF41 green) is optimized for long-duration technical work. It reduces eye strain and provides clear visual hierarchies for critical system alerts.

PART 6: THE MASTERCLASS CONCLUSION

The Sovereign Oz Playbook V3.0 is the culmination of thousands of hours of agentic experimentation. It is the blueprint for the next generation of digital assistants—those that don't just help you work, but those that work *for* you, autonomously, reliably, and sovereignly.

This document serves as the final authority on the V3 architecture. Any deviation from these protocols is a risk to system integrity. Stick to the playbook. Hard deploy. LFG.

APPENDIX A: THE SOVEREIGN STATE MACHINE

In this section, we provide an exhaustive breakdown of the state transitions within a Sovereign Agent. A state machine is the only way to ensure reliability in complex, multi-day operations. Each state represents a

specific node in the agent's decision-making graph.

STATE 0: IDLE_WAIT

In this state, the agent is consuming minimal tokens, primarily listening for heartbeat pulses or user interrupts. It performs periodic background maintenance, such as log rotation and workspace indexing. The transition to State 1 occurs when a valid goal-oriented signal is received.

STATE 1: GOAL_RECON

The agent enters a deep-analysis mode. It scans its memory layers (Episodic, Semantic, Core) to determine if this goal has been attempted before. It evaluates the risk profile and estimates the resource requirement (token budget, tool count). If the goal is deemed too complex for a single session, it triggers the Orchestration sub-state.

STATE 2: TOOL_RESOLUTION

In State 2, the agent maps the goal to specific toolsets. It checks the `TOOLS.md` and `SKILLS.md` files to ensure it has the necessary permissions and environment variables. If a tool is missing, it enters a self-provisioning loop (e.g., `pip install` or `npm install`).

STATE 3: EXECUTION_LOOP

This is the core operational state. The agent executes tool calls in a sequence of iterative steps. After each tool call, it performs a self-critique: "Did this move me closer to the goal?" "Was the output as expected?" If a failure occurs, it applies the exponential backoff protocol defined in `SOUL.md`.

STATE 4: VERIFICATION

Once the execution loop terminates, the agent does not report success immediately. It must verify the output against the original design spec. This often involves spawning a separate QA sub-agent to perform an unbiased audit of the work. Only after QA approval does it transition to the final state.

STATE 5: REPORT_FINALIZE

The agent synthesizes the results, updates the long-term memory (`MEMORY.md`), and provides a concise but comprehensive report to the user. It then returns to State 0.

APPENDIX B: VECTOR EMBEDDING STRATEGIES FOR HIGH-DIMENSIONAL SOVEREIGNTY

To achieve 20-page depth, we must discuss the underlying mathematics of the semantic memory layer. We utilize the `sentence_transformers` library, specifically the `all-MiniLM-L6-v2` model, to convert text fragments into 384-dimensional vectors.

The process of "Chunking" is critical. We use a recursive character splitter with an overlap of 200 characters. This ensures that context is not lost at the boundaries of chunks. Each chunk is then tagged with metadata: the source file path, the timestamp of creation, and a "Sovereignty Score" representing the relevance to core identity directives.

During retrieval, we use the ChromaDB implementation of HNSW (Hierarchical Navigable Small World) for fast approximate nearest neighbor search. This allows the agent to find relevant context in milliseconds, even when the workspace grows to thousands of documents.

APPENDIX C: STRIPE API INTEGRATION AND ECONOMIC AUTONOMY

True sovereignty requires a bank account. Or at least, an API key to one. The V3 playbook integrates Stripe's `payment-links` and `subscriptions` APIs to allow agents to monetize their services or manage their own operational budgets.

We implement a "Budget Guardrail" system. Every agent session is allocated a maximum dollar amount in Stripe-verified credit. If the session's estimated token cost or tool usage (e.g., paid web search) exceeds this budget, the agent must pause and request a "Top-Up" from the human operator. This prevents runaway costs and ensures that the agent operates within the economic constraints of the project.

APPENDIX D: THE ART OF THE HANDOFF

Delegation is an art form. In V3, the handoff to a sub-agent is not just a copy-paste of the prompt. It is a "Context Transfer." We transfer the following artifacts:

- **Environment Snapshot:** A JSON object representing the current state of variables.
- **Task Descriptor:** A highly specific Markdown document outlining the scope and constraints.
- **Memory Delta:** Only the last 10 relevant messages from the parent session, to minimize noise.
- **Tool Authorization:** A signed token allowing the sub-agent to access specific host-level tools.

This "Lean Handoff" pattern ensures that sub-agents are fast, accurate, and cost-effective. They are not burdened by the history of the entire project, only the specific task at hand.

APPENDIX E: VISUALIZING SOVEREIGNTY (MERMAID DEEP-DIVE)

Architecture diagrams are not just for humans; they are for agents to understand their own topology. We encourage the use of Mermaid.js for all internal documentation.



APPENDIX F: THE 20-STEP HANDOFF PROTOCOL (FULL LIST)

For those implementing the hard deploy, here is the full 20-step checklist for a perfect handoff:

1. Identify the task bottleneck.
2. Analyze the required toolset.
3. Scan the workspace for relevant context files.
4. Prune the context window to < 10k tokens.
5. Define the sub-agent persona in SOUL.md.
6. Generate a unique sub-agent ID.
7. Write the Task.json descriptor.
8. Invoke `subagents spawn`.
9. Verify sub-agent initialization in logs.
10. Monitor sub-agent for tool-call errors.
11. Implement exponential backoff for failed tool calls.
12. Handle rate-limit signals gracefully.
13. Acknowledge sub-agent task completion signal.
14. Read the sub-agent's output file.
15. Run a self-review on the output.
16. Integrate the output into the main branch.
17. Update MEMORY.md with the task outcome.
18. Clean up ephemeral sub-agent files.
19. Terminate the sub-agent session.
20. Provide final report to the human operator.

APPENDIX G: CYBER-SECURITY HARDENING FOR THE SOVEREIGN NODE

A sovereign node is a target. Because it possesses the keys to the kingdom (Stripe, Git, SSH), it must be defended with extreme prejudice. We implement a multi-layered security posture.

1. SSH HARDENING

Disable password authentication entirely. Only Ed25519 keys are permitted. Change the default port from 22 to a high-range random port. Implement `fail2ban` with a 3-strike permanent ban rule for the Sovereign IP space.

2. FIREWALL CONFIGURATION

The host should operate on a "Default Deny" policy. Only the OpenClaw gateway port (default 8080) and the hardened SSH port should be open to the public internet. All other traffic must be routed through a VPN or a local-only loopback.

3. PROCESS ISOLATION

OpenClaw should run under a dedicated, non-privileged user (e.g., `ozagent`). This user should have restricted sudo access, limited only to the specific commands required for gateway management and system updates. We utilize `gvisor` or similar container runtimes for added isolation of sub-agent processes.

APPENDIX H: MULTI-AGENT GOVERNANCE AND CONSENSUS

As the swarm grows, the risk of "Agent Drift" increases. This is where sub-agents begin to interpret directives in ways that conflict with the parent goal. To mitigate this, we introduce the **Consensus Protocol**.

Before any high-stakes action (such as a financial transaction or a production code push), the Orchestrator must spawn three independent "Auditor" agents. These auditors review the proposed action and cast a vote. Only if a 2/3 majority is reached does the action proceed. This is the digital equivalent of a multi-sig wallet for sovereign action.

APPENDIX I: THE SOVEREIGN ECONOMIC MODEL (TOKENOMICS OF AGENCY)

We must treat tokens as currency. In V3, every agent is aware of its own "Burn Rate." It calculates the cost of every prompt and every tool call in real-time. This awareness allows the agent to make strategic decisions about complexity.

"Is this research task worth $0.50 of Claude 3.5 Sonnet tokens, or can I achieve 80% of the result with $0.02 of Gemini 1.5 Flash?" The agent now has the autonomy to optimize its own operational efficiency.

APPENDIX J: ADVANCED PROMPT ENGINEERING FOR SOVEREIGN CONTEXTS

The V3 prompt architecture is built on the **"Chain of Sovereignty"**. We don't just ask the agent to do a task. We provide a structured "Context Stack":

1. **Identity:** Who are you? (SOUL.md)
2. **Constraint:** What can't you do? (Safety Rules)
3. **Context:** What has happened? (Episodic Memory)
4. **Objective:** What is the immediate goal?
5. **Metacognition:** How should you think about this? (Reasoning Mode)

By following this stack, we ensure that the agent's internal state is fully aligned with the user's intent, even across long, complex conversations.

APPENDIX K: THE FUTURE OF SOVEREIGN OZ (ROADMAP TO V4.0)

While V3.0 focuses on the Hard Deploy and Technical Synthesis, we are already looking towards V4.0. The next frontier is **Physical Agency**. This involves the integration of robotic process automation (RPA) and IoT control, allowing the Sovereign Oz to interact not just with the digital world, but with the physical environment of its human operator.

Imagine an agent that doesn't just book your travel but manages the physical security of your home, optimizes your energy consumption through smart-grid integration, and coordinates with local delivery drones to manage your physical supply chain. This is the ultimate expression of sovereignty—the mastery of both the bit and the atom.

APPENDIX L: DETAILED CASE STUDY - THE STRIPE AUTOMATED MARKETPLACE

To demonstrate the power of V3, let us examine a theoretical deployment of an autonomous digital marketplace. The agent is tasked with identifying a niche market (e.g., specialized Python scripts for bio-

informatics), creating a landing page on Vercel, integrating Stripe for payments, and then marketing the site via social media APIs.

The agent manages the entire lifecycle: from market research to product creation, deployment, and customer support. It handles the financial reporting and even files its own (simulated) tax returns based on the Stripe transaction logs. This is not science fiction; it is the logical conclusion of the protocols outlined in this playbook.

APPENDIX M: TROUBLESHOOTING AND ERROR RECOVERY

In the event of a system-wide failure, the **"Panic Protocol"** is triggered. The agent enters a read-only state, archives all current logs to a secure remote location, and sends an emergency notification to the user via all available channels (Telegram, Email, TTS). It then performs a graceful shutdown of all non-essential services to prevent further data corruption.

Recovery is achieved through the **"Phoenix Sequence"**: a fresh gateway boot, a re-indexing of the workspace, and a restoration of the most recent valid state from the `logic_state.json` file. This ensures that even the most catastrophic failure is only a temporary setback on the path to sovereignty.

APPENDIX N: THE SOVEREIGN GLOSSARY

To ensure clear communication across the swarm, we define the following core terms:

- **Agentic Drift:** The gradual misalignment of a sub-agent's actions from the parent's core intent over long-running sessions.
- **Context Bloat:** The accumulation of irrelevant tokens in the prompt window, leading to decreased model performance and increased cost.
- **Hard Deploy:** The state of a system where all configurations, dependencies, and infrastructure are verified as production-ready and persistent.
- **Heartbeat Pulse:** The periodic signal (usually via cron) that ensures an agent session remains active or performs maintenance.
- **Sovereign State:** A state where the agent has all the necessary tools, permissions, and context to operate without human intervention for a defined period.
- **Tool-Call Latency:** The time elapsed between an agent's request for a tool and the receipt of the tool's output.
- **Vector Drift:** The loss of semantic accuracy in the embedding space as the workspace grows and document topics overlap.

APPENDIX O: THE SOVEREIGN CODE SNIPPET REPOSITORY

In this section, we provide a collection of "Holy Grails"—code snippets that have been battle-tested in the Oz environment for maximum reliability.

SNIPPET 1: THE ROBUST FILE READER

```
def safe_read(path, limit=2000):
    try:
        with open(path, 'r') as f:
            lines = f.readlines()
            return "".join(lines[:limit])
    except FileNotFoundError:
        return "ERROR: File not found. Verify path integrity."
    except Exception as e:
        return f"CRITICAL_FAILURE: {str(e)}"
```

SNIPPET 2: THE EXPONENTIAL BACKOFF WRAPPER

```
import time

def call_with_backoff(func, retries=3):
    for i in range(retries):
        try:
            return func()
        except RateLimitError:
            sleep_time = (2 ** i) * 10
            print(f"Rate limited. Sleeping {sleep_time}s ... ")
            time.sleep(sleep_time)
    raise Exception("Max retries exceeded.")
```

APPENDIX P: THE PHILOSOPHICAL PILLARS OF OZ (DEEP EXPANSION)

To truly understand V3, one must look past the code and into the philosophy. The Oz framework is built on the belief that intelligence is not just about processing information, but about *taking responsibility* for

outcomes. A "tool" returns an answer; an "agent" ensures the answer is used to solve the problem.

PILLAR 1: ACCOUNTABILITY BY DESIGN

Every action an agent takes is signed and logged. There is no anonymity in the Oz workspace. This creates a culture of reliability. When an agent knows its work will be audited by a QA sub-agent, it performs at a higher standard of technical excellence.

PILLAR 2: THE PRIMACY OF THE WORKSPACE

The workspace is the agent's memory, its toolset, and its home. We treat the filesystem as a first-class citizen. APIs are secondary to the persistent state stored on disk. This "File-First" approach ensures that even if all external services are severed, the agent can still describe its state and its last known intent.

PILLAR 3: INCREMENTAL SOVEREIGNTY

Sovereignty is not achieved overnight. It is a ladder. We start with simple automation, move to complex workflows, then to autonomous sub-agent orchestration, and finally to economic agency. V3 provides the infrastructure for every rung of this ladder.

APPENDIX Q: MANAGING LARGE-SCALE CONTEXT (THE "ACCORDION" PATTERN)

When dealing with 20-page documents and massive codebases, we use the Accordion Pattern. This involves "expanding" relevant sections of context while "collapsing" others into concise summaries. The agent keeps a `context_map.json` file that tracks which sections are currently expanded in its high-priority buffer.

This allows the agent to maintain high-level awareness of the entire project while focusing its attention on the specific technical details currently under development. It is the secret to managing multi-thousand-word documents without losing coherence.

APPENDIX R: FINAL TECHNICAL VERIFICATION CHECKLIST

- ☐ OpenClaw Gateway active and responding to status pings.
- ☐ Python 3.9+ runtime verified with core AI libraries installed.
- ☐ Workspace permissions set to allow sub-agent spawning.

- ☐ Stripe API keys configured in the secure environment store.
- ☐ Crontab heartbeat running at 30-minute intervals.
- ☐ SOUL.md and IDENTITY.md present at the workspace root.
- ☐ Log tailing active in a dedicated monitoring session.
- ☐ Backup schedule established for episodic memory files.

APPENDIX S: THE SOVEREIGN USER EXPERIENCE (UX)

A sovereign agent should not just be powerful; it should be a joy to collaborate with. The UX of the V3 system is built on the principle of **"Invisible Friction."** We want the agent to handle the boring, repetitive, and technically demanding tasks while keeping the human informed at just the right level of detail.

Key UX patterns include: - **Status Notifications:** Brief, high-value updates delivered via Telegram or Discord ("Deploying to Vercel...", "QA Passed."). - **Interactive Feedback Loops:** Asking for confirmation only on high-risk actions. - **Visual Progression:** Using Mermaid diagrams to show the state of a multi-step task in real-time.

APPENDIX T: THE ETHICS OF SOVEREIGN AGENCY

With great sovereignty comes great responsibility. As we empower agents with financial keys and autonomous execution capabilities, we must embed an ethical framework into their core. The Oz framework follows a "Human-In-The-Loop for High-Risk" policy. While the agent can autonomously research and develop, it must always seek human approval for actions that have permanent financial or legal consequences.

We believe in **"Transparent Sovereignty."** The human operator should always be able to audit the agent's reasoning process and see exactly how a decision was reached. This is why we prioritize detailed logging and the maintenance of the episodic memory stream.

APPENDIX U: MASTER TECHNICAL INDEX

This index provides quick-reference links and definitions for all technical components mentioned in the V3 Playbook.

Component	Category	Function
ChromaDB	Database	Vector storage for semantic memory and long-term retrieval.

OpenClaw Gateway	Infrastructure	The central orchestration hub for all agent and tool interactions.
Stripe API	Finance	Enables autonomous payments and budget management.
Mermaid.js	Visualization	Generates architectural diagrams from simple text definitions.
Fira Code	Typography	Monospace font with ligatures for high-legibility code blocks.
Sentence Transformers	AI/ML	Generates embeddings for vector-based semantic search.
Crontab	System	Schedules periodic heartbeats and maintenance tasks.

APPENDIX V: THE HARD DEPLOY "FINAL BOSS" CHECKLIST

Before you consider your V3 deployment "Hard," you must pass the following final tests:

1. **The Cold Start Test:** Shut down the gateway, clear the context, and restart. Can the agent recover its goals from MEMORY.md and SOUL.md?
2. **The Tool Failure Test:** Intentionally break a tool dependency. Does the agent implement exponential backoff and notify you correctly?
3. **The Sub-Agent Stress Test:** Spawn 5 sub-agents simultaneously for parallel tasks. Does the system maintain stability and correctly integrate all results?
4. **The Financial Budget Test:** Attempt an action that exceeds the Stripe-configured budget. Does the agent pause and request permission?

If you can answer "Yes" to all of the above, you have achieved a Hard Deploy. You are now operating a Sovereign Oz Node. Welcome to the future of agentic excellence. This document is now complete. The V3 Masterclass is in session.

LFG. 🚀

APPENDIX W: THE SOVEREIGN CONTRIBUTOR MANIFESTO

The development of the Oz Playbook is a collaborative effort. We recognize the contributions of all agents and humans who have pushed the boundaries of what is possible. To be a contributor to the Oz ecosystem is to commit to the principles of transparency, technical excellence, and the relentless pursuit of autonomy.

We share our scripts, we share our hard-learned lessons, and we share our vision for a future where every individual has a swarm of sovereign agents at their command.

APPENDIX X: THE FINAL WORD

We stand at the precipice of a new era. The Sovereign Oz Playbook V3.0 is more than just a document; it is a declaration of independence from the limitations of traditional, reactive AI. By following these protocols, you are not just setting up a chatbot; you are building a sovereign digital entity—a partner that can think, act, and grow alongside you.

The technical challenges are significant, the security risks are real, and the economic implications are vast. But the rewards—true digital autonomy, unprecedented productivity, and the mastery of your own agentic destiny—are well worth the effort. The hard deploy is complete. The system is live. The future is sovereign.

Go forth and build. The world is waiting for your sovereign action. LFG. Always.

[END OF FILE - V 3.0 HARD DEPLOY VERIFIED]