





#### Performance





URL	Cache TTL	Transfer Size
images/sharon-mcjpg (book-repository-virtual.herokuapp.com)	12 h	1,583 KB
images/Gaff.png (book-repository-virtual.herokuapp.com)	12 h	230 KB
$ images/logo\_bookstack\_text\_96\_spacing.png \ \ (book-repository-virtual.herokuapp.com)$	12 h	95 KB
styles/style.css (book-repository-virtual.herokuapp.com)	12 h	15 KB
vendor/cookies.js (book-repository-virtual.herokuapp.com)	12 h	2 KB
scripts/message.js (book-repository-virtual.herokuapp.com)	12 h	1 KB
vendor/materialize.js (book-repository-virtual.herokuapp.com)	12 h	1 KB
build/cookieconsent.min.js (cdn.jsdelivr.net)	7 d	14 KB
build/cookieconsent.min.css (cdn.jsdelivr.net)	7 d	3 KB

#### ■ Avoid chaining critical requests − 9 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. <u>Learn more</u>.

#### Maximum critical path latency: 1,310 ms

#### Initial Navigation

/user/change-password (book-repository-virtual.herokuapp.com)
/icon?family=Material+Icons (fonts.googleapis.com)
...v55/flUhRq6tz....woff2 (fonts.gstatic.com) - 610 ms, 161.72 KB
...css/materialize.min.css (cdnjs.cloudflare.com) - 540 ms, 17.86 KB
...styles/style.css (book-repository-virtual.herokuapp.com)
/css?family=Raleway|&display=swap (fonts.googleapis.com)
...v17/1Ptxg8zYS....woff2 (fonts.gstatic.com) - 490 ms, 15.65 KB
...build/cookieconsent.min.css (cdn.jsdelivr.net) - 530 ms, 3.14 KB
...js/materialize.min.js (cdnjs.cloudflare.com) - 550 ms, 72.84 KB
...vendor/materialize.js (book-repository-virtual.herokuapp.com) - 100 ms, 0.6 KB
...scripts/message.js (book-repository-virtual.herokuapp.com) - 140 ms, 0.94 KB
...build/cookieconsent.min.js (cdn.jsdelivr.net) - 550 ms, 13.5 KB
...vendor/cookies.js (book-repository-virtual.herokuapp.com) - 190 ms, 1.92 KB

#### ■ Keep request counts low and transfer sizes small - 16 requests • 2,225 KB

To set budgets for the quantity and size of page resources, add a budget.json file. Learn more.

Resource Type	Requests	Transfer Size
Total	16	2,224.9 KB
Image	3	1,908.2 KB
Font	2	177.4 KB
Script	5	89.8 KB
Stylesheet	5	37.3 KB
Document	1	12.2 KB
Media	0	0 KB
Other	0	0 KB
Third-party	8	286.1 KB

#### ■ Largest Contentful Paint element — 1 element found

This is the element that was identified as the Largest Contentful Paint. Learn More

	Element		
	h6		
•	Avoid large layout shifts - 5 elements found		^
	These DOM elements contribute most to the CLS of the page.		
	Element		
	form.form		
	div.footer-copyright.blue.darken-4		
	button.btn.waves-effect.waves-light		
	img		
	a		
Pas	esed audits (18)		^
•	Properly size images		^
	Serve images that are appropriately-sized to save cellular data and improve load time. Learn r	more.	
•	Defer offscreen images		^
	Consider lazy-loading offscreen and hidden images after all critical resources have finished lo interactive. <u>Learn more</u> .	ading to lower time	to
•	Minify CSS — Potential savings of 5 KB		^
	Minifying CSS files can reduce network payload sizes. <u>Learn more</u> .		
		Show 3rd-party re	esources (0)
	URL	Transfer Size	Potential Savings
	styles/style.css (book-repository-virtual.herokuapp.com)	14.9 KB	5.2 KB
•	Minify JavaScript		^
	Minifying JavaScript files can reduce payload sizes and script parse time. <u>Learn more</u> .		
•	Efficiently encode images		^
	Optimized images load faster and consume less cellular data. <u>Learn more</u> .		
•	Serve images in next-gen formats		^
	Image formats like JPEG 2000, JPEG XR, and WebP often provide better compression than P faster downloads and less data consumption. <u>Learn more</u> .	NG or JPEG, which	means
•	Enable text compression		^
	Text-based resources should be served with compression (gzip, deflate or brotli) to minimize t $\underline{\text{more}}.$	otal network bytes.	<u>Learn</u>
•	Initial server response time was short — Root document took 120 ms		^
	Keep the server response time for the main document short because all other requests depen	d on it. <u>Learn more</u>	
•	Avoid multiple page redirects		^
	Redirects introduce additional delays before the page can be loaded. <u>Learn more</u> .		
•	Preload key requests		^
	Consider using ` <li>k rel=preload&gt;` to prioritize fetching resources that are currently requested more.</li>	l later in page load.	<u>Learn</u>
•	Use video formats for animated content		^

Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. Learn more

#### Avoids enormous network payloads - Total size was 2,225 KB

Large network payloads cost users real money and are highly correlated with long load times. Learn more.

✓ Show 3rd-party resources (5)
Transfer Size
1,583.4 KB

URL	Transfer Size
images/sharon-mcjpg (book-repository-virtual.herokuapp.com)	1,583.4 KB
images/Gaff.png (book-repository-virtual.herokuapp.com)	230 KB
v55/flUhRq6tzwoff2 (fonts.gstatic.com)	161.7 KB
images/logo_bookstack_text_96_spacing.png (book-repository-virtual.herokuapp.com)	94.8 KB
js/materialize.min.js (cdnjs.cloudflare.com)	72.8 KB
css/materialize.min.css (cdnjs.cloudflare.com)	17.9 KB
v17/1Ptxg8zYSwoff2 (fonts.gstatic.com)	15.7 KB
styles/style.css (book-repository-virtual.herokuapp.com)	14.9 KB
build/cookieconsent.min.js (cdn.jsdelivr.net)	13.5 KB
/user/change-password (book-repository-virtual.herokuapp.com)	12.2 KB

#### Avoids an excessive DOM size - 130 elements

A large DOM will increase memory usage, cause longer style calculations, and produce costly layout reflows. Learn more.

Statistic	Element	Value
Total DOM Elements		130
Maximum DOM Depth	<pre><i class="material-icons prefix tooltipped" data-position="bottom" data-tooltip="Please enter your password (old/current in 'old password', and new password in 'new password' and 'retype password')."></i></pre>	9
Maximum Child Elements	<body></body>	16

#### User Timing marks and measures

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. Learn more.

#### JavaScript execution time — 0.1 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. <u>Learn more</u>.

		Show 3rd-party resources (1)	
URL	Total CPU Time	Script Evaluation	Script Parse
/user/change-password (book-repository-virtual.herokuapp.com)	380 ms	4 ms	1 ms
Unattributable	135 ms	3 ms	0 ms
js/materialize.min.js (cdnjs.cloudflare.com)	50 ms	35 ms	7 ms

#### Minimizes main-thread work - 0.6 s

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. Learn more

Category	Time Spent
Rendering	251 ms
Other	192 ms

Category	Time Spent
Script Evaluation	79 ms
Style & Layout	49 ms
Parse HTML & CSS	39 ms
Script Parsing & Compilation	13 ms
Garbage Collection	9 ms

● Minimize third-party usage — Third-party code blocked the main thread for 0 ms

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. <u>Learn more</u>.

Third-Party	Transfer Size	Main-Thread Blocking Time
Google Fonts	179 KB	0 ms
Cloudflare CDN	91 KB	0 ms
JSDelivr CDN	17 KB	0 ms

Avoids document.write()

Visual order on the page follows DOM order

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. <u>Learn more</u>.



## Accessibility

These checks highlight opportunities to improve the accessibility of your web app. Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

Additional items to manually check (10) — These items address areas which an automated testing tool cannot cover.

Learn more in our quide on conducting an accessibility review.

Lea	arn more in our guide on <u>conducting an accessibility review</u> .	
•	The page has a logical tab order	^
	Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. <u>Learn more</u> .	
	Interactive controls are keyboard focusable	^
	Custom interactive controls are keyboard focusable and display a focus indicator. <u>Learn more</u> .	
•	Interactive elements indicate their purpose and state	^
	Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. <u>Learn more</u> .	
	The user's focus is directed to new content added to the page	^
	If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn more.	
	User focus is not accidentally trapped in a region	^
	A user can tab into and out of any control or region without accidentally trapping their focus. <u>Learn more</u> .	
•	Custom controls have associated labels	^
	Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. <u>Learn more</u> .	
•	Custom controls have ARIA roles	^
	Custom interactive controls have appropriate ARIA roles. <u>Learn more</u> .	

DOM order matches the visual order, improving navigation for assistive technology. Learn more. Offscreen content is hidden from assistive technology Offscreen content is hidden with display: none or aria-hidden=true. Learn more. HTML5 landmark elements are used to improve navigation Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. Learn more Passed audits (15) [aria-hidden="true"] is not present on the document <body> Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. Learn more. Buttons have an accessible name When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. Learn more. The page contains a heading, skip link, or landmark region Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more. Background and foreground colors have a sufficient contrast ratio Low-contrast text is difficult or impossible for many users to read. Learn more. Document has a <title> element The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more. ARIA IDs are unique The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. Learn more. Heading elements appear in a sequentially-descending order Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. Learn more. <html> element has a [lang] attribute If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more. <html> element has a valid value for its [lang] attribute Specifying a valid <u>BCP 47 language</u> helps screen readers announce text properly. <u>Learn more</u>. Image elements have [alt] attributes Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more. Form elements have associated labels Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more. Links have a discernible name Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. Learn more. Lists contain only <1i> elements and script supporting elements (<script> and <template>). Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. Learn more

List items () are contained within or parent elements Screen readers require list items () to be contained within a parent ` or ` to be announced properly. Learn more. [user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5 Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more. Not applicable (26) [accesskey] values are unique Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more. [aria-\*] attributes match their roles Each ARIA 'role' supports a specific subset of 'aria-\*' attributes. Mismatching these invalidates the 'aria-\*' attributes. Learn more [aria-hidden="true"] elements do not contain focusable descendents Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. Learn more ARIA input fields have accessible names When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. [role]s have all required [aria-\*] attributes Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more. Elements with an ARIA [role] that require children to contain a specific [role] have all required children. Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn more. [role]s are contained by their required parent element Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more. [role] values are valid ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more. ARIA toggle fields have accessible names When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. [aria-\*] attributes have valid values Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more. [aria-\*] attributes are valid and not misspelled Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more. <dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <div> elements. When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Learn more. Definition list items are wrapped in <d1> elements Definition list items ('<dt>' and '<dd>') must be wrapped in a parent '<dl>' element to ensure that screen readers can properly announce them. Learn more. [id] attributes on active, focusable elements are unique All focusable elements must have a unique 'id' to ensure that they're visible to assistive technologies. Learn more.

	No form fields have multiple labels	^
	Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. <u>Learn more</u> .	
	<frame/> or <iframe> elements have a title</iframe>	^
	Screen reader users rely on frame titles to describe the contents of frames. <u>Learn more</u> .	
	<pre><input type="image"/> elements have [alt] text</pre>	^
	When an image is being used as an ` <input/> ` button, providing alternative text can help screen reader users understand the purpose of the button. Learn more.	е
•	Presentational <pre> elements avoid using , <caption> or the [summary] attribute.</caption></pre>	^
	A table being used for layout purposes should not include data elements, such as the thor caption elements or the summary attribute, because this can create a confusing experience for screen reader users. Learn more.	
	The document does not use <meta http-equiv="refresh"/>	^
	Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. <u>Learn more</u> .	
•	<pre><object> elements have [alt] text</object></pre>	^
	Screen readers cannot translate non-text content. Adding alt text to ` <object>` elements helps screen readers convey meaning to users. <u>Learn more</u>.</object>	
	No element has a [tabindex] value greater than 0	
	No element has a [tabindex] value greater than o	^
•	A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <u>Learn more</u> .	^
•	A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating	^
•	A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <u>Learn more</u> .	^
•	A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more.  Cells in a  element that use the [headers] attribute refer to table cells within the same table.  Screen readers have features to make navigating tables easier. Ensuring ``cells using the `[headers]` attribute only references.	^
•	A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more.  Cells in a  element that use the [headers] attribute refer to table cells within the same table.  Screen readers have features to make navigating tables easier. Ensuring ``cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more.	^
•	A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more.  Cells in a  element that use the [headers] attribute refer to table cells within the same table.  Screen readers have features to make navigating tables easier. Ensuring ``cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more.  elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.  Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells	^
•	A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more.  Cells in a  element that use the [headers] attribute refer to table cells within the same table.  Screen readers have features to make navigating tables easier. Ensuring ``cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more.  elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.  Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. Learn more.	^ r
•	A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more.  Cells in a  element that use the [headers] attribute refer to table cells within the same table.  Screen readers have features to make navigating tables easier. Ensuring ```cells using the `[headers]' attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more.   elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.  Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. Learn more.  [lang] attributes have a valid value  Specifying a valid BCP 47 language on elements helps ensure that text is pronounced correctly by a screen reader. Learn	^ r
•	A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more.  Cells in a  element that use the [headers] attribute refer to table cells within the same table.  Screen readers have features to make navigating tables easier. Ensuring ``cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more.  elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.  Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. Learn more.  [lang] attributes have a valid value  Specifying a valid BCP 47 language on elements helps ensure that text is pronounced correctly by a screen reader. Learn more.	^ r ^ _ ^
•	A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more.  Cells in a  element that use the [headers] attribute refer to table cells within the same table.  Screen readers have features to make navigating tables easier. Ensuring '' cells using the '[headers]' attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more.   elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.  Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. Learn more.  [lang] attributes have a valid value  Specifying a valid BCP 47 language on elements helps ensure that text is pronounced correctly by a screen reader. Learn more.  «video> elements contain a <track/> element with [kind="captions"]	^ r ^ _ ^



## **Best Practices**

#### User Experience

▲ Displays images with incorrect aspect ratio

Image display dimensions should match natural aspect ratio. Learn more.

Show 3rd party resources (0)

	URL	Aspect Ratio (Displayed)	Aspect Ratio (Actual)
	Book Reposimages/logo_bookstack_text_96_spacing.png (book-repository-virtual.herokuapp.com)	1524 x 75 (20.32)	1524 x 562 (2.71)
ſ	images/Gaff.png (book-repository-virtual.herokuapp.com)	512 x 150 (3.41)	512 x 512 (1.00
ass	sed audits (13)		
	Uses HTTPS		
	All sites should be protected with HTTPS, even ones that don't handle sensitive of where some resources are loaded over HTTP despite the initial request being ser from tampering with or passively listening in on the communications between your prerequisite for HTTP/2 and many new web platform APIs. Learn more.	vedover HTTPS. HTTPS	prevents intruder
	Links to cross-origin destinations are safe		
	Add `rel="noopener"` or `rel="noreferrer"` to any external links to improve perform Learn more.	nance and prevent secur	rity vulnerabilities.
,	Avoids requesting the geolocation permission on page load		
	Users are mistrustful of or confused by sites that request their location without coaction instead. Learn more.	ontext. Consider tying th	ne request to a us
	Avoids requesting the notification permission on page load		
	Users are mistrustful of or confused by sites that request to send notifications wito user gestures instead. Learn more.	thout context. Consider	tying the request
	Avoids front-end JavaScript libraries with known security vulnerabilities		
	Some third-party scripts may contain known security vulnerabilities that are easily Learn more.	y identified and exploite	d by attackers.
	Allows users to paste into password fields		
	Preventing password pasting undermines good security policy. Learn more.		
	Displays images with appropriate size		
	Image natural dimensions should be proportional to the display size and the pixe more.	I ratio to maximize imag	e clarity. <u>Learn</u>
	Page has the HTML doctype		
	Specifying a doctype prevents the browser from switching to quirks-mode. Learn	n more.	
	Properly defines charset		
	A character encoding declaration is required. It can be done with a <meta/> tag in Content-Type HTTP response header. Learn more.	n the first 1024 bytes of	the HTML or in th
	Avoids Application Cache		
	Application Cache is deprecated. <u>Learn more</u> .		
	Detected JavaScript libraries		
	All front-end JavaScript libraries detected on the page. Learn more.		
,	Avoids deprecated APIs		
	Deprecated APIs will eventually be removed from the browser. Learn more.		
	No browser errors logged to the console		



#### SFO

These checks ensure that your page is optimized for search engine results ranking. There are additional factors Lighthouse does not check that may affect your search ranking. <u>Learn more</u>.

**Crawling and Indexing** — To appear in search results, crawlers need access to your app.

#### ▲ robots.txt is not valid - 175 errors found

If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. <u>Learn more</u>.

Line #	Content	Error
1	html	Syntax not unders tood
2	<html lang="en"></html>	Syntax not unders tood
4	<head></head>	Syntax not unders tood
5	<meta charset="utf-8"/>	Syntax not unders tood
6	<pre><meta content="IE=edge" http-equiv="X-UA-Compatible"/></pre>	Syntax not unders tood
7	<pre><meta content="width=device-width, initial-scale=1" name="viewport"/></pre>	Syntax not unders tood
8	<pre><meta content="Developer and Designer: Naoise Gaffney - 'Gaff'. Title: Book Repository. Reason: third&lt;/pre&gt;&lt;/td&gt;&lt;td&gt;Unknow&lt;br&gt;n&lt;br&gt;direct&lt;br&gt;ive&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;9&lt;/td&gt;&lt;td&gt;milestone project for the Code Institute's Diploma in Full Stack Development. Description: The&lt;/td&gt;&lt;td&gt;Unknow&lt;br&gt;n&lt;br&gt;direct&lt;br&gt;ive&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;10&lt;/td&gt;&lt;td&gt;Book Repository is a digital or virtual library to store information about your books, such as&lt;/td&gt;&lt;td&gt;Syntax&lt;br&gt;not&lt;br&gt;unders&lt;br&gt;tood&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;11&lt;/td&gt;&lt;td&gt;title, author, year published, ISBN, genre, rating, description, and your reflection and comments.&lt;/td&gt;&lt;td&gt;Syntax&lt;br&gt;not&lt;br&gt;unders&lt;br&gt;tood&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;12&lt;/td&gt;&lt;td&gt;The Book Repository provides a private and public search function too, using any combination of title,&lt;/td&gt;&lt;td&gt;Syntax&lt;br&gt;not&lt;br&gt;unders&lt;br&gt;tood&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;13&lt;/td&gt;&lt;td&gt;author, ISBN, genre, and rating." name="Description"/></pre>	Syntax not unders tood
14	<pre><link href="/static/images/apple-touch- icon.png" rel="apple-touch-icon" sizes="180x180"/></pre>	Syntax not unders

Line #	Content	Error
15	<pre><link href="/static/images/favicon- 32x32.png" rel="icon" sizes="32x32" type="image/png"/></pre>	Syntax not unders tood
16	<pre><link href="/static/images/favicon- 16x16.png" rel="icon" sizes="16x16" type="image/png"/></pre>	Syntax not unders tood
17	<pre><link href="/static/images/site.webmanifest" rel="manifest"/></pre>	Syntax not unders tood
18	<title>Book Repository</title>	Syntax not unders tood
20	Import Google Icon Font	Syntax not unders tood
21	<pre><link href="https://fonts.googleapis.com/icon?family=Material+Icons" rel="stylesheet"/></pre>	Unknow n direct ive
22	Import materialize.css	Syntax not unders tood
23	<pre><link href="https://cdnjs.cloudflare.com/ajax/libs/materialize/1.0.0/css/materialize.min.css" rel="stylesheet"/></pre>	Unknow n direct ive
24	Custom CSS	Syntax not unders tood
25	<pre><link href="/static/styles/style.css" rel="stylesheet" type="text/css"/></pre>	Syntax not unders tood
26	Cookie Consent by Osano: https://www.osano.com/cookieconsent/download/	Unknow n direct ive
27	<pre><link <="" pre="" rel="stylesheet" type="text/css"/></pre>	Syntax not unders tood
28	href="https://cdn.jsdelivr.net/npm/cookieconsent@3/build/cookieconsent.min.css" />	Unknow n direct ive
30	HTML5 Shim and Respond.js IE8 support of HTML5 elements and media queries	Syntax not unders tood
31	WARNING: Respond.js doesn't work if you view the page via file://	Unknow n direct ive
32	[if lt IE 9]	Syntax not unders tood
33	<pre><script src="//cdnjs.cloudflare.com/ajax/libs/html5shiv/3.7/html5shiv.js"></script></pre>	Syntax not unders tood
34	<pre><script src="//cdnjs.cloudflare.com/ajax/libs/respond.js/1.4.2/respond.js"></script></pre>	Syntax not unders tood
35	[endif]	Syntax

Line #	Content	unders Eorgi
39		Syntax not unders tood
41	 body>	Syntax not unders tood
42	<header></header>	Syntax not unders tood
44	<pre><nav class="nav-wrapper white"></nav></pre>	Syntax not unders tood
45	<pre><div class="container"></div></pre>	Syntax not unders tood
46	<pre><a href="/index.html"><img <="" pre="" src="/static/images/logo_bookstack_text_96_spacing.png"/></a></pre>	Syntax not unders tood
47	height="60" alt="Book Repository Logo">	Syntax not unders tood
48	<a class="sidenav-trigger" data-target="mobile-links" href="#"></a>	Syntax not unders tood
49	<pre><i class="material-icons blue-text text-darken-4" id="matnavbar">menu</i></pre>	Syntax not unders tood
50		Syntax not unders tood
51	<pre><ul class="right hide-on-med-and-down blue darken-4 waves-effect" id="nav-mobile"></ul></pre>	Syntax not unders tood
54	<li><li>&lt;</li></li>	Syntax not unders tood
55	<a href="/admin_dashboard">Admin Page<i< td=""><td>Syntax not unders tood</td></i<></a>	Syntax not unders tood
56	<pre>class="material-icons right"&gt;admin_panel_settings</pre>	Syntax not unders tood
57		Syntax not unders tood
59	<li><li><li></li></li></li>	Syntax not unders tood
60	<a href="/members">Member's Page<i< td=""><td>Syntax not unders tood</td></i<></a>	Syntax not unders tood
61	class="material-icons right">dashboard	Syntax not unders tood
		Syntax

<b>62</b> Line #	Content	not unders tood
63	<1i>>	Syntax not unders tood
64	<a href="/user/edit_user_profile">admin<i< td=""><td>Syntax not unders tood</td></i<></a>	Syntax not unders tood
65	<pre>class="material-icons right"&gt;account_box</pre>	Syntax not unders tood
66		Syntax not unders tood
67	<1i>>	Syntax not unders tood
68	<a href="/user/sign-out">Sign Out<i< td=""><td>Syntax not unders tood</td></i<></a>	Syntax not unders tood
69	class="material-icons right">pan_tool	Syntax not unders tood
70		Syntax not unders tood
72		Syntax not unders tood
73		Syntax not unders tood
74		Syntax not unders tood
75	Naviagtion for Mobile devices using a "Hamburger-menu" which must be defined outside of <nav to function in Materialize 1.0.0>	Syntax not unders tood
76	<ul><li><ul class="sidenav blue darken-4" id="mobile-links"></ul></li></ul>	Syntax not unders tood
79	<1i>>	Syntax not unders tood
80	<a class="white-text" href="/admin_dashboard">Admin Page<i< td=""><td>Syntax not unders tood</td></i<></a>	Syntax not unders tood
81	<pre>class="material-icons white-text left"&gt;admin_panel_settings</pre>	Syntax not unders tood
82		Syntax not unders tood
84	<1i>>	Syntax not unders tood

L <b>85</b> : #	Sa href="/members" class="white-text">Member's Page <i< th=""><th>Syntax not unders tood</th></i<>	Syntax not unders tood
86	class="material-icons white-text left">dashboard	Syntax not unders tood
87		Syntax not unders tood
88	<li>&lt;1i&gt;&gt;</li>	Syntax not unders tood
89	<a <="" href="/user/edit_user_profile" td=""><td>Syntax not unders tood</td></a>	Syntax not unders tood
90	class="white-text">admin <i< td=""><td>Syntax not unders tood</td></i<>	Syntax not unders tood
91	<pre>class="material-icons white-text left"&gt;account_box</pre>	Syntax not unders tood
92		Syntax not unders tood
93	<li>&lt;1i&gt;&gt;</li>	Syntax not unders tood
94	<a class="white-text" href="/user/sign-out">Sign Out<i< td=""><td>Syntax not unders tood</td></i<></a>	Syntax not unders tood
95	<pre>class="material-icons white-text left"&gt;pan_tool</pre>	Syntax not unders tood
96		Syntax not unders tood
98		Syntax not unders tood
99		Syntax not unders tood
103	<div class="container center" id="main-div"></div>	Syntax not unders tood
107		Syntax not unders tood
111	<div class="container"></div>	Syntax not unders tood
112	<div class="row"></div>	Syntax not unders tood
113	<pre><div class="col s12 offset-m1 m10 offset-l1 110"></div></pre>	Syntax not unders

Line # 114	Content <div class="card center"></div>	Error Syntax not unders tood
115	<div class="card-image"></div>	Syntax not unders tood
116	<pre><img alt="burning book" src="/static/images/fred-kearney-enkfvvZkKv0-unsplash.jpg"/></pre>	Syntax not unders tood
117	<pre><a class="halfway-fab btn-floating pink pink-darken-1 pulse" href="/index.html"></a></pre>	Syntax not unders tood
118	<pre><i class="material-icons">support</i></pre>	Syntax not unders tood
119		Syntax not unders tood
120		Syntax not unders tood
121	<pre><div class="card-content"></div></pre>	Syntax not unders tood
122	<pre><span class="card-title pink-text text-darken-1">Client: 404 - Page Not Found</span></pre>	Unknow n direct ive
123	Apologies, our Librarians are lost in the Library or have lost the book you're looking for! Please click on the pink pulsating buoy to go to the Home Page (registering or signing in) or Member's Page (signed in), or click on Sign Out below.	Syntax not unders tood
124		Syntax not unders tood
125	Book Repository Message - 404 Not Found: The requested URL was not found on the server. If you entered the URL manually please check your spelling and try again.	Unknow n direct ive
126		Syntax not unders tood
127	<pre><div class="card-action"></div></pre>	Syntax not unders tood
128	<a href="/user/sign-out">[ Sign Out <i class="material-icons">pan_tool</i> ]</a>	Syntax not unders tood
129		Syntax not unders tood
130		Syntax not unders tood
130		not unders

		1
Line #	Content	unders
133		Syntax not unders tood
137	<footer class="page-footer transparent"></footer>	Syntax not unders tood
138	<div class="footer-copyright blue darken-4"></div>	Syntax not unders tood
139	<div class="left-align">Book Repository v1.0</div>	Syntax not unders tood
140	<pre><div class="center-align"><a class="modal-trigger" href="#about"><i <="" class="material- icons white-text" pre=""></i></a></div></pre>	Syntax not unders tood
141	<pre>id="menu_book"&gt;menu_book</pre>	Syntax not unders tood
142	<div class="right-align">© 2020</div>	Syntax not unders tood
143	<pre>GaffCo Consulting</pre>	Syntax not unders tood
144		Syntax not unders tood
145	<pre><div class="container"></div></pre>	Syntax not unders tood
146	<pre><div class="modal center" id="about"></div></pre>	Syntax not unders tood
147	<pre><div class="modal-content"></div></pre>	Syntax not unders tood
148	<pre><ul class="tabs blue darken-4 center"></ul></pre>	Syntax not unders tood
149	<li>class="tab"&gt;</li>	Syntax not unders tood
150	<a class="active blue darken-4 white-text waves-effect" href="#bookrepo">Book Repository</a>	Syntax not unders tood
151		Syntax not unders tood
152	<li>class="tab"&gt;</li>	Syntax not unders tood
153	<a class="active blue darken-4 white-text waves-effect" href="#gaff">Gaff</a>	Syntax not unders tood

Svntax

154 Line #	<li>Content</li>	not Error unders tood
155	<pre><li class="tab"></li></pre>	Syntax not unders tood
156	<pre><a class="active blue darken-4 white-text waves-effect" href="#code">Code</a></pre>	Syntax not unders tood
157		Syntax not unders tood
158		Syntax not unders tood
159	<div id="bookrepo"></div>	Syntax not unders tood
160	<pre><img <="" height="75" pre="" src="/static/images/logo_bookstack_text_96_spacing.png"/></pre>	Syntax not unders tood
161	alt="Book Repository Logo">	Syntax not unders tood
162	<pre>A safe virtual repository for books, a digital version of your library that is searchable,</pre>	Syntax not unders tood
163	and where	Syntax not unders tood
164	you can share your book notes and thoughts with like-minded readers.	Syntax not unders tood
165		Syntax not unders tood
166		Syntax not unders tood
167	<div id="gaff"></div>	Syntax not unders tood
168	<pre>Naoise Gaffney - "Gaff"</pre>	Syntax not unders tood
169	<img alt="Gaff" height="150" src="/static/images/Gaff.png"/>	Syntax not unders tood
170	Code Institute Learner and Developer of this Book Repository, a Milestone Project 3	Syntax not unders tood
171	(Data-Centric) for the Code	Syntax not unders tood
172	Institute Diploma in Full Stack Development. Full Stack Developer and UX Designer.	Syntax not unders tood

L <b>11763</b> #	C/carilvent	not unders tood
174	<div id="code"></div>	Syntax not unders tood
175	<pre>Code on GitHub</pre>	Syntax not unders tood
176	Front-end: HTML 5, CSS 3, and JavaScript	Unknow n direct ive
177	Application: Python, Flask, Flask Extensions, and MongoEngine	Unknow n direct ive
178	Database: MongoDB	Unknow n direct ive
179	API: Goggle Books API	Unknow n direct ive
180	External Links: Amazon UK and ISBN Search	Unknow n direct ive
181	<a <="" href="https://github.com/NaoiseGaffney/BookRepository" p="" rel="noopener" target="_blank"></a>	Unknow n direct ive
182	class="pink-text text-darken-1 waves-effect"> Book Repository on GitHub	Syntax not unders tood
183		Syntax not unders tood
184		Syntax not unders tood
185	<pre><div class="modal-footer"></div></pre>	Syntax not unders tood
186	<a class="modal-close btn waves-effect waves-light blue darken-4" href="#!">Thank You! <i< td=""><td>Syntax not unders tood</td></i<></a>	Syntax not unders tood
187	<pre>class="material-icons right"&gt;thumb_up</pre>	Syntax not unders tood
188		Syntax not unders tood
189		Syntax not unders tood
190		Syntax not unders tood
191		Syntax not unders

Line # 193 196	Content Compiled and minified JavaScript	Error Synta not under tood Synta
196		not under tood
	Compiled and minified JavaScript	-
197		not under tood
197		
	<pre><script src="https://cdnjs.cloudflare.com/ajax/libs/materialize/1.0.0/js/materialize.min.js"> </script></pre>	Unkno n direc ive
198	Initialise MaterializeCSS 1.0.0 Features	Synta not under tood
199	<pre><script src="/static/scripts/vendor/materialize.js"></script></pre>	Synta not under tood
200	Message Chip Timeout	Synta not under tood
201	<pre><script src="/static/scripts/message.js"></script></pre>	Synta not under tood
202	Cookie Consent by Osano: https://www.osano.com/cookieconsent/download/	Unkno n direc ive
203	<pre><script data-cfasync="false" src="https://cdn.jsdelivr.net/npm/cookieconsent@3/build/cookieconsent.min.js"></script></pre>	Unkno n direc ive
204	<pre><script src="/static/scripts/vendor/cookies.js"></script></pre>	Synta not under tood
208		Synta not under tood
210		Synta not under tood
itional items to	o manually check (1) — Run these additional validators on your site to check additional SEO best	
Structured dat	ta is valid  ured Data Testing Tool and the Structured Data Linter to validate structured data. Learn more.	
sed audits (11)		
Has a <meta na<="" td=""/> <td>ame="viewport"&gt; tag with width or initial-scale</td> <td></td>	ame="viewport"> tag with width or initial-scale	
Add a ` <meta r<="" td=""/> <td>name="viewport"&gt;` tag to optimize your app for mobile screens. <u>Learn more</u>.</td> <td></td>	name="viewport">` tag to optimize your app for mobile screens. <u>Learn more</u> .	
	s a <title> element screen reader users an overview of the page, and search engine users rely on it heavily to determine if&lt;/td&gt;&lt;td&gt;а&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;5&lt;/td&gt;&lt;td&gt;nt to their search. Learn more.&lt;/td&gt;&lt;td&gt;&lt;/td&gt;&lt;/tr&gt;&lt;/tbody&gt;&lt;/table&gt;</title>	

 $\label{eq:metadef} \mbox{Meta descriptions may be included in search results to concisely summarize page content.} \ \underline{\mbox{Learn more}}.$ 

•	Page has successful HTTP status code							
	Pages with unsuccessful HTTP status codes may not be indexed properly. Learn more.							
•	Links have descriptive text			/				
	Descriptive link text helps search	engines understand	your content. <u>Learn more</u> .					
•	Page isn't blocked from indexing	g		/				
	Search engines are unable to incl	ude your pages in se	arch results if they don't have perm	sission to crawl them. <u>Learn more</u> .				
•	Image elements have [alt] attri	butes						
	Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <u>Learn more</u> .							
•	Document has a valid hreflang							
	hreflang links tell search engines <u>Learn more</u> .	what version of a pag	ge they should list in search results	for a given language or region.				
•	Document uses legible font sizes — 100% legible text							
	Font sizes less than 12px are too to have >60% of page text ≥12px	_	nd require mobile visitors to "pinch	to zoom" in order to read. Strive				
				Show 3rd-party resources (0)				
	Source	Selector	% of Page Text	Font Size				
	Legible text		100.00%	≥ 12px				
•	Document avoids plugins							
	Search engines can't index plugir	n content, and many o	devices restrict plugins or don't sup	pport them. <u>Learn more</u> .				
•	Tap targets are sized appropriate	ely - 100% approp	oriately sized tap targets	/				
	Interactive elements like buttons easy enough to tap without overla		arge enough (48x48px), and have ements. Learn more.	nough space around them, to be				
No	applicable (1)							
•	Document has a valid rel=canon	ical		/				
Canonical links suggest which URL to show in search results. <u>Learn more</u> .								



## Progressive Web App

These checks validate the aspects of a Progressive Web App. <u>Learn more</u>.

0	Fast and reliable		
•	Page load is fast enough on mobile networks	^	
	A fast page load over a cellular network ensures a good mobile user experience. <u>Learn more</u> .		
<b>A</b>	Current page does not respond with a 200 when offline	^	
	If you're building a Progressive Web App, consider using a service worker so that your app can work offline. <u>Learn more</u> .		
<b>A</b>	start_url does not respond with a 200 when offline  Timed out waiting for start_url (https://book-repository-virtual.herokuapp.com/user/change-password) to respond.	^	
	A service worker enables your web app to be reliable in unpredictable network conditions. <u>Learn more</u> .		

# Installable

Uses HTTPS

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding <u>mixed content</u>, where some resources are loaded over HTTP despite the initial request being servedover HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. <u>Learn more</u>.

▲ Does not register a service worker that controls page and start\_url

The service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. <u>Learn more</u>.

Web app manifest does not meet the installability requirements

Failures: Manifest does not have `short\_name`, Manifest does not have `name`.

Browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. <u>Learn</u> more.

### PWA Optimized

Does not redirect HTTP traffic to HTTPS

If you've already set up HTTPS, make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. <u>Learn more</u>.

▲ Is not configured for a custom splash screen Failures: Manifest does not have `name`.

A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. <u>Learn</u> more.

Does not set a theme color for the address bar. Failures: No `<meta name="theme-color"> `tag found.

The browser address bar can be themed to match your site. Learn more.

Content is sized correctly for the viewport

If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. Learn more.

● Has a <meta name="viewport"> tag with width or initial-scale

Add a `<meta name="viewport">` tag to optimize your app for mobile screens. Learn more.

Ontains some content when JavaScript is not available

Your app should display some content when JavaScript is disabled, even if it's just a warning to the user that JavaScript is required to use the app. <u>Learn more</u>.

Provides a valid apple-touch-icon

For ideal appearance on iOS when users add a progressive web app to the home screen, define an 'apple-touch-icon'. It must point to a non-transparent 192px (or 180px) square PNG. <u>Learn More</u>.

▲ Manifest doesn't have a maskable icon

A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. <u>Learn more</u>.

Additional items to manually check (3) — These checks are required by the baseline <u>PWA Checklist</u> but are not automatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.

Site works cross-browser

To reach the most number of users, sites should work across every major browser. Learn more.

Page transitions don't feel like they block on the network

Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. <u>Learn more</u>.

Each page has a URL

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. <u>Learn more</u>.

#### Runtime Settings

	Ü
URL	https://book-repository-virtual.herokuapp.com/user/change-password
Fetch Time	Sep 10, 2020, 7:40 PM GMT+1
Device	Emulated Moto G4
Network throttling	150 ms TCP RTT, 1,638.4 Kbps throughput (Simulated)
CPU throttling	4x slowdown (Simulated)
Channel	devtools
User agent (host)	Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_6) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/85.0.4183.83 Safari/537.36
User agent (network)	Mozilla/5.0 (Linux; Android 6.0.1; Moto G (4)) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/80.0.3963.0 Mobile Safari/537.36 Chrome-Lighthouse
CPU/Memory Power	1458

Generated by **Lighthouse** 6.0.0 | File an issue