



# B3 - C++ Pool

---

B-CPP-300

## Day 02 afternoon

---

data structures





# Day 02 afternoon

repository name: `cpp_d02a_$ACADEMICYEAR`  
repository rights: `ramassage-tek`  
language: `C`



- The totality of your source files, except all useless files (binary, temp files, obj files,...), must be included in your delivery.

All your exercises will be compiled with the `-std=gnu11 -Wall -Wextra -Werror` **flags**, unless specified otherwise.

All output goes to the standard output, and must be ended by a newline, unless specified otherwise.



None of your files must contain a `main` function, unless specified otherwise.  
We will use our own `main` functions to compile and test your code.

For each exercise, the files to turn-in are path relative to the root of the directory. So you **don't** have to put everything in an `exXX` folder.



Read the examples **CAREFULLY**. They might require things that weren't mentioned in the subject...



## UNIT TESTS

---

It is highly recommended to test your functions as you implement them. It is common practice to create and use what are called **unit tests**.

From now on, we expect you to write unit tests for your functions (when possible). To do so, please follow the instructions in the “**How to write Unit Tests**” document on the intranet, available [here](#).



## EXERCISE 0 - DOUBLE LIST

Turn in: all the .c files required

Notes: The `double_list.h` file is provided. You must use it without modifying it.

The purpose of this exercise is to create a set of functions to manipulate a list of double.  
We will consider a list as the following:

```
typedef struct doublelist_node
{
    double          value;
    struct doublelist_node *next;
} doublelist_node_t;

typedef doublelist_node_t *double_list_t;
```

An empty list is represented by a `NULL` pointer.

Implement the following functions:

01. `unsigned int double_list_get_size(double_list_t list);`

returns the number of elements in the list.

02. `bool double_list_is_empty(double_list_t list);`

returns `true` if the list is empty, `false` otherwise.

03. `void double_list_dump(double_list_t list);`

displays every element in the list, separated by new-line characters.  
Use the default display of `printf (%f)` with no particular precision.

04. `bool double_list_add_elem_at_front(double_list_t *front_ptr, double elem);`

adds a new node at the beginning of the list with `elem` as its value.  
The function returns `false` if it cannot allocate memory for the new node, `true` otherwise.

05. `bool double_list_add_elem_at_back(double_list_t *front_ptr, double elem);`

adds a new node at the end of the list with `elem` as its value.  
The function returns `false` if it cannot allocate memory for the new node, `true` otherwise.



```
06. bool double_list_add_elem_at_position(double_list_t *front_ptr, double elem,
    unsigned int position);
```

adds a new node at the `position` position with `elem` as its value; returns `false` if it cannot allocate memory for the new node or if `position` is out of bounds, `true` otherwise.

If the value of `position` is 0, a call to this function is equivalent to a call to `double_list_add_elem_at_front`.

```
07. bool double_list_del_elem_at_front(double_list_t *front_ptr);
```

deletes the first node of the list; returns `false` if the list is empty, `true` otherwise.

```
08. bool double_list_del_elem_at_back(double_list_t *front_ptr);
```

deletes the last node of the list; returns `false` if the list is empty, `true` otherwise.

```
09. bool double_list_del_elem_at_position(double_list_t *front_ptr, unsigned int
    position);
```

deletes the node at the `position` position; returns `false` if the list is empty or if `position` is out of bounds, `true` otherwise.

If the value of `position` is 0, a call to this function is equivalent to a call to `double_list_del_elem_at_front`.

```
10. double double_list_get_elem_at_front(double_list_t list);
```

returns the value of the first node in the list; returns 0 if the list is empty.

```
11. double double_list_get_elem_at_back(double_list_t list);
```

returns the value of the last node in the list; returns 0 if the list is empty.

```
12. double double_list_get_elem_at_position(double_list_t list, unsigned int position
    );
```

returns the value of the node at the `position` position; returns 0 if the list is empty or if `position` is out of bounds.

If the value of `position` is 0, a call to this function is equivalent to a call to `double_list_get_elem_at_front`.

```
13. doublelist_node_t *double_list_get_first_node_with_value(double_list_t list,
    double value);
```

returns a pointer to the first node of `list` having `value` as its value.

If no node matches `value`, the function returns `NULL`.



Here is a sample `main` function and its expected output:

```
static void populate_list(double_list_t *list_head)
{
    double_list_add_elem_at_back(list_head, 5.2);
    double_list_add_elem_at_back(list_head, 42.5);
    double_list_add_elem_at_back(list_head, 3.3);
}

static void test_size(double_list_t list_head)
{
    printf("There are %u elements in the list\n", double_list_get_size(list_head));
    double_list_dump(list_head);
}

static void test_del(double_list_t *list_head)
{
    double_list_del_elem_at_back(list_head);
    printf("There are %u elements in the list\n", double_list_get_size(*list_head));
    double_list_dump(*list_head);
}

int main(void)
{
    double_list_t list_head = NULL;

    populate_list(&list_head);
    test_size(list_head);
    test_del(&list_head);
    return 0;
}
```

```
~/B-CPP-300> gcc -Wall -Wextra -Werror *.c
~/B-CPP-300> ./a.out
There are 3 elements in the list
5.200000
42.500000
3.300000
There are 2 elements in the list
5.200000
42.500000
```



## EXERCISE 1 - DOUBLE BTREE

---

Turn in: all the .c files required

Notes: The `double_btree.h` file is provided. You must use it without modifying it.

The purpose of this exercise is to create a set of functions to manipulate a binary tree of double. We will consider a binary tree as the following:

```
typedef struct doublebtree_node
{
    double          value;
    struct doublebtree_node *left;
    struct doublebtree_node *right;
} doublebtree_node_t;

typedef doublebtree_node_t *double_btree_t;
```

An empty tree is represented by a `NULL` pointer.

Implement the following functions:

01. `bool double_btree_is_empty(double_btree_t tree);`

returns `true` if tree is empty, `false` otherwise.

02. `unsigned int double_btree_get_size(double_btree_t tree);`

returns the number of nodes in tree.

03. `unsigned int double_btree_get_depth(double_btree_t tree);`

returns the depth of tree.

04. `bool double_btree_create_node(double_btree_t *node_ptr, double value);`

creates a new node with `value` as its value and places it at the location pointed to by `node_ptr`. Returns `false` if the node could not be added, `true` otherwise.

05. `bool double_btree_delete(double_btree_t *root_ptr);`

deletes the tree pointed to by `root_ptr` in its entirety, including its children. The function returns `false` if the tree is empty, `true` otherwise.

06. `double double_btree_get_max_value(double_btree_t tree);`

returns the maximal value in tree; returns 0 if the tree is empty.

07. `double double_btree_get_min_value(double_btree_t tree);`

returns the minimal value in tree; returns 0 if the tree is empty.



Here is a sample `main` function with its expected output:

```
static void populate_left(double_btree_t tree)
{
    double_tree_t left_sub_tree = tree->left;

    double_btree_create_node(&(left_sub_tree->left), 30);
    double_btree_create_node(&(left_sub_tree->right), 5);
}

static void populate_tree(double_btree_t *tree)
{
    double_btree_create_node(tree, 42.5);
    double_btree_create_node(&((*tree)->right), 100);
    double_btree_create_node(&((*tree)->left), 20);
    populate_left(*tree);
}

static void test_size(double_btree_t tree)
{
    unsigned int size = double_btree_get_size(tree);
    unsigned int depth = double_btree_get_depth(tree);

    printf("The tree's size is %u\n", size);
    printf("The tree's depth is %u\n", depth);
}

static void test_values(double_btree_t tree)
{
    double max = double_btree_get_max_value(tree);
    double min = double_btree_get_min_value(tree);

    printf("The tree's values range from %f to %f\n", min, max);
}

int main(void)
{
    double_btree_t tree = NULL;

    populate_tree(&tree);
    test_size(tree);
    test_values(tree);
    return (0);
}
```

```
~/B-CPP-300> gcc -Wall -Wextra -Werror *.c
~/B-CPP-300> ./a.out
The tree's size is 5
The tree's depth is 3
The tree's values range from 5.000000 to 100.000000
```





## EXERCISE 2 - GENERIC LIST

Turn in: all the .c files required

Notes: The `generic_list.h` file is provided. You must use it without modifying it.

The purpose of this exercise is to create a generic list.

The difference between this and the `Simple List` exercise is that a node is defined like this:

```
typedef struct node
{
    void *value;
    struct node *next;
} node_t;

typedef node_t * list_t;
```

The functions you have to implement are similar, with some minor differences in their prototypes:

```
unsigned int list_get_size(list_t list);
bool list_is_empty(list_t list);
bool list_add_elem_at_front(list_t *front_ptr, void *elem);
bool list_add_elem_at_back(list_t *front_ptr, void *elem);
bool list_add_elem_at_position(list_t *front_ptr, void *elem, unsigned int pos);
bool list_del_elem_at_front(list_t *front_ptr);
bool list_del_elem_at_back(list_t *front_ptr);
bool list_del_elem_at_position(list_t *front_ptr, unsigned int position);
void list_clear(list_t *front); // Releases all nodes in the list and
                               // makes `front_ptr` point to an empty list
void *list_get_elem_at_front(list_t list);
void *list_get_elem_at_back(list_t list);
void *list_get_elem_at_position(list_t list, unsigned int position);
```

Only two functions truly differ:

```
typedef void (*value_displayer_t)(void *value);
void list_dump(list_t list, value_displayer_t val_disp);
```

`list_dump` now takes a `value_displayer_t` function pointer as its second parameter.

Using the function pointed to by `val_disp`, it is now possible to display the `value` of each node, followed by a newline.

```
typedef int (*value_comparator_t)(void *first, void *second);
node_t *list_get_first_node_with_value(list_t list, void *value,
                                       value_comparator_t val_comp);
```

`list_get_first_node_with_value` now takes a `value_comparator_t` function pointer as its second parameter, which lets you compare two values of the list.

The comparison function returns a positive value if `first` is greater than `second`, a negative value if `second` is greater than `first`, and 0 if `first` and `second` are equal.



Here is a sample `main` function with its expected output:

```
static void int_displayer(void *data)
{
    int value = *((int *)data);

    printf("%d\n", value);
}

static void test_size(list_t list_head)
{
    printf("There are %u elements in the list\n", list_get_size(list_head));
    list_dump(list_head, &int_displayer);
}

static void test_del(list_t *list_head)
{
    list_del_elem_at_back(list_head);
    printf("There are %u elements in the list\n", list_get_size(*list_head));
    list_dump(*list_head, &int_displayer);
}

int main(void)
{
    list_t list_head = NULL;
    int i = 5;
    int j = 42;
    int k = 3;

    list_add_elem_at_back(&list_head, &i);
    list_add_elem_at_back(&list_head, &j);
    list_add_elem_at_back(&list_head, &k);
    test_size(list_head);
    test_del(&list_head);
    return 0;
}
```

```
Terminal
~/B-CPP-300> gcc -Wall -Wextra -Werror *.c
~/B-CPP-300> ./a.out
There are 3 elements in the list
5
42
3
There are 2 elements in the list
5
42
```



## EXERCISE 3 - STACK

**Turn in:** all the .c files required

**Notes:** The `stack.h` and `generic_list.h` files are provided. You must use them without modifying them.

A code built around another code is called a wrapper.

The purpose of this exercise is to create a stack based on the previously created generic list.



Copy and reuse your files from the previous exercises without modifying them.

As you may have guessed, we will consider a stack as a list which has smart feature limitations. Therefore:

```
typedef list_t stack_t;
```

**Implement the following functions:**

```
01. unsigned int stack_get_size(stack_t stack);
```

returns the number of elements in the stack.

```
02. bool stack_is_empty(stack_t stack);
```

returns `true` if the stack is empty, `false` otherwise.

```
03. bool stack_push(stack_t *stack_ptr, void *elem);
```

pushes `elem` to the top of the stack; returns `false` if the new element could not be pushed, `true` otherwise.

```
04. bool stack_pop(stack_t *stack_ptr);
```

pops the top element off the stack; returns `false` if the stack is empty, `true` otherwise.

```
05. void *stack_top(stack_t stack);
```

returns the value of the element on top of the stack.



Here is a sample `main` function and its expected output:

```
int main(void)
{
    stack_t stack = NULL;
    int i = 5;
    int j = 4;
    int *data = NULL;

    stack_push(&stack, &i);
    stack_push(&stack, &j);
    data = (int *)stack_top(stack);
    printf("%d\n", *data);
    return (0);
}
```

```
Terminal
~/B-CPP-300> gcc -Wall -Wextra -Werror *.c
~/B-CPP-300> ./a.out
4
```



## EXERCISE 4 - QUEUE

**Turn in:** all the .c files required

**Notes:** The `queue.h` and `generic_list.h` files are provided. You must use them without modifying them.

The purpose of this exercise is to create a queue based on the previously created generic list.



Copy and reuse your files from the “generic list” exercise without modifying them.

As you may have guessed again, we will consider a queue as a list with some smart feature limitations. Therefore:

```
typedef list_t queue_t;
```

**Implement the following functions:**

```
01. unsigned int queue_get_size(queue_t queue);
```

returns the number of elements in the queue.

```
02. bool queue_is_empty(queue_t queue);
```

returns `true` if the queue is empty, `false` otherwise.

```
03. bool queue_push(queue_t *queue_ptr, void *elem);
```

pushes `elem` into the queue; returns `false` if the new element cannot be pushed, `true` otherwise.

```
04. bool queue_pop(queue_t *queue_ptr);
```

pops the next element from the queue; returns `false` if the queue is empty, `true` otherwise.

```
05. void *queue_front(queue_t queue);
```

returns the value of the next element in the queue.



Here is a sample `main` function and its expected output:

```
int main(void)
{
    queue_t queue = NULL;
    int i = 5;
    int j = 4;
    int *data = NULL;

    queue_push(&queue, &i);
    queue_push(&queue, &j);
    data = (int *)queue_front(queue);
    printf("%d\n", *data);
    return 0;
}
```

```
Terminal
~/B-CPP-300> gcc -Wall -Wextra -Werror *.c
~/B-CPP-300> ./a.out
5
```



## EXERCISE 5 - MAP

Turn in: all the .c files required

Notes: The `map.h` and `generic_list.h` files are provided. You must use them without modifying them.

The purpose of this exercise is to create a map (which you may know as an associative array) based on the previously create generic list.



Copy and reuse your files from the “generic list” exercise without modifying them.

Once again, you may have guessed it: we will consider a map as a list with some smart feature limitations. Therefore:

```
typedef list_t map_t;
```

The remaining question you may have is: “What is a map a list of?”. Well, here’s the answer:

```
typedef struct pair
{
    void *key;
    void *value;
} pair_t;
```



Think about it..

Implement the following functions:

```
01. unsigned int map_get_size(map_t map);
```

returns the number of elements in the map.

```
02. bool map_is_empty(map_t map);
```

returns true if the map is empty, false otherwise.



Here comes the tricky part.

Because our map is generic, the `key` may contain any data type.

To be able to compare these data and know whether two keys are equal (among other things), we need a key comparator:

```
03. typedef int (*key_comparator_t)(void *first_key, void *second_key);
```



returns 0 if the keys are equal, a positive number if `first_key` is greater than `second_key`, and a negative number if `second_key` is greater than `first_key`.



If you remember correctly, our generic list uses the same function pointer system to find a node with a particular value.

The question now is “How can we make the function called by our list call the key comparison function when we cannot add new parameters?”

There are two solutions to this problem:

- a global variable,
- a wrapper around a global variable ;)

Because you love nice and maintainable code, you will obviously choose the second solution. Good. Implement the following functions:

```
04. key_comparator_t key_cmp_container(bool store, key_comparator_t new_key_cmp);
```

holds a static `key_comparator_t`.

If `store` is set to `true`, the value of the static variable must be set to `new_key_cmp`.

The function always returns the value of the static variable.

This simulates the behavior of a global variable: if you want to set its value, call this function with `true` as its first parameter and the value as its second. If you want to access the value, call this function with `false` as its argument and `NULL` as its second.

```
05. int pair_comparator(void *first, void *second);
```

compares the keys in each pair (the two parameters being values from the list which point to `pair_ts`).

Returns 0 if the keys are equal, a positive value if the key of `first` is greater than that of `second`, and a negative value if the key of `second` is greater than that of `first`.

Before we go back to our map, add a basic function to the generic list.



Implement this function in `generic_list.c`.

```
06. bool list_del_node(list_t *front_ptr, node_t *node_ptr);
```

deletes `node_ptr` from the list; returns `false` if the node is not in the list, `true` otherwise.

Now back to the map (in `map.c`):

```
07. bool map_add_elem(map_t *map_ptr, void *key, void *value, key_comparator_t  
    key_cmp);
```

adds `value` at the `key` index of the map.

If a value already exists at the `key` index, it is replaced by `value`.

`key_cmp` is to be called to compare the keys of the map.

Returns `false` if the element could not be added, `true` otherwise.





```
08. bool map_del_elem(map_t *map_ptr, void *key, key_comparator_t key_cmp);
```

deletes the value at the `key` index.

`key_cmp` is to be called to compare the keys of the map.

Returns `false` if there is no value at the `key` index, `true` otherwise.

```
09. void *map_get_elem(map_t map, void *key, key_comparator_t key_cmp);
```

returns the value held at the `key` index of the map.

If there is no value at the `key` index, returns `NULL`.

`key_cmp` is to be called to compare the keys of the map.

Here is a sample `main` function and its expected output:

```
int int_comparator(void *first, void *second)
{
    int val1 = *(int *)first;
    int val2 = *(int *)second;
    return (val1 - val2);
}

int main(void)
{
    map_t map = NULL;
    int first_key = 1;
    int second_key = 2;
    int third_key = 3;
    char *first_value = "first";
    char *first_value_rw = "first_rw";
    char *second_value = "second";
    char *third_value = "third";
    char **data = NULL;

    map_add_elem(&map, &first_key, &first_value, &int_comparator);
    map_add_elem(&map, &first_key, &first_value_rw, &int_comparator);
    map_add_elem(&map, &second_key, &second_value, &int_comparator);
    map_add_elem(&map, &third_key, &third_value, &int_comparator);
    data = (char **)map_get_elem(map, &second_key, &int_comparator);
    printf("The key [%d] maps to value [%s]\n", second_key, *data);
    return 0;
}
```

```
~/B-CPP-300> gcc -Wall -Wextra -Werror *.c
~/B-CPP-300> ./a.out
The key [2] maps to value [second]
```



## EXERCISE 6 - TREE TRAVERSAL

**Turn in:** all the .c files required

**Notes:** The `tree_traversal.h`, `stack.h`, `queue.h` and `generic_list.h` files are provided. You have to use them without modifying them.

The purpose of this exercise is to iterate over a tree in a generic way, using containers.  
Here is how we'll define a tree:

```
typedef struct tree_node
{
    void *data;
    struct tree_node *parent;
    list_t children;
} tree_node_t;

typedef tree_node_t *tree_t;
```

- data is the data contained in the node,
- parent is a pointer to the parent node,
- children is a generic list of child nodes.

An empty tree is represented by a `NULL` pointer.

**Implement the following functions:**

01. `bool tree_is_empty(tree_t tree);`

returns `true` if the tree is empty, `false` otherwise.

02. `typedef void (*dump_func_t)(void *data);`  
`void tree_node_dump(tree_node_t *tree_node, dump_func_t dump_func);`

displays the content of a node.

The first argument is a pointer to a node, and the second is a function pointer to a display function.

03. `bool init_tree(tree_t *tree_ptr, void *data);`

initializes `tree_ptr` by creating a root node holding data.

Returns `false` if the root node could not be allocated, `true` otherwise.

04. `tree_node_t *tree_add_child(tree_node_t *tree_node, void *data);`

adds a child node holding data to `tree_node`.

Returns a pointer to the child node, or `NULL` if the child node could not be added.

05. `bool tree_destroy(tree_t *tree_ptr);`

deletes `tree_ptr`, including all its children.

Resets `tree_ptr` to an empty tree.

Returns `false` if it fails, `true` otherwise.



To code the ultimate function, we need to define a generic container:

```
typedef struct container_s
{
    void *container;
    push_func_t push_func;
    pop_func_t pop_func;
} container_t;

typedef bool (*push_func_t)(void *container, void *data);
typedef void (*pop_func_t)(void *container);
```

`container_t` is a generic container.

The `container` field holds the address of the actual container. `push_func` is a function pointer that inserts an element in the container.

`pop_func` is a function pointer that extracts an element from the container.

Here is the ultimate function you must implement:

```
06. void tree_traversal(tree_t tree, container_t *container, dump_func_t dump_func);
```

iterates over `tree` and displays its content using `container` and `dump_func`.



To do this, each node of the tree has to insert its child nodes in the container, display itself, and start over with the next node, extracted from the container.



Output must go from left to right with a FIFO container and from right to left with a LIFO container, naturally.



Here is a sample `main` function and its expected output:

```
void dump_int(void *data)
{
    printf("%d\n", *(int *)data);
}

bool generic_push_stack(void *container, void *data)
{
    return stack_push((stack_t *)container, data);
}

void *generic_pop_stack(void *container)
{
    void *data = stack_top((stack_t *)container);

    stack_pop((stack_t *)container);
    return data;
}

bool generic_push_queue(void *container, void *data)
{
    return queue_push((queue_t *)container, data);
}

void *generic_pop_queue(void *container)
{
    void *data = queue_front((queue_t *)container);

    queue_pop((queue_t *)container);
    return data;
}

static void test_depth(tree_t tree)
{
    container_t container;
    stack_t stack = NULL;

    printf("Depth walk:\n");
    container.container = &stack;
    container.push_func = &generic_push_stack;
    container.pop_func = &generic_pop_stack;
    tree_traversal(tree, &container, &dump_int);
}

static void test_width(tree_t tree)
{
    container_t container;
    queue_t queue = NULL;

    printf("Width walk:\n");
    container.container = &queue;
    container.push_func = &generic_push_queue;
    container.pop_func = &generic_pop_queue;
    tree_traversal(tree, &container, &dump_int);
}
```



```
static void fill_tree(tree_t tree)
{
    int val_a = 1;
    int val_aa = 11;
    int val_b = 2;
    int val_c = 3;
    int val_ca = 31;
    int val_cb = 32;
    int val_cc = 33;
    tree_node_t *node = NULL;

    node = tree_add_child(tree, &val_a);
    tree_add_child(node, &val_aa);
    tree_add_child(tree, &val_b);
    node = tree_add_child(tree, &val_c);
    tree_add_child(node, &val_ca);
    tree_add_child(node, &val_cb);
    tree_add_child(node, &val_cc);
}

int main(void)
{
    int val_0 = 0;
    tree_t tree = NULL;

    init_tree(&tree, &val_0);
    fill_tree(tree);
    test_depth(tree);
    test_width(tree);
    return 0;
}
```

```
Terminal
~/B-CPP-300> gcc -Wall -Wextra -Werror *.c
~/B-CPP-300> ./a.out
Depth walk:
0
3
33
32
31
2
1
11
Width walk:
0
1
2
3
11
31
32
33
```

