

Public Ingress & Cloudflare Orchestration

This document covers the public-facing stack, ensuring secure remote access to Jellyfin (media.domain.local) while completely isolating internal tools (like Home Assistant) from the web.

1. Domain Registration & Delegation (Namecheap)

1. Purchase your domain (domain.local) via Namecheap.
2. In Namecheap: **Domain List > Manage > Nameservers**.
3. Select **Custom DNS** and enter your assigned Cloudflare nameservers (e.g., dina.ns.cloudflare.com and phil.ns.cloudflare.com).

2. SSL & Edge Setup (Cloudflare Dashboard)

When you delegate to Cloudflare, Cloudflare automatically provisions a **Universal SSL Certificate** for the edge.

- External users connecting to https://media.domain.local will perform an SSL handshake with Cloudflare's servers.
- Go to **SSL/TLS > Overview** and ensure your encryption mode is set to **Full (Strict)**.

Caching Rules (CRITICAL for Jellyfin)

Cloudflare's Terms of Service strictly prohibit disproportionate non-HTML content (like video streaming) via their caching network. You must bypass the cache to prevent domain suspension.

1. Cloudflare Dashboard > **Caching > Cache Rules**.
2. Create rule: **"Bypass Jellyfin Media"**.
3. **If...** Hostname equals media.domain.local -> **Then...** Cache status: **Bypass cache**.

3. cloudflared LXC Configuration (CT 110)

This LXC acts as the outbound secure tunnel. It connects to Cloudflare and forwards incoming traffic to the internal Nginx Proxy Manager (NPM).

- **ID:** 110 | **OS:** Debian 12 | **IP:** 10.0.1.110/23 | **Gateway:** 10.0.0.1

Installation

```
apt update && apt upgrade -y
curl -L
```

```
'https://github.com/cloudflare/cloudflared/releases/latest/download/cloudflared-linux-amd64.deb' -o cloudflared.deb
```

```
dpkg -i cloudflared.deb
cloudflared tunnel login
cloudflared tunnel create batcave-tunnel
```

Routing Configuration (/etc/cloudflared/config.yml)

Only public services are defined here. Home Assistant is strictly excluded.

```
tunnel: <YOUR_TUNNEL_UUID>
credentials-file: /root/.cloudflared/<YOUR_TUNNEL_UUID>.json
```

ingress:

```
# Route Jellyfin traffic to the NPM LXC
- hostname: "media.domain.local"
  service: http://10.0.1.111:80
  originRequest:
    httpHostHeader: "media.domain.local"
```

```
# Catch-all
- service: http_status:404
```

Start Service

```
cloudflared service install
systemctl start cloudflared && systemctl enable cloudflared
```