

natUlive framework

| Element | Code | Options |
|-------------|--|--|
| Grid | <pre><div class=row> <div> ... </div> ... </div></pre> | <ul style="list-style-type: none">• Columns: just a div, .col3, .col23, .col34 etc.• .contain constrains to standard page width• Columns have equal width automatically. If a column gets explicit width, the others divide the rest equally among themselves.• .row.wrap wraps columns on multiple lines• .row.half for 2-column row on mobile• .row.border for column borders• use .pad or .pad-x2 for padding• embed .box in cells for boxes with different background, border etc.• .row.border-all for borders around each cell• cell alignment classes: .align-right, .align-center, .align-top, .align-middle, .align-bottom• add space between cells with .row's border-spacing property or .spacing, .spacing-horizontal or .spacing-vertical |

natUlive framework

| Element | Code | Options |
|-------------------------------|---|--|
| Mobile/Desktop Content | <pre><div class=narrow-screen> ... </div> <div class=wide-screen> ... </div></pre> | |
| Structure | <pre><div class=header-and-banner> <header> ... </header> <div class=banner> </div> </div> <main id=content> <div class=contain> ... </div> ... </main> <footer> ... </footer></pre> | <ul style="list-style-type: none">• .header-and-banner.viewport sets header/banner to viewport height |
| Modal Window | <pre> Open in modal window </pre> | <ul style="list-style-type: none">• #container is recommended to avoid HTML head parts• openFullWindow(HTML) shows the HTML code in a modal window. |

natUlive framework

| Element | Code | Options |
|------------------|---|--|
| Slider | <pre><div class=slider data-autoslide=5 data-duration=.5> <div> ... </div> ... </div></pre> | <ul style="list-style-type: none">• Any element with <code>.tab</code> inside slides makes thumbnail navigation instead of numbered one.• supported <code>.toptabs</code>, optional <code>.slider.wrap</code> for auto-width tab links• <code>data-autoslide=5</code> slides to next slide after a 5" delay• Create sliders dynamically with <code>makeSlider(el)</code>• <code>.slider.vertical-thumbnails</code> option• <code>.slider.vertical</code> option• <code>.slider.full-window</code> option• <code>.slider.full-window.headless</code> option• <code>data-duration=x</code> option for x seconds of sliding animation |
| Tooltip | <pre> Hover for a tip Info ... </pre> | |
| Accordion | <pre><div class=accordion> <label class=trigger for=unique- id> <input type=checkbox class=trigger id=unique-id> <div> ... </div> </div></pre> | <ul style="list-style-type: none">• Embedded accordions supported |

natUlive framework

| Element | Code | Options |
|----------------|--|---|
| Buttons | <code> Call to Action </code> | <ul style="list-style-type: none"> • .big option |
| Forms | <pre> <form> <label> Description <input // <textarea></ textarea> </label> <label> Select a file <input type=file> </label> <div class=checkbox> Description for all checkboxes <label> <input type=checkbox> <b class=checkbox-icon> Specific description </label> ... </div> <label> Select Description </ span> <select> ... </select> </label> ... <input type=submit> </form> </pre> | <ul style="list-style-type: none"> • Description with Tooltip: <code>Descri ption </ span></code> • <code><label class=mandatory></code> • <code><form class=flat></code> • <code><input type=number data-digits=4></code> |

natUlive framework

| Element | Code | Options |
|--|---|---|
| Lightbox | <pre><div class=lightbox> Click for Image 1 </ a> ... </div></pre> | When clicked, a <code>.lightbox</code> child link to image forms a common slider gallery with its siblings. |
| Quote | <pre><p class=quote> ... </p></pre> | |
| Aspect ratio image container | <pre> </pre> | Ratio = (y / x) * 100, default 16:9, only when container is 100% wide. |
| Android Browser scroll polyfill | <pre><div class=overthrow> ... </div></pre> | |
| Masonry CSS-only | <pre><div class=masonry> <a>Column ... </div></pre> | |
| Tables | | <code><td data-sort></code> makes it sortable, where the <code>data-sort</code> value can be unspecified, asc or desc . |

natUlve framework

| Element | Code | Options |
|---------------|---|---------|
| Drop-down nav | <pre><nav class=drop> <form id=level1> </form> <form id=level2> </form> <input type=checkbox class='trigger burger'> <input type=radio class=trigger form=level1 name=level1> <input type=reset form=level1> <a>One <b class=sub> <input type=radio class=trigger form=level2 name=level2> <input type=reset form=level2> <a>Middle One</ a> <b class=sub></ b> Bottom One </nav></pre> | |

natUlive framework

| Element | Code | Options |
|------------------|--|---------|
| Drop caps | <pre><p class=drop-cap> ... </p></pre> | |