natUIve framework

Element	Code	Options

Grid	`<div class=row>`
	
	    `<div> … </div>`
	    `…`
	
	`</div>`
		• Columns: just a `div`, `.col3`, `.col23`, `.col34` etc.
		• `.contain` constrains to standard page width
		• Columns have equal width automatically. If a column gets explicit width, the others divide the rest equally among themselves.
		• `.row.wrap` wraps columns on multiple lines
		• `.row.half` for 2-column row on mobile
		• `.row.border` for column borders
		• use `.pad` or `.pad-x2` for padding
		• embed `.box` in cells for boxes with different background, border etc.
		• `.row.border-all` for borders around each cell
		• cell alignment classes: `.align-right`, `.align-center`, `.align-top`, `.align-middle`, `.align-bottom`

Mobile/Desktop Content	`<div class=narrow-screen>`
	    `…`
	`</div>`
	
	`<div class=wide-screen>`
	    `…`
	`</div>`	

natUIve framework

Element	Code	Options

Structure	```
	<div class=header-and-banner>
	
	    <header>
	        …
	    </header>
	
	    <div class=banner>
	
	    </div>
	
	</div>
	
	<main id=content>
	
	   <div class=contain>
	        …
	    </div>
	    …
	</main>
	
	<footer>
	
	  …
	
	</footer>
	``
		• .header-and-banner.viewport sets header/banner to viewport height

Modal Window	``` Open in modal window ```	• #container is recommended to avoid HTML head parts • openFullWindow(HTML) shows the HTML code in a modal window.

natUIve framework

Element	Code	Options

Slider	```<div class=slider data-autoslide=5 data-duration=.5>```
	
	``` <div> … </div>```
	``` …```
	
	```</div>```
		• Any element with `.tab` inside slides makes thumbnail navigation instead of numbered one. supported `.toptabs`
		• `data-autoslide=5` slides to next slide after a 5" delay
		• Create sliders dynamically with `makeSlider(el)`
		• `.slider.vertical-thumbnails` option
		• `.slider.vertical` option
		• `.slider.full-window` option
		• `.slider.full-window.headless` option
		• `data-duration=x` option for x seconds of sliding animation

Tooltip	``````
	
	``` Hover for a tip```
	``` Info ```
	``` …```
	
	``````	

Accordion	```<div class=accordion>```
	
	``` <label class=trigger for=unique-id>```
	``` <input type=checkbox class=trigger id=unique-id>```
	
	``` <div> … </div>```
	
	```</div>```
		• Embedded accordions supported

Buttons	``` Call to Action ```	• `.big` option

natUIve framework

Element	Code	Options

Forms	```<form>```
	
	    `<label>`
	        `<span> Description </span>`
	        `<input> // <textarea></textarea>`
	    `</label>`
	
	    `<label>`
	        `<span>Select a file</span>`
	        `<span class=file-input>`
	            `<input type=file>`
	            `<span></span>`
	        `</span>`
	    `</label>`
	
	    `<div class=checkbox>`
	        `<span> Description for all checkboxes</span>`
	        `<label>`
	            `<input type=checkbox> <b class=checkbox-icon> </b>Specific description`
	        `</label>`
	        `…`
	    `</div>`
	
	    `<label>`
	
	        `<span> Select Description </span>`
	        `<span class=selector>`
	            `<select> … </select>`
	        `</span>`
	
	    `</label>`
	  `…`
	    `<input type=submit>`
	
	`</form>`
		• Description with Tooltip: `<span class=tool>Description <span class=tip> </span>`
		• `<label class=mandatory>`
		• `<form class=flat>`
		• `<input type=number data-digits=4>`

natUIve framework

Element	Code	Options

Lightbox	`<div class=lightbox>`
	
	`    <a href=1.png title=Image 1> Click for Image 1 </a>`
	`    <a href=2.png> <img src=thumbnail.png alt=Thumbnail> </a>`
	`    …`
	
	`</div>`
		When clicked, a `.lightbox` child link to image forms a common slider gallery with its siblings.

Quote	`<p class=quote>`
	`    …`
	`</p>`	

Aspect ratio image container	`<span class=aspect>`
	
	`    <span style='padding-bottom: Ratio %'></span>`
	`    <img src=image.jpg alt=''>`
	
	`</span>`
		`Ratio` = (y / x) * 100, default 16:9, only when container is 100% wide.

Android Browser scroll polyfill	`<div class=overthrow>`
	`    …`
	`</div>`	

Masonry CSS-only	`<div class=masonry>`
	`    <a>Column</a>`
	`    …`
	`</div>`	

Tables		`<td data-sort>` makes it sortable, where the `data-sort` value can be unspecified, **asc** or **desc**.

natUIve framework

Element	Code	Options

Drop-down nav	```<nav class=drop>```
	``` <form id=level1> </form>```
	``` <form id=level2> </form>```
	``` <input type=checkbox class='trigger burger'>```
	``` ```
	``` ```
	``` <input type=radio class=trigger form=level1 name=level1>```
	``` <input type=reset form=level1>```
	``` <a>One```
	``` <b class=sub>```
	``` ```
	``` ```
	``` <input type=radio class=trigger form=level2 name=level2>```
	``` <input type=reset form=level2>```
	``` <a>Middle One```
	``` <b class=sub>```
	``` ```
	``` ```
	``` Bottom One```
	``` ```
	``` ```
	``` ```
	``` ```
	``` ```
	``` ```
	```</nav>```	

Drop caps	```<p class=drop-cap>```
	``` …```
	```</p>```	

natUlve framework