Element	Code	Options
Grid	<pre><div class="row"></div></pre>	 Columns: just a div, .col3, .col23, .col34 etc. .contain constrains to standard page width Columns have equal width automatically. If a column gets explicit width, the others divide the rest equally among themselves. When columns become too narrow for one row, they are wrapped to another row automatically. .row.half for 2-column row on mobile .row.border for column borders use.pad or .pad-x2 for padding; .unpad for enlarging with negative margin embed .box in cells for boxes with different background, border etc. .row.border-all for borders around each cell cell alignment classes: .align-right, .align-center, .align-middle, .align-bottom. Vertically-Aligned elements must be wrapped inside an extra divrow inherits alignment .align-children inherits alignment .row > .vertical-row - vertical row as tall as the parent row with equal-height full-width children

Element	Code	Options
Grid (cont'd)		 .row.no-spacing glues the cells together .row.no-padding for glued rows and cells .row > .full-mobile-width for full width columns on mobile
Mobile/Desktop Content	<pre><div class="narrow-screen"> </div> <div class="wide-screen"> </div></pre>	
Structure	<pre><div class="header-and-banner"></div></pre>	 .header-and-banner.viewport sets header/banner to viewport heightviewport.pu sh-up to move the content upwards for a better visual balance section clears inner margins at top/bottom section.fixed-background – element as a window to an image spanning the viewport. Requires child <div class="fixed-background-image"></div> for touch devices. header.fixed for fixed header on top on narrow screens

Element	Code	Options
Modal Window	<a href="page.html#container<br">class=modal> Open in modal window 	 #container is recommended to avoid HTML head parts openFullWindow(HT ML) shows the HTML code in a modal window.

Element	Code	Options
Slider	<pre><div class="slider" data-autoslide="5" data-duration=".5"></div></pre>	 slider.tabs makes thumbnail navigation instead of numbered one. Tab titles from a .tab-title child or a data-tab-title attribute. Supports .top.tabs, optional .slider.wr ap for auto-width tab links data-autoslide=5 slides to next slide after a 5" delay Create sliders dynamically with makeSlider(el) .slider.vertical-thumbnails option .slider.full-window option .slider.full-window option .slider.full-window option .slider.full-window option .slider.full-window option .slider.full-window.headless option data-duration=x option for x seconds of sliding animation .slider.center centers slides content .slider.auto-height matches slider height to the current slide .slider.fade to fade in/out instead of sliding .vertical.right, .vertical.tabs.right

Element	Code	Options
Tooltip	<pre> Hover for a tip Info </pre>	
Accordion	<pre><div class="fold"> <label <input="" class="trigger" type="checkbox"> <div> </div> </label></div></pre>	 Embedded accordions supported Optionally open by default with .fold.open
Buttons	 Call to Action 	• .big option

Element	Code	Options
Forms	<pre><form></form></pre>	 Description with Tooltip: Description <label class="mandatory"></label> form.mast for a balanced layout with labels in left column and inputs on right column <input datadigits="4" type="number"/> form.wide for 100% wide inputs form.sticky-submit positions the submit button to the right/center of the form form.dynamic submits without reloading the page and displays the result in a modal window form { placeholder_color: #aaa; } is the custom placeholder colour variable

Element	Code	Options
Lightbox	<pre><div class="lightbox"> <a 1="" href="1.png" title="Image"> Click for Image 1 </div></pre>	When clicked, a .lightbox child link to image forms a common slider gallery with its siblings. • lightbox.full-screen option • Use http://url#lightbox_id to open it automatically on page load • a.video
Quote	<pre> </pre>	
Aspect ratio image container	<pre><picture class="aspect" style=" ratio: Ratio"></picture></pre>	Ratio = x/y. Works only when container is 100% wide.
Android Browser scroll polyfill	<pre><div class="overthrow"> </div></pre>	
Masonry CSS- only	<pre><div class="masonry"> <a>Column </div></pre>	
Tables		makes a column sortable. The data-sort value can be unspecified, asc or desc .

Element	Code	Options
Top navigation	<pre><header></header></pre>	Hidden and burgerised on mobile • header.fixed option

Element	Code	Options
Drop-down nav	<pre><nav class="drop"></nav></pre>	

Element	Code	Options
Scrollable nav	<nav class="scroll"> </nav>	
Drop caps	<pre> </pre>	
CSS-only parallax scrolling	<html class="parallax"> <head> </head> <body> <div class="parallax-back"> </div> <div class="parallax-front"> </div> <body> <html></html></body></body></html>	parallax-back is the back layer, scrolling slower than the front layer .parallax- front
Right to left language support	<body dir="rtl"></body>	
Cards	<pre><div class="card"> <div class="head"> </div> <div class="content"> </div> </div></pre>	head.image with inline CSS for background-image

Element	Code	Options
Notification bar	<body></body>	 option .fixed create dynamically by notify('Message') with optional parameter 'fixed' if already present in HTML statically, close action will work
Lists	/ul>	 ul.vertical stacks list items vertically ul.indent
Typography		• option .big-text