

natUlive framework

Element	Code	Options
Grid	<pre><div class=row> <div> ... </div> ... </div></pre>	<ul style="list-style-type: none">• Columns: just a div, .col3, .col23, .col34 etc.• .contain constrains to standard page width• Columns have equal width automatically. If a column gets explicit width, the others divide the rest equally among themselves. When columns become too narrow for one row, they are wrapped to another row automatically.• .row.half for 2-column row on mobile• .row.border for column borders• use .pad or .pad-x2 for padding; .unpad for enlarging with negative margin• embed .box in cells for boxes with different background, border etc.• .row.border-all for borders around each cell• cell alignment classes: .align-right, .align-center, .align-top, .align-middle, .align-bottom. Vertically-Aligned elements must be wrapped inside an extra div. .align-children aligns inherits alignment

natUlive framework

Element	Code	Options
Grid (cont'd)		<ul style="list-style-type: none">• <code>.row.no-spacing</code> glues the cells together• <code>.row.no-padding</code> for glued rows and cells
Mobile/Desktop Content	<pre><div class=narrow-screen> ... </div> <div class=wide-screen> ... </div></pre>	
Structure	<pre><div class=header-and-banner> <header> ... </header> <div class=banner> </div> </div> <main id=content> <section class=contain> ... </section> ... </main> <footer> ... </footer></pre>	<ul style="list-style-type: none">• <code>.header-and-banner.viewport</code> sets header/banner to viewport height• <code>section</code> clears inner margins at top/bottom

natUlive framework

Element	Code	Options
Modal Window	<pre> Open in modal window </pre>	<ul style="list-style-type: none">• #container is recommended to avoid HTML head parts• openFullWindow(HTML) shows the HTML code in a modal window.
Slider	<pre><div class=slider data-autoslide=5 data-duration=.5> <div> ... </div> ... </div></pre>	<ul style="list-style-type: none">• Any element with .tab inside slides makes thumbnail navigation instead of numbered one.• supported .toptabs, optional .slider.wrap for auto-width tab links• data-autoslide=5 slides to next slide after a 5" delay• Create sliders dynamically with makeSlider(el)• .slider.vertical-thumbnails option• .slider.vertical option• .slider.full-window option• .slider.full-window.headless option• data-duration=x option for x seconds of sliding animation
Tooltip	<pre> Hover for a tip Info ... </pre>	

natUlv framework

Element	Code	Options
Accordion	<pre><div class=accordion> <label class=trigger for=unique- id> <input type=checkbox class=trigger id=unique-id> <div> ... </div> </div></pre>	<ul style="list-style-type: none">• Embedded accordions supported
Buttons	<pre> Call to Action </pre>	<ul style="list-style-type: none">• .big option

natUlive framework

Element	Code	Options
Forms	<pre><form> <label> Description <input> // <textarea></ textarea> </label> <label> Select a file <input type=file> </label> <div class=checkbox> Description for all checkboxes <label> <input type=checkbox> <b class=checkbox-icon> Specific description </label> ... </div> <label> Select Description </ span> <select> ... </select> </label> ... <input type=submit> </form></pre>	<ul style="list-style-type: none">• Description with Tooltip: Descri ption </ span>• <label class=mandatory>• <form class=flat>• <input type=number data- digits=4>

natUlive framework

Element	Code	Options
Lightbox	<pre><div class=lightbox> Click for Image 1 </ a> ... </div></pre>	When clicked, a <code>.lightbox</code> child link to image forms a common slider gallery with its siblings.
Quote	<pre><p class=quote> ... </p></pre>	
Aspect ratio image container	<pre> </pre>	Ratio = (y / x) * 100, default 16:9, only when container is 100% wide.
Android Browser scroll polyfill	<pre><div class=overthrow> ... </div></pre>	
Masonry CSS-only	<pre><div class=masonry> <a>Column ... </div></pre>	
Tables		<code><td data-sort></code> makes it sortable, where the <code>data-sort</code> value can be unspecified, asc or desc .

natUlive framework

Element	Code	Options
Drop-down nav	<pre><nav class=drop> <form id=level1> </form> <form id=level2> </form> <input type=checkbox class='trigger burger'> <input type=radio class=trigger form=level1 name=level1> <input type=reset form=level1> <a>One <b class=sub> <input type=radio class=trigger form=level2 name=level2> <input type=reset form=level2> <a>Middle One</ a> <b class=sub></ b> Bottom One </nav></pre>	

natUlive framework

Element	Code	Options
Drop caps	<pre><p class=drop-cap> ... </p></pre>	
CSS-only parallax scrolling	<pre><html class=parallax> <head> ... </head> <body> <div class=parallax-back> ... </div> <div class=parallax-front> ... </div> </body> </html></pre>	<ul style="list-style-type: none">• .parallax-back is the back layer, scrolling slower than the front layer .parallax-front
Right to left language support	<pre><body dir=rtl></pre>	
Cards	<pre><div class=card> <div class=head> ... </div> <div class=content> ... </div> </div></pre>	<ul style="list-style-type: none">• .head.image with inline CSS for background-image