

```

In[2]:= (* Coin flip, problem 3 *)

In[3]:= (* Assumption: Coin radius is 1, height is 1 *)

(* I will first define several functions to help calculate the coin flip simulation *)

In[4]:= (* Calculates total time to go back to initial height *)

In[5]:= timeFunction[v_] := 2 v / 9.8
timeFunction[4.5]

Out[6]:= 0.918367

In[7]:= (* Angular velocity is in radians *)
(* converts angular velocity to degrees per second *)
angularToDegrees[a_] := N[a * (180 / Pi)]

In[8]:= (* Function to find where the coin is rotated once
it falls back into initial height. Imagine a unit circle. *)
(* The rightmost part of the coin, facing heads up,
is at degree 0. It is rotated counterclockwise when flipped *)
finalDegrees[timetofunction_, degrees_] := timetofunction * degrees

(* Reduces the result from finalDegrees into
a value from 0 to 360 degrees on a unit circle *)
reducetobounds[finaldegrees_] := finaldegrees - (360 * Floor[finaldegrees / 360])

(* Takes a reduced degree and finds if it will land heads or tails. 1 = heads,
0 = tails. Assumes that the coin is starting heads up. *)
headsortails[reducedDegree_] := If[(reducedDegree > 270 || reducedDegree < 90), 1, 0]

In[11]:= (* This is where I am going to introduce some error *)

In[12]:= (* To land on the side, the coin needs to rotate exactly 90 or 270 degrees *)
(* However this will never happen as the
precision of my calculation always has a decimal *)
(* Instead of rounding to the nearest n-th degree, I am going to take a ratio *)
(* If reducedDegree/90 or reducedDegree/270 is between .99 and 1.01,
it lands on its side. This seems reasonable *)
(* As a real coin has some thickness on its side,
allowing it to land on its side without rotating exactly 90 or 270 degrees *)
(* 1 = lands on side and 0 = no *)

```

```
In[13]:= side[reducedDegree_] := If[(reducedDegree/90 ≥ .99 && reducedDegree/90 ≤ 1.01) ||
  (reducedDegree/270 ≥ .99 && reducedDegree/270 ≤ 1.01), 1, 0];
```

```
(* Implement a function to use all the above functions. Takes in a velocity
  and an angular momentum. Returns 1 = heads, 0 = tails, 2 = side *)
coinFlip[v_, w_] := (
  time = timeFunction[v];
  degrees = angularToDegrees[w];
  totalDegrees = finalDegrees[time, degrees];
  actualDegree = reducetobounds[totalDegrees];
  If[side[actualDegree] == 1, Return[2], Return[headsortails[actualDegree]]])
```

```
(* Create a list for the corresponding velocity and angular
  velocity that makes the coin land heads, tails, or on its side *)
```

```
headsListv = {};
headsListw = {};
tailsListv = {};
tailsListw = {};
sideListv = {};
sideListw = {};
```

```
In[21]:=
```

```
In[22]:= (* Simulate all integer trials of the coin flip of
  velocity and angular velocity from 0 to 99 (inclusive) *)
```

```
a = 0;
b = 0;
```


```
In[24]:= While[a < 100,
  While[b < 100,
    result = coinFlip[a, b];
    If[result == 1, (AppendTo[headsListv, a]; AppendTo[headsListw, b])];
    If[result == 0, (AppendTo[tailsListv, a]; AppendTo[tailsListw, b])];
    If[result == 2, (AppendTo[sideListv, a]; AppendTo[sideListw, b])];
    b = b + 1
  ];
  b = 0;
  a = a + 1
];
```

```
In[25]:= (* Transpose the trials into a table in order to plot it *)
```


```
headsTable = Transpose[{headsListv, headsListw}];
tailsTable = Transpose[{tailsListv, tailsListw}];
sidesTable = Transpose[{sideListv, sideListw}];
```

```
In[28]:=
```


```
In[29]:= (* Plot the phase diagram for heads, tails, and side *)
ListPlot[headsTable]
```



```
In[30]:= ListPlot[tailsTable]
```



```
In[31]:= ListPlot[sidesTable]
```



In[32]:=

```
( * There are several observations I can make from these phase diagrams * )
( * Most obviously, the sidesTable plot looks entirely random. There is no "pattern" * )
( * However, there is a distinct pattern when
  plotting velocity and angular velocity for heads and tails * )
( * The plot seems to have circles of increasing radii,
  and intuitively this makes sense * )

( * Imagine a unit circle where the x axis is velocity and y axis is angular velocity * )
( * Take (0,0) and (1,0) and (0,1) lands on heads * )
( * To land on heads again if velocity was increased from 0 to,
  say, .2, we would need a smaller angular velocity
  to make up for the increased velocity (the coin flips higher,
  so it has to spin a little less. The inverse of this statement is true too. * )
( * This point could be a point like (.2,.7) and if apply this
  pattern to all x values [-1,1] the plot will form a circle * )

( * Results for maximum v and w values: * )
( * 50: .502 heads, .4796 tails, .0184 side * )
( * 100: .4964 heads, .4842 tails, .0194 side * )
( * 150: .4934 heads, .4856 tails, .020 side * )
( * Conclusion: As v and w increase,
  the ratio of heads and tails approaches 50/50 via Squeeze theorem. * )
( * A larger data set could not be computed as the program runs for quite some time! * )

( * I will now find the ratios for heads, tails, and sides for this trial * )
totalLength = Length[headsListv] + Length[tailsListv] + Length[sideListv]
```

Out[32]= 10000

```
In[33]:= headsratio = N[Length[headsListv] / totalLength]
tailsratio = N[Length[tailsListv] / totalLength]
sideratio = N[Length[sideListv] / totalLength]
```

Out[33]= 0.4964

Out[34]= 0.4842

Out[35]= 0.0194

In[36]:=

```
( * I will now add error into the velocity and angular velocity calculations. First,
  reset our lists to be empty * )
headsListv = {};
headsListw = {};
tailsListv = {};
tailsListw = {};
sideListv = {};
sideListw = {};
```

In[42]:=

```
( * This is a trial where there is a random error to v and w between [-.1 and .1] * )
```

```

In[43]:= a = 0;
b = 0;
While[a < 100,
  While[b < 100,
    vError = RandomReal[{- .1, .1}] + a; (* Error is applied here *)
    wError = RandomReal[{- .1, .1}] + b;
    result = coinFlip[vError, wError];
    If[result == 1, (AppendTo[headsListv, a]; AppendTo[headsListw, b])];
    If[result == 0, (AppendTo[tailsListv, a]; AppendTo[tailsListw, b])];
    If[result == 2, (AppendTo[sideListv, a]; AppendTo[sideListw, b])];
    b = b + 1
  ];
  b = 0;
  a = a + 1
];

```

(* Transpose the data into a Table in order to plot *)

```


In[46]:= headsTable = Transpose[{headsListv, headsListw}];
tailsTable = Transpose[{tailsListv, tailsListw}];
sidesTable = Transpose[{sideListv, sideListw}];

```


```

In[49]:= (* Plot the phase diagram for heads, tails, and side *)
ListPlot[headsTable]


```



```
In[50]:= ListPlot[tailsTable]
```



```
In[57]:= ListPlot[sidesTable]
```



(* As we can see, the sidesTable is seemingly random again *)
 (* The heads and tails graphs exhibit the circular patterns again. However, the patterns only apply to low v and w values. As one can see, the patterns start to break up and become random data as v and w increase. I believe this is because the small "error" applied to v and w becomes very large over time as the time the coin is flipping increases. So there is no pattern anymore for heads and tails, just a seemingly random 50/50 data *)

(*Again, we take the ratio for this test and we see that it is about a 50/50 split *)
 totalLength = Length[headsListv] + Length[tailsListv] + Length[sideListv]

Out[51]= 10000

```
In[52]:= headsratio = N[Length[headsListv] / totalLength]  
         tailsratio = N[Length[tailsListv] / totalLength]  
         sideratio = N[Length[sideListv] / totalLength]
```

```
Out[52]= 0.4921
```

```
Out[53]= 0.4867
```

```
Out[54]= 0.0212
```

```
In[55]:=
```

```
In[56]:=
```