1. Read array A and number of rotations K
   IF A is empty:
      Return A

   Else
      FOR rotation FROM 1 to K
      SET last TO the last element of A
      REMOVE the last element from A
      INSERT last at the beginning of A

   RETURN A

#END

2. #Begin

   READ array A
   SET counts TO an empty dictionary

   FOR each number in A
      IF number is in counts
         INCREASE counts [number] by 1
      ELSE
         SET counts [number] TO 1

   FOR each number in counts
      IF counts [number] is odd
         RETURN number
#END

3. # Begin
READ starting position X, target position Y, and jump distance D

SET distance TO Y-X
SET jumps TO the whole-number quotient of distance divided by D

IF remainder of distance divided by D is not 0
INCREASE jumps by 1

RETURN jumps
#END

4. #Begin
READ array A
SET N TO the length of A
SET expected_total TO 0.

FOR number FROM 1 TO N+1:
SET expected_total TO expected_total + number

FOR each number in A
SET expected_total TO expected_total - number

RETURN expected_total

#END

5. #BEGIN
READ array A
SET right_total TO 0

FOR each number in A
    SET right_total TO right_total + number

SET left_total TO 0
SET smallest TO NONE

FOR i FROM 0 TO length A-2
    SET left_total TO left_total + A[i]
    SET right_total TO right_total - A[i]

    SET difference TO left_total - right_total

    IF difference < 0
        SET difference TO -difference

    IF smallest is None OR difference < smallest
        SET smallest TO difference

RETURN smallest
#END