

pFUnit

Generated by Doxygen 1.7.6

Thu Dec 10 2015 14:50:11



# Contents

<b>1</b>	<b>pFUnit 3 - Documentation - Version 3.1.1 development 2015-1210-1447-48-EST MLR</b>	<b>1</b>
1.1	Overview . . . . .	1
1.2	Contents . . . . .	1
1.3	See Also . . . . .	2
1.4	LICENSE . . . . .	2
1.5	Copyright . . . . .	2
<b>2</b>	<b>Obtaining pFUnit</b>	<b>3</b>
<b>3</b>	<b>Installation</b>	<b>5</b>
3.1	Installing pFUnit . . . . .	5
3.2	Prerequisites . . . . .	5
3.3	Obtaining pFUnit . . . . .	6
3.4	Manifest - What's in the directory? . . . . .	6
3.5	Configuration . . . . .	7
3.6	Building pFUnit . . . . .	8
3.6.1	Building pFUnit for testing serial codes (Non-MPI) . . . . .	8
3.6.2	Building pFUnit for testing parallel codes (MPI) . . . . .	8
3.6.3	OPENMP . . . . .	9
3.6.4	Cleaning . . . . .	9
3.6.5	Documentation . . . . .	9
3.6.6	CMAKE . . . . .	10
3.7	Installation . . . . .	10

3.7.1	Installation - Serial	10
3.7.2	Installation - MPI	11
3.7.3	Installation - OPENMP	11
3.7.4	Installation - DEFAULT DIRECTORY	11
<b>4</b>	<b>Usage</b>	<b>13</b>
4.1	Usage	13
4.1.1	Usage - Configuration	13
4.1.2	Usage - Hello World	13
4.2	Usage - Preprocessor	14
4.3	Compiling and Executing The Test	14
4.3.1	- Compiling and Executing the Tests (MPI PARALLEL)	14
4.3.2	Command Line Options	15
4.3.3	XML output	15
<b>5</b>	<b>Development</b>	<b>17</b>
<b>6</b>	<b>Feedback &amp; Support</b>	<b>19</b>
6.1	Feedback	19
6.2	Support	19
<b>7</b>	<b>FAQ and Tips</b>	<b>21</b>
7.1	FAQ	21
7.1.1	Zero Tests Run	21
7.1.2	Some Tests Are Not Running	22
7.1.3	Intel Fortran Version 13: -DINTEL_13	22
7.1.4	Segmentation Faults and Odd Link Errors	22
7.2	Tips	23
7.2.1	Environment Modules	23
7.2.2	Compile Time Errors	23
7.2.3	Intermediate files used by pFUnit	23
7.2.4	Ignoring whitespace differences in assertions on strings.	23

<b>8 Platform Specific Notes</b>	<b>25</b>
8.1 Mac OSX . . . . .	25
8.2 Windows/CYGWIN . . . . .	25
8.3 Intel Fortran Version 13: -DINTEL_13 . . . . .	25
<b>9 Acknowledgments</b>	<b>27</b>
<b>10 Known Installations &amp; Versions</b>	<b>29</b>
<b>11 TODO</b>	<b>31</b>
<b>12 The Preprocessor - pFUnitParser</b>	<b>33</b>
12.1 Using The Preprocessor . . . . .	33
12.1.1 Configuration - testSuites.inc . . . . .	34
12.1.2 Invocation . . . . .	34
12.1.3 Preprocessor Input File (.pf) . . . . .	34
12.1.4 Directives . . . . .	35
12.1.4.1 @Test . . . . .	35
12.1.4.2 @MPITest . . . . .	35
12.1.4.3 @Assert . . . . .	36
12.1.4.4 @Parameters . . . . .	37
12.1.4.5 @TestCase . . . . .	37
<b>13 @Assert Preprocessor Directives</b>	<b>39</b>
13.1 @Assert Preprocessor Directives . . . . .	40
13.1.1 @assertEqual . . . . .	40
13.1.2 @assertTrue . . . . .	40
13.1.3 @assertEqualUserDefined . . . . .	40
13.1.4 @assertFalse . . . . .	40
13.1.5 @assertLessThan . . . . .	40
13.1.6 @assertLessThanOrEqual . . . . .	40
13.1.7 @assertGreaterThan . . . . .	40
13.1.8 @assertGreaterThanOrEqual . . . . .	40

13.1.9 @assertIsMemberOf . . . . .	40
13.1.10 @assertContains . . . . .	40
13.1.11 @assertAny . . . . .	41
13.1.12 @assertAll . . . . .	41
13.1.13 @assertNotAll . . . . .	41
13.1.14 @assertNone . . . . .	41
13.1.15 @assertIsPermutationOf . . . . .	41
13.1.16 @assertExceptionRaised . . . . .	41
13.1.17 @assertSameShape . . . . .	41
13.1.18 @assertIsNaN . . . . .	41
13.1.19 @assertIsFinite . . . . .	41
13.1.20 @assertAssociated . . . . .	41
13.1.21 @assertNotAssociated . . . . .	42
13.1.22 @assertEquivalent . . . . .	42
<b>14 Revision Notes</b>	<b>43</b>
<b>15 Data Type Index</b>	<b>45</b>
15.1 Class Hierarchy . . . . .	45
<b>16 Data Type Index</b>	<b>51</b>
16.1 Data Types List . . . . .	51
<b>17 Data Type Documentation</b>	<b>57</b>
17.1 AbstractTestParameter_mod Module Reference . . . . .	57
17.2 AbstractTestResult_mod Module Reference . . . . .	57
17.3 pFUnitParser::Action Class Reference . . . . .	58
17.4 add_mod Module Reference . . . . .	59
17.5 addComplex_mod Module Reference . . . . .	59
17.6 CodeUtilities::ArrayDescription Class Reference . . . . .	59
17.7 Assert_mod Module Reference . . . . .	60
17.7.1 Detailed Description . . . . .	60
17.8 AssertBasic_mod Module Reference . . . . .	60

17.8.1 Detailed Description . . . . .	61
17.9 GenerateAssertsOnArrays::AssertRealArrayArgument Class Reference . . . . .	62
17.10pFUnitParser::AtAfter Class Reference . . . . .	63
17.11pFUnitParser::AtAssert Class Reference . . . . .	63
17.12pFUnitParser::AtAssertAssociated Class Reference . . . . .	64
17.13pFUnitParser::AtAssertEqualUserDefined Class Reference . . . . .	65
17.13.1 Detailed Description . . . . .	65
17.14pFUnitParser::AtAssertEquivalent Class Reference . . . . .	66
17.14.1 Detailed Description . . . . .	66
17.15pFUnitParser::AtAssertNotAssociated Class Reference . . . . .	66
17.16pFUnitParser::AtBefore Class Reference . . . . .	67
17.17pFUnitParser::AtBegin Class Reference . . . . .	68
17.18pFUnitParser::AtMpiAssert Class Reference . . . . .	68
17.19pFUnitParser::AtMpiTest Class Reference . . . . .	69
17.20pFUnitParser::AtSuite Class Reference . . . . .	69
17.21pFUnitParser::AtTest Class Reference . . . . .	70
17.22pFUnitParser::AtTestCase Class Reference . . . . .	71
17.23pFUnitParser::AtTestParameter Class Reference . . . . .	71
17.24TestCaseB_mod::B_Parameter Type Reference . . . . .	72
17.25BaseTestRunner_mod Module Reference . . . . .	72
17.25.1 Detailed Description . . . . .	73
17.26BeforeAfter_mod Module Reference . . . . .	73
17.27BrokenSetUpCase_mod Module Reference . . . . .	74
17.27.1 Detailed Description . . . . .	74
17.28BrokenTestCase_mod Module Reference . . . . .	74
17.28.1 Detailed Description . . . . .	75
17.29TestCaseC_mod::C_Parameter Type Reference . . . . .	75
17.30Cases_mod Module Reference . . . . .	76
17.31GenerateAssertsOnArrays::constraintASSERT Class Reference . . . . .	76
17.31.1 Constructor & Destructor Documentation . . . . .	77
17.31.1.1 __init__ . . . . .	77

17.31.2 Member Data Documentation . . . . .	77
17.31.2.1 name1 . . . . .	77
17.31.2.2 tolerance . . . . .	77
17.32 Test_mod::countTestCases Interface Reference . . . . .	77
17.33 mods::pre::pre2::dataString Class Reference . . . . .	78
17.34 DebugListener_mod Module Reference . . . . .	78
17.34.1 Detailed Description . . . . .	79
17.35 CodeUtilities::declaration Class Reference . . . . .	79
17.36 DynamicTestCase_mod Module Reference . . . . .	80
17.36.1 Detailed Description . . . . .	80
17.37 Exception_mod Module Reference . . . . .	81
17.38 Expectation_mod Module Reference . . . . .	81
17.39 Fixture_mod Module Reference . . . . .	82
17.40 FixtureTestCase_mod Module Reference . . . . .	82
17.40.1 Detailed Description . . . . .	83
17.41 CodeUtilities::fortranSubroutineSignature Class Reference . . . . .	83
17.42 AbstractTestResult_mod::getErrors Interface Reference . . . . .	84
17.43 Test_mod::getName Interface Reference . . . . .	84
17.44 AbstractTestResult_mod::getSuccesses Interface Reference . . . . .	84
17.45 Halo_mod Module Reference . . . . .	84
17.46 mods::pre::pre_if::IfDirective Class Reference . . . . .	84
17.47 CodeUtilities::implementation Class Reference . . . . .	85
17.48 CodeUtilities::interfaceBlock Class Reference . . . . .	85
17.49 mods::pre::pre_if::interval Class Reference . . . . .	86
17.50 GenerateAssertsOnArrays::IsWithinTolerance Class Reference . . . . .	86
17.51 Test_RestrictSphericalCoordinates_mod::LatLonCase Type Reference . . . . .	87
17.52 LinearInterpolator_mod Module Reference . . . . .	87
17.53 MakeInfinity_mod Module Reference . . . . .	88
17.53.1 Detailed Description . . . . .	88
17.54 MakeNaN_mod Module Reference . . . . .	88
17.54.1 Detailed Description . . . . .	89



17.55Mock_mod Module Reference . . . . .	89
17.55.1 Detailed Description . . . . .	89
17.56MockCall_mod Module Reference . . . . .	90
17.56.1 Detailed Description . . . . .	90
17.57MockListener_mod Module Reference . . . . .	91
17.57.1 Detailed Description . . . . .	91
17.58testParser::MockParser Class Reference . . . . .	91
17.59MockRepository_mod Module Reference . . . . .	92
17.59.1 Detailed Description . . . . .	93
17.60MockSUT_mod Module Reference . . . . .	93
17.61testParser::MockWriter Class Reference . . . . .	93
17.62CodeUtilities::module Class Reference . . . . .	94
17.63MpiContext_mod Module Reference . . . . .	94
17.63.1 Detailed Description . . . . .	95
17.64MpiStubs_mod Module Reference . . . . .	95
17.64.1 Detailed Description . . . . .	96
17.65MpiTestCase_mod Module Reference . . . . .	96
17.65.1 Detailed Description . . . . .	97
17.66MpiTestCaseB_mod::MpiTestCaseB Type Reference . . . . .	97
17.67MpiTestCaseB_mod Module Reference . . . . .	97
17.68MpiTestMethod_mod Module Reference . . . . .	98
17.68.1 Detailed Description . . . . .	98
17.69MpiTestParameter_mod Module Reference . . . . .	99
17.70pFUnitParser::MyError Class Reference . . . . .	99
17.71Cases_mod::MyParamType Type Reference . . . . .	99
17.72Cases_mod::MyTestCase Type Reference . . . . .	100
17.73TestCaseC_mod::newC_Parameter Interface Reference . . . . .	100
17.74node_mod Module Reference . . . . .	100
17.75ParallelContext_mod Module Reference . . . . .	101
17.75.1 Detailed Description . . . . .	101
17.76ParallelException_mod Module Reference . . . . .	101

17.76.1 Detailed Description . . . . .	102
17.77ParameterizedTestCase_mod Module Reference . . . . .	102
17.77.1 Detailed Description . . . . .	103
17.78Params_mod Module Reference . . . . .	103
17.78.1 Detailed Description . . . . .	104
17.79pFUnitParser::Parser Class Reference . . . . .	104
17.80Test_Parameters_mod::peCase Type Reference . . . . .	105
17.81pFUnit Module Reference . . . . .	106
17.81.1 Detailed Description . . . . .	106
17.82pFUnit_mod Module Reference . . . . .	106
17.82.1 Detailed Description . . . . .	107
17.83PrivateException_mod Module Reference . . . . .	107
17.83.1 Detailed Description . . . . .	108
17.84mods::pre::pre2::procDirective Class Reference . . . . .	108
17.84.1 Member Function/Subroutine Documentation . . . . .	109
17.84.1.1 addTokenRE . . . . .	109
17.85RemoteProxyTestCase_mod Module Reference . . . . .	109
17.85.1 Detailed Description . . . . .	109
17.86mods::pre::pre_Repeat::RepeatDirective Class Reference . . . . .	110
17.87ResultPrinter_mod Module Reference . . . . .	110
17.87.1 Detailed Description . . . . .	111
17.88RobustRunner_mod Module Reference . . . . .	111
17.88.1 Detailed Description . . . . .	112
17.89robustTestSuite_mod Module Reference . . . . .	112
17.89.1 Detailed Description . . . . .	113
17.90CodeUtilities::routineUnit Class Reference . . . . .	113
17.91SerialContext_mod Module Reference . . . . .	114
17.91.1 Detailed Description . . . . .	114
17.92SimpleTestCase_mod Module Reference . . . . .	115
17.92.1 Detailed Description . . . . .	115
17.93SourceLocation_mod Module Reference . . . . .	116

17.93.1 Detailed Description . . . . .	116
17.94SphericalCoordinates_mod Module Reference . . . . .	117
17.95TestListener_mod::startTest Interface Reference . . . . .	117
17.96StringConversionUtilities_mod Module Reference . . . . .	117
17.96.1 Detailed Description . . . . .	118
17.97SubsetRunner_mod Module Reference . . . . .	118
17.97.1 Detailed Description . . . . .	119
17.98SurrogateTestCase_mod Module Reference . . . . .	119
17.98.1 Detailed Description . . . . .	119
17.99SUT_mod Module Reference . . . . .	120
17.99.1 Detailed Description . . . . .	120
17.100Test_mod::Test Type Reference . . . . .	121
17.101Test_Assert_mod Module Reference . . . . .	121
17.101.1 Detailed Description . . . . .	121
17.102Test_AssertBasic_mod Module Reference . . . . .	122
17.102.1 Detailed Description . . . . .	122
17.103Test_AssertComplex_mod Module Reference . . . . .	123
17.103.1 Detailed Description . . . . .	124
17.104Test_AssertInteger_mod Module Reference . . . . .	124
17.104.1 Detailed Description . . . . .	124
17.105Test_AssertReal_mod Module Reference . . . . .	125
17.105.1 Detailed Description . . . . .	126
17.106Test_BasicOpenMP_mod Module Reference . . . . .	126
17.106.1 Detailed Description . . . . .	127
17.107Test_Exception_mod Module Reference . . . . .	127
17.107.1 Detailed Description . . . . .	127
17.108Test_FixtureTestCase_mod Module Reference . . . . .	128
17.108.1 Detailed Description . . . . .	128
17.109Test_LinearInterpolator_mod::Test_LinearInterpolator Type Reference . . . . .	129
17.110Test_LinearInterpolator_mod Module Reference . . . . .	129
17.111Test_MockCall_mod Module Reference . . . . .	129

17.111. Detailed Description	130
17.112 Test_MockRepository_mod Module Reference	130
17.113 Test_mod Module Reference	130
17.113. Detailed Description	131
17.114 Test_MpiContext_mod Module Reference	131
17.114. Detailed Description	131
17.115 Test_MpiException_mod Module Reference	132
17.115. Detailed Description	132
17.116 Test_MpiParameterizedTestCase_mod Module Reference	133
17.116. Detailed Description	133
17.117 Test_MpiTestCase_mod Module Reference	133
17.117. Detailed Description	134
17.118 Test_Parameters_mod::Test_Parameters Type Reference	135
17.119 Test_Parameters_mod Module Reference	135
17.120 Test_RestrictSphericalCoordinates_mod::Test_RestrictSpherical- Coordinates Type Reference	135
17.121 Test_RestrictSphericalCoordinates_mod Module Reference	136
17.122 Test_RobustRunner_mod Module Reference	136
17.122. Detailed Description	136
17.123 Test_SimpleTestCase_mod Module Reference	137
17.123. Detailed Description	137
17.124 Test_StringConversionUtilities_mod Module Reference	138
17.124. Detailed Description	138
17.125 Test_TestMethod_mod Module Reference	138
17.125. Detailed Description	139
17.126 Test_TestResult_mod Module Reference	139
17.126. Detailed Description	140
17.127 Test_TestSuite_mod Module Reference	140
17.127. Detailed Description	141
17.128 Test_UnixProcess_mod Module Reference	141
17.128. Detailed Description	141

17.129	<a href="#">Test_XmlPrinter_mod Module Reference</a>	142
17.129.1	<a href="#">Detailed Description</a>	142
17.130	<a href="#">TestA_mod Module Reference</a>	143
17.131	<a href="#">TestCase_mod Module Reference</a>	143
17.131.1	<a href="#">Detailed Description</a>	143
17.132	<a href="#">TestCaseA_mod::TestCaseA Type Reference</a>	144
17.133	<a href="#">TestCaseA_mod Module Reference</a>	144
17.134	<a href="#">TestCaseB_mod::TestCaseB Type Reference</a>	145
17.135	<a href="#">TestCaseB_mod Module Reference</a>	145
17.136	<a href="#">TestCaseC_mod::TestCaseC Type Reference</a>	146
17.137	<a href="#">TestCaseC_mod Module Reference</a>	147
17.138	<a href="#">TestFailure_mod Module Reference</a>	147
17.138.1	<a href="#">Detailed Description</a>	148
17.139	<a href="#">nodes::pre::pre_If::TestIfDirective Class Reference</a>	148
17.140	<a href="#">nodes::pre::interleavedp::TestInterleaved Class Reference</a>	149
17.141	<a href="#">TestListener_mod Module Reference</a>	149
17.141.1	<a href="#">Detailed Description</a>	150
17.142	<a href="#">TestMethod_mod Module Reference</a>	150
17.142.1	<a href="#">Detailed Description</a>	150
17.143	<a href="#">nodes::pre::parseArgs::TestParseArgs Class Reference</a>	151
17.144	<a href="#">parseDirectiveArgs::TestParseDirectiveArgs Class Reference</a>	151
17.145	<a href="#">TestParser::TestParseLine Class Reference</a>	152
17.145.1	<a href="#">Member Function/Subroutine Documentation</a>	152
17.145.1.1	<a href="#">testAtMpiTest</a>	152
17.145.1.2	<a href="#">testAtTest</a>	153
17.145.1.3	<a href="#">testAtTestFail</a>	153
17.145.1.4	<a href="#">testAtTestNoParens</a>	153
17.145.1.5	<a href="#">testAtTestSkipComment</a>	153
17.145.1.6	<a href="#">testMatchAtAfter</a>	153
17.145.1.7	<a href="#">testMatchAtAssertAssociated</a>	153
17.145.1.8	<a href="#">testMatchAtAssertAssociatedOverloaded1</a>	153

17.145.1.9	<a href="#">TestMatchAtAssertAssociatedOverloaded2</a>	153
17.145.1.10	<a href="#">TestMatchAtAssertEqual</a>	154
17.145.1.11	<a href="#">TestMatchAtAssertEqualUserDefined</a>	154
17.145.1.12	<a href="#">TestMatchAtAssertEqualUserDefinedWithMessage</a>	154
17.145.1.13	<a href="#">TestMatchAtAssertEquivalent</a>	154
17.145.1.14	<a href="#">TestMatchAtAssertNotassociated</a>	154
17.145.1.15	<a href="#">TestMatchAtAssertNotassociatedWith</a>	154
17.145.1.16	<a href="#">TestMatchAtAssertOther</a>	154
17.145.1.17	<a href="#">TestMatchAtAssertUnAssociated</a>	155
17.145.1.18	<a href="#">TestMatchAtAssertUnAssociatedWith</a>	155
17.145.1.19	<a href="#">TestMatchAtBefore</a>	155
17.145.1.20	<a href="#">TestMatchAtMpiAssert</a>	155
17.145.1.21	<a href="#">TestMatchAtSuite</a>	155
17.145.1.22	<a href="#">TestMatchAtTestCase</a>	155
17.145.1.23	<a href="#">TestParseArgsFirstRest</a>	155
17.145.1.24	<a href="#">TestParseArgsFirstSecondRest</a>	156
17.146	<a href="#">ParseBrackets::TestRejoinBracketed Class Reference</a>	156
17.147	<a href="#">mods::pre::pre_Repeat::TestRepeatDirective Class Reference</a>	156
17.148	<a href="#">TestResult_mod Module Reference</a>	156
17.148.1	<a href="#">Detailed Description</a>	157
17.149	<a href="#">TestRunner_mod Module Reference</a>	157
17.149.1	<a href="#">Detailed Description</a>	158
17.150	<a href="#">TestSuite_mod Module Reference</a>	158
17.150.1	<a href="#">Detailed Description</a>	159
17.151	<a href="#">ThrowFundamentalTypes_mod Module Reference</a>	159
17.151.1	<a href="#">Detailed Description</a>	159
17.152	<a href="#">UnixPipeInterfaces_mod Module Reference</a>	160
17.152.1	<a href="#">Detailed Description</a>	160
17.153	<a href="#">UnixProcess_mod Module Reference</a>	161
17.153.1	<a href="#">Detailed Description</a>	161
17.154	<a href="#">GenerateAssertsOnArrays::VECTOR_NORM Class Reference</a>	162

---

17.155	<a href="#">AbstractTestResult_mod::wasSuccessful Interface Reference</a>	162
17.156	<a href="#">WrapbeforeAfter Module Reference</a>	163
17.157	<a href="#">WrapMpiTestCaseB_mod Module Reference</a>	163
17.158	<a href="#">Wrapsimple Module Reference</a>	163
17.159	<a href="#">WrapTestA_mod Module Reference</a>	163
17.160	<a href="#">WrapTestCaseA_mod Module Reference</a>	164
17.161	<a href="#">WrapTestCaseB_mod Module Reference</a>	164
17.162	<a href="#">WrapTestCaseC_mod Module Reference</a>	164
17.163	<a href="#">XmlPrinter_mod Module Reference</a>	165
17.163	<a href="#">Detailed Description</a>	165





## Chapter 1

# pFUnit 3 - Documentation - Version

## 3.1.1 development

## 2015-1210-1447-48-EST MLR

Quick links to the [code](#) or the project's [SourceForge site](#).

### 1.1 Overview

[pFUnit](#) is a unit testing framework enabling JUnit-like testing of serial and MPI-parallel software written in Fortran. Initial support for OPENMP has been implemented. [pFUnit](#) makes use of modern Fortran programming techniques, including object oriented programming, offering a convenient, lightweight mechanism for Fortran developers to create and run software tests that specify the desired behavior for a given piece of code. The framework was originally created by developers from NASA and NGC TASC. The project is hosted at [sourceforge/projects/pfunit](#).

If you are using [pFUnit](#), please leave a note/topic at [Applications of pFUnit](#), or send a note to [Tom Clune](#), Ph.D., Advanced Software Technology Group, NASA Goddard Space Flight Center.

Please refer revisions and comments about the documentation to [Mike Rilee](#), Ph.D., Rilee Systems Technologies.

### 1.2 Contents

- [Installation](#)

– [Obtaining pFUnit](#)

- [Usage](#)
- [Development](#)
- [Feedback & Support](#)
- [FAQ and Tips](#)
- [Platform Specific Notes](#)
- [Acknowledgments](#)
- [Known Installations & Versions](#)
- [TODO](#)
- [The Preprocessor - pFUnitParser](#)
- [Revision Notes](#)

## 1.3 See Also

- [sourceforge/projects/pfunit](https://sourceforge.net/projects/pfunit)
- [NASA Modeling Guru](#)
- [JUnit.org](http://JUnit.org)

## 1.4 LICENSE

Rights of use for GSC-15,137-1 F-UNIT, also known as [pFUnit](#), are defined by the N-ASA Open Source Agreement (version 1.3). The LICENSE document may be found in the head directory of the [pFUnit](#) distribution.

## 1.5 Copyright

Copyright 2005,2013 United States Government as represented by the Administrator of the National Aeronautics and Space Administration. All Rights Reserved.

## Chapter 2

# Obtaining pFUnit

The best way to obtain **pFUnit** is to `clone pFUnit from the git repository` from SourceForge as follows.

```
# Read Only Access
git clone git://git.code.sf.net/p/pfunit/code pFUnit
```

This will create the directory **pFUnit** in the current working directory.

You may also visit the project page at SourceForge and download the source tarfile "pFUnit.tar.gz" there.

`http://sourceforge.net/projects/pfunit/` or `http://sourceforge.net/projects/pfunit/files/latest/download`

Extracting this tarfile via a command like

```
'$ tar xzf ./pFUnit.tar.gz'
```

will place the **pFUnit** files into the current working directory.

For other ways to acquire the code visit

`https://sourceforge.net/p/pfunit/code/ci/master/tree/`

or contact the **pFUnit** team.



## Chapter 3

# Installation

### 3.1 Installing pFUnit

Comentatry for the page.

- [Prerequisites](#)
- [Obtaining pFUnit](#)
- [Manifest - What's in the directory?](#)
- [Configuration](#)
- [Building pFUnit](#)
  - [Building pFUnit for testing serial codes \(Non-MPI\)](#)
  - [Building pFUnit for testing parallel codes \(MPI\)](#)
  - [OPENMP](#)
  - [Cleaning](#)
  - [Documentation](#)
- [Installation](#)

### 3.2 Prerequisites

The development work for [pFUnit](#) has mostly been carried out on a mixture of systems, including high-end computers, Apple Mac OSX, and linux-based systems. A preliminary Windows/CYGWIN port has been contributed by a user. Full use of the system depends on the following being available.

- Fortran 2003+ (Tested with Intel 14+, NAG 6.0, GCC 4.9.+, IBM's XLF, PGI 15.4)
- The Message Passing Interface (MPI)
- OpenMP
- GNU Make
- Python

Note: Recent changes have exposed a latent bug in GCC 4.8.2. The fix is available in the GCC 4.9 development branch and will also appear in GCC 4.8.3 when that is released. Users that require older versions of GCC should use [pFUnit 2.1.x](#).

[Doxygen](#) is used to generate documentation.

The system routinely undergoes regression testing with GNU, Intel, and NAG fortran compilers and OpenMPI.

### 3.3 Obtaining pFUnit

The best way to obtain [pFUnit](#) is to [clone pFUnit from the git repository](#) from SourceForge as follows.

```
# Read Only Access
git clone git://git.code.sf.net/p/pfunit/code pFUnit
```

This will create the directory [pFUnit](#) in the current working directory.

You may also visit the project page at SourceForge and download the source tarfile "pFUnit.tar.gz" there.

<http://sourceforge.net/projects/pfunit/> or <http://sourceforge.net/projects/pfunit/files/latest/download>

Extracting this tarfile via a command like

```
'$ tar xzf ./pFUnit.tar.gz'
```

will place the [pFUnit](#) files into the current working directory.

For other ways to acquire the code visit

<https://sourceforge.net/p/pfunit/code/ci/master/tree/>

or contact the [pFUnit](#) team.

### 3.4 Manifest - What's in the directory?

In the top level of the [pFUnit](#) distribution you will see the following files.

CMakeLists.txt - Initial support for cmake-based builds.

COPYRIGHT - Contains information pertaining to the use and distribution of [pFUnit](#).

Examples - Contains examples of how to use [pFUnit](#) once it is installed.

GNUmakefile - The top level makefile for building and installing [pFUnit](#).

LICENSE - The NASA Open Source Agreement for GSC-15,137-1 F-UNIT, also known as [pFUnit](#).

README-INSTALL - Basic documentation on [pFUnit](#) installation and use.

bin - Executables used to construct and perform unit tests.

include - Files to be included into makefiles or source, including use code.

source - Source code and scripts of the [pFUnit](#) library and framework.

tests - Source code for unit testing [pFUnit](#) itself.

tools - Tools used to help develop, build, and install [pFUnit](#).

VERSION - Contains a string describing the current version of the framework.

## 3.5 Configuration

Little needs to be done to configure [pFUnit](#) for the build, however there are several environment variables on which the package depends.

'F90\_VENDOR' - is set to include the correct makefile in /include, i.e. GNU, Intel, NAG, or PGI. Case insensitive file systems may cause some confusion from time-to-time.

'F90' - is set to the Fortran compiler being used: e.g. ifort for Intel, gfortran for GNU.

'COMPILER' - is set according to 'F90\_VENDOR' and is automatically set in the top level makefile.

For MPI-based unit testing, your setup may require the following as well.

'MPIF90'

```
$ export MPIF90=mpif90
```

As a convenience for working with multiple MPI configurations, you may also set the following.

'MPIRUN'

```
$ export MPIRUN=/some.path/mpiexec
```

PFUNIT\_MAX\_ARRAY\_RANK

'PFUNIT\_MAX\_ARRAY\_RANK' - controls the maximum size of the arrays asserts are defined over. If PFUNIT\_MAX\_ARRAY\_RANK is not set, the default is 5 and [pFUnit](#)'s

assertions will be able to handle arrays up to rank 5, i.e. `A(:, :, :, :)`. `PFUNIT_MAX_ARRAY_RANK` and `MAX_RANK` do not refer to MPI ranks (process id within a group). Example:

```
$ export PFUNIT_MAX_ARRAY_RANK=5
```

'`PFUNIT_MAX_RANK`' is a deprecated way to set maximum rank and is to be removed in version 4.

'`DOXYGEN`' - To generate documentation, set `DOXYGEN` to the desired executable. NOTE: Doxygen Version 1.8.5 does not respect CamelCase names from Fortran source code by currently converting all to lowercase. It does this to get HTML links correct for references in the source code that also do not respect the CamelCase convention. The Fortran standard specifies case insensitivity. Doxygen 1.7.x seems to better respect CamelCase.

```
$ export DOXYGEN=/opt/local/share/doxygen/doxygen-1.7.6/bin/doxygen
```

## 3.6 Building pFUnit

### 3.6.1 Building pFUnit for testing serial codes (Non-MPI)

1. Change to the directory into which `pFUnit` has been placed. 2. Set the environment variables (for example in bash):

```
$ export F90=gfortran-mp-4.8
$ export F90_VENDOR=GNU
```

3. To build `pFUnit` for unit testing of serial codes, execute `make`. The unit tests for `pFUnit` itself will run automatically.

```
$ make tests
```

3.1 Occasionally on the first run through, one will get a spurious (runtime) error, for example in the unix process component.

Re-execute "`make tests`" to check again.

4. At this point the `pFUnit` object library is in the source directory, along with a large number of Fortran module files.

### 3.6.2 Building pFUnit for testing parallel codes (MPI)

To build `pFUnit` for unit testing MPI-based codes, be sure that the environment is properly set up for the MPI implementation you are using. Depending on your local environment, you may need execute the build within a batch or other job queuing system, e.g. an interactive batch job under PBS. The steps for building `pFUnit` start out the same as for



the serial case above, but add `MPI=YES` to the environment to switch on MPI support. The MPI-based unit tests for `pFUnit` itself will run automatically. Again, occasionally a spurious (runtime) error may appear on the first execution.

3. Execute make as follows.

```
$ make tests MPI=YES
```

4. At this point an MPI-enabled `pFUnit` object library is in the source directory, along with a large number of Fortran module files.

Also, one may get some harmless "no symbols" warnings when the `pFUnit` library is constructed.

### 3.6.3 OPENMP

Initial (limited) support for OPENMP has been implemented. At this writing, a basic functionality is available.

The process for building `pFUnit` for testing OPENMP-based codes is similar to that for other paradigms.

3. To compile for OPENMP support execute make as follows.

```
$ make tests OPENMP=YES
```

4. At this point the OPENMP-enabled `pFUnit` is ready to be installed.

### 3.6.4 Cleaning

To clean the `pFUnit` build directory for the space or to rebuild there are two options.

1. Make clean to remove object files and other intermediate products.

```
$ make clean
```

2. Make distclean to remove libraries and other more final products.

```
$ make distclean
```

3. Some directories support a 'make src\_clean' to remove intermediate products in subdirectories.

### 3.6.5 Documentation

A start at documentation for `pFUnit` is in the documentation directory. `Doxygen` is our primary documentation tool. To make the documentation, which will be generated in the

documentation directory, please invoke the following from the top level of your [pFUnit](#) distribution.

```
$ make documentation
```

Or to make a reference manual.

```
$ make documentation/pFUnit2-ReferenceManual.pdf
```

To select a specific version of Doxygen, please set the DOXYGEN environment variable as in [Configuration](#). You may wish to do this if your code uses CamelCase names as current versions of Doxygen (1.8.5) do not respect this convention for Fortran.

### 3.6.6 CMAKE

Initial support for CMAKE has been implemented. At this writing, a basic functionality is available.

3. The process for building [pFUnit](#) using cmake is as follows. In the top directory of the distribution make a new directory to support the build, then change to that directory and run cmake (pointing back to the source) to generate the required makefiles.

```
$ mkdir build
$ cd build
$ # e.g. cmake -DMPI=YES -DOPENMP=NO -DINSTALL_PATH=<A path> <path to source>
$ cmake -DMPI=NO ..
$ make tests
```

One may also set the environment variable PFUNIT instead of setting INSTALL\_PATH on the cmake command line as given above.

If your MPI installation does not provide mpirun, you may try to set -DMPI\_USE\_MPIEXEC=YES to tell CMake to use its FindMPI function to find out how to execute the tests.

4. If the build is successful, then at this point make install should work.

## 3.7 Installation

### 3.7.1 Installation - Serial

To install [pFUnit](#) for regular use, set INSTALL\_DIR to the location in which to place [pFUnit](#). This can be done on the make command line. For example, after compiling [pFUnit](#) for serial use (MPI absent or MPI=NO), please try.

```
$ # In the top of the pFUnit build directory.
$ make install INSTALL_DIR=/opt/pfunit/pfunit-serial
```

Note: you may need special privileges to install in some locations, e.g. via sudo.

To test the installation set PFUNIT to INSTALL\_DIR, then change the working directory to Examples in [pFUnit](#) distribution and execute "make," which will run a number of examples. These include some expected (intentional) failures.

```
$ # In the top pFUnit build directory...
$ export PFUNIT=/opt/pfunit/pfunit-serial
$ cd Examples
$ make
```

### 3.7.2 Installation - MPI

For installing an MPI-enabled [pFUnit](#) library, change to the top of the distribution and execute make with MPI=YES. You may need to "make distclean" first. After compilation and [pFUnit](#) passes its self-tests, then installation proceeds as for the serial case above.

```
$ make install INSTALL_DIR=/opt/pfunit/pfunit-parallel
```

To test, set PFUNIT and go into Examples/MPI\_Halo directory.

```
$ # In the top pFUnit build directory...
$ export PFUNIT=/opt/pfunit/pfunit-parallel
$ # The variable MPIF90 must be set to the appropriate build script.
$ export MPIF90=mpif90
$ cd Examples/MPI_Halo
$ make
```

This will compile and run a set of parallel examples that includes intentional failures. To run all of the examples try executing "make MPI=YES" in the Examples directory.

### 3.7.3 Installation - OPENMP

At this time the OPENMP version of [pFUnit](#) can be installed in the same way as for the serial or MPI-parallel codes. OPENMP support, tests, and examples are limited as of this writing.

### 3.7.4 Installation - DEFAULT DIRECTORY

If INSTALL\_DIR is not set, "make install" will attempt to install [pFUnit](#) into the top build directory. This will create directories such as lib and mod in the top level of the build directory and will overwrite the include/base.mk with include/base-install.mk. If this is not desired, then "make develop" will put back the original base.mk, which is the file to be used for development and building [pFUnit](#). In general, we recommend installing to a directory that is not also the build directory.



## Chapter 4

# Usage

- [Usage - Configuration](#)
- [Usage - Hello World](#)
- [Usage - Preprocessor](#)
- [Compiling and Executing The Test](#)

### 4.1 Usage

#### 4.1.1 Usage - Configuration

For regular use, after installation, the same compiler/MPI development configuration that was used to build [pFUnit](#) should be used. Once the environment variables and paths associated with the environment are set, to configure [pFUnit](#), please set the following.

'PFUNIT' - set to the directory into which [pFUnit](#) was installed.

'F90\_VENDOR' - set to Intel, GNU, NAG, or PGI accordingly.

#### 4.1.2 Usage - Hello World

For an example of a simple usage of [pFUnit](#), see Examples/Simple/tests.

The simplest way to write a test is to write a preprocessor input file (extension ".pf"), which is a Fortran free format file with preprocessor directives added. An example from "helloWorld.pf" follows.

```
! from helloWorld.pf
@test
```

```

subroutine testHelloWorld()
  use pfunit_mod
  implicit none
  @assertEqual("Hello World!", "Hello World!")
end subroutine testHelloWorld

```

One then instructs the preprocessor to construct a suite to execute these tests via the "testSuites.inc" file as follows.

```

! from testSuites.inc
ADD_TEST_SUITE(helloWorld_suite)

```

At this point, one can invoke the preprocessor to generate a Fortran file that when compiled and linked with [pFUnit](#) will execute the tests. For more information please see [The Preprocessor - pFUnitParser](#) or try out the examples in Example/Simple.

## 4.2 Usage - Preprocessor

Please see [The Preprocessor - pFUnitParser](#).

## 4.3 Compiling and Executing The Test

An example of a GNU make rule for the final step of compiling a test follows.

```

# This step presumes "include $(PFUNIT)/include/base.mk" earlier in the
# makefile.
tests.x: testSuites.inc myTests.pf
  $(F90) -o $@ -I$(PFUNIT)/mod -I$(PFUNIT)/include \
    $(PFUNIT)/include/driver.F90 \
    ./*$(OBJ_EXT) $(LIBS) $(FFLAGS)

```

To execute the tests, one invokes "./tests.x" with the appropriate command line options (see below).

In some cases, since include/driver.F90 is "implicit none," it may be necessary to insert a "use" clause to identify external suite-wide fixture code to the compiler. As a convenience, the CPP macro PFUNIT\_EXTRA\_USAGE can be set to a module of fixture code via a compiler command line argument turning on a "use PFUNIT\_EXTRA\_USAGE" line at the beginning of include/driver.F90.

### 4.3.1 - Compiling and Executing the Tests (MPI PARALLEL)

One invokes MPI-based parallel tests according to the MPI framework being used. For example:

```
$ mpirun -np 4 tests.x
```

### 4.3.2 Command Line Options

The executable test program provides several command line options, when "include/driver.F90" is used, as it is automatically when using the PFUNIT preprocessor.

-v or -verbose	Verbose execution.
-d or -debug	Provide debugging information.
-h	Print help message.
-o <outputfile>	Direct <a href="#">pFUnit</a> messages to a file.
-robust	Use the robust runner. Runs tests as processes so failures do not halt testing.
-max-timeout-duration <duration> Limit detection time for robust runner.	Use the subset runner, which runs a subset of the tests in a suite.
-max-launch-duration <duration> Limit detection time for robust runner.	
-skip <number of tests to skip>	
-xml <xmlfile>	Generate XML output in JUnit compatible format, write it to given file. This XML output can be used in integration with e.g. Jenkins. To ensure the XML file is written correctly, it is recommended to also use the -robust flag.
-name <name>	Give the set of tests an identifying name, which is used in the XML output.

An example from Examples/Robust:

```
$ ./tests.x -robust
```

### 4.3.3 XML output

To output JUnit XML, execute tests with the -xml flag:

```
$ ./tests.x -robust -xml test.xml -name my_suite_name
```

This creates a file named test.xml. As an example, the output may look like this:

```
<testsuite name="my_suite_name" errors="1" failures="1" tests="3" time="2.1020"
>
<testcase name="test_math_suite.test_addition"/>
<testcase name="test_math_suite.test_division">
<error message="Location: [[unknown location]], RUNTIME-ERROR: terminated
during execution "/>
</testcase>
<testcase name="test_other_suite.test_foo">
```

---

```
<failure message="Location: [ test_other.pf:24],  "/>
</testcase>
</testsuite>
```

Output explained: The test suite took 2.1020 seconds to execute. One test (test\_addition) succeeded, one (test\_division) crashed for some reason, and one test (test\_foo) failed at line 24 of test\_other.pf.



## Chapter 5

# Development

Generally [pFUnit](#) development is performed in the build directory structure. Care should be taken to make clean or distclean in between configuration changes. As stated in - [Installation](#), it is best to set `INSTALL_DIR` and "make install" [pFUnit](#) to another directory that can be placed in a user's paths.



## Chapter 6

# Feedback & Support

- [Feedback](#)
- [Support](#)

### 6.1 Feedback

Feedback is welcome, please use the facilities at [sourceforge/projects/pfunit](#) to share your views.

Open a [ticket](#) for bugs, features, and patch recommendations.

If you use [pFUnit](#), please let us know by leaving a note in our [Applications of pFUnit](#) forum, or email [Tom Clune](#), Ph.D., NASA Goddard Space Flight Center. - Letting us know about your application helps us seek support for [pFUnit](#)'s continued development and improvement.

### 6.2 Support

Please open a [ticket](#) for bugs, features, and patch recommendations. For longer term needs or considerations, please visit our [discussion forums](#) or contact - [Tom Clune](#), Ph.D., NASA Goddard Space Flight Center.

You may also find some help at [FAQ and Tips](#).

[pFUnit](#) supports the software development of several weather and climate simulations efforts. We constantly seek to improve and correct [pFUnit](#) for our users' benefit, granting priority to the needs of our major users. Please share with us information about your application on our [Applications of pFUnit](#) forum.



## Chapter 7

# FAQ and Tips

- [FAQ](#)
  - [Zero Tests Run](#)
  - [Some Tests Are Not Running](#)
  - [Intel Fortran Version 13: -DINTEL\\_13](#)
  - [Segmentation Faults and Odd Link Errors](#)
- [Tips](#)
  - [Environment Modules](#)
  - [Compile Time Errors](#)
  - [Intermediate files used by pFUnit](#)
  - [Ignoring whitespace differences in assertions on strings.](#)

## 7.1 FAQ

### 7.1.1 Zero Tests Run

*Symptom:* The system under test compiles and runs fine, but reports zero tests run.

*Solutions:*

- There is no `testSuites.inc` file. Please add a `testSuites.inc` that lists the suites to add via `ADD_TEST_SUITE ( the_suite_to_add )`, one to a line.
- There is no `-DUSE_MPI` passed to the compiler during the build. Please add to the compiler invocation. Please see [Some Tests Are Not Running](#).

### 7.1.2 Some Tests Are Not Running

*Symptom:* The system under test compiles and runs fine, but reports that some tests don't run.

*Solutions:*

- There is no `-DUSE_MPI` passed to the compiler during the build. Please add as in the following example.

```
% $PFUNIT/bin/pFUnitParser.py test_pio.pf test_pio.F90
% mpif90 -DUSE_MPI $PFUNIT/include/driver.F90 \
%      -I$PFUNIT/mod -L$PFUNIT/lib -lpfunit test_pio.F90

% mpirun -np 8 ./a.out

.
Time:          0.004 seconds

OK
```

### 7.1.3 Intel Fortran Version 13: -DINTEL\_13

Using version 13 is deprecated. We have encountered problems using version 13, which we believe may be due to subtle compiler bugs. We strongly recommend upgrading to the latest version possible.

To make [pFUnit](#) work with Intel Fortran Version 13, please ensure that `-DINTEL_13` is passed to the compiler when building or using [pFUnit](#). In the build process for [pFUnit](#), this is added to the make variables `CPPFLAGS` and `FPPFLAGS`.

### 7.1.4 Segmentation Faults and Odd Link Errors

Q. [pFUnit](#) fails to build or now leads to segmentation faults. Did something change?

A. One cause for failure to build or odd runtime segmentation faults is when we change compiler configurations and some object or library files are left over from a previous environment. This might be hard to spot, for example, during compiler upgrades. - Switching from one compiler to another, e.g. from Intel to GNU, is more likely to generate link-time errors if old code is still around. A few items to check follow.

- Execute `make distclean` or remove objects (or their directories if using CMAKE) associated with previous builds.
- Ensure [pFUnit](#) and user applications are compiled using compatible (or the same) compilers.
- Ensure the environment variable `PFUNIT` is set to the appropriate install directory.

Finally, it is quite possible that a bug has been uncovered. Please contact the development team or open a [bug ticket](#).

## 7.2 Tips

### 7.2.1 Environment Modules

Though not strictly required, the Environment Modules package can be a convenient way to package, maintain, and switch between environments. This can be particularly important for [pFUnit](#), which must be built using the same tool suite being used for development, e.g. compilers, linkers, etc. [To do: A sample [pFUnit](#) modulefile is provided in the OTHER directory.]

### 7.2.2 Compile Time Errors

Compile time errors like "'include [...]include/.mk" not found' likely signify that you are not executing make in the top level directory during a build. Alternatively, during regular usage after installation, PFUNIT has not been set.

During building, if you wish to compile in a subdirectory within the [pFUnit](#) hierarchy, please try setting the COMPILER environment variable on the make command line. For example:

```
$ make all COMPILER=Intel
```

### 7.2.3 Intermediate files used by pFUnit

If you wish to see the intermediate files, use the target .PRECIOUS in the makefile to keep them from being deleted. For example:

```
# In GNUmakefile
.PRECIOUS: %_cpp.F90
```

### 7.2.4 Ignoring whitespace differences in assertions on strings.

Several options exist for how to compare strings with assertEquals.

```
call assertEquals(expectedString, foundString, &
    & whitespace=IGNORE_DIFFERENCES )
```

#### WhitespaceOptions:

- **IGNORE\_DIFFERENCES** ignores whitespace differences (number and value).
- **IGNORE\_ALL** strictly ignores all whitespace (spaces & tabs).
- **TRIM\_ALL** strictly ignores leading and trailing whitespace.
- **KEEP\_ALL** keeps all whitespace as significant, even discriminating between tabs and spaces.

Example usages can be seen in `tests/Test_AssertBasic.F90` or `Examples/Simple/tests/helloWorld.pf`.



## Chapter 8

# Platform Specific Notes

### 8.1 Mac OSX

The MacPorts package management system is a convenient way to install and maintain many packages, including gcc which includes gfortran.

### 8.2 Windows/CYGWIN

User contributed code for Windows/CYGWIN has been added, but is currently not tested and supported by the [pFUnit](#) team. At this writing, 2013-1031, serial Examples and MPI are not known to be supported. Please contact us if you wish to either contribute or otherwise discuss this port.

### 8.3 Intel Fortran Version 13: -DINTEL\_13

To make [pFUnit](#) work with Intel Fortran Version 13, please ensure that `-DINTEL_13` is passed to the compiler when building or using [pFUnit](#). In the build process for [pFUnit](#), this is added to the make variables CPPFLAGS and FPPFLAGS.



## Chapter 9

# Acknowledgments

Thanks to the following for their review and comments: B. Van Aartsen, T. Clune.

Windows/CYGWIN contributions from E. Lezar.

PGI port contributions from M. Leair (PG Group).

Other acknowledgments: S.P. Santos (NCAR), M. Hambley (UK Met Office), J. Krishna (ANL).

The design of **pFUnit** is strongly influenced by **JUnit**.

Initial **pFUnit** 2 documentation by Michael Rilee (Rilee Systems Technologies).



## Chapter 10

# Known Installations & Versions

master - The current release.

development - The cutting edge of [pFUnit](#) development.

mock\_services - Experimental support for mocking.

pfunit\_2.1.0 - A feature freeze prior to a major upgrade of the preprocessor.



## Chapter 11

### TODO

- Make other directory.
- Make Environment Modules example in other directory.





## Chapter 12

# The Preprocessor - pFUnitParser

Overview of Preprocessor (pFUnitParser.py)

- [Using The Preprocessor](#)
  - [Configuration - testSuites.inc](#)
  - [Invocation](#)
  - [Command Line Options](#)
  - [Preprocessor Input File \(.pf\)](#)
  - [Directives](#)
    - \* [@Test](#)
    - \* [@MPITest](#)
    - \* [@Assert](#) (or [Preprocessor Directives](#))
    - \* [@Parameters](#)
    - \* [@TestCase](#)

//

### 12.1 Using The Preprocessor

How to write tests using the ".pf" files. We expect this to be the main way people write pFUnit-based tests. Please see the Examples directory for a wide range of examples. The .pf files themselves are generally to be found in an example's "tests" subdirectory.

### 12.1.1 Configuration - testSuites.inc

The include file "testSuites.inc" tells the preprocessor to generate code for TestSuites listed therein. The suite names are based on the TestCases provided in the preprocessor input file or the name of the preprocessor input file (.pf) itself. For example, if no module is defined in a .pf file, i.e. the preprocessor will define the module, one can set up a "testSuites.inc" as follows.

```
! To load "exampleTestsNoModule.pf".
ADD_TEST_SUITE(exampleTestsNoModule_suite)
```

For a .pf file that contains a module associated with a test suite the syntax is as follows.

```
! To load "exampleTests.pf" implementing the module exampleTests_mod.
ADD_TEST_SUITE(exampleTests_mod_suite)
```

### 12.1.2 Invocation

To run the preprocessor on a preprocessor input file "exampleTests.pf", invoke:

```
$ ${PFUNIT}/bin/pFUnitParser.py exampleTests.pf exampleTests.F90
```

A convenient GNUmakefile rule is as follows.

```
%.F90: %.pf
    ${PFUNIT}/bin/pFUnitParser.py $< $@
```

### 12.1.3 Preprocessor Input File (.pf)

The preprocessor input file is a Fortran free format file that contains subroutines, including those implementing the suite of tests, or a module with the tests, TestCases, and support for parameters. The preprocessor reads and parses this file producing a fortran file implementing the tests, automating some boilerplate code. Embedded "@" directives inform the preprocessor about information needed to generate the test suite. If the .pf file does not implement a module providing a test suite, the preprocessor will use the name of .pf file referred to by "testSuites.inc". Currently only one test suite per .pf file is allowed, a limitation of the current implementation of the parser.

Many example .pf files may be found in the examples' "tests" subdirectories in the - Examples directory.

Below we present the most commonly used directives first, but in a .pf file using all of these capabilities, the most common order is as follows.

- [@Parameters](#)
- [@TestCase](#)
- [@Test](#) or [@MPITest](#)
- [@Assert](#)

### 12.1.4 Directives

Preprocessor "@" directives, which in keeping with Fortran style are not case sensitive, instruct the preprocessor how to interpret parts of the code relevant to the generation of the test suite. The most important directives follow.

#### 12.1.4.1 @Test

This directive is used to indicate a test routine to the preprocessor, which then includes it in the test suite. There may be multiple tests in the .pf file, each annotated by the @Test directive.

@Test also supports MPI-parallel tests (see [@MPITest](#) ).

An example, from Examples/Fixture:

```
@Test
  subroutine testBracketInterior(this)
    class (Test_LinearInterpolator), intent(inout) :: this
    @assertEqual([3,4], this%interpolator%getBracket(at=4.))
  end subroutine testBracketInterior

@Test
  subroutine testInterpolateAtNode(this)
    class (Test_LinearInterpolator), intent(inout) :: this
    @assertEqual(2., this%interpolator%interpolate(at=3.))
  end subroutine testInterpolateAtNode
```

#### 12.1.4.2 @MPITest

[@MPITest](#) is deprecated as @Test now handles this case.

This directive indicates an MPI parallel test to the preprocessor, which then includes it in an MPI enabled test suite. The directive takes a single argument, the requested number of MPI processes to run. The syntax, exemplified by one of the tests from Examples/MPI\_Halo:

```
@Test( npes=[1,2,3])
subroutine testHaloInterior(this)
  use Halo_mod
  use pfunit_mod
  implicit none
  class (MpiTestMethod) :: this

  integer, parameter :: N = 2
  real :: a(N,0:N+1)
  integer :: p

  p = this%getProcessRank()
  a(:,1:N) = p
```

```
a(:,0) = -1
a(:,N+1) = -1

call haloFill(a, this%getMpiCommunicator())

@assertEqual(real(p), a(1,1))
@assertEqual(real(p), a(2,1))
@assertEqual(real(p), a(1,2))
@assertEqual(real(p), a(2,2))

end subroutine testHaloInterior
```

#### 12.1.4.3 @Assert

The @Assert directives are expanded into calls to similarly named [pFUnit](#) library routines. The syntax for the directives follows the pattern for @assertEqual below.

```
@assertEqual(expected,found,'An identifying or explanatory message.')
```

The preprocessor will automatically add information about source location (file & line number) to the call emitted to the test suite code. It also adds the check for exceptions.

For more information about @assert directives, please refer to the following.

- [@assertEqual](#)
- [@assertTrue](#)
- [@assertEqualUserDefined](#)
- [@assertFalse](#)
- [@assertLessThan](#)
- [@assertLessThanOrEqual](#)
- [@assertGreaterThan](#)
- [@assertGreaterThanOrEqual](#)
- [@assertIsMemberOf](#)
- [@assertContains](#)
- [@assertAny](#)
- [@assertAll](#)
- [@assertNotAll](#)
- [@assertNone](#)

- [@assertIsPermutationOf](#)
- [@assertExceptionRaised](#)
- [@assertSameShape](#)
- [@assertIsNaN](#)
- [@assertIsFinite](#)
- [@assertAssociated](#)
- [@assertNotAssociated](#)
- [@assertEquivalent](#)

#### 12.1.4.4 @Parameters

The `@Parameter` directive indicates the declaration of the parameterized type used to generate the iteration over the multiple parameter values. It also identifies the names of the parameters to be iterated over. The preprocessor extracts type information from the declaration of the parameter type collection that immediately follows the directive. This directive will set up the iteration. To define the parameter values per iteration the `getParameters` method of the abstract `ParameterizedTest` must be implemented. For example:

```
@Parameters = [p1,p2]
type, extends(AbstractTestParameter) :: exampleCase
  integer :: i
  real :: x
end type exampleCase
```

#### 12.1.4.5 @TestCase

This directive identifies to the preprocessor the `TestCase` declaration. The type declared at this point extends `TestCase` (or its extension), which includes setting methods such as the following: `setUp`, `tearDown`, `runMethod`, `userMethod`. For the extension `MPITestCase`, as with `ParameterizedTestCase`, you have the option (requirement if parameters are used) to set `getParameters` and `getParameterString`. For example:

```
@TestCase
type, extends(MPITestCase) :: Test_Parameters
  integer :: p1, p2
  procedure(runMethod), pointer :: userMethod => null()
contains
  procedure, nopass :: getParameters
  procedure :: getParameterString => getParameterString_
  procedure :: runMethod
end type Test_Parameters
```



## Chapter 13

# @Assert Preprocessor Directives

- [@assertEqual](#)
- [@assertTrue](#)
- [@assertEqualUserDefined](#)
- [@assertFalse](#)
- [@assertLessThan](#)
- [@assertLessThanOrEqual](#)
- [@assertGreaterThan](#)
- [@assertGreaterThanOrEqual](#)
- [@assertIsMemberOf](#)
- [@assertContains](#)
- [@assertAny](#)
- [@assertAll](#)
- [@assertNotAll](#)
- [@assertNone](#)
- [@assertIsPermutationOf](#)
- [@assertExceptionRaised](#)
- [@assertSameShape](#)
- [@assertIsNaN](#)

- [@assertIsFinite](#)
- [@assertAssociated](#)
- [@assertNotAssociated](#)
- [@assertEquivalent](#)

## 13.1 @Assert Preprocessor Directives

### 13.1.1 @assertEqual

### 13.1.2 @assertTrue

### 13.1.3 @assertEqualUserDefined

A convenience function that allows a user to write

```
@assertEqualUserDefined(a,b)
```

instead of

```
call assertTrue(a==b,...)
```

while a more instructive error message about the arguments and source code position is added by the preprocessor. The user may add an error message as follows.

```
@assertEqualUserDefined(a,b,message='a and b should be equal here.')
```

### 13.1.4 @assertFalse

### 13.1.5 @assertLessThan

### 13.1.6 @assertLessThanOrEqual

### 13.1.7 @assertGreaterThan

### 13.1.8 @assertGreaterThanOrEqual

### 13.1.9 @assertIsMemberOf

### 13.1.10 @assertContains



13.1.11 @assertAny

13.1.12 @assertAll

13.1.13 @assertNotAll

13.1.14 @assertNone

13.1.15 @assertIsPermutationOf

13.1.16 @assertExceptionRaised

13.1.17 @assertSameShape

13.1.18 @assertIsNaN

13.1.19 @assertIsFinite

13.1.20 @assertAssociated

maps to a call to the logical intrinsic function associated.

```
@assertAssociated(a)
```

becomes

```
call assertTrue(associated(a))
```

The directive also handles the two-argument pointer-target case.

```
@assertAssociated(pointer,target)
```

becomes

```
call assertTrue(associated(pointer,target))
```

neglecting message and source location information.

A message may be passed as follows.

```
@assertAssociated(a,message="A message.")
```

```
@assertAssociated(pointer,target,message="A message.")
```

### 13.1.21 @assertNotAssociated

This directive is the same as `assertAssociated`, except that it maps to `assertFalse`. This directive was originally released as `assertUnAssociated`.

### 13.1.22 @assertEquivalent

This directive compares two logical values and throws an exception annotated with some useful information. We get a special directive for this one because comparing logicals uses the `.eqv.` infix operator in standard Fortran. The arguments `a` and `b` below may be 1d arrays.

```
@assertEquivalent (a,b)
```

becomes

```
call assertTrue(a.eqv.b)
```

neglecting the specification of message and source location information.

## Chapter 14

### Revision Notes

- 2015-0508 Some PGI workarounds removed for PGI 15.4. MLR
- 2015-0320 PGI port workarounds, including examples. 3.1. MLR
- 2014-1211 Minor updates for 3.0.2. MLR
- 2014-1110, 2014-1031 Minor edits. MLR
- 2014-0915 Minor updates for 3.0.1. MLR
- 2014-0404 Updated for release of 3.0. TLC
- 2014-0131, 2014-0205. Updated. MLR
- 2013-1227. First note of OPENMP additions by T. Clune. MLR.
- 2013-1212. Initial draft of Doxygen version. MLR
- 2013-1107. Minor edits. MLR
- 2013-1031. Added user contributed code for Windows/CYGWIN & IBM's XLF. MLR
- 2013-0830-1359. Minor corrections and added MPIF90 to 6.2. MLR
- 2013-0806-1345. Corrected git reference. Was using old URL. MLR
- 2013-0805. Initial draft. MLR



## Chapter 15

# Data Type Index

### 15.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

AbstractTestParameter_mod . . . . .	57
AbstractTestResult_mod . . . . .	57
pUnitParser::Action . . . . .	58
pUnitParser::AtAfter . . . . .	63
pUnitParser::AtAssert . . . . .	63
pUnitParser::AtAssertAssociated . . . . .	64
pUnitParser::AtAssertEqualUserDefined . . . . .	65
pUnitParser::AtAssertEquivalent . . . . .	66
pUnitParser::AtAssertNotAssociated . . . . .	66
pUnitParser::AtBefore . . . . .	67
pUnitParser::AtBegin . . . . .	68
pUnitParser::AtMpiAssert . . . . .	68
pUnitParser::AtSuite . . . . .	69
pUnitParser::AtTest . . . . .	70
pUnitParser::AtMpiTest . . . . .	69
pUnitParser::AtTestCase . . . . .	71
pUnitParser::AtTestParameter . . . . .	71
add_mod . . . . .	59
addComplex_mod . . . . .	59
CodeUtilities::ArrayDescription . . . . .	59
Assert_mod . . . . .	60
AssertBasic_mod . . . . .	60
GenerateAssertsOnArrays::AssertRealArrayArgument . . . . .	62
TestCaseB_mod::B_Parameter . . . . .	72
BaseTestRunner_mod . . . . .	72

BeforeAfter_mod . . . . .	73
BrokenSetUpCase_mod . . . . .	74
BrokenTestCase_mod . . . . .	74
TestCaseC_mod::C_Parameter . . . . .	75
Cases_mod . . . . .	76
Test_mod::countTestCases . . . . .	77
mods::pre::pre2::dataString . . . . .	78
DebugListener_mod . . . . .	78
CodeUtilities::declaration . . . . .	79
DynamicTestCase_mod . . . . .	80
Exception_mod . . . . .	81
Expectation_mod . . . . .	81
Fixture_mod . . . . .	82
FixtureTestCase_mod . . . . .	82
CodeUtilities::fortranSubroutineSignature . . . . .	83
AbstractTestResult_mod::getErrors . . . . .	84
Test_mod::getName . . . . .	84
AbstractTestResult_mod::getSuccesses . . . . .	84
Halo_mod . . . . .	84
CodeUtilities::implementation . . . . .	85
CodeUtilities::interfaceBlock . . . . .	85
mods::pre::pre_if::interval . . . . .	86
Test_RestrictSphericalCoordinates_mod::LatLonCase . . . . .	87
LinearInterpolator_mod . . . . .	87
MakeInfinity_mod . . . . .	88
MakeNaN_mod . . . . .	88
Mock_mod . . . . .	89
MockCall_mod . . . . .	90
MockListener_mod . . . . .	91
MockRepository_mod . . . . .	92
MockSUT_mod . . . . .	93
testParser::MockWriter . . . . .	93
CodeUtilities::module . . . . .	94
MpiContext_mod . . . . .	94
MpiStubs_mod . . . . .	95
MpiTestCase_mod . . . . .	96
MpiTestCaseB_mod::MpiTestCaseB . . . . .	97
MpiTestCaseB_mod . . . . .	97
MpiTestMethod_mod . . . . .	98
MpiTestParameter_mod . . . . .	99
pFUnitParser::MyError . . . . .	99
Cases_mod::MyParamType . . . . .	99
Cases_mod::MyTestCase . . . . .	100
TestCaseC_mod::newC_Parameter . . . . .	100
node_mod . . . . .	100
ParallelContext_mod . . . . .	101

ParallelException_mod . . . . .	101
ParameterizedTestCase_mod . . . . .	102
Params_mod . . . . .	103
pFUnitParser::Parser . . . . .	104
testParser::MockParser . . . . .	91
Test_Parameters_mod::peCase . . . . .	105
pFUnit . . . . .	106
pFUnit_mod . . . . .	106
PrivateException_mod . . . . .	107
mods::pre::pre2::procDirective . . . . .	108
mods::pre::pre_If::IfDirective . . . . .	84
mods::pre::pre_Repeat::RepeatDirective . . . . .	110
RemoteProxyTestCase_mod . . . . .	109
ResultPrinter_mod . . . . .	110
RobustRunner_mod . . . . .	111
robustTestSuite_mod . . . . .	112
CodeUtilities::routineUnit . . . . .	113
GenerateAssertsOnArrays::constraintASSERT . . . . .	76
GenerateAssertsOnArrays::IsWithinTolerance . . . . .	86
GenerateAssertsOnArrays::VECTOR_NORM . . . . .	162
SerialContext_mod . . . . .	114
SimpleTestCase_mod . . . . .	115
SourceLocation_mod . . . . .	116
SphericalCoordinates_mod . . . . .	117
TestListener_mod::startTest . . . . .	117
StringConversionUtilities_mod . . . . .	117
SubsetRunner_mod . . . . .	118
SurrogateTestCase_mod . . . . .	119
SUT_mod . . . . .	120
Test_mod::Test . . . . .	121
Test_Assert_mod . . . . .	121
Test_AssertBasic_mod . . . . .	122
Test_AssertComplex_mod . . . . .	123
Test_AssertInteger_mod . . . . .	124
Test_AssertReal_mod . . . . .	125
Test_BasicOpenMP_mod . . . . .	126
Test_Exception_mod . . . . .	127
Test_FixtureTestCase_mod . . . . .	128
Test_LinearInterpolator_mod::Test_LinearInterpolator . . . . .	129
Test_LinearInterpolator_mod . . . . .	129
Test_MockCall_mod . . . . .	129
Test_MockRepository_mod . . . . .	130
Test_mod . . . . .	130
Test_MpiContext_mod . . . . .	131
Test_MpiException_mod . . . . .	132

Test_MpiParameterizedTestCase_mod . . . . .	133
Test_MpiTestCase_mod . . . . .	133
Test_Parameters_mod::Test_Parameters . . . . .	135
Test_Parameters_mod . . . . .	135
Test_RestrictSphericalCoordinates_mod::Test_RestrictSphericalCoordinates . . . . .	135
Test_RestrictSphericalCoordinates_mod . . . . .	136
Test_RobustRunner_mod . . . . .	136
Test_SimpleTestCase_mod . . . . .	137
Test_StringConversionUtilities_mod . . . . .	138
Test_TestMethod_mod . . . . .	138
Test_TestResult_mod . . . . .	139
Test_TestSuite_mod . . . . .	140
Test_UnixProcess_mod . . . . .	141
Test_XmlPrinter_mod . . . . .	142
TestA_mod . . . . .	143
TestCase_mod . . . . .	143
TestCaseA_mod::TestCaseA . . . . .	144
TestCaseA_mod . . . . .	144
TestCaseB_mod::TestCaseB . . . . .	145
TestCaseB_mod . . . . .	145
TestCaseC_mod::TestCaseC . . . . .	146
TestCaseC_mod . . . . .	147
TestFailure_mod . . . . .	147
mods::pre::pre_If::TestIfDirective . . . . .	148
mods::pre::interleavedp::TestInterleaved . . . . .	149
TestListener_mod . . . . .	149
TestMethod_mod . . . . .	150
mods::pre::parseArgs::TestParseArgs . . . . .	151
parseDirectiveArgs::TestParseDirectiveArgs . . . . .	151
testParser::TestParseLine . . . . .	152
parseBrackets::TestRejoinBracketed . . . . .	156
mods::pre::pre_Repeat::TestRepeatDirective . . . . .	156
TestResult_mod . . . . .	156
TestRunner_mod . . . . .	157
TestSuite_mod . . . . .	158
ThrowFundamentalTypes_mod . . . . .	159
UnixPipeInterfaces_mod . . . . .	160
UnixProcess_mod . . . . .	161
AbstractTestResult_mod::wasSuccessful . . . . .	162
WrapbeforeAfter . . . . .	163
WrapMpiTestCaseB_mod . . . . .	163
Wrapsimple . . . . .	163
WrapTestA_mod . . . . .	163
WrapTestCaseA_mod . . . . .	164
WrapTestCaseB_mod . . . . .	164
WrapTestCaseC_mod . . . . .	164



XmlPrinter\_mod . . . . .

165



## Chapter 16

# Data Type Index

### 16.1 Data Types List

Here are the data types with brief descriptions:

<a href="#">AbstractTestParameter_mod</a>	57
<a href="#">AbstractTestResult_mod</a>	57
<a href="#">pUnitParser::Action</a>	58
<a href="#">add_mod</a>	59
<a href="#">addComplex_mod</a>	59
<a href="#">CodeUtilities::ArrayDescription</a>	59
<a href="#">Assert_mod</a>	
<BriefDescription>	60
<a href="#">AssertBasic_mod</a>	
Provides fundamental assertions over the most basic types, a foundation for providing test services to end users	60
<a href="#">GenerateAssertsOnArrays::AssertRealArrayArgument</a>	62
<a href="#">pUnitParser::AtAfter</a>	63
<a href="#">pUnitParser::AtAssert</a>	63
<a href="#">pUnitParser::AtAssertAssociated</a>	64
<a href="#">pUnitParser::AtAssertEqualUserDefined</a>	65
<a href="#">pUnitParser::AtAssertEquivalent</a>	66
<a href="#">pUnitParser::AtAssertNotAssociated</a>	66
<a href="#">pUnitParser::AtBefore</a>	67
<a href="#">pUnitParser::AtBegin</a>	68
<a href="#">pUnitParser::AtMpiAssert</a>	68
<a href="#">pUnitParser::AtMpiTest</a>	69
<a href="#">pUnitParser::AtSuite</a>	69
<a href="#">pUnitParser::AtTest</a>	70
<a href="#">pUnitParser::AtTestCase</a>	71

<a href="#">pUnitParser::AtTestParameter</a>	71
<a href="#">TestCaseB_mod::B_Parameter</a>	72
<a href="#">BaseTestRunner_mod</a>	
<BriefDescription>	72
<a href="#">BeforeAfter_mod</a>	73
<a href="#">BrokenSetUpCase_mod</a>	
<BriefDescription>	74
<a href="#">BrokenTestCase_mod</a>	
<BriefDescription>	74
<a href="#">TestCaseC_mod::C_Parameter</a>	75
<a href="#">Cases_mod</a>	76
<a href="#">GenerateAssertsOnArrays::constraintASSERT</a>	76
<a href="#">Test_mod::countTestCases</a>	77
<a href="#">mods::pre::pre2::dataString</a>	78
<a href="#">DebugListener_mod</a>	
<BriefDescription>	78
<a href="#">CodeUtilities::declaration</a>	79
<a href="#">DynamicTestCase_mod</a>	
<BriefDescription>	80
<a href="#">Exception_mod</a>	81
<a href="#">Expectation_mod</a>	81
<a href="#">Fixture_mod</a>	82
<a href="#">FixtureTestCase_mod</a>	
<BriefDescription>	82
<a href="#">CodeUtilities::fortranSubroutineSignature</a>	83
<a href="#">AbstractTestResult_mod::getErrors</a>	84
<a href="#">Test_mod::getName</a>	84
<a href="#">AbstractTestResult_mod::getSuccesses</a>	84
<a href="#">Halo_mod</a>	84
<a href="#">mods::pre::pre_If::IfDirective</a>	84
<a href="#">CodeUtilities::implementation</a>	85
<a href="#">CodeUtilities::interfaceBlock</a>	85
<a href="#">mods::pre::pre_If::interval</a>	86
<a href="#">GenerateAssertsOnArrays::IsWithinTolerance</a>	86
<a href="#">Test_RestrictSphericalCoordinates_mod::LatLonCase</a>	87
<a href="#">LinearInterpolator_mod</a>	87
<a href="#">MakeInfinity_mod</a>	
<BriefDescription>	88
<a href="#">MakeNaN_mod</a>	
<BriefDescription>	88
<a href="#">Mock_mod</a>	
<BriefDescription>	89
<a href="#">MockCall_mod</a>	
<BriefDescription>	90
<a href="#">MockListener_mod</a>	
<BriefDescription>	91

testParser::MockParser	91
MockRepository_mod	
<BriefDescription>	92
MockSUT_mod	93
testParser::MockWriter	93
CodeUtilities::module	94
MpiContext_mod	
<BriefDescription>	94
MpiStubs_mod	
<BriefDescription>	95
MpiTestCase_mod	
<BriefDescription>	96
MpiTestCaseB_mod::MpiTestCaseB	97
MpiTestCaseB_mod	97
MpiTestMethod_mod	
<BriefDescription>	98
MpiTestParameter_mod	99
pFUnitParser::MyError	99
Cases_mod::MyParamType	99
Cases_mod::MyTestCase	100
TestCaseC_mod::newC_Parameter	100
node_mod	100
ParallelContext_mod	
<BriefDescription>	101
ParallelException_mod	
<BriefDescription>	101
ParameterizedTestCase_mod	
<BriefDescription>	102
Params_mod	
<BriefDescription>	103
pFUnitParser::Parser	104
Test_Parameters_mod::peCase	105
pFUnit	
<BriefDescription>	106
pFUnit_mod	
<BriefDescription>	106
PrivateException_mod	
<BriefDescription>	107
mods::pre::pre2::procDirective	108
RemoteProxyTestCase_mod	
<BriefDescription>	109
mods::pre::pre_Repeat::RepeatDirective	110
ResultPrinter_mod	
<BriefDescription>	110
RobustRunner_mod	
<BriefDescription>	111

<a href="#">robustTestSuite_mod</a>	
<BriefDescription>	112
<a href="#">CodeUtilities::routineUnit</a>	113
<a href="#">SerialContext_mod</a>	
<BriefDescription>	114
<a href="#">SimpleTestCase_mod</a>	
<BriefDescription>	115
<a href="#">SourceLocation_mod</a>	
<BriefDescription>	116
<a href="#">SphericalCoordinates_mod</a>	117
<a href="#">TestListener_mod::startTest</a>	117
<a href="#">StringConversionUtilities_mod</a>	
A collection of utilities used throughout the framework	117
<a href="#">SubsetRunner_mod</a>	
<BriefDescription>	118
<a href="#">SurrogateTestCase_mod</a>	
<BriefDescription>	119
<a href="#">SUT_mod</a>	
<BriefDescription>	120
<a href="#">Test_mod::Test</a>	121
<a href="#">Test_Assert_mod</a>	
<BriefDescription>	121
<a href="#">Test_AssertBasic_mod</a>	
<BriefDescription>	122
<a href="#">Test_AssertComplex_mod</a>	
<BriefDescription>	123
<a href="#">Test_AssertInteger_mod</a>	
<BriefDescription>	124
<a href="#">Test_AssertReal_mod</a>	
<BriefDescription>	125
<a href="#">Test_BasicOpenMP_mod</a>	
<BriefDescription>	126
<a href="#">Test_Exception_mod</a>	
<BriefDescription>	127
<a href="#">Test_FixtureTestCase_mod</a>	
<BriefDescription>	128
<a href="#">Test_LinearInterpolator_mod::Test_LinearInterpolator</a>	129
<a href="#">Test_LinearInterpolator_mod</a>	129
<a href="#">Test_MockCall_mod</a>	
<BriefDescription>	129
<a href="#">Test_MockRepository_mod</a>	130
<a href="#">Test_mod</a>	
<BriefDescription>	130
<a href="#">Test_MpiContext_mod</a>	
<BriefDescription>	131

Test_MpiException_mod	
<BriefDescription>	132
Test_MpiParameterizedTestCase_mod	
<BriefDescription>	133
Test_MpiTestCase_mod	
<BriefDescription>	133
Test_Parameters_mod::Test_Parameters	135
Test_Parameters_mod	135
Test_RestrictSphericalCoordinates_mod::Test_RestrictSphericalCoordinates	135
Test_RestrictSphericalCoordinates_mod	136
Test_RobustRunner_mod	
<BriefDescription>	136
Test_SimpleTestCase_mod	
<BriefDescription>	137
Test_StringConversionUtilities_mod	
<BriefDescription>	138
Test_TestMethod_mod	
<BriefDescription>	138
Test_TestResult_mod	
<BriefDescription>	139
Test_TestSuite_mod	
<BriefDescription>	140
Test_UnixProcess_mod	
<BriefDescription>	141
Test_XmlPrinter_mod	
Output test messages in junit.xsd-compatible XML	142
TestA_mod	143
TestCase_mod	
<BriefDescription>	143
TestCaseA_mod::TestCaseA	144
TestCaseA_mod	144
TestCaseB_mod::TestCaseB	145
TestCaseB_mod	145
TestCaseC_mod::TestCaseC	146
TestCaseC_mod	147
TestFailure_mod	
<BriefDescription>	147
mods::pre::pre_If::TestIfDirective	148
mods::pre::interleavedp::TestInterleaved	149
TestListener_mod	
<BriefDescription>	149
TestMethod_mod	
<BriefDescription>	150
mods::pre::parseArgs::TestParseArgs	151
parseDirectiveArgs::TestParseDirectiveArgs	151
testParser::TestParseLine	152

<a href="#">parseBrackets::TestRejoinBracketed</a>	156
<a href="#">mods::pre::pre_Repeat::TestRepeatDirective</a>	156
<a href="#">TestResult_mod</a>	
<BriefDescription> Note: A possible extension point for user-specialized TestResults	156
<a href="#">TestRunner_mod</a>	
<BriefDescription>	157
<a href="#">TestSuite_mod</a>	
<BriefDescription>	158
<a href="#">ThrowFundamentalTypes_mod</a>	
<BriefDescription>	159
<a href="#">UnixPipeInterfaces_mod</a>	
<BriefDescription>	160
<a href="#">UnixProcess_mod</a>	
<BriefDescription>	161
<a href="#">GenerateAssertsOnArrays::VECTOR_NORM</a>	162
<a href="#">AbstractTestResult_mod::wasSuccessful</a>	162
<a href="#">WrapbeforeAfter</a>	163
<a href="#">WrapMpiTestCaseB_mod</a>	163
<a href="#">Wrapsimple</a>	163
<a href="#">WrapTestA_mod</a>	163
<a href="#">WrapTestCaseA_mod</a>	164
<a href="#">WrapTestCaseB_mod</a>	164
<a href="#">WrapTestCaseC_mod</a>	164
<a href="#">XmlPrinter_mod</a>	
<BriefDescription>	165



## Chapter 17

# Data Type Documentation

### 17.1 AbstractTestParameter\_mod Module Reference

#### Data Types

- type **AbstractTestParameter**
- interface **toString**

The documentation for this module was generated from the following file:

- AbstractTestParameter.F90

### 17.2 AbstractTestResult\_mod Module Reference

#### Data Types


- type **AbstractTestResult**
- interface **errorCount**
- interface **failureCount**
- interface **getErrors**
- interface **getFailures**
- interface **getName**
- interface **getRunTime**
- interface **getSuccesses**
- interface **runCount**
- interface **setName**
- interface **wasSuccessful**

The documentation for this module was generated from the following file:

- AbstractTestResult.F90

### 17.3 pFUnitParser::Action Class Reference

Inheritance diagram for pFUnitParser::Action:



#### Public Member Functions

- def **apply**

The documentation for this class was generated from the following file:

- `pFUnitParser.py`

## 17.4 `add_mod` Module Reference

### Public Member Functions

- real function **add** (`x`, `y`)
- real function **add** (`x`, `y`)

The documentation for this module was generated from the following files:

- `Robust/src/add.F90`
- `Simple/src/add.F90`

## 17.5 `addComplex_mod` Module Reference

### Public Member Functions

- complex function, `dimension(size(z0))` **add** (`z0`, `z1`)

The documentation for this module was generated from the following file:

- `addComplex.F90`

## 17.6 `CodeUtilities::ArrayDescription` Class Reference

### Public Member Functions

- `def __init__`
- `def NAME`
- `def DECLARE`
- `def DECLARESCALAR`
- `def KIND`
- `def RANK`
- `def FTYPE`
- `def EXPANDSHAPE`
- `def FailureMessageFork`

### Public Attributes

- **fType**
- **kind**
- **rank**

The documentation for this class was generated from the following file:

- CodeUtilities.py

## 17.7 Assert\_mod Module Reference

<BriefDescription>

### 17.7.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Assert.F90

## 17.8 AssertBasic\_mod Module Reference

Provides fundamental assertions over the most basic types, a foundation for providing test services to end users.

## Data Types

- interface **assertEqual**
- interface **assertExceptionRaised**
- interface **assertFail**
- interface **assertFalse**
- interface **assertIsFinite**
- interface **assertIsNaN**
- interface **assertTrue**
- interface **fail**
- type **UnusableArgument**

## Public Member Functions

- subroutine **assertExceptionRaisedMessage** (message, location)
- subroutine, public **assertSameShape** (shapeA, shapeB, message, location)
- logical function, public **conformable** (shapeA, shapeB)
- logical function, public **nonConformable** (shapeA, shapeB)
- subroutine **assertEqualString\_** (expected, found, message, location, whitespace)
- subroutine, public **assertAny** (conditions, message, location)
- subroutine, public **assertAll** (conditions, message, location)
- subroutine, public **assertNone** (conditions, message, location)
- subroutine, public **assertNotAll** (conditions, message, location)
- subroutine **assertIsNaN\_double** (x, message, location)
- subroutine **assertIsFinite\_single** (x, message, location)
- subroutine **assertIsFinite\_double** (x, message, location)

### 17.8.1 Detailed Description

Provides fundamental assertions over the most basic types, a foundation for providing test services to end users.

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

**Note**

For assertions on strings whitespace may or may not be significant to a test. We now have several options for dealing with whitespace via the optional argument `Whitespace`. These options are `IGNORE_ALL`, `TRIM_ALL`, and `KEEP_ALL`. - Usage is as follows.

```
call assertEquals(expectedString, foundString, & & Whitespace==  
IGNORE_ALL )
```

**WhitespaceOptions:**

- **TRIM\_ALL** ignores leading and trailing whitespace.
- **KEEP\_ALL** keeps all whitespace as significant, even discriminating between tabs and spaces.
- **IGNORE\_ALL** ignores all whitespace (spaces & tabs).

Example usages can be seen in `tests/Test_AssertBasic.F90` or `Examples/-Simple/tests/helloWorld.pf`.

The documentation for this module was generated from the following file:

- `AssertBasic.F90`

## 17.9 GenerateAssertsOnArrays::AssertRealArrayArgument Class - Reference

**Public Member Functions**

- `def __init__`
- `def updateDescriptions`
- `def getAssertionName`
- `def getExpectedDescription`
- `def getFoundDescription`
- `def getTolerance`

**Public Attributes**

- `assertionName`
- `expectedFType`
- `expectedPrecision`
- `expectedRank`


- **foundFType**
- **foundPrecision**
- **foundRank**
- **tolerance**
- **expectedDescription**
- **foundDescription**

The documentation for this class was generated from the following file:

- `GenerateAssertsOnArrays.py`

## 17.10 pFUnitParser::AtAfter Class Reference

Inheritance diagram for pFUnitParser::AtAfter:



### Public Member Functions

- `def __init__`
- `def match`
- `def action`

### Public Attributes


- **parser**

The documentation for this class was generated from the following file:

- `pFUnitParser.py`

## 17.11 pFUnitParser::AtAssert Class Reference

Inheritance diagram for pFUnitParser::AtAssert:



### Public Member Functions

- `def __init__`
- `def match`
- `def appendSourceLocation`
- `def action`

### Public Attributes


- `parser`

The documentation for this class was generated from the following file:

- `pFUnitParser.py`

## 17.12 pFUnitParser::AtAssertAssociated Class Reference

Inheritance diagram for `pFUnitParser::AtAssertAssociated`:



### Public Member Functions

- `def __init__`
- `def match`
- `def appendSourceLocation`
- `def action`



### Public Attributes


- **parser**

The documentation for this class was generated from the following file:

- pFUnitParser.py

## 17.13 pFUnitParser::AtAssertEqualUserDefined Class Reference

Inheritance diagram for pFUnitParser::AtAssertEqualUserDefined:



### Public Member Functions

- def **\_\_init\_\_**
- def **match**
- def **appendSourceLocation**
- def **action**

### Public Attributes

- **parser**

#### 17.13.1 Detailed Description


Convenience directive replacing (a,b) with a call to `assertTrue(a==b)` and an error message, if none is provided when invoked.

The documentation for this class was generated from the following file:

- pFUnitParser.py

## 17.14 pFUnitParser::AtAssertEquivalent Class Reference

Inheritance diagram for pFUnitParser::AtAssertEquivalent:



### Public Member Functions

- def `__init__`
- def `match`
- def `appendSourceLocation`
- def `action`

### Public Attributes

- `parser`

### 17.14.1 Detailed Description


Convenience directive replacing `(a,b)` with a call to `assertTrue(a.eqv.b)` and an error message, if none is provided when invoked.

The documentation for this class was generated from the following file:

- `pFUnitParser.py`

## 17.15 pFUnitParser::AtAssertNotAssociated Class Reference

Inheritance diagram for pFUnitParser::AtAssertNotAssociated:



### Public Member Functions

- def **\_\_init\_\_**
- def **match**
- def **appendSourceLocation**
- def **action**

### Public Attributes


- **parser**
- **name**

The documentation for this class was generated from the following file:

- pFUnitParser.py

## 17.16 pFUnitParser::AtBefore Class Reference

Inheritance diagram for pFUnitParser::AtBefore:



### Public Member Functions

- def **\_\_init\_\_**
- def **match**
- def **action**

### Public Attributes


- **parser**

The documentation for this class was generated from the following file:

- pFUnitParser.py

## 17.17 pFUnitParser::AtBegin Class Reference

Inheritance diagram for pFUnitParser::AtBegin:



### Public Member Functions

- def **\_\_init\_\_**
- def **match**
- def **action**

### Public Attributes


- **parser**

The documentation for this class was generated from the following file:

- pFUnitParser.py

## 17.18 pFUnitParser::AtMpiAssert Class Reference

Inheritance diagram for pFUnitParser::AtMpiAssert:



### Public Member Functions

- def **\_\_init\_\_**
- def **match**
- def **appendSourceLocation**
- def **action**

### Public Attributes


- **parser**

The documentation for this class was generated from the following file:

- pFUnitParser.py

## 17.19 pFUnitParser::AtMpiTest Class Reference

Inheritance diagram for pFUnitParser::AtMpiTest:



### Public Member Functions

- def **\_\_init\_\_**

### Public Attributes


- **parser**
- **keyword**

The documentation for this class was generated from the following file:

- pFUnitParser.py

## 17.20 pFUnitParser::AtSuite Class Reference

Inheritance diagram for pFUnitParser::AtSuite:



### Public Member Functions

- `def __init__`
- `def match`
- `def action`

### Public Attributes


- `parser`

The documentation for this class was generated from the following file:

- `pFUnitParser.py`

## 17.21 pFUnitParser::AtTest Class Reference

Inheritance diagram for `pFUnitParser::AtTest`:



### Public Member Functions

- `def __init__`
- `def match`
- `def action`

### Public Attributes


- **parser**
- **keyword**

The documentation for this class was generated from the following file:

- pFUnitParser.py

## 17.22 pFUnitParser::AtTestCase Class Reference

Inheritance diagram for pFUnitParser::AtTestCase:



### Public Member Functions

- def **\_\_init\_\_**
- def **match**
- def **action**

### Public Attributes


- **parser**

The documentation for this class was generated from the following file:

- pFUnitParser.py

## 17.23 pFUnitParser::AtTestParameter Class Reference

Inheritance diagram for pFUnitParser::AtTestParameter:



### Public Member Functions

- def **\_\_init\_\_**
- def **match**
- def **action**

### Public Attributes

- **parser**

The documentation for this class was generated from the following file:

- pFUnitParser.py

## 17.24 TestCaseB\_mod::B\_Parameter Type Reference

### Public Member Functions

- procedure **toString**
- procedure **toString**

### Public Attributes

- real **phi**
- real **theta**

The documentation for this type was generated from the following files:

- ParameterizedTestCaseB.F90
- ParameterizedTestCaseB.pf

## 17.25 BaseTestRunner\_mod Module Reference

<BriefDescription>



## Data Types

- type **BaseTestRunner**
- interface **run2**

### 17.25.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- BaseTestRunner.F90

## 17.26 BeforeAfter\_mod Module Reference

### Public Member Functions

- subroutine **first** (this)
- subroutine **last** (this)
- subroutine **firstAndLastCalled** (this)
- subroutine **succeeds** (this)
- subroutine **fails** (this)

### Public Attributes

- integer **countStart** = 0
- integer **countComplete** = 0

The documentation for this module was generated from the following file:

- Examples/MPI\_Halo/tests/beforeAfter.pf

## 17.27 BrokenSetUpCase\_mod Module Reference

<BriefDescription>

### Data Types

- type **BrokenSetUpCase**

### Public Member Functions

- type(BrokenSetUpCase) function, pointer, public **newBrokenSetUpCase** ()

### 17.27.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

20 Mar 2015

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- BrokenSetUpCase.F90

## 17.28 BrokenTestCase\_mod Module Reference

<BriefDescription>

### Data Types

- type **BrokenTestCase**

### Public Member Functions

- subroutine **tearDown** (this)

#### 17.28.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

20 Mar 2015

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- BrokenTestCase.F90

## 17.29 TestCaseC\_mod::C\_Parameter Type Reference

### Public Member Functions

- procedure **toString**
- procedure **toString**

### Public Attributes

- real **phi**
- real **theta**

The documentation for this type was generated from the following files:

- MpiParameterizedTestCaseC.F90
- MpiParameterizedTestCaseC.pf

## 17.30 Cases\_mod Module Reference

### Data Types

- type [MyParamType](#)
- type [MyTestCase](#)

### Public Member Functions


- type([MyParamType](#)) function **newMyParam** (i)
- type([MyTestCase](#)) function **newMyTestCase** (param)
- subroutine **test\_odd** (this)
- subroutine **test\_even** (this)
- character(:) function, allocatable **toString** (this)

The documentation for this module was generated from the following file:

- Test\_Cases.pf

## 17.31 GenerateAssertsOnArrays::constraintASSERT Class - Reference

Inheritance diagram for GenerateAssertsOnArrays::constraintASSERT:



### Public Member Functions

- def [\\_\\_init\\_\\_](#)  
*Dependency injection.*

### Public Attributes

- **expectedDescr**
- **foundDescr**

- **name**

- [name1](#)

*Add in the extra module procedures...*

- [tolerance](#)

*If you need another kind of code generator, perhaps conditioned on eDesc., fDesc., or tol, then that logic would go here...*

### 17.31.1 Constructor & Destructor Documentation

17.31.1.1 `def GenerateAssertsOnArrays::constraintASSERT::__init__( self, assertionName, expectedDescr, foundDescr, tolerance )`

Dependency injection.

Will generate "assert"+assertionName assertionName="Equal" This next line actually generates the text of the code.

### 17.31.2 Member Data Documentation

17.31.2.1 `GenerateAssertsOnArrays::constraintASSERT::name1`

Add in the extra module procedures...

If needed... Kluge. Need to make makeSubroutineNames and load the extra interface entries there.

17.31.2.2 `GenerateAssertsOnArrays::constraintASSERT::tolerance`

If you need another kind of code generator, perhaps conditioned on eDesc., fDesc., or tol, then that logic would go here...

E.g. to implement assertEquals(Logical(...))

The documentation for this class was generated from the following file:

- GenerateAssertsOnArrays.py

## 17.32 Test\_mod::countTestCases Interface Reference

The documentation for this interface was generated from the following file:

- Test.F90

## 17.33 mods::pre::pre2::dataString Class Reference

### Public Member Functions

- def **\_\_init\_\_**
- def **insert**
- def **getLength**
- def **getPosition**
- def **setPosition**
- def **getItem**
- def **getDataAtPosition**
- def **getData**
- def **getSlice**
- def **getSliceForward**
- def **removeSlice**
- def **getCurrentData**
- def **insertAtCurrent**
- def **append**
- def **advanceAndGetNextData**
- def **validPosition**
- def **findToEnd**
- def **match**
- def **matchToEnd**
- def **searchToEnd**
- def **searchToPosition**
- def **finditerToEnd**
- def **finditerToPosition**

### Public Attributes

- **data**
- **position**

The documentation for this class was generated from the following file:

- pre2.py

## 17.34 DebugListener\_mod Module Reference

<BriefDescription>

## Data Types

- interface **DebugListener**

## Public Member Functions

- subroutine **addFailure** (this, testName, exceptions)
- subroutine **startTest** (this, testName)

### 17.34.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- DebugListener.F90

## 17.35 CodeUtilities::declaration Class Reference

### Public Member Functions

- def **\_\_init\_\_**
- def **generate**

### Public Attributes

- **simpleDeclaration**
- **fullDeclaration**
- **name**

The documentation for this class was generated from the following file:

- CodeUtilities.py

## 17.36 DynamicTestCase\_mod Module Reference

<BriefDescription>

### Data Types

- interface **delete**
- type **DynamicTestCase**
- interface **testmethod**

### Public Member Functions

- type(DynamicTestCase) function, pointer, public **newDynamicTestCase** (test-Method, name)

#### 17.36.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- DynamicTestCase.F90



## 17.37 Exception\_mod Module Reference

### Data Types

- interface **anyExceptions**
- interface **catch**
- interface **getNumExceptions**
- interface **throw**

### Public Member Functions

- subroutine, public **initializeGlobalExceptionList** ()
- type(Exception) function, public **catchNext** (preserve)
- type(Exception) function, dimension(:), allocatable, public **getExceptions** ()
- logical function, public **noExceptions** ()
- logical function, public **anyErrors** ()
- subroutine, public **gatherExceptions** (context)
- subroutine, public **clearAll** ()

The documentation for this module was generated from the following file:

- Exception.F90

## 17.38 Expectation\_mod Module Reference

### Data Types

- type **Expectation**
- type **Predicate**
- type **Subject**
- interface **subVoid**

### Public Member Functions

- type(Predicate) function, public **newPredicate** (name)
- type(Subject) function, public **newSubject** (name, sub)
- type(Subject) function, public **newSubjectNameOnly** (name)
- type(Expectation) function, public **newExpectation** (subj, pred)

### Public Attributes

- type(Predicate), parameter, public **wasCalled** = Predicate('wasCalled')
- type(Predicate), parameter, public **wasNotCalled** = Predicate('wasNotCalled')
- type(Predicate), parameter, public **wasCalledOnce** = Predicate('wasCalled-Once')

The documentation for this module was generated from the following file:

- Expectation.F90

## 17.39 Fixture\_mod Module Reference

### Public Member Functions

- subroutine **mySetup** ()
- subroutine **myTearDown** ()
- subroutine **testRead** ()
- subroutine **testEOF** ()

The documentation for this module was generated from the following file:

- fixtureTests.pf

## 17.40 FixtureTestCase\_mod Module Reference

<BriefDescription>

### Data Types

- interface **delete**
- type **FixtureTestCase**

### Public Member Functions

- type(FixtureTestCase) function, public **newFixtureTestCase** ()
- subroutine, public **simpleTestMethod** (this)
- subroutine, public **methodA** (this)
- subroutine, public **methodB** (this)

### 17.40.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

20 Mar 2015

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- FixtureTestCase.F90

## 17.41 CodeUtilities::fortranSubroutineSignature Class Reference

### Public Member Functions

- def **\_\_init\_\_**
- def **setReturnFType**
- def **addArg**
- def **generateInterfaceEntry**
- def **generateImplementationSignature**
- def **generateImplementationClose**

### Public Attributes

- **name**
- **ArgumentToFType**
- **ReturnFType**
- **SubroutineType**

The documentation for this class was generated from the following file:

- CodeUtilities.py

## 17.42 AbstractTestResult\_mod::getErrors Interface Reference

The documentation for this interface was generated from the following file:

- AbstractTestResult.F90

## 17.43 Test\_mod::getName Interface Reference

The documentation for this interface was generated from the following file:

- Test.F90

## 17.44 AbstractTestResult\_mod::getSuccesses Interface Reference

The documentation for this interface was generated from the following file:

- AbstractTestResult.F90

## 17.45 Halo\_mod Module Reference

### Public Member Functions


- subroutine **haloFill** (array, communicator)

The documentation for this module was generated from the following file:

- Halo.F90

## 17.46 mods::pre::pre\_If::IfDirective Class Reference

Inheritance diagram for mods::pre::pre\_If::IfDirective:



### Public Member Functions

- def **evaluate**

### Public Attributes

- **startPosition**
- **newPosition**

The documentation for this class was generated from the following file:

- pre\_lf.py

## 17.47 CodeUtilities::implementation Class Reference

### Public Member Functions

- def **\_\_init\_\_**
- def **generate**

### Public Attributes

- **name**
- **source**

The documentation for this class was generated from the following file:

- CodeUtilities.py

## 17.48 CodeUtilities::interfaceBlock Class Reference

The documentation for this class was generated from the following file:

- CodeUtilities.py

## 17.49 mods::pre::pre\_If::interval Class Reference

### Public Member Functions

- def `__init__`
- def `getInterval`
- def `setInterval`
- def `getStart`
- def `getEnd`

### Public Attributes


- `start`
- `end`
- `interval`

The documentation for this class was generated from the following file:

- `pre_If.py`

## 17.50 GenerateAssertsOnArrays::IsWithinTolerance Class Reference

Inheritance diagram for `GenerateAssertsOnArrays::IsWithinTolerance`:



### Public Member Functions

- def `__init__`

### Public Attributes

- `rank`
- `precision`
- `name`

## 17.51 Test\_RestrictSphericalCoordinates\_mod::LatLonCase Type Reference 87

---

- **fType**
- **declaration**
- **declarations**

The documentation for this class was generated from the following file:

- GenerateAssertsOnArrays.py

## 17.51 Test\_RestrictSphericalCoordinates\_mod::LatLonCase Type - Reference

### Public Member Functions

- procedure **toString**

### Public Attributes

- real **lat**
- real **lon**
- real **restrictedLat**
- real **restrictedLon**

The documentation for this type was generated from the following file:

- Test\_RestrictedSphericalCoordinates.pf

## 17.52 LinearInterpolator\_mod Module Reference

### Data Types

- interface **LinearInterpolator**
- type **Node**

The documentation for this module was generated from the following file:

- LinearInterpolator.F90

## 17.53 MakeInfinity\_mod Module Reference

<BriefDescription>

### Public Member Functions

- real(r32) function, public **makeInf\_32** ()
- real(r64) function, public **makeInf\_64** ()

### 17.53.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC SIVO

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- MakeInfinity.F90

## 17.54 MakeNaN\_mod Module Reference

<BriefDescription>

### Public Member Functions

- real(r32) function, public **makeNaN\_32** ()
- real(r64) function, public **makeNaN\_64** ()



### 17.54.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- MakeNaN.F90

## 17.55 Mock\_mod Module Reference

<BriefDescription>

**Data Types**

- type **Mock**

### 17.55.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

12 May 2014

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Mock.F90

## 17.56 MockCall\_mod Module Reference

<BriefDescription>

**Data Types**

- type **MockCall**

**Public Member Functions**

- type(MockCall) function, public **newMockCall** (name)

### 17.56.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- MockCall.F90

## 17.57 MockListener\_mod Module Reference

<BriefDescription>

### Data Types

- type **MockListener**

### Public Member Functions

- subroutine **startTest** (this, testName)

### 17.57.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

20 Mar 2015

#### Note


<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- MockListener.F90

## 17.58 testParser::MockParser Class Reference

Inheritance diagram for testParser::MockParser:



### Public Member Functions

- def **\_\_init\_\_**
- def **nextLine**
- def **reset**

### Public Attributes

- **saveLines**
- **lines**
- **outputFile**
- **outLines**
- **userTestCase**
- **userTestMethods**
- **currentSelfObjectName**

The documentation for this class was generated from the following file:

- testParser.py

## 17.59 MockRepository\_mod Module Reference

<BriefDescription>

### Data Types

- interface **addExpectationThat\_**
- type **MockRepository**
- interface **registerMockCallBy\_**
- interface **subVoid**

### Public Member Functions

- type(MockRepository) function, pointer, public **newMockRepository** ()
- subroutine **expectCall** (this, obj, method)

### Public Attributes

- integer, parameter, public **MAX\_LEN\_METHOD\_NAME** = 32
- integer, parameter, public **MAX\_LEN\_CALL\_REGISTRATION** = 32
- class(MockRepository), pointer, public **MockRepositoryPointer** = > null()

### 17.59.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- MockRepository.F90

## 17.60 MockSUT\_mod Module Reference

**Data Types**

- type **MockSUT**

**Public Member Functions**

- type(MockSUT) function, allocatable, public **newMockSUT** (repository)
- subroutine **method1** (this)

The documentation for this module was generated from the following file:

- Test\_MockRepository.F90

## 17.61 testParser::MockWriter Class Reference

**Public Member Functions**

- def **\_\_init\_\_**
- def **write**

### Public Attributes

- **parser**

The documentation for this class was generated from the following file:

- testParser.py

## 17.62 CodeUtilities::module Class Reference

### Public Member Functions

- def **\_\_init\_\_**
- def **generate**
- def **addDeclaration**
- def **addImplementation**
- def **addRoutineUnit**
- def **addInterfaceBlock**
- def **getName**
- def **setFileName**
- def **getFileName**

### Public Attributes

- **name**
- **declarations**
- **implementations**
- **generation**
- **fileName**

The documentation for this class was generated from the following file:

- CodeUtilities.py

## 17.63 MpiContext\_mod Module Reference

<BriefDescription>

## Data Types

- type **MpiContext**
- interface **newMpiContext**

## Public Member Functions

- subroutine **barrier** (this)

### 17.63.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- MpiContext.F90

## 17.64 MpiStubs\_mod Module Reference

<BriefDescription>

## Public Member Functions

- subroutine, public **MPI\_Comm\_rank** (comm, rank, ier)
- subroutine, public **MPI\_Comm\_size** (comm, size, ier)
- subroutine, public **MPI\_Comm\_dup** (comm, newComm, ier)
- subroutine, public **MPI\_Comm\_group** (comm, group, ier)
- subroutine, public **MPI\_Group\_range\_incl** (group, n, ranges, newGroups, ier)
- subroutine, public **MPI\_Comm\_create** (comm, group, newComm, ier)

### Public Attributes

- integer, parameter, public **MPI\_COMM\_WORLD** = -1
- integer, parameter, public **MPI\_COMM\_NULL** = -1
- integer, parameter, public **MPI\_COMM\_SUCCESS** = 0

### 17.64.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- MpiStubs.F90

## 17.65 MpiTestCase\_mod Module Reference

<BriefDescription>

### Data Types

- type **MpiTestCase**

### Public Member Functions

- recursive subroutine **runBare** (this)
- integer function **getMpiCommunicator** (this)
- integer function **getProcessRank** (this)



### 17.65.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- `MpiTestCase.F90`

## 17.66 `MpiTestCaseB_mod::MpiTestCaseB` Type Reference

**Public Member Functions**

- procedure **setUp**
- procedure **tearDown**
- procedure **setUp**
- procedure **tearDown**

**Public Attributes**

- integer **componentI**

The documentation for this type was generated from the following files:

- `MpiTestCaseB.F90`
- `MpiTestCaseB.pf`

## 17.67 `MpiTestCaseB_mod` Module Reference

**Data Types**

- type [MpiTestCaseB](#)

### Public Member Functions

- subroutine **setUp** (this)
- subroutine **tearDown** (this)
- subroutine **testA** (this)
- subroutine **testB** (this)
- subroutine **setUp** (this)
- subroutine **tearDown** (this)
- subroutine **testA** (this)
- subroutine **testB** (this)

The documentation for this module was generated from the following files:

- `MpiTestCaseB.F90`
- `MpiTestCaseB.pf`

## 17.68 `MpiTestMethod_mod` Module Reference

<BriefDescription>

### Data Types

- interface **mpiMethod**
- type **MpiTestMethod**
- interface **newMpiTestMethod**

### 17.68.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- `MpiTestMethod.F90`

## 17.69 `MpiTestParameter_mod` Module Reference

### Data Types

- type **`MpiTestParameter`**

### Public Member Functions

- `type(MpiTestParameter)` function, public **`newMpiTestParameter`** (`num-ProcessesRequested`)

The documentation for this module was generated from the following file:

- `MpiTestParameter.F90`

## 17.70 `pFUnitParser::MyError` Class Reference

Inherits `Exception`.

### Public Member Functions

- `def __init__`
- `def __str__`

### Public Attributes

- **`value`**

The documentation for this class was generated from the following file:

- `pFUnitParser.py`

## 17.71 `Cases_mod::MyParamType` Type Reference

### Public Member Functions

- procedure **`toString`**

### Public Attributes

- integer `i`

The documentation for this type was generated from the following file:

- `Test_Cases.pf`

## 17.72 `Cases_mod::MyTestCase` Type Reference

### Public Attributes

- integer `i`

The documentation for this type was generated from the following file:

- `Test_Cases.pf`

## 17.73 `TestCaseC_mod::newC_Parameter` Interface Reference

### Public Member Functions

- type([C\\_Parameter](#)) function `newC_Parameter_phiTheta` (`npes`, `phi`, `theta`)
- elemental function `newC_Parameter_case` (`i`)
- type([C\\_Parameter](#)) function `newC_Parameter_phiTheta` (`npes`, `phi`, `theta`)
- elemental function `newC_Parameter_case` (`i`)

The documentation for this interface was generated from the following files:

- `MpiParameterizedTestCaseC.F90`
- `MpiParameterizedTestCaseC.pf`

## 17.74 `node_mod` Module Reference

### Data Types

- interface `node`

The documentation for this module was generated from the following file:

- `node.F90`

## 17.75 ParallelContext\_mod Module Reference

<BriefDescription>

### Data Types

- interface **allReduceLogical**
- interface **gatherInteger**
- interface **gatherLogical**
- interface **gatherString**
- interface **getNumProcesses**
- type **ParallelContext**
- interface **processRank**
- interface **sum**

### 17.75.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- ParallelContext.F90

## 17.76 ParallelException\_mod Module Reference

<BriefDescription>

### Data Types

- interface **anyExceptions**
- interface **getNumExceptions**

### Public Member Functions

- subroutine, public **gather** (context)

#### 17.76.1 Detailed Description

<BriefDescription>

##### Author

Tom Clune, NASA/GSFC

##### Date

07 Nov 2013

##### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- `ParallelException.F90`

#### 17.77 ParameterizedTestCase\_mod Module Reference

<BriefDescription>

### Data Types

- type **ParameterizedTestCase**

### Public Attributes

- integer, parameter, public **MAX\_LEN\_LABEL** = 32

### 17.77.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- ParameterizedTestCase.F90

## 17.78 Params\_mod Module Reference

<BriefDescription>

**Public Attributes**

- integer, parameter, public **MAX\_LENGTH\_NAME** = 128
- integer, parameter **R32** = selected\_real\_kind(p=6)
- integer, parameter **R64** = selected\_real\_kind(p=14)
- integer, parameter **C32** = selected\_real\_kind(p=6)
- integer, parameter **C64** = selected\_real\_kind(p=14)
- integer, parameter **I32** = INT32
- integer, parameter **I64** = INT64
- integer, parameter **NEQP** = 0
- integer, parameter **EQP** = 1
- integer, parameter **GTP** = 2
- integer, parameter **GEP** = 3
- integer, parameter **LTP** = 4
- integer, parameter **LEP** = 5
- integer, parameter **RELEQP** = 6

### 17.78.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**


<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Params.F90

## 17.79 pFUnitParser::Parser Class Reference

Inheritance diagram for pFUnitParser::Parser:



### Public Member Functions

- def **\_\_init\_\_**
- def **commentLine**
- def **run**
- def **isComment**
- def **nextLine**
- def **printHeader**
- def **printTail**
- def **printWrapUserTestCase**
- def **printRunMethod**



- def **printParameterHeader**
- def **printMakeSuite**
- def **addSimpleTestMethod**
- def **addMpiTestMethod**
- def **addUserTestMethod**
- def **printMakeCustomTest**
- def **makeWrapperModule**
- def **final**

#### Public Attributes

- **fileName**
- **inputFile**
- **outputFile**
- **defaultSuiteName**
- **suiteName**
- **currentLineNumber**
- **userModuleName**
- **userTestCase**
- **userTestMethods**
- **wrapModuleName**
- **actions**

The documentation for this class was generated from the following file:

- pFUnitParser.py

## 17.80 Test\_Parameters\_mod::peCase Type Reference

#### Public Member Functions

- procedure **toString**

#### Public Attributes

- integer **p1**
- integer **p2**

The documentation for this type was generated from the following file:

- parameterizedTests.pf

## 17.81 pFUnit Module Reference

<BriefDescription>

### Public Member Functions

- integer function **run** ()

### 17.81.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- pFUnitPackage.F90

## 17.82 pFUnit\_mod Module Reference

<BriefDescription>

### Public Member Functions

- subroutine, public **initialize** (useMpi)
- subroutine, public **finalize** (successful)

### 17.82.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- pFUnit.F90

## 17.83 PrivateException\_mod Module Reference

<BriefDescription>

### Data Types

- type **Exception**
- type **ExceptionList**
- interface **newException**

### Public Member Functions

- type(ExceptionList) function, public **newExceptionList** ()
- logical function **noExceptions** (this)

### Public Attributes

- integer, parameter, public **MAXLEN\_MESSAGE** = 80\*15
- integer, parameter, public **MAXLEN\_FILE\_NAME** = 80
- character(len=\*), parameter, public **NULL\_MESSAGE** = "

### 17.83.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**


<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Exception.F90

## 17.84 mods::pre::pre2::procDirective Class Reference

Inheritance diagram for mods::pre::pre2::procDirective:



### Public Member Functions

- def `__init__`
- def `getLength`
- def `match`
- def `evaluate`
- def `getNewPosition`
- def `addTokenRE`
- def `searchTokenToEnd`
- def `searchTokenToPosition`
- def `finditerTokenToPosition`
- def `makeTokenErrorMessage`

## Public Attributes

- **name**
- **newPosition**
- **tokens**
- **TokenREs**

### 17.84.1 Member Function/Subroutine Documentation

**17.84.1.1** `def mods::pre::pre2::procDirective::addTokenRE ( self, args, key, defaultToken, prefix = r' ' '(?i) [ \t]* ' ', postfix = ' ' )`

Add a token/create an RE with a prefix that by default ignores preceding whitespace. Stores the RE in a dictionary for this directive. Note this currently expects complex tokens like <EndToken> not something as overloaded as a close paren.

The documentation for this class was generated from the following file:

- pre2.py

## 17.85 RemoteProxyTestCase\_mod Module Reference

<BriefDescription>

### Data Types

- interface **RemoteProxyTestCase**

### 17.85.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

**Note**


<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- RemoteProxyTestCase.F90

## 17.86 mods::pre::pre\_Repeat::RepeatDirective Class Reference

Inheritance diagram for mods::pre::pre\_Repeat::RepeatDirective:

**Public Member Functions**

- def **evaluate**

**Public Attributes**

- **startPosition**
- **newPosition**

The documentation for this class was generated from the following file:

- pre\_Repeat.py

## 17.87 ResultPrinter\_mod Module Reference

<BriefDescription>

**Data Types**

- type **ResultPrinter**

## Public Member Functions

- type(ResultPrinter) function, public **newResultPrinter** (unit)
- subroutine **addError** (this, testName, exceptions)
- subroutine **startTest** (this, testName)
- subroutine **print** (this, result)
- subroutine **printHeader** (this, runTime)
- subroutine **printFooter** (this, result)
- subroutine **incrementColumn** (this)

### 17.87.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- ResultPrinter.F90

## 17.88 RobustRunner\_mod Module Reference

<BriefDescription>

### Data Types

- interface **RobustRunner**
- type **TestCaseMonitor**

### Public Member Functions

- subroutine **runWithResult** (this, aTest, context, result)
- subroutine **launchRemoteRunner** (this, numSkip)
- subroutine **startTest** (this, testName)
- subroutine **addFailure** (this, testName, exceptions)
- subroutine **addError** (this, testName, exceptions)
- type(TestResult) function **createTestResult** (this)

#### 17.88.1 Detailed Description

<BriefDescription>

##### Author

Tom Clune, NASA/GSFC

##### Date

07 Nov 2013

##### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- RobustRunner.F90

### 17.89 robustTestSuite\_mod Module Reference

<BriefDescription>

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testRunSucceeds** ()
- subroutine **testRunAssertFailure** ()
- subroutine **testRunStops** ()



### 17.89.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

21 Mar 2015

**Note**


<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- robustTestSuite.F90

## 17.90 CodeUtilities::routineUnit Class Reference

Inheritance diagram for CodeUtilities::routineUnit:



### Public Member Functions

- def `__init__`
- def `setName`
- def `getName`
- def `setDeclaration`
- def `addDeclaration`
- def `setImplementation`
- def `getDeclaration`
- def `getDeclarations`
- def `getImplementation`
- def `clearDeclarations`

### Public Attributes

- **name**
- **declaration**
- **declarations**
- **implementation**

The documentation for this class was generated from the following file:

- CodeUtilities.py

## 17.91 SerialContext\_mod Module Reference

<BriefDescription>

### Data Types

- type **SerialContext**

### Public Member Functions

- type(SerialContext) function, public **newSerialContext** ()

### Public Attributes

- type(SerialContext), parameter, public **THE\_SERIAL\_CONTEXT** = SerialContext()

### 17.91.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- SerialContext.F90

## 17.92 SimpleTestCase\_mod Module Reference

<BriefDescription>

**Data Types**

- interface **method**
- type **SimpleTestCase**

**Public Member Functions**

- type(TestSuite) function, public **suite** ()
- type(SimpleTestCase) function, public **newSimpleTestCase** (name, user-Method)
- subroutine, public **method1** (this)
- subroutine, public **method2** (this)
- subroutine, public **methodWith2Exceptions** (this)
- subroutine **delete\_** (this)

### 17.92.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

20 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- SimpleTestCase.F90

## 17.93 SourceLocation\_mod Module Reference

<BriefDescription>

**Data Types**

- type **SourceLocation**

**Public Attributes**

- character(len=MAXLEN\_FILE\_NAME), parameter, public **UNKNOWN\_FILE\_NAME** = '<unknown file>'
- integer, parameter, public **UNKNOWN\_LINE\_NUMBER** = -1
- type(SourceLocation), parameter, public **UNKNOWN\_SOURCE\_LOCATION** = SourceLocation()

### 17.93.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- SourceLocation.F90

## 17.94 SphericalCoordinates\_mod Module Reference

### Data Types

- interface **SphericalCoordinates**

The documentation for this module was generated from the following file:

- SphericalCoordinates.F90

## 17.95 TestListener\_mod::startTest Interface Reference

The documentation for this interface was generated from the following file:

- TestListener.F90

## 17.96 StringConversionUtilities\_mod Module Reference

A collection of utilities used throughout the framework.

### Data Types

- interface **toString**
- type **WhitespaceOptions**

### Public Member Functions

- character(len=len\_trim(a)+1+len\_trim(b)) function, public **appendWithSpace** (a, b)
- character(len=:) function, allocatable, public **nullTerminate** (string)
- character(len=:) function, allocatable, public **unlessScalar** (vShape, string)
- logical function, public **whitespacep** (c)
- character(len=:) function, allocatable, public **trimAll** (s)
- character(len=:) function, allocatable, public **trimTrailingWhitespace** (s)

### Public Attributes

- integer, parameter, public **MAXLEN\_STRING** = 80
- type(WhitespaceOptions), parameter, public **IGNORE\_ALL** = WhitespaceOptions(IGNORE\_ALL\_)
- type(WhitespaceOptions), parameter, public **TRIM\_ALL** = WhitespaceOptions(-TRIM\_ALL\_)
- type(WhitespaceOptions), parameter, public **KEEP\_ALL** = WhitespaceOptions(-KEEP\_ALL\_)
- type(WhitespaceOptions), parameter, public **IGNORE\_DIFFERENCES** = - WhitespaceOptions(IGNORE\_DIFFERENCES\_)

### 17.96.1 Detailed Description

A collection of utilities used throughout the framework.

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- StringConversionUtilities.F90

## 17.97 SubsetRunner\_mod Module Reference

<BriefDescription>

### Data Types

- interface **SubsetRunner**

## Public Member Functions

- subroutine **addFailure** (this, testName, exceptions)
- subroutine **startTest** (this, testName)

### 17.97.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- SubsetRunner.F90

## 17.98 SurrogateTestCase\_mod Module Reference

<BriefDescription>

### Data Types

- interface **getName**
- interface **runBare**
- interface **setName**
- type **SurrogateTestCase**

### 17.98.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- SurrogateTestCase.F90

## 17.99 SUT\_mod Module Reference

<BriefDescription>

**Data Types**

- type **SUT**

### 17.99.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

21 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_MockRepository.F90



## 17.100 Test\_mod::Test Type Reference

### Public Member Functions

- procedure([countTestCases](#)), deferred **countTestCases**
- procedure(**run**), deferred **run**
- procedure([getName](#)), deferred **getName**
- procedure **setName**

### Public Attributes

- integer **placeholder**

The documentation for this type was generated from the following file:

- Test.F90

## 17.101 Test\_Assert\_mod Module Reference

<BriefDescription>

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testAssertEqualStringDiffer1st** ()

### 17.101.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

20 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_Assert.F90

## 17.102 Test\_AssertBasic\_mod Module Reference

<BriefDescription>

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testAssertTrueF** ()
- subroutine **testAssertIsFinite** ()
- subroutine **testAssertExceptionRaised** ()
- subroutine **testAssertFail** ()

### 17.102.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

20 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_AssertBasic.F90

## 17.103 Test\_AssertComplex\_mod Module Reference

<BriefDescription>

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testEquals\_C\_complexScalar** ()
- subroutine **testEquals\_C\_0D1D** ()
- subroutine **testEquals\_C\_1D\_nonConformable1** ()
- subroutine **testEquals\_C\_2D\_SingleElementDifferent** ()
- subroutine **testEquals\_C\_MultiD\_SingleElementDifferent** ()
- subroutine **testEquals\_C\_MultiD\_SingleElementDifferent1**
- subroutine **testEquals\_C\_MultiD\_SingleElementDifferent2**
- subroutine **testEquals\_C\_MultiD\_SingleElementDifferent3**
- subroutine **testEquals\_C\_MultiD\_SingleElementDifferent4**
- subroutine **testEquals\_C\_MultiD\_SingleElementDifferent5**
- subroutine **testEquals\_C\_MultiDMultiPrec\_SingleEltDiff** ()
- subroutine **testEquals\_C\_MultiDMultiPrec\_SingleEltDiff1** ()
- subroutine **testEquals\_C\_MultiDMultiPrec\_SingleEltDiff2** ()
- subroutine **testEquals\_C\_MultiDMultiPrec\_SingleEltDiff3** ()
- subroutine **testEquals\_C\_MultiDMultiPrec\_SingleEltDiff4** ()
- subroutine **testEquals\_C\_MultiDMultiPrec\_SingleEltDiff5** ()
- subroutine **testEquals\_C\_MultiDMultiPrec\_SingleEltDiff6** ()
- subroutine **testEquals\_C\_MultiDMultiPrec\_SingleEltDiff7** ()
- subroutine **testEquals\_C\_MultiDMultiPrec\_SingleEltDiff8** ()
- subroutine **testEquals\_ScalarWithTolerance** ()
- subroutine **testEquals\_C\_MultiDWithTolerance** ()
- subroutine **testEquals\_C\_MultiDWithTolerance1** ()
- subroutine **testEquals\_C\_MultiDWithTolerance64** ()
- subroutine **testEquals\_C\_MultiDWithTolerance64\_1** ()
- subroutine **testEquals\_C\_MultiDWithTolerance64\_2** ()
- subroutine **testEquals\_C\_MultiDSourceLocation** ()
- subroutine **testEquals\_4DPComplex\_DifferenceReport** ()
- subroutine **testEquals\_ComplexMultiD\_SingleElementNE1**
- subroutine **testEquals\_ComplexMultiD\_SingleElementRE1**
- subroutine **testEquals\_ComplexMultiD\_SingleEltVarious1**
- subroutine **assertCatch** (string, location)

### 17.103.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

20 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_AssertComplex.F90

## 17.104 Test\_AssertInteger\_mod Module Reference

<BriefDescription>

**Public Member Functions**

- type(TestSuite) function, public **suite** ()
- subroutine **testAssertEqual\_equal** ()

### 17.104.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

20 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_AssertInteger.F90

## 17.105 Test\_AssertReal\_mod Module Reference

<BriefDescription>

**Public Member Functions**

- type(TestSuite) function, public **suite** ()
- subroutine **testEquals\_0D1D** ()
- subroutine **testEquals\_1D\_nonConformable1** ()
- subroutine **testEquals\_2D\_SingleElementDifferent** ()
- subroutine **testEquals\_MultiD\_SingleElementDifferent** ()
- subroutine **testEquals\_MultiD\_SingleElementDifferent1**
- subroutine **testEquals\_MultiD\_SingleElementDifferent2**
- subroutine **testEquals\_MultiD\_SingleElementDifferent3**
- subroutine **testEquals\_MultiD\_SingleElementDifferent4**
- subroutine **testEquals\_MultiD\_SingleElementDifferent5**
- subroutine **testEquals\_MultiDMultiPrec\_SingleEltDiff** ()
- subroutine **testEquals\_MultiDMultiPrec\_SingleEltDiff1** ()
- subroutine **testEquals\_MultiDMultiPrec\_SingleEltDiff2** ()
- subroutine **testEquals\_MultiDMultiPrec\_SingleEltDiff3** ()
- subroutine **testEquals\_MultiDMultiPrec\_SingleEltDiff4** ()
- subroutine **testEquals\_MultiDMultiPrec\_SingleEltDiff5** ()
- subroutine **testEquals\_MultiDMultiPrec\_SingleEltDiff6** ()
- subroutine **testEquals\_MultiDMultiPrec\_SingleEltDiff7** ()
- subroutine **testEquals\_MultiDMultiPrec\_SingleEltDiff8** ()
- subroutine **testEquals\_ScalarWithTolerance** ()
- subroutine **testEquals\_ScalarWithToleranceNoMsg** ()
- subroutine **testEquals\_VectorWithToleranceNoMsg** ()
- subroutine **testEquals\_MultiDWithTolerance** ()
- subroutine **testEquals\_MultiDWithTolerance1** ()
- subroutine **testEquals\_MultiDWithTolerance64** ()
- subroutine **testEquals\_MultiDWithTolerance64\_1** ()
- subroutine **testEquals\_MultiDWithTolerance64\_2** ()
- subroutine **testEquals\_MultiDSourceLocation** ()

- subroutine **testEquals\_ScalarAndLocation** ()
- subroutine **testEquals\_ScalarInfinity\_equal** ()
- subroutine **testEquals\_ScalarInfinity\_unequal\_A** ()
- subroutine **testEquals\_ScalarInfinity\_unequal\_B** ()
- subroutine **testEquals\_ScalarInfinity\_unequal\_C** ()
- subroutine **testEquals\_MultiD\_SingleElementGT1**
- subroutine **testEquals\_MultiD\_SingleElementGT2**
- subroutine **testEquals\_MultiD\_SingleEltVarious1**
- subroutine **testEquals\_MultiD\_SingleEltVarious2**
- subroutine **assertCatch** (string, location)

### 17.105.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

20 Mar 2015

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_AssertReal.F90

## 17.106 Test\_BasicOpenMP\_mod Module Reference

<BriefDescription>

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testRunWithOpenMP** ()
- subroutine **testSerializeExceptions** ()

### 17.106.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

20 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_BasicOpenMP.F90

## 17.107 Test\_Exception\_mod Module Reference

<BriefDescription>

**Public Member Functions**

- type(TestSuite) function, public **suite** ()
- subroutine **testGetNumExceptions** ()
- subroutine **testCatchSucceed** ()
- subroutine **testGetLineNumber** ()
- subroutine **testGetFileName** ()

### 17.107.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

20 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_Exception.F90

## 17.108 Test\_FixtureTestCase\_mod Module Reference

<BriefDescription>

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testRunWithFixture** ()
- subroutine **testBrokenTestCase** ()
- subroutine **testBrokenSetUpCase** ()

### 17.108.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

21 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_FixtureTestCase.F90



## 17.109 Test\_LinearInterpolator\_mod::Test\_LinearInterpolator Type Reference

### Public Member Functions

- procedure **setUp**
- procedure **tearDown**

### Public Attributes

- type(LinearInterpolator) **interpolator**

The documentation for this type was generated from the following file:

- Test\_LinearInterpolator.pf

## 17.110 Test\_LinearInterpolator\_mod Module Reference

### Data Types

- type [Test\\_LinearInterpolator](#)

### Public Member Functions

- subroutine **setUp** (this)
- subroutine **tearDown** (this)
- subroutine **testBracketAtNode** (this)
- subroutine **testBracketInterior** (this)
- subroutine **testInterpolateAtNode** (this)
- subroutine **testInterpolateConstant** (this)

The documentation for this module was generated from the following file:

- Test\_LinearInterpolator.pf

## 17.111 Test\_MockCall\_mod Module Reference

<BriefDescription>

### Public Member Functions

- type(`TestSuite`) function, public **suite** ()
- subroutine **testExpectOneIntegerArgument**
- subroutine **testFailExpectOneIntegerArgument**

#### 17.111.1 Detailed Description

<BriefDescription>

##### Author

Tom Clune, NASA/GSFC

##### Date

21 Mar 2015

##### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- `Test_MockCall.F90`

### 17.112 `Test_MockRepository_mod` Module Reference

#### Public Member Functions

- type(`TestSuite`) function, public **suite** ()
- subroutine **testNoAction** ()

The documentation for this module was generated from the following file:

- `Test_MockRepository.F90`

### 17.113 `Test_mod` Module Reference

<BriefDescription>

## Data Types

- interface [countTestCases](#)
- interface [getName](#)
- interface **run**
- type [Test](#)

### 17.113.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test.F90

## 17.114 Test\_MpiContext\_mod Module Reference

<BriefDescription>

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testNumProcesses1** (context)

### 17.114.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

21 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_MpiContext.F90

## 17.115 Test\_MpiException\_mod Module Reference

<BriefDescription>

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **test\_anyExceptions\_none** (this)
- subroutine **test\_getNumExceptions** (this)
- subroutine **test\_gather** (this)

### 17.115.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

21 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_MpiException.F90

## 17.116 Test\_MpiParameterizedTestCase\_mod Module Reference

<BriefDescription>

### Data Types

- type **ExtendedTestParameter**
- interface **method**
- type **Test\_MpiTestCase**

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- type(Test\_MpiTestCase) function, public **newTest\_MpiTestCase** (name, user-Method, testParameter)
- subroutine **testToString** (this)
- recursive subroutine **runMethod** (this)

### 17.116.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

21 Mar 2015

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_MpiParameterizedTestCase.F90

## 17.117 Test\_MpiTestCase\_mod Module Reference

<BriefDescription>

## Data Types

- interface **method**
- type **Test\_MpiTestCase**

## Public Member Functions

- type(TestSuite) function, public **suite** ()
- type(Test\_MpiTestCase) function, public **newTest\_MpiTestCase** (name, user-Method, numProcesses)
- subroutine **testRunOn2Processors** (this)
- subroutine **brokenProcess1** (this)
- subroutine **brokenOnProcess2** (this)
- subroutine **testFailOn1** (this)
- subroutine **testFailOn2** (this)
- subroutine **testTooFewProcs** (this)
- recursive subroutine **runMethod** (this)

### 17.117.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

21 Mar 2015

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_MpiTestCase.F90

## 17.118 Test\_Parameters\_mod::Test\_Parameters Type Reference

### Public Attributes

- integer **p1**
- integer **p2**

The documentation for this type was generated from the following file:

- parameterizedTests.pf

## 17.119 Test\_Parameters\_mod Module Reference

### Data Types

- type [peCase](#)
- type [Test\\_Parameters](#)

### Public Member Functions

- type([Test\\_Parameters](#)) function **newTest** (testParameter)
- type([peCase](#)) function **newPeCase** (p1, p2)
- type([peCase](#)) function, dimension(:), allocatable **getParameters** ()
- character(:) function, allocatable **toString** (this)
- subroutine **testParamBroken** (this)

The documentation for this module was generated from the following file:

- parameterizedTests.pf

## 17.120 Test\_RestrictSphericalCoordinates\_mod::Test\_Restrict-SphericalCoordinates Type Reference

### Public Attributes

- real **lat**
- real **lon**
- real **restrictedLat**
- real **restrictedLon**

- type(SphericalCoordinates) **unrestricted**
- type(SphericalCoordinates) **restricted**

The documentation for this type was generated from the following file:

- Test\_RestrictedSphericalCoordinates.pf

## 17.121 Test\_RestrictSphericalCoordinates\_mod Module Reference

### Data Types

- type [LatLonCase](#)
- type [Test\\_RestrictSphericalCoordinates](#)

### Public Member Functions

- type([Test\\_RestrictSphericalCoordinates](#)) function **newTest** (testParameter)
- type([LatLonCase](#)) function, dimension(:), allocatable **getParameters** ()
- subroutine **testRestrict** (this)
- character(:) function, allocatable **toString** (this)

The documentation for this module was generated from the following file:

- Test\_RestrictedSphericalCoordinates.pf

## 17.122 Test\_RobustRunner\_mod Module Reference

<BriefDescription>

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testRunVariety** ()

### 17.122.1 Detailed Description

<BriefDescription>



**Author**

Tom Clune, NASA/GSFC

**Date**

21 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_RobustRunner.F90

## 17.123 Test\_SimpleTestCase\_mod Module Reference

<BriefDescription>

**Public Member Functions**

- type(TestSuite) function, public **suite** ()
- type(TestSuite) function **internalSuite** ()
- subroutine **testWorks** ()
- subroutine **testFails** ()
- subroutine **testRunSuite** ()
- subroutine **testRunMethodShouldFail** ()

### 17.123.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

21 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_SimpleTestCase.F90

## 17.124 Test\_StringConversionUtilities\_mod Module Reference

<BriefDescription>

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testToStringInteger1D** ()

### 17.124.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

21 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_StringConversionUtilities.F90

## 17.125 Test\_TestMethod\_mod Module Reference

<BriefDescription>

## Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testMethodWasRun** ()
- subroutine **testWasRun** ()

### 17.125.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

21 Mar 2015

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_TestMethod.F90

## 17.126 Test\_TestResult\_mod Module Reference

<BriefDescription>

## Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testGetNumRun** ()
- subroutine **testGetNumFailed** ()
- subroutine **testAddListenerEnd** ()
- subroutine **testAddListenerStart** ()
- subroutine **testAddListenerFailure** ()

### 17.126.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

21 Mar 2015

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_TestResult.F90

## 17.127 Test\_TestSuite\_mod Module Reference

<BriefDescription>

### Data Types

- type **Verbose**

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testCountTestCases** ()
- subroutine **testCountTestCasesNestedA** ()
- subroutine **testCountTestCasesNestedB** ()
- subroutine **testCountTestCasesNestedC** ()
- subroutine **testGetTestCases** ()
- subroutine **myTestMethod** ()

### 17.127.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

21 Mar 2015

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_TestSuite.F90

## 17.128 Test\_UnixProcess\_mod Module Reference

<BriefDescription>

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testIsActive** ()

### 17.128.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

21 Mar 2015

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- Test\_UnixProcess.F90

## 17.129 Test\_XmlPrinter\_mod Module Reference

Output test messages in junit.xsd-compatible XML.

### Public Member Functions

- type(TestSuite) function, public **suite** ()
- subroutine **testValidXml** ()
- subroutine **compareXMLFileToExpectation** (xmlFile)

### 17.129.1 Detailed Description

Output test messages in junit.xsd-compatible XML.

**Author**

Halvor Lund

**Date**

2014 July

**Note**

Set up a test failure and feed it to an XML-based printer so that we can test its output. Use command line call (via "system") to try to find "xmllint," and if available, use it to validate the output against junit.xsd. Either way, check the output against a hard-coded expected result (a regression test).

The documentation for this module was generated from the following file:

- Test\_XmlPrinter.F90

## 17.130 TestA\_mod Module Reference

### Public Member Functions

- subroutine **testMethodA** ()
- subroutine **testMethodB** ()
- subroutine **testMethodC** (this)
- subroutine **testMethodA** ()
- subroutine **testMethodB** ()
- subroutine **testMethodC** (this)

The documentation for this module was generated from the following files:

- TestA.F90
- TestA.pf

## 17.131 TestCase\_mod Module Reference

<BriefDescription>

### Data Types

- type **ConcreteSurrogate**
- type **TestCase**
- type **TestCaseReference**

### Public Member Functions

- recursive subroutine **runBare** (this)
- recursive subroutine **runBare\_surrogate** (this)

### 17.131.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- TestCase.F90

## 17.132 TestCaseA\_mod::TestCaseA Type Reference

**Public Member Functions**

- procedure **setUp**
- procedure **tearDown**
- procedure **setUp**
- procedure **tearDown**

**Public Attributes**

- integer **componentI**

The documentation for this type was generated from the following files:

- TestCaseA.F90
- TestCaseA.pf

## 17.133 TestCaseA\_mod Module Reference

**Data Types**

- type [TestCaseA](#)

**Public Member Functions**

- subroutine **setUp** (this)
- subroutine **tearDown** (this)



- subroutine **testA** (this)
- subroutine **testB** (this)
- subroutine **setUp** (this)
- subroutine **tearDown** (this)
- subroutine **testA** (this)
- subroutine **testB** (this)

The documentation for this module was generated from the following files:

- `TestCaseA.F90`
- `TestCaseA.pf`

## 17.134 `TestCaseB_mod::TestCaseB` Type Reference

### Public Member Functions

- procedure **setUp**
- procedure **tearDown**
- procedure **setUp**
- procedure **tearDown**

### Public Attributes

- integer, dimension(:), allocatable **table**
- real **phi**
- real **theta**

The documentation for this type was generated from the following files:

- `ParameterizedTestCaseB.F90`
- `ParameterizedTestCaseB.pf`

## 17.135 `TestCaseB_mod` Module Reference

### Data Types

- type [B\\_Parameter](#)
- type [TestCaseB](#)

### Public Member Functions

- type([TestCaseB](#)) function **newTestCaseB** (testParameter)
- subroutine **setUp** (this)
- subroutine **tearDown** (this)
- subroutine **testA** (this)
- subroutine **testB** (this)
- character(:) function, allocatable **toString** (this)
- type([TestCaseB](#)) function **newTestCaseB** (testParameter)
- subroutine **setUp** (this)
- subroutine **tearDown** (this)
- subroutine **testA** (this)
- subroutine **testB** (this)
- character(:) function, allocatable **toString** (this)

The documentation for this module was generated from the following files:

- ParameterizedTestCaseB.F90
- ParameterizedTestCaseB.pf

## 17.136 TestCaseC\_mod::TestCaseC Type Reference

### Public Member Functions

- procedure **setUp**
- procedure **tearDown**
- procedure **setUp**
- procedure **tearDown**

### Public Attributes

- integer, dimension(:), allocatable **table**
- real **phi**
- real **theta**

The documentation for this type was generated from the following files:

- MpiParameterizedTestCaseC.F90
- MpiParameterizedTestCaseC.pf

## 17.137 TestCaseC\_mod Module Reference

### Data Types

- type [C\\_Parameter](#)
- interface [newC\\_Parameter](#)
- type [TestCaseC](#)

### Public Member Functions

- type([TestCaseC](#)) function **newTestCaseC** (testParameter)
- subroutine **setUp** (this)
- subroutine **tearDown** (this)
- subroutine **testA** (this)
- subroutine **testB** (this)
- subroutine **testC** (this)
- type([C\\_Parameter](#)) function **newC\_Parameter\_phiTheta** (npes, phi, theta)
- elemental function **newC\_Parameter\_case** (i)
- type([C\\_Parameter](#)) function, allocatable **paramGenerator** ()
- character(:) function, allocatable **toString** (this)
- type([TestCaseC](#)) function **newTestCaseC** (testParameter)
- subroutine **setUp** (this)
- subroutine **tearDown** (this)
- subroutine **testA** (this)
- subroutine **testB** (this)
- subroutine **testC** (this)
- type([C\\_Parameter](#)) function **newC\_Parameter\_phiTheta** (npes, phi, theta)
- elemental function **newC\_Parameter\_case** (i)
- type([C\\_Parameter](#)) function, allocatable **paramGenerator** ()
- character(:) function, allocatable **toString** (this)

The documentation for this module was generated from the following files:

- `MpiParameterizedTestCaseC.F90`
- `MpiParameterizedTestCaseC.pf`

## 17.138 TestFailure\_mod Module Reference

<BriefDescription>

## Data Types

- type **TestFailure**

### 17.138.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- TestFailure.F90

## 17.139 mods::pre::pre\_if::TestIfDirective Class Reference

### Public Member Functions

- def **testTokenNotFound1**
- def **testNoTest**
- def **testIFTestFalse**
- def **testIFTestTrue1**
- def **testIFTestTrue2**
- def **testIFClearTokens**
- def **testIFClearTokensUntilEnd1**

The documentation for this class was generated from the following file:

- pre\_if.py

## 17.140 `mods::pre::interleavedp::TestInterleaved` Class Reference

### Public Member Functions

- def `test_InOrder`
- def `test_NumberMismatch`
- def `test_OrderMismatch1`
- def `test_OrderMismatch2`
- def `test_OrderMismatch3`
- def `test_ElseMid1`
- def `test_ElseMid2`
- def `test_ElseMid3`
- def `test_ElseMid4`
- def `test_ElseMid5`
- def `test_ElseMid6`
- def `test_ElseMid7`
- def `test_ElseMid8`
- def `test_ElseMid9`
- def `test_ElseMid10`

The documentation for this class was generated from the following file:

- `interleavedp.py`

## 17.141 `TestListener_mod` Module Reference

<BriefDescription>

### Data Types

- interface `addFailure`
- interface `endRun`
- interface `endTest`
- type `ListenerPointer`
- interface `startTest`
- type `TestListener`

### Public Member Functions

- subroutine `addError` (this, testName, exceptions)
- subroutine `setDebug` (this)

### 17.141.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- TestListener.F90

## 17.142 TestMethod\_mod Module Reference

<BriefDescription>

### Data Types

- interface **empty**
- interface **newTestMethod**
- type **TestMethod**

### 17.142.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- TestMethod.F90

## 17.143 mods::pre::parseArgs::TestParseArgs Class Reference

**Public Member Functions**

- def **test\_ParseArgs\_OneArgWithBrackets1**
- def **test\_ParseArgs\_OneArgWithBrackets2**
- def **test\_ParseArgs\_OneArgWithBrackets3**
- def **test\_ParseArgs\_OneArgWithBrackets4**
- def **test\_ParseArgs\_OneArgWithBrackets5**
- def **test\_ParseArgs\_OneArgWithBrackets6**
- def **test\_ParseArgs\_OneArgWithBrackets7**
- def **test\_ParseArgs\_oneArg**
- def **test\_ParseArgs\_twoArgs1**
- def **test\_ParseArgs\_twoArgs2**
- def **test\_ParseArgs\_oneArgArray1**
- def **test\_ParseArgs\_TwoArgArray**
- def **test\_ParseArgs\_ThreeArgs**

The documentation for this class was generated from the following file:

- parseArgs.py

## 17.144 parseDirectiveArgs::TestParseDirectiveArgs Class Reference

**Public Member Functions**

- def **test\_args1**
- def **test\_args2**
- def **test\_args3**
- def **test\_args4**
- def **test\_args5**

The documentation for this class was generated from the following file:

- parseDirectiveArgs.py

## 17.145 testParser::TestParseLine Class Reference

### Public Member Functions

- def **testCppSetLineAndFile**
- def **testGetSubroutineName**
- def **testGetSelfObjectName**
- def **testGetTypeNames**
- def [testAtTest](#)
- def [testAtTestNoParens](#)
- def [testAtTestFail](#)
- def [testAtTestSkipComment](#)
- def [testAtMpiTest](#)
- def [testMatchAtTestCase](#)
- def [testMatchAtAssertEqual](#)
- def [testParseArgsFirstRest](#)
- def [testParseArgsFirstSecondRest](#)
- def [testMatchAtAssertAssociated](#)
- def [testMatchAtAssertAssociatedOverloaded1](#)
- def [testMatchAtAssertAssociatedOverloaded2](#)
- def [testMatchAtAssertUnAssociated](#)
- def [testMatchAtAssertUnAssociatedWith](#)
- def [testMatchAtAssertNotassociated](#)
- def [testMatchAtAssertNotassociatedWith](#)
- def [testMatchAtAssertEqualUserDefined](#)
- def [testMatchAtAssertEqualUserDefinedWithMessage](#)
- def [testMatchAtAssertEquivalent](#)
- def [testMatchAtAssertOther](#)
- def [testMatchAtMpiAssert](#)
- def [testMatchAtBefore](#)
- def [testMatchAtAfter](#)
- def [testMatchAtSuite](#)

### 17.145.1 Member Function/Subroutine Documentation

#### 17.145.1.1 def testParser::TestParseLine::testAtMpiTest ( *self* )

Check that a line starting with '@mpitest' is detected as an annotation and that optional parameters are collected.



**17.145.1.2 def testParser::TestParseLine::testAtTest ( self )**

Check that a line starting with '@test' is detected as an annotation.

**17.145.1.3 def testParser::TestParseLine::testAtTestFail ( self )**

Check that useful error is sent if next line is not properly formatted.

**17.145.1.4 def testParser::TestParseLine::testAtTestNoParens ( self )**

Check that test procedure with no parens is accepted.

**17.145.1.5 def testParser::TestParseLine::testAtTestSkipComment ( self )**

Ignore comment lines between @test and subroutine foo().

**17.145.1.6 def testParser::TestParseLine::testMatchAtAfter ( self )**

Check that a line starting with '@after\*' ...

**17.145.1.7 def testParser::TestParseLine::testMatchAtAssertAssociated ( self )**

Check that a line starting with '@assertAssociated' is detected as an annotation.

**17.145.1.8 def testParser::TestParseLine::testMatchAtAssertAssociated-Overloaded1 ( self )**

Check that a line starting with '@assertAssociated' is detected as an annotation. atAssertAssociated(a,b) implies a points to b. Overriding the name @assertAssociated.

**17.145.1.9 def testParser::TestParseLine::testMatchAtAssertAssociated-Overloaded2 ( self )**

Check that a line starting with '@assertAssociated' is detected as an annotation. atAssertAssociated(a,b) implies a points to b. Overriding the name @assertAssociated.

**17.145.1.10 def testParser::TestParseLine::testMatchAtAssertEqual ( self )**

Check that a line starting with '@assertEqual' is detected as an annotation.

**17.145.1.11 def testParser::TestParseLine::testMatchAtAssertEqualUserDefined ( self )**

Check that a line starting with '@assertEqualUserDefined' is detected as an annotation. atAssertEqualUserDefined(a,b) implies a points to b.

**17.145.1.12 def testParser::TestParseLine::testMatchAtAssertEqualUserDefined-  
WithMessage ( self )**

Check that a line starting with '@assertEqualUserDefined' is detected as an annotation. atAssertEqualUserDefined(a,b) implies a points to b.

**17.145.1.13 def testParser::TestParseLine::testMatchAtAssertEquivalent ( self )**

Check that a line starting with '@assertEquivalent' is detected as an annotation. atAssertEquivalent(a,b) implies a points to b.

**17.145.1.14 def testParser::TestParseLine::testMatchAtAssertNotassociated ( self )**

Check that a line starting with '@assertNotAssociated' is detected as an annotation.

**17.145.1.15 def testParser::TestParseLine::testMatchAtAssertNotassociatedWith ( self )**

Check that a line starting with '@assertNotassociatedWith' is detected as an annotation. atAssertNotassociated(a,b) implies a points to b.

**17.145.1.16 def testParser::TestParseLine::testMatchAtAssertOther ( self )**

Check that a line starting with '@assert\*' is detected as an annotation.

**17.145.1.17** `def testParser::TestParseLine::testMatchAtAssertUnAssociated ( self )`

Check that a line starting with '@assertUnAssociated' is detected as an annotation.

**17.145.1.18** `def testParser::TestParseLine::testMatchAtAssertUnAssociatedWith ( self )`

Check that a line starting with '@assertUnAssociatedWith' is detected as an annotation. atAssertUnAssociated(a,b) implies a points to b.

**17.145.1.19** `def testParser::TestParseLine::testMatchAtBefore ( self )`

Check that a line starting with '@before\*' ...

**17.145.1.20** `def testParser::TestParseLine::testMatchAtMpiAssert ( self )`

Check that a line starting with '@mpiAssert\*' is detected as an annotation.

**17.145.1.21** `def testParser::TestParseLine::testMatchAtSuite ( self )`

Check that a line starting with '@suite changes the suite name ...

**17.145.1.22** `def testParser::TestParseLine::testMatchAtTestCase ( self )`

Check that a line starting with '@testcase' is detected as an annotation.

**17.145.1.23** `def testParser::TestParseLine::testParseArgsFirstRest ( self )`

Test that the first-rest argument parsing is adequate.

#### 17.145.1.24 `def testParser::TestParseLine::testParseArgsFirstSecondRest ( self )`

Test that the first-second-rest argument parsing is adequate.

The documentation for this class was generated from the following file:

- testParser.py

### 17.146 `parseBrackets::TestRejoinBracketed` Class Reference

#### Public Member Functions

- `def testRejoinBracketed`
- `def testParseBrackets`

The documentation for this class was generated from the following file:

- parseBrackets.py

### 17.147 `mods::pre::pre_Repeat::TestRepeatDirective` Class Reference

#### Public Member Functions

- `def test_copyBlock1`
- `def test_copyBlock2`
- `def test_copyBlock2Vars`
- `def test_copyBlock2VarsMulti`
- `def test_copyBlock2VarsMultiWithStrings`
- `def test_copyNaiveRecursion`
- `def test_copyNaiveRecursion1`
- `def test_copyFunction1`

The documentation for this class was generated from the following file:

- pre\_Repeat.py

### 17.148 `TestResult_mod` Module Reference

<BriefDescription> Note: A possible extension point for user-specialized TestResults.

## Data Types

- type **TestResult**

## Public Member Functions

- type(TestResult) function, public **newTestResult** (name)
- subroutine **addError** (this, aTest, exceptions)
- subroutine **addSuccess** (this, aTest)
- integer function **failureCount** (this)
- subroutine **endTest** (this, aTest)
- subroutine **addListener** (this, listener)

### 17.148.1 Detailed Description

<BriefDescription> Note: A possible extension point for user-specialized TestResults.

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- TestResult.F90

## 17.149 TestRunner\_mod Module Reference

<BriefDescription>

## Data Types

- interface **newTestRunner**
- type **TestRunner**

### Public Member Functions

- type(TestResult) function **run** (this, aTest, context)
- subroutine **startTest** (this, testName)
- subroutine **addFailure** (this, testName, exceptions)

#### 17.149.1 Detailed Description

<BriefDescription>

##### Author

Tom Clune, NASA/GSFC

##### Date

07 Nov 2013

##### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- TestRunner.F90

### 17.150 TestSuite\_mod Module Reference

<BriefDescription>

#### Data Types

- interface **newTestSuite**
- type **TestReference**
- type **TestSuite**

#### Public Member Functions

- recursive subroutine **addTest** (this, aTest)

### 17.150.1 Detailed Description

<BriefDescription>

#### Author

Tom Clune, NASA/GSFC

#### Date

07 Nov 2013

#### Note

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- TestSuite.F90

## 17.151 ThrowFundamentalTypes\_mod Module Reference

<BriefDescription>

### Data Types

- interface **throwDifferentValues**
- interface **throwDifferentValuesWithLocation**

### Public Member Functions

- subroutine, public **throwNonConformable** (shapeExpected, shapeFound, location)
- character(len=MAXLEN\_SHAPE) function, public **locationFormat** (iLocation)

### 17.151.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- ThrowFundamentalTypes.F90

## 17.152 UnixPipeInterfaces\_mod Module Reference

<BriefDescription>

### Data Types

- interface **fgets**
- interface **free**
- interface **getdelim**
- interface **getline**
- interface **pclose**
- interface **popen**

### Public Attributes

- integer(C\_INT), parameter, public **CLOSE\_FAILED** = -1

### 17.152.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC



**Date**

07 Nov 2013

**Note**

<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- UnixPipeInterfaces.F90

## 17.153 UnixProcess\_mod Module Reference

<BriefDescription>

**Data Types**

- interface **UnixProcess**

**Public Member Functions**

- character(len=:) function, allocatable **makeCommand** (baseCommand, runIn-Background)
- logical function **isActive** (this)
- character(len=:) function, allocatable **getDelim** (this, delimiter)
- integer function **getPid** (this)

### 17.153.1 Detailed Description

<BriefDescription>

**Author**

Tom Clune, NASA/GSFC

**Date**

07 Nov 2013

**Note**


<A note here.> <Or starting here...>

The documentation for this module was generated from the following file:

- UnixProcess.F90

## 17.154 **GenerateAssertsOnArrays::VECTOR\_NORM** Class Reference

Inheritance diagram for GenerateAssertsOnArrays::VECTOR\_NORM:

**Public Member Functions**

- `def __init__`

**Public Attributes**

- **rank**
- **fType**
- **precision**
- **name**
- **declaration**
- **declarations**

The documentation for this class was generated from the following file:

- GenerateAssertsOnArrays.py

## 17.155 **AbstractTestResult\_mod::wasSuccessful** Interface Reference

The documentation for this interface was generated from the following file:

- AbstractTestResult.F90

## 17.156 WrapbeforeAfter Module Reference

The documentation for this module was generated from the following file:

- beforeAfter.F90

## 17.157 WrapMpiTestCaseB\_mod Module Reference

### Data Types

- interface **userTestMethod**
- type **WrapUserTestCase**

### Public Member Functions

- subroutine **runMethod** (this)
- type(WrapUserTestCase) function, public **makeCustomTest** (methodName, testMethod, npesRequested)

The documentation for this module was generated from the following file:

- MpiTestCaseB.F90

## 17.158 Wrapsimple Module Reference

The documentation for this module was generated from the following file:

- simple.F90

## 17.159 WrapTestA\_mod Module Reference

The documentation for this module was generated from the following file:

- TestA.F90

## 17.160 WrapTestCaseA\_mod Module Reference

### Data Types

- interface **userTestMethod**
- type **WrapUserTestCase**

### Public Member Functions

- subroutine **runMethod** (this)
- type(WrapUserTestCase) function, public **makeCustomTest** (methodName, testMethod)

The documentation for this module was generated from the following file:

- TestCaseA.F90

## 17.161 WrapTestCaseB\_mod Module Reference

### Data Types

- interface **userTestMethod**
- type **WrapUserTestCase**

### Public Member Functions

- subroutine **runMethod** (this)
- type(WrapUserTestCase) function, public **makeCustomTest** (methodName, testMethod, testParameter)

The documentation for this module was generated from the following file:

- ParameterizedTestCaseB.F90

## 17.162 WrapTestCaseC\_mod Module Reference

### Data Types

- interface **userTestMethod**
- type **WrapUserTestCase**

## Public Member Functions

- subroutine **runMethod** (this)
- type(WrapUserTestCase) function, public **makeCustomTest** (methodName, testMethod, testParameter, npesRequested)

The documentation for this module was generated from the following file:

- `MpiParameterizedTestCaseC.F90`

## 17.163 XmlPrinter\_mod Module Reference

<BriefDescription>

## Data Types

- type **XmlPrinter**

## Public Member Functions

- type(XmlPrinter) function, public **newXmlPrinter** (unit)
- subroutine **addError** (this, testName, exceptions)
- subroutine **startTest** (this, testName)
- subroutine **print** (this, result)
- subroutine **printHeader** (this, result)
- subroutine **printFailure** (this, label, aFailedTest)
- subroutine **printExceptions** (this, label, testName, exceptions)
- subroutine **printFailure1** (this, label, aFailedTest)
- subroutine **printFailures** (this, label, failures)
- subroutine **printTestName** (this, testName)
- subroutine **printSuccess** (this, aSuccessTest)
- subroutine **printSuccesses** (this, successes)
- subroutine **printFooter** (this, result)
- character(:) function, allocatable **cleanXml** (string\_in)

### 17.163.1 Detailed Description

<BriefDescription>

**Author**

Halvor Lund, SINTEF Energy Research

**Date**

30 Jan 2014

**Note**

<A note here.> Need to improve the handling of nested quotes.

The documentation for this module was generated from the following file:

- XmlPrinter.F90