

Section 4: Threads and Context Switching

CS162

February 9, 2016

Contents

1	Warmup	2
1.1	Hello World	2
2	Vocabulary	2
3	Problems	3
3.1	Join	3
3.2	Stack Allocation	4
3.3	Heap Allocation	4
3.4	Threads and Processes	5
3.5	Context Switching	6
3.6	Interrupt Handlers	7
3.7	Pintos Context Switch	8
3.8	Pintos Interrupt Handler	9

1 Warmup

1.1 Hello World

What does C print in the following code?

```
void identify() {
    pid_t pid = getpid();
    printf("My pid is %d\n", pid);
    return NULL;
}

void main() {
    pthread_t thread;
    pthread_create(&thread, NULL, (void *) &identify, NULL);
    identify();
}
```

2 Vocabulary

- **thread** - a thread of execution is the smallest unit of sequential instructions that can be scheduled for execution by the operating system. Multiple threads can share the same address space, but each thread independently operates using its own program counter.
- **threads** - A POSIX-compliant (standard specified by IEEE) implementation of threads. A `pthread_t` is usually just an alias for “unsigned long int”.
- **pthread_create** - Creates and immediately starts a child thread running in the same address space of the thread that spawned it. The child executes starting from the function specified. Internally, this is implemented by calling the clone syscall.

```
/* On success, pthread_create() returns 0; on error, it returns an error
 * number, and the contents of *thread are undefined. */
int pthread_create(pthread_t *thread, const pthread_attr_t *attr,
                  void *(*start_routine) (void *), void *arg);
```

- **pthread_join** - Waits for a specific thread to terminate, similar to `waitpid(3)`.

```
/* On success, pthread_join() returns 0; on error, it returns an error number. */
int pthread_join(pthread_t thread, void **retval);
```

- **pthread_yield** - Equivalent to `thread_yield()` in Pintos. Causes the calling thread to vacate the CPU and go back into the ready queue without blocking. The calling thread is able to be scheduled again immediately. This is not the same as an interrupt and will succeed in Pintos even if interrupts are disabled.

```
/* On success, pthread_yield() returns 0; on error, it returns an error number. */
int pthread_yield(void);
```

3 Problems

3.1 Join

What does C print in the following code?

(Hint: There may be zero, one, or multiple answers.)

```
void main() {
    pthread_t thread;
    pthread_create(&thread, NULL, &helper, NULL);
    pthread_yield();
    printf("MAIN\n");
    exit(0);
}

void *helper(void *arg) {
    printf("HELPER\n");
    return NULL;
}
```

How can we modify the code above to always print out "HELPER" followed by "MAIN"?

3.2 Stack Allocation

What does C print in the following code?

```
void main() {
    int i = 0;
    pthread_t thread;
    pthread_create(&thread, NULL, &helper, &i);
    pthread_join(thread, NULL);
    printf("i is %d\n", i);
}

void *helper(void *arg) {
    int *num = (int*) arg;
    *num = 2;
    return NULL;
}
```

3.3 Heap Allocation

What does C print in the following code?

```
void main() {
    char *message = malloc(100);
    strcpy(message, "I am the parent");
    pthread_t thread;
    pthread_create(&thread, NULL, &helper, message);
    pthread_join(thread, NULL);
    printf("%s\n", message);
}

void *helper(void *arg) {
    char *message = (char *) arg;
    strcpy(message, "I am the child");
    return NULL;
}
```

3.4 Threads and Processes

What does C print in the following code?

(Hint: There may be zero, one, or multiple answers.)

```
void *worker(void *arg) {
    int *data = (int *) arg;
    *data = *data + 1;
    printf("Data is %d\n", *data);
    return (void *) 42;
}

int data;
void main() {
    int status;
    data = 0;
    pthread_t thread;

    pid_t pid = fork();
    if (pid == 0) {
        pthread_create(&thread, NULL, &worker, &data);
        pthread_join(thread, NULL);
    } else {
        pthread_create(&thread, NULL, &worker, &data);
        pthread_join(thread, NULL);
        pthread_create(&thread, NULL, &worker, &data);
        pthread_join(thread, NULL);
        wait(&status);
    }
}
```

How would you retrieve the return value of worker? (e.g. "42")

3.5 Context Switching

Refer to the “Pintos Context Switch” section at the end of this discussion worksheet to answer these questions:

How many stacks are involved in a context switch? Identify the purpose of each stack.

The value of `SWITCH_CUR` is 20. The value of `SWITCH_NEXT` is 24. With this information, please draw the stack frame of `switch_threads` for a thread that is about to switch the stack pointer to the next thread’s stack. Your stack frame should include the arguments `cur` and `next`.

In addition to the code inside `switch_threads`, what other actions are required to perform a context switch between 2 **user program threads**?

In order to perform a context switch, the kernel must copy all of a thread’s registers onto the CPU’s registers. How is the `%eip` (instruction pointer) register copied onto the CPU? Identify which instruction is responsible for this.

3.6 Interrupt Handlers

Refer to the “Pintos Interrupt Handler” section at the end of this discussion worksheet to answer these questions:

What do the instructions `pushal` and `popal` do?

The interrupt service routine (ISR) must run with the kernel’s stack. Why is this the case? And which instruction is responsible for switching the stack pointer to the kernel stack?

The `pushal` instruction pushes 8 values onto the stack (32 bytes). With this information, please draw the stack at the moment when “`call intr_handler`” is about to be executed.

What is the purpose of the “`pushl %esp`” instruction that is right before “`call intr_handler`”?

Inside the `intr_exit` function, what would happen if we reversed the order of the 5 `pop` instructions?

3.7 Pintos Context Switch

```

3 ##### struct thread *switch_threads (struct thread *cur, struct thread *next);
4 #####
5 ##### Switches from CUR, which must be the running thread, to NEXT,
6 ##### which must also be running switch_threads(), returning CUR in
7 ##### NEXT's context.
8 #####
9 ##### This function works by assuming that the thread we're switching
10 ##### into is also running switch_threads(). Thus, all it has to do is
11 ##### preserve a few registers on the stack, then switch stacks and
12 ##### restore the registers. As part of switching stacks we record the
13 ##### current stack pointer in CUR's thread structure.
14
15 .globl switch_threads
16 .func switch_threads
17 switch_threads:
18     # Save caller's register state.
19     #
20     # Note that the SVR4 ABI allows us to destroy %eax, %ecx, %edx,
21     # but requires us to preserve %ebx, %ebp, %esi, %edi. See
22     # [SysV-ABI-386] pages 3-11 and 3-12 for details.
23     #
24     # This stack frame must match the one set up by thread_create()
25     # in size.
26     pushl %ebx
27     pushl %ebp
28     pushl %esi
29     pushl %edi
30
31     # Get offsetof (struct thread, stack).
32 .globl thread_stack_ofs
33     mov thread_stack_ofs, %edx
34
35     # Save current stack pointer to old thread's stack, if any.
36     movl SWITCH_CUR(%esp), %eax
37     movl %esp, (%eax,%edx,1)
38
39     # Restore stack pointer from new thread's stack.
40     movl SWITCH_NEXT(%esp), %ecx
41     movl (%ecx,%edx,1), %esp
42
43     # Restore caller's register state.
44     popl %edi
45     popl %esi
46     popl %ebp
47     popl %ebx
48     ret
49 .endfunc

```


3.8 Pintos Interrupt Handler

```

1 /**
2  * An example of an entry point that would reside in the interrupt
3  * vector. This entry point is for interrupt number 0x30.
4  */
5 .func intr30_stub
6 intr30_stub:
7     pushl %ebp      /* Frame pointer */
8     pushl $0        /* Error code */
9     pushl $0x30     /* Interrupt vector number */
10    jmp intr_entry
11 .endfunc
12 /* Main interrupt entry point.
13
14    An internal or external interrupt starts in one of the
15    intrNN_stub routines, which push the 'struct intr_frame'
16    frame_pointer, error_code, and vec_no members on the stack,
17    then jump here.
18
19    We save the rest of the 'struct intr_frame' members to the
20    stack, set up some registers as needed by the kernel, and then
21    call intr_handler(), which actually handles the interrupt.
22
23    We "fall through" to intr_exit to return from the interrupt.
24 */
25 .func intr_entry
26 intr_entry:
27     /* Save caller's registers. */
28     pushl %ds
29     pushl %es
30     pushl %fs
31     pushl %gs
32     pushal
33
34     /* Set up kernel environment. */
35     cld                /* String instructions go upward. */
36     mov $SEL_KDSEG, %eax /* Initialize segment registers. */
37     mov %eax, %ds
38     mov %eax, %es
39     leal 56(%esp), %ebp /* Set up frame pointer. */
40
41     /* Call interrupt handler. */
42     pushl %esp
43 .globl intr_handler
44     call intr_handler
45     addl $4, %esp
46 .endfunc

```

```
48 /* Interrupt exit.
49
50     Restores the caller's registers, discards extra data on the
51     stack, and returns to the caller.
52
53     This is a separate function because it is called directly when
54     we launch a new user process (see start_process() in
55     userprog/process.c). */
56 .globl intr_exit
57 .func intr_exit
58 intr_exit:
59     /* Restore caller's registers. */
60     popal
61     popl %gs
62     popl %fs
63     popl %es
64     popl %ds
65
66     /* Discard 'struct intr_frame' vec_no, error_code,
67     frame_pointer members. */
68     addl $12, %esp
69
70     /* Return to caller. */
71     iret
72 .endfunc
```