

Schéma de base de données

Application type Uber Eats — toutes les tables

33 tables • 6 domaines • ● rouge = PK ● bleu = FK

UTILISATEURS

users	type	info
● id	<i>uuid</i>	PK
email	<i>varchar</i>	
phone	<i>varchar</i>	
name	<i>varchar</i>	
photo_url	<i>text</i>	
preferences	<i>jsonb</i>	
allergies	<i>jsonb</i>	
phone_verified	<i>boolean</i>	
created_at	<i>timestamp</i>	
updated_at	<i>timestamp</i>	

user_addresses	type	info
● id	<i>uuid</i>	PK
● user_id	<i>uuid</i>	FK → users
label	<i>varchar</i>	
street	<i>varchar</i>	
city	<i>varchar</i>	
lat	<i>float</i>	
lng	<i>float</i>	
is_default	<i>boolean</i>	

payment_methods	type	info
● id	<i>uuid</i>	PK
● user_id	<i>uuid</i>	FK → users
type	<i>enum</i>	— cb/paypal/apple/google
stripe_token	<i>varchar</i>	
last4	<i>char(4)</i>	
is_default	<i>boolean</i>	

user_sessions	type	info
● id	<i>uuid</i>	PK
● user_id	<i>uuid</i>	FK → users
token	<i>varchar</i>	
device	<i>varchar</i>	
ip	<i>inet</i>	
expires_at	<i>timestamp</i>	

otp_codes	type	info
● id	<i>uuid</i>	PK
● user_id	<i>uuid</i>	FK → users
code	<i>char(6)</i>	
purpose	<i>enum</i>	— phone_verify/login
expires_at	<i>timestamp</i>	
used_at	<i>timestamp</i>	

subscriptions	type	info
● id	<i>uuid</i>	PK
● user_id	<i>uuid</i>	FK → users
plan	<i>enum</i>	— free/premium
price	<i>decimal</i>	
status	<i>enum</i>	— active/cancelled/expired
started_at	<i>timestamp</i>	
expires_at	<i>timestamp</i>	

RESTAURANTS

restaurants	type	info
● id	<i>uuid</i>	PK
● owner_id	<i>uuid</i>	FK → users
name	<i>varchar</i>	
description	<i>text</i>	
logo_url	<i>text</i>	
address	<i>varchar</i>	
lat / lng	<i>float</i>	
opening_hours	<i>jsonb</i>	
is_active	<i>boolean</i>	
rating_avg	<i>float</i>	
rating_count	<i>int</i>	
cuisine_type	<i>varchar</i>	
prep_time_min	<i>int</i>	
delivery_fee	<i>decimal</i>	

menu_categories	type	info
● id	<i>uuid</i>	PK
● restaurant_id	<i>uuid</i>	FK → restaurants
name	<i>varchar</i>	
position	<i>int</i>	
availability	<i>enum</i>	— always/lunch/dinner/weekend

menu_items	type	info
● id	<i>uuid</i>	PK
● category_id	<i>uuid</i>	FK → menu_categories
name	<i>varchar</i>	
description	<i>text</i>	
photo_url	<i>text</i>	
price	<i>decimal</i>	
is_available	<i>boolean</i>	
is_popular	<i>boolean</i>	

menu_item_stock	type	info
● id	<i>uuid</i>	PK
● item_id	<i>uuid</i>	FK → menu_items
quantity	<i>int</i>	
is_unlimited	<i>boolean</i>	
updated_at	<i>timestamp</i>	

menu_item_options	type	info
● id	<i>uuid</i>	PK
● item_id	<i>uuid</i>	FK → menu_items
name	<i>varchar</i>	— ex: "Cuisson"
type	<i>enum</i>	— single/multiple
is_required	<i>boolean</i>	

menu_item_option_values	type	info
● id	<i>uuid</i>	PK
● option_id	<i>uuid</i>	FK → menu_item_options
label	<i>varchar</i>	— ex: "Saignant"
extra_price	<i>decimal</i>	

COMMANDES

orders	type	info
● id	<i>uuid</i>	PK
● user_id	<i>uuid</i>	FK → users
● restaurant_id	<i>uuid</i>	FK → restaurants
● driver_id	<i>uuid</i>	FK → drivers
● delivery_address_id	<i>uuid</i>	FK → user_addresses
● promo_code_id	<i>uuid</i>	FK → promo_codes
● payment_method_id	<i>uuid</i>	FK → payment_methods
status	<i>enum</i>	— created/confirmed/preparing/ready/picked_up/delivering/delivered
subtotal	<i>decimal</i>	
delivery_fee	<i>decimal</i>	
taxes	<i>decimal</i>	
tip_amount	<i>decimal</i>	
total	<i>decimal</i>	
estimated_delivery_at	<i>timestamp</i>	
delivered_at	<i>timestamp</i>	
created_at	<i>timestamp</i>	

order_items	type	info
● id	<i>uuid</i>	PK
● order_id	<i>uuid</i>	FK → orders
● menu_item_id	<i>uuid</i>	FK → menu_items
quantity	<i>int</i>	
unit_price	<i>decimal</i>	— snapshoté
notes	<i>text</i>	

order_item_selections	type	info
● id	<i>uuid</i>	PK
● order_item_id	<i>uuid</i>	FK → order_items
● option_value_id	<i>uuid</i>	FK → menu_item_option_values
extra_price	<i>decimal</i>	— snapshoté

order_status_history	type	info
● id	<i>uuid</i>	PK
● order_id	<i>uuid</i>	FK → orders
status	<i>enum</i>	
note	<i>text</i>	
changed_at	<i>timestamp</i>	

order_chats	type	info
● id	<i>uuid</i>	PK
● order_id	<i>uuid</i>	FK → orders
● sender_id	<i>uuid</i>	FK → users
role	<i>enum</i>	— client/driver
message	<i>text</i>	
sent_at	<i>timestamp</i>	

reviews	type	info
● id	<i>uuid</i>	PK
● order_id	<i>uuid</i>	FK → orders
● user_id	<i>uuid</i>	FK → users
● restaurant_id	<i>uuid</i>	FK → restaurants
● driver_id	<i>uuid</i>	FK → drivers
restaurant_rating	<i>int</i>	— 1 à 5
driver_rating	<i>int</i>	— 1 à 5
comment	<i>text</i>	
photo_url	<i>text</i>	
created_at	<i>timestamp</i>	

refunds	type	info
● id	<i>uuid</i>	PK
● order_id	<i>uuid</i>	FK → orders
● user_id	<i>uuid</i>	FK → users
amount	<i>decimal</i>	
type	<i>enum</i>	— refund/credit
reason	<i>text</i>	
status	<i>enum</i>	— pending/processed
created_at	<i>timestamp</i>	

LIVREURS

drivers	type	info
● id	<i>uuid</i>	PK
name	<i>varchar</i>	
email	<i>varchar</i>	
phone	<i>varchar</i>	
photo_url	<i>text</i>	
transport_type	<i>enum</i>	— bike/scooter/car
is_online	<i>boolean</i>	
lat / lng	<i>float</i>	— position temps réel
rating_avg	<i>float</i>	
is_verified	<i>boolean</i>	
created_at	<i>timestamp</i>	

driver_earnings	type	info
● id	<i>uuid</i>	PK
● driver_id	<i>uuid</i>	FK → drivers
● order_id	<i>uuid</i>	FK → orders
base_amount	<i>decimal</i>	
bonus	<i>decimal</i>	— heures de pointe
tip	<i>decimal</i>	
total	<i>decimal</i>	
status	<i>enum</i>	— pending/paid
paid_at	<i>timestamp</i>	

delivery_zones	type	info
● id	<i>uuid</i>	PK
name	<i>varchar</i>	
polygon	<i>jsonb</i>	— coordonnées GeoJSON
base_fee	<i>decimal</i>	
is_active	<i>boolean</i>	

pricing_rules	type	info
● id	<i>uuid</i>	PK
● zone_id	<i>uuid</i>	FK → delivery_zones
type	<i>enum</i>	— distance/time/surge
multiplier	<i>float</i>	
condition	<i>jsonb</i>	— ex: {hour_from: 18, hour_to: 21}
is_active	<i>boolean</i>	

restaurant_payouts	type	info
● id	<i>uuid</i>	PK
● restaurant_id	<i>uuid</i>	FK → restaurants
period_start	<i>date</i>	
period_end	<i>date</i>	
gross_amount	<i>decimal</i>	
commission	<i>decimal</i>	
net_amount	<i>decimal</i>	
status	<i>enum</i>	— pending/paid
paid_at	<i>timestamp</i>	

FIDÉLITÉ & PROMOS

promo_codes	type	info
● id	<i>uuid</i>	PK
code	<i>varchar</i>	— unique
type	<i>enum</i>	— percent/fixed/free_delivery
value	<i>decimal</i>	
min_order	<i>decimal</i>	
max_uses	<i>int</i>	
uses_count	<i>int</i>	
expires_at	<i>timestamp</i>	

promo_campaigns	type	info
● id	<i>uuid</i>	PK
name	<i>varchar</i>	
target	<i>enum</i>	— all/segment/restaurant
discount_type	<i>enum</i>	— percent/fixed
value	<i>decimal</i>	
started_at	<i>timestamp</i>	
ends_at	<i>timestamp</i>	
is_active	<i>boolean</i>	

loyalty_points	type	info
● id	<i>uuid</i>	PK
● user_id	<i>uuid</i>	FK → users
● order_id	<i>uuid</i>	FK → orders
points	<i>int</i>	— positif ou négatif
reason	<i>enum</i>	— order/referral/redeem
created_at	<i>timestamp</i>	

referrals	type	info
● id	<i>uuid</i>	PK
● referrer_id	<i>uuid</i>	FK → users (parrain)
● referred_id	<i>uuid</i>	FK → users (filleul)
code	<i>varchar</i>	
status	<i>enum</i>	— pending/rewarded
created_at	<i>timestamp</i>	

badges	type	info
● id	<i>uuid</i>	PK
name	<i>varchar</i>	
description	<i>text</i>	
icon_url	<i>text</i>	
type	<i>enum</i>	— driver/client

user_badges	type	info
● id	<i>uuid</i>	PK
● user_id	<i>uuid</i>	FK → users
● badge_id	<i>uuid</i>	FK → badges
earned_at	<i>timestamp</i>	

SUPPORT

notifications	type	info
● id	<i>uuid</i>	PK
● user_id	<i>uuid</i>	FK → users
channel	<i>enum</i>	— push/sms/email
type	<i>varchar</i>	— ex: order_confirmed
title	<i>varchar</i>	
body	<i>text</i>	
is_read	<i>boolean</i>	
sent_at	<i>timestamp</i>	

support_tickets	type	info
● id	<i>uuid</i>	PK
● user_id	<i>uuid</i>	FK → users
● order_id	<i>uuid</i>	FK → orders
reason	<i>enum</i>	— missing_item/wrong_order/late/other
status	<i>enum</i>	— open/in_progress/resolved
created_at	<i>timestamp</i>	

support_messages	type	info
● id	<i>uuid</i>	PK
● ticket_id	<i>uuid</i>	FK → support_tickets
● sender_id	<i>uuid</i>	FK → users
role	<i>enum</i>	— user/agent/bot
content	<i>text</i>	
sent_at	<i>timestamp</i>	