

# Lab 14

Adam Bisharat

Today we will complete an RNASeq analysis from counts to pathways

We will work with data on differential analysis of lung fibroblasts in response to loss of the developmental transcription factor.

```
library(DESeq2)
```

```
Loading required package: S4Vectors
```

```
Loading required package: stats4
```

```
Loading required package: BiocGenerics
```

```
Attaching package: 'BiocGenerics'
```

```
The following objects are masked from 'package:stats':
```

```
IQR, mad, sd, var, xtabs
```

```
The following objects are masked from 'package:base':
```

```
anyDuplicated, aperm, append, as.data.frame, basename, cbind,  
colnames, dirname, do.call, duplicated, eval, evalq, Filter, Find,  
get, grep, grepl, intersect, is.unsorted, lapply, Map, mapply,  
match, mget, order, paste, pmax, pmax.int, pmin, pmin.int,  
Position, rank, rbind, Reduce, rownames, sapply, saveRDS, setdiff,  
table, tapply, union, unique, unsplit, which.max, which.min
```

Attaching package: 'S4Vectors'

The following object is masked from 'package:utils':

findMatches

The following objects are masked from 'package:base':

expand.grid, I, unname

Loading required package: IRanges

Loading required package: GenomicRanges

Loading required package: GenomeInfoDb

Loading required package: SummarizedExperiment

Loading required package: MatrixGenerics

Loading required package: matrixStats

Attaching package: 'MatrixGenerics'

The following objects are masked from 'package:matrixStats':

colAlls, colAnyNAs, colAnys, colAvgsPerRowSet, colCollapse,  
colCounts, colCummaxs, colCummins, colCumprods, colCumsums,  
colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,  
colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,  
colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,  
colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,  
colWeightedMeans, colWeightedMedians, colWeightedSds,  
colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgsPerColSet,  
rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,  
rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,  
rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,

```
rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,  
rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,  
rowWeightedMads, rowWeightedMeans, rowWeightedMedians,  
rowWeightedSds, rowWeightedVars
```

Loading required package: Biobase

Welcome to Bioconductor

```
Vignettes contain introductory material; view with  
'browseVignettes()'. To cite Bioconductor, see  
'citation("Biobase")', and for packages 'citation("pkgname")'.
```

Attaching package: 'Biobase'

The following object is masked from 'package:MatrixGenerics':

```
rowMedians
```

The following objects are masked from 'package:matrixStats':

```
anyMissing, rowMedians
```

```
# Read the metadata and count files  
metaFile <- "GSE37704_metadata.csv"  
countFile <- "GSE37704_featurecounts.csv"  
  
# Read in the metadata file using the file path as a string  
colData <- read.csv(metaFile, row.names=1)  
head(colData)
```

```
              condition  
SRR493366 control_sirna  
SRR493367 control_sirna  
SRR493368 control_sirna  
SRR493369      hoxa1_kd  
SRR493370      hoxa1_kd  
SRR493371      hoxa1_kd
```

```
counts <- read.csv(countFile, header=TRUE, row.names=1)

colnames(counts)
```

```
[1] "length"      "SRR493366" "SRR493367" "SRR493368" "SRR493369" "SRR493370"
[7] "SRR493371"
```

```
metadata <- read.csv("GSE37704_metadata.csv")
metadata$id
```

```
[1] "SRR493366" "SRR493367" "SRR493368" "SRR493369" "SRR493370" "SRR493371"
```

```
countData <- counts[, -1]
colnames(countData) == metadata$id
```

```
[1] TRUE TRUE TRUE TRUE TRUE TRUE
```

How many genes do we have?

```
to.keep <- rowSums(countData) != 0
countData <- countData[to.keep,]

nrow(countData)
```

```
[1] 15975
```

```
library(DESeq2)

dds = DESeqDataSetFromMatrix(countData=countData,
                              colData=colData,
                              design=~condition)
```

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in design formula are characters, converting to factors

```
dds = DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

```
res <- results(dds)
head(res)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 6 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.9136	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.2296	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.1881	-0.6927205	0.0548465	-12.630158	1.43989e-36
ENSG00000187961	209.6379	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.2551	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.9798	0.5428105	0.5215599	1.040744	2.97994e-01
	padj				
	<numeric>				
ENSG00000279457	6.86555e-01				
ENSG00000187634	5.15718e-03				
ENSG00000188976	1.76549e-35				
ENSG00000187961	1.13413e-07				
ENSG00000187583	9.19031e-01				
ENSG00000187642	4.03379e-01				

```
dds = DESeqDataSetFromMatrix(countData=countData,
                              colData=colData,
                              design=~condition)
```

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in design formula are characters, converting to factors

```
dds = DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship


final dispersion estimates

fitting model and testing

```
dds
```

```
class: DESeqDataSet
dim: 15975 6
metadata(1): version
assays(4): counts mu H cooks
rownames(15975): ENSG00000279457 ENSG00000187634 ... ENSG00000276345
               ENSG00000271254
rowData names(22): baseMean baseVar ... deviance maxCooks
colnames(6): SRR493366 SRR493367 ... SRR493370 SRR493371
colData names(2): condition sizeFactor
```

```
plot( res$log2FoldChange, -log(res$padj) )
```




add some color

```
mycols <- rep("gray", nrow(res))

mycols[ abs(res$log2FoldChange) > 2 ] <- "red"

inds <- (res$padj < 0.01) & (abs(res$log2FoldChange) > 2)
mycols[ inds ] <- "blue"

plot(res$log2FoldChange, -log10(res$padj), col=mycols,
      xlab="Log2(FoldChange)", ylab="-Log10(P-value)")
```



```
library("AnnotationDbi")
library("org.Hs.eg.db")
```

```
# Check available columns
columns(org.Hs.eg.db)
```

```
[1] "ACCNUM"      "ALIAS"       "ENSEMBL"     "ENSEMBLPROT" "ENSEMBLTRANS"
[6] "ENTREZID"    "ENZYME"      "EVIDENCE"    "EVIDENCEALL"  "GENENAME"
[11] "GENETYPE"    "GO"          "GOALL"       "IPI"          "MAP"
[16] "OMIM"        "ONTOLOGY"    "ONTOLOGYALL" "PATH"         "PFAM"
[21] "PMID"        "PROSITE"     "REFSEQ"      "SYMBOL"       "UCSCCKG"
[26] "UNIPROT"
```

```
# Add SYMBOL annotation
res$symbol = mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="SYMBOL",
                    multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
# Add ENTREZID annotation
res$entrez = mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="ENTREZID",
                    multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
# Add GENENAME annotation
res$name = mapIds(org.Hs.eg.db,
                  keys=row.names(res),
                  keytype="ENSEMBL",
                  column="GENENAME",
                  multiVals="first")
```



'select()' returned 1:many mapping between keys and columns

```
# View the first 10 rows
head(res, 10)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 10 rows and 9 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.913579	0.1792571	0.3248216	0.551863	5.81042e-01
ENSG00000187634	183.229650	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.188076	-0.6927205	0.0548465	-12.630158	1.43989e-36
ENSG00000187961	209.637938	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.255123	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.979750	0.5428105	0.5215599	1.040744	2.97994e-01
ENSG00000188290	108.922128	2.0570638	0.1969053	10.446970	1.51282e-25
ENSG00000187608	350.716868	0.2573837	0.1027266	2.505522	1.22271e-02
ENSG00000188157	9128.439422	0.3899088	0.0467163	8.346304	7.04321e-17
ENSG00000237330	0.158192	0.7859552	4.0804729	0.192614	8.47261e-01
	padj	symbol	entrez	name	
	<numeric>	<character>	<character>	<character>	
ENSG00000279457	6.86555e-01	NA	NA	NA	
ENSG00000187634	5.15718e-03	SAMD11	148398	sterile alpha motif	..
ENSG00000188976	1.76549e-35	NOC2L	26155	NOC2 like nucleolar	..
ENSG00000187961	1.13413e-07	KLHL17	339451	kelch like family me..	
ENSG00000187583	9.19031e-01	PLEKHN1	84069	pleckstrin homology	..
ENSG00000187642	4.03379e-01	PERM1	84808	PPARGC1 and ESRR ind..	
ENSG00000188290	1.30538e-24	HES4	57801	hes family bHLH tran..	
ENSG00000187608	2.37452e-02	ISG15	9636	ISG15 ubiquitin like..	
ENSG00000188157	4.21963e-16	AGRN	375790	agrin	
ENSG00000237330	NA	RNF223	401934	ring finger protein	..

```
# Reorder results by adjusted p-value
res <- res[order(res$padj), ]

# Save the ordered results to a CSV file
write.csv(res, file="deseq_results.csv")
```

##Section 2. Pathway Analysis

```
BiocManager::install( c("pathview", "gage", "gageData") )
```

Bioconductor version 3.20 (BiocManager 1.30.25), R 4.4.1 (2024-06-14)

Warning: package(s) not installed when version(s) same as or greater than current; use  
`force = TRUE` to re-install: 'gage' 'gageData'

Installing package(s) 'pathview'

The downloaded binary packages are in  
/var/folders/8s/f390q53j38s5kvhctkntckzh0000gn/T//RtmpGg8XNz/downloaded\_packages

Old packages: 'BiocParallel', 'curl', 'pathview'

```
library(pathview)
```

```
#####  
Pathview is an open source software package distributed under GNU General  
Public License version 3 (GPLv3). Details of GPLv3 is available at  
http://www.gnu.org/licenses/gpl-3.0.html. Particullary, users are required to  
formally cite the original Pathview paper (not just mention it) in publications  
or products. For details, do citation("pathview") within R.
```

The pathview downloads and uses KEGG data. Non-academic uses may require a KEGG  
license agreement (details at <http://www.kegg.jp/kegg/legal.html>).

```
#####
```

```
library(gage)
```

```
library(gageData)
```

```
data(kegg.sets.hs)  
data(sigmet.idx.hs)
```

```
# Focus on signaling and metabolic pathways only
```

```
kegg.sets.hs = kegg.sets.hs[sigmet.idx.hs]
```

```
# Examine the first 3 pathways  
head(kegg.sets.hs, 3)
```

```
$`hsa00232 Caffeine metabolism`
```

```
[1] "10" "1544" "1548" "1549" "1553" "7498" "9"
```

```
$`hsa00983 Drug metabolism - other enzymes`
```

```
[1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"  
[9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"  
[17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"  
[25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"  
[33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"  
[41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"  
[49] "8824" "8833" "9" "978"
```

```
$`hsa00230 Purine metabolism`
```

```
[1] "100" "10201" "10606" "10621" "10622" "10623" "107" "10714"  
[9] "108" "10846" "109" "111" "11128" "11164" "112" "113"  
[17] "114" "115" "122481" "122622" "124583" "132" "158" "159"  
[25] "1633" "171568" "1716" "196883" "203" "204" "205" "221823"  
[33] "2272" "22978" "23649" "246721" "25885" "2618" "26289" "270"  
[41] "271" "27115" "272" "2766" "2977" "2982" "2983" "2984"  
[49] "2986" "2987" "29922" "3000" "30833" "30834" "318" "3251"  
[57] "353" "3614" "3615" "3704" "377841" "471" "4830" "4831"  
[65] "4832" "4833" "4860" "4881" "4882" "4907" "50484" "50940"  
[73] "51082" "51251" "51292" "5136" "5137" "5138" "5139" "5140"  
[81] "5141" "5142" "5143" "5144" "5145" "5146" "5147" "5148"  
[89] "5149" "5150" "5151" "5152" "5153" "5158" "5167" "5169"  
[97] "51728" "5198" "5236" "5313" "5315" "53343" "54107" "5422"  
[105] "5424" "5425" "5426" "5427" "5430" "5431" "5432" "5433"  
[113] "5434" "5435" "5436" "5437" "5438" "5439" "5440" "5441"  
[121] "5471" "548644" "55276" "5557" "5558" "55703" "55811" "55821"  
[129] "5631" "5634" "56655" "56953" "56985" "57804" "58497" "6240"  
[137] "6241" "64425" "646625" "654364" "661" "7498" "8382" "84172"  
[145] "84265" "84284" "84618" "8622" "8654" "87178" "8833" "9060"  
[153] "9061" "93034" "953" "9533" "954" "955" "956" "957"  
[161] "9583" "9615"
```

```
foldchanges = res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)
```

```
      1266      54855      1465      51232      2034      2317
-2.422719  3.201955 -2.313738 -2.059631 -1.888019 -1.649792
```

```
keggres = gage(foldchanges, gsets=kegg.sets.hs)
```

```
nrow(countData)
```

```
[1] 15975
```

```
nrow(res)
```

```
[1] 15975
```

```
attributes(keggres)
```

```
$names
[1] "greater" "less"    "stats"
```

```
head(keggres$less,4)
```

	p.geomean	stat.mean	p.val
hsa04110 Cell cycle	8.995727e-06	-4.378644	8.995727e-06
hsa03030 DNA replication	9.424076e-05	-3.951803	9.424076e-05
hsa03013 RNA transport	1.375901e-03	-3.028500	1.375901e-03
hsa03440 Homologous recombination	3.066756e-03	-2.852899	3.066756e-03


	q.val	set.size	exp1
hsa04110 Cell cycle	0.001448312	121	8.995727e-06
hsa03030 DNA replication	0.007586381	36	9.424076e-05
hsa03013 RNA transport	0.073840037	144	1.375901e-03
hsa03440 Homologous recombination	0.121861535	28	3.066756e-03

```
pathview(gene.data=foldchanges, pathway.id="hsa04110")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/adambish/Lab 14

Info: Writing image file hsa04110.pathview.png



```
pathview(gene.data=foldchanges, pathway.id="hsa04110", kegg.native=FALSE)
```

'select()' returned 1:1 mapping between keys and columns

Warning: reconcile groups sharing member nodes!

```
      [,1] [,2]
[1,] "9"  "300"
[2,] "9"  "306"
```

Info: Working in directory /Users/adambish/Lab 14

Info: Writing image file hsa04110.pathview.pdf

```
keggrespathways <- rownames(keggres$greater)[1:5]
```

```
keggresids = substr(keggrespathways, start=1, stop=8)
keggresids
```

```
[1] "hsa04640" "hsa04630" "hsa00140" "hsa04142" "hsa04330"
```

```
pathview(gene.data=foldchanges, pathway.id=keggresids, species="hsa")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/adambish/Lab 14

Info: Writing image file hsa04640.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/adambish/Lab 14

Info: Writing image file hsa04630.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/adambish/Lab 14

Info: Writing image file hsa00140.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/adambish/Lab 14

Info: Writing image file hsa04142.pathview.png

'select()' returned 1:1 mapping between keys and columns


Info: Working in directory /Users/adambish/Lab 14

Info: Writing image file hsa04330.pathview.png







## Pathway: hsa04640



# Pathway: hsa04630




## Pathway: hsa00140



## 20

## Pathway: hsa04330



## ##Section 3. Gene Ontology (GO)

```
data(go.sets.hs)
data(go.subs.hs)

# Focus on Biological Process subset of GO
gobpsets = go.sets.hs[go.subs.hs$BP]

gobpres = gage(foldchanges, gsets=gobpsets, same.dir=TRUE)

lapply(gobpres, head)
```

```
$greater
```

	p.geomean	stat.mean	p.val
G0:0007156 homophilic cell adhesion	8.519724e-05	3.824205	8.519724e-05
G0:0002009 morphogenesis of an epithelium	1.396681e-04	3.653886	1.396681e-04
G0:0048729 tissue morphogenesis	1.432451e-04	3.643242	1.432451e-04
G0:0007610 behavior	1.925222e-04	3.565432	1.925222e-04
G0:0060562 epithelial tube morphogenesis	5.932837e-04	3.261376	5.932837e-04
G0:0035295 tube development	5.953254e-04	3.253665	5.953254e-04
	q.val	set.size	exp1
G0:0007156 homophilic cell adhesion	0.1951953	113	8.519724e-05

G0:0002009	morphogenesis of an epithelium	0.1951953	339	1.396681e-04
G0:0048729	tissue morphogenesis	0.1951953	424	1.432451e-04
G0:0007610	behavior	0.1967577	426	1.925222e-04
G0:0060562	epithelial tube morphogenesis	0.3565320	257	5.932837e-04
G0:0035295	tube development	0.3565320	391	5.953254e-04

\$less

		p.geomean	stat.mean	p.val
G0:0048285	organelle fission	1.536227e-15	-8.063910	1.536227e-15
G0:0000280	nuclear division	4.286961e-15	-7.939217	4.286961e-15
G0:0007067	mitosis	4.286961e-15	-7.939217	4.286961e-15
G0:0000087	M phase of mitotic cell cycle	1.169934e-14	-7.797496	1.169934e-14
G0:0007059	chromosome segregation	2.028624e-11	-6.878340	2.028624e-11
G0:0000236	mitotic prometaphase	1.729553e-10	-6.695966	1.729553e-10
		q.val	set.size	expl
G0:0048285	organelle fission	5.841698e-12	376	1.536227e-15
G0:0000280	nuclear division	5.841698e-12	352	4.286961e-15
G0:0007067	mitosis	5.841698e-12	352	4.286961e-15
G0:0000087	M phase of mitotic cell cycle	1.195672e-11	362	1.169934e-14
G0:0007059	chromosome segregation	1.658603e-08	142	2.028624e-11
G0:0000236	mitotic prometaphase	1.178402e-07	84	1.729553e-10

\$stats


	stat.mean	expl
G0:0007156	homophilic cell adhesion	3.824205
G0:0002009	morphogenesis of an epithelium	3.653886
G0:0048729	tissue morphogenesis	3.643242
G0:0007610	behavior	3.565432
G0:0060562	epithelial tube morphogenesis	3.261376
G0:0035295	tube development	3.253665

##Section 4. Reactome Analysis

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
[1] "Total number of significant genes: 8147"
```

```
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quote=
```



##Save Results

```
write.csv(res, file="myresults.csv")
```