

Google Ads API — Basic Access Design Documentation

Turan Elite Limo LLC (dba TuranEliteLimo) · Server-Side Conversion Tracking System
Prepared: July 02, 2026 · Version 1.0

1. Applicant & Business Overview

Company (Legal)	Turan Elite Limo LLC (California Single-Member LLC)
Doing business as	TuranEliteLimo
Registered address	501 Broadway Ste 251, Millbrae, CA 94030
Website	https://turanelitelimo.com
Business	Licensed Bay Area luxury chauffeur service (CA TCP-classed)
Google Ads MCC / CID	(as provided in application form)
Primary contact	Abdulkhafiz Fayzullaev · support@turanelitelimo.com · (650) 410-0687
Access tier requested	Basic Access (15,000 ops/day)
Tool users	Internal only — single business, own Google Ads account
Third-party access	None. Tool is not resold, redistributed, or offered as SaaS.

2. Tool Purpose

The tool is a **server-side conversion tracking system** that reports offline / delayed conversion events from our Stripe payment webhook to our own Google Ads account. It sends verified purchase-conversion events (deposit paid, booking confirmed) via the Google Ads API as Enhanced Conversions for Leads. The tool exists solely to improve the accuracy of our own campaign optimization — we do not resell, redistribute, or provide this functionality to any third party.

The tool addresses two well-known limitations of client-side conversion tracking:

- Ad-blockers, iOS Private Relay, and Safari Intelligent Tracking Prevention block **25–40%** of gtag.js client-side pixel fires, causing systematic under-reporting of conversions.
- Our sales cycle includes an operator-emailed quote → customer clicks confirm link → pays deposit path where the browser session may occur days after the initial ad click, breaking client-side attribution.

By emitting the conversion server-side from the Stripe webhook, Google Ads Smart Bidding receives accurate signals, which allows PMax and Search campaigns to optimize toward high-value customers rather than under-attributed placements.

3. Scope of Google Ads API Usage

3.1 Endpoints called

- customers.uploadClickConversions — upload one purchase-event conversion per confirmed booking, with GCLID + conversion value + Enhanced Conversions user data (hashed email/phone).
- customers.conversionActions.list — one-time read at startup to resolve the resource name of our pre-configured "Purchase" conversion action.

No other endpoints are called. The tool does not read campaign performance, modify bids, create campaigns, manage budgets, generate reports, or perform any read/write operations on the Google Ads account beyond the two endpoints listed above.

3.2 Volume forecast

Metric	Current	12-month forecast
Confirmed bookings / month	~30–60	~120–200
Google Ads API operations / day (avg)	~2	~7
Peak-day operations (World Cup 2026)	~15	~40
Basic Access daily limit	15,000	15,000
Utilization vs limit	< 0.1%	< 0.3%

Well under the Basic Access daily limit. No burst-write patterns — the tool fires at most one operation per confirmed booking, which is naturally rate-limited by real-world booking volume.

4. System Architecture

4.1 Stack

- Frontend: React + Tailwind (deployed to turanelitelimo.com)
- Backend: Python 3 · FastAPI · Motor (async MongoDB driver)
- Database: MongoDB (bookings, quote_requests, promos, affiliates collections)
- Payment processor: Stripe (Checkout Sessions + webhooks)
- Google Ads API client: Official google-ads Python library, most recent stable version
- Hosting: Managed cloud with static outbound IP

4.2 Data flow

The tool activates in a single, well-defined moment: when Stripe confirms a customer's deposit payment via its checkout.session.completed webhook. The full path from customer action to Google Ads conversion event is:

1. Customer clicks Google Ad → lands on turanelitelimo.com
2. gtag.js captures GCLID from URL query & stores in first-party cookie
3. Customer submits booking form → row created in bookings collection
4. Backend passes GCLID + booking_id (transaction_id) to Stripe Checkout metadata
5. Customer completes payment on Stripe-hosted checkout
6. Stripe → HTTPS POST → /api/webhooks/stripe on our backend
7. Backend verifies webhook signature, marks booking.payment_status = "paid"
8. Backend calls google_ads_client.upload_click_conversions() with:
 - conversion_action = our pre-configured Purchase action
 - gclid = value captured at step 2 (from booking metadata)
 - conversion_value = deposit amount (USD)
 - conversion_date_time = webhook receipt timestamp
 - order_id = booking.id (UUID) – enables Google-side dedupe
 - user_identifiers = SHA-256 hashed email + phone (Enhanced Conv.)
9. Google Ads API returns success or partial_failure
10. Backend logs response; on failure, retries with exponential backoff (3 attempts max)

4.3 Deduplication

Every conversion upload includes the booking's UUID as the order_id field. Google Ads uses this to dedupe against any client-side pixel fire that may have also succeeded (belt-and-suspenders). The same UUID is used as the transaction_id in our client-side gtag.js calls upstream, so both signals converge on the same identifier and Google reports one conversion per booking.

5. Authentication & Credential Handling

- OAuth 2.0 refresh-token grant, per Google Ads API best practices.
- Developer Token, OAuth Client ID/Secret, Refresh Token, and Login-Customer-ID are all stored as environment variables on the backend host. Never committed to source control. Never sent to the browser. Never logged.
- Access token refresh is handled automatically by the official google-ads client library.
- All calls are made from our fixed outbound IP over HTTPS to googleads.googleapis.com.

6. Data Handling & Privacy

The tool sends only the minimum data necessary to record a conversion event on our own Google Ads account.

6.1 Data sent to Google Ads API

- GCLID (already provided to us by Google when the ad was clicked).
- Conversion value (deposit amount in USD).
- Timestamp of the conversion.
- Booking UUID as order_id (opaque identifier — no PII embedded).
- SHA-256 hashed email address and hashed phone number (Enhanced Conversions for Leads — plaintext PII is never transmitted, only the hash).

6.2 Data NOT sent

- No customer names, plaintext emails, plaintext phones, mailing addresses, IP addresses, or session data.
- No trip details (pickup / drop-off / vehicle / passengers / occasion).
- No credit-card or payment-method data.
- No third-party customer data (the tool only processes our own paying customers).

6.3 Consent & disclosures

- Customers accept our Privacy Policy (turanitelimo.com/privacy) before checkout, which discloses use of Google Ads conversion tracking including Enhanced Conversions.
- Our site displays a Consent Mode v2 banner allowing users to decline analytics/ads storage. When declined, GCLID is not stored and no conversion is sent.
- Compliant with California CCPA/CPRA and GDPR data-minimization principles.

7. Error Handling, Retries & Monitoring

- On transient API errors (5xx, rate-limit): exponential backoff, max 3 retries, then log and continue (the booking is not blocked by ads-tracking failure).
- On permanent errors (bad GCLID, invalid conversion action): log to backend, alert operator via admin-notification email, no retry.
- All API responses are logged with request-id and correlation-id for auditability.
- Weekly automated cron reconciles Stripe webhook events vs Google Ads upload logs; any missing uploads are flagged for manual review.
- No conversion-blocking user-facing path — if the API is unreachable, the customer's booking still completes normally.

8. Explicit Non-Goals

To make the scope unambiguous, we explicitly do NOT:

- Manage bids, budgets, keywords, negative keywords, or campaign settings via the API.
- Read campaign or reporting data for automated decisioning.
- Manage or access any Google Ads account other than our own.
- Provide functionality to third parties, resellers, agencies, or as a SaaS product.
- Store, cache, or export any customer PII to systems other than our own compliant infrastructure.
- Emit conversions that were not the result of a verified Stripe payment webhook.

9. Launch Timeline

Phase	Milestone
Week 0	Basic Access approval received. Sandbox testing against Google Ads test manager account.
Week 1	Verify conversion upload flow end-to-end using historical Stripe test transactions.
Week 2	Enable in production; monitor Google Ads "Diagnostics" tab for accepted conversions.
Week 3+	Standard operation. Weekly reconciliation cron running. No further code changes anticipated.

10. Sign-off

The tool described above is scoped narrowly to a single-tenant, single-purpose conversion-tracking pipeline. Basic Access at the standard 15,000 ops/day limit is more than sufficient for current and projected volume. We commit to following Google's Required Minimum Functionality (RMF) standards and API Terms of Service.

Applicant: Abdulkhafiz Fayzullaev, Sole Member

Company: Turan Elite Limo LLC (dba TuranEliteLimo)

Registered address: 501 Broadway Ste 251, Millbrae, CA 94030

Email: support@turanelitelimo.com

Phone: (650) 410-0687

Date: July 02, 2026

This document was prepared for the sole purpose of Google Ads API Basic Access application Question 7 (design documentation). It describes a tool built by and for Turan Elite Limo LLC.