



Technical Information and Typical Properties

MEV One Side-Cling Cast Machine Film 0.54 mil



Product Description

Evolve is a brand new formulation, made with proprietary resin blends on state of the art extrusion equipment. This all purpose film is a highly engineered, one side cling, cast super film. It's the first of it's kind in North America. Evolve is manufactured on equipment that produces perfect roll edges and tight gauge tolerances, making it perfect for today's high speed wrapping equipment.

General

Applications •High volume • High speed wrapping •One side-cling required
Revision Date 3/8/2018 Available in 500 and 750 mm widths

Film Properties	Typical Value (English)	Tolerance	Test Method
Tensile Strength at Yield MD	N/A	N/A	N/A
Tensile Strength at Yield TD	4800 psi	± 15%	ASTM D882
Tensile Strength at Break MD	11900 psi	± 15%	ASTM D882
Tensile Strength at Break TD	8500 psi	± 15%	ASTM D882
Elongation at Break MD	610%	± 15%	ASTM D882
Elongation at Break TD	690%	± 15%	ASTM D882
Protrusion Puncture	4.3 lbs	± 15%	ASTM D5748
Protrusion Puncture Energy	16.9 in-lb	± 15%	ASTM D5748
Elmendorf Tear Strength MD	650 g/mil	± 15%	ASTM D1922
Elmendorf Tear Strength TD	970 g/mil	± 15%	ASTM D1922
Cling - Outside to Inside @ 225%	min 150 g/in	± 15%	ASTM D5458

Dimensions	Value	Tolerance
Core ID	3.05 inches	± 0.05 in
Film Thickness	13.7 micron	

Little & Co. Inc.

Phone: 863-430-8861

Email: Adamm285@gmail.com

www.littleandcompany.com