

## **MACHINE FILM**

## **Premium Cast Machine Designed for High Stretch Applications.**

Sigma Magnum is the ideal film for machinery set up to run at high pre-stretch levels. This film is a high performance, cast, coextruded product developed for optimum performance when pre-stretched between 250 and 300 percent. Magnum is a premium 2-side cling stretch film. The enhanced strength and stretch characteristics mean minimal amount of film is required while providing maximum containment and load integrity.



**Bagged Products Food Processors** Most A/B-Load Profiles Worn/damaged equipment Light to Moderate weight loads **Distribution Warehouses** Automatic Equipment High Speed Overhead Equipment **Boxed Product** Items prone to crush

Film Width	Roll Length	Film Gauge	Roll Weight	Rolls/Pallet	<b>Product Number</b>
20"	4,500′	1.00 mil	36.0 lb	40	MFC2045100
20"	6,000′	.80 mil	38.4 lb	40	MFC206080
20"	6,000′	.75 mil	36.0 lb	40	MFC206075
30"	6,000′	.75 mil	54.0 lb	20	MFC306075
20"	6,000′	.70 mil	33.6 lb	40	MFC206070
20"	6,000′	.65 mil	31.2 lb	40	MFC206065
30"	6,000′	.65 mil	46.8 lb	20	MFC306065
20"	8,000′	.55 mil	35.2 lb	40	MFC208055
30"	8,000′	.55 mil	52.8 lb	20	MFC308055

Your Sigma Sales Pro will be pleased to discuss your requirements.

## Σ Sigma Stretch Film

PO Box 808, Lyndhurst, NJ 07071 T: 201-507-9100 F:201-507-0447 www.sigmastretchfilm.com

Email: stretch.info@sigmaplastics.com