

Model: WDC WD2500BEVT-7

S/N: WD-WX11A11D4674

Disk Erasure Report

Page 1 - Erasure Status



Organisation Performing The Disk Erasure

Business Name: Adam Matthiesen Support Center

Business Address: <https://matthiesen.xyz>

Contact Name: IT Support

Contact Phone: support@matthiesen.xyz

Customer Details

Name: General Sale

Address:

Contact Name:

Contact Phone:

Disk Information

Make/Model: WDC WD2500BEVT-7

Serial: WD-WX11A11D4674

Size(Apparent): 250 GB, 250059350016 bytes

Bus: USB

Size(Real): 250 GB, 250059350016 bytes

Disk Erasure Details

Start time: 2023/12/26 15:13:49

End time: 2023/12/26 21:49:14

Duration: 06:35:25

Status: **ERASED** See Warning !

Method: DoD Short

PRNG algorithm: Isaac64

Final Pass(Zeros/Ones/None): Zeros

Verify Pass(Last/All/None): Verify Last

*Bytes Erased: 250059350016, (100.00%)

Rounds(completed/requested): 1/1

HPA/DCO: Unknown

HPA/DCO Size: Unknown

Errors(pass/sync/verify): 0/0/0

Throughput: 52 MB/sec


Information: **Warning** HPA/DCO data unavailable, can not determine hidden sector status.

* bytes erased: The amount of drive that's been erased at least once

Technician/Operator ID

Signature:

Name/ID: Adam M.



Model: WDC WD2500BEVT-7

S/N: WD-WX11A11D4674

Disk Erasure Report

Page 2 - Smart Data



smartctl 7.3 2022-02-28 r5338 [x86_64-linux-6.1.0-13-amd64] (local build)
copyright (c) 2002-22, bruce allen, christian franke, www.smartmontools.org

=== start of information section ===

model family: Western Digital Scorpio Blue Serial ATA
device model: WDC WD2500BEVT-75A23T0
serial number: WD-WX11A11D4674
lu wwn device id: 5 0014ee 656363ad5
firmware version: 01.01A01
user capacity: 250,059,350,016 bytes [250 GB]
sector size: 512 bytes logical/physical
rotation rate: 5400 rpm
device is: In smartctl database 7.3/5319
ata version is: ATA8-ACS (minor revision not indicated)
sata version is: SATA 2.6, 3.0 Gb/s
local time is: Wed Dec 27 02:07:53 2023 PST
smart support is: Available - device has SMART capability.
smart support is: Enabled

=== start of read smart data section ===

smart status not supported: Incomplete response, ATA output registers missing
smart overall-health self-assessment test result: PASSED
warning: This result is based on an Attribute check.


general smart values:

offline data collection status: (0x00)Offline data collection activity
was never started.
auto offline data collection: Disabled.
self-test execution status: (0)The previous self-test routine completed
without error or no self-test has ever
been run.
total time to complete offline
data collection: (6780) seconds.
offline data collection
capabilities: (0x7b) SMART execute Offline immediate.
auto offline data collection on/off support.
suspend offline collection upon new
command.
offline surface scan supported.
self-test supported.
conveyance self-test supported.
selective self-test supported.
smart capabilities: (0x0003)Saves SMART data before entering
power-saving mode.
supports smart auto save timer.
error logging capability: (0x01)Error logging supported.
general purpose logging supported.
short self-test routine
recommended polling time: (2) minutes.
extended self-test routine
recommended polling time: (82) minutes.
conveyance self-test routine
recommended polling time: (5) minutes.
sct capabilities: (0x7037)SCT Status supported.
sct feature control supported.
sct data table supported.

smart attributes data structure revision number: 16

vendor specific smart attributes with thresholds:

id#	attribute_name	flag	value	worst	thresh	type	updated	when_failed	raw_value
1	raw_read_error_rate	0x002f	200	200	051	pre-fail	always	-	1
3	spin_up_time	0x0027	155	151	021	pre-fail	always	-	1208
4	start_stop_count	0x0032	099	099	000	old_age	always	-	1219
5	reallocated_sector_ct	0x0033	200	200	140	pre-fail	always	-	0



Model: WDC WD2500BEVT-7

S/N: WD-WX11A11D4674

Disk Erasure Report

Page 3 - Smart Data



7	seek_error_rate	0x002e	200	200	000	old_age	always	-	0
9	power_on_hours	0x0032	092	092	000	old_age	always	-	6176
10	spin_retry_count	0x0032	100	100	000	old_age	always	-	0
11	calibration_retry_count	0x0032	100	100	000	old_age	always	-	0
12	power_cycle_count	0x0032	099	099	000	old_age	always	-	1201
191	g-sense_error_rate	0x0032	001	001	000	old_age	always	-	842
192	power-off_retract_count	0x0032	200	200	000	old_age	always	-	409
193	load_cycle_count	0x0032	001	001	000	old_age	always	-	986322
194	temperature_celsius	0x0022	115	088	000	old_age	always	-	28
196	reallocated_event_count	0x0032	200	200	000	old_age	always	-	0
197	current_pending_sector	0x0032	200	200	000	old_age	always	-	0
198	offline_uncorrectable	0x0030	100	253	000	old_age	offline	-	0
199	udma_crc_error_count	0x0032	200	200	000	old_age	always	-	0
200	multi_zone_error_rate	0x0008	100	253	000	old_age	offline	-	0
240	head_flying_hours	0x0032	096	096	000	old_age	always	-	3390
241	total_lbas_written	0x0032	200	200	000	old_age	always	-	10809593323
242	total_lbas_read	0x0032	200	200	000	old_age	always	-	6550662369
254	free_fall_sensor	0x0032	200	200	000	old_age	always	-	0

smart error log version: 1
no errors logged

smart self-test log structure revision number 1

num	test_description	status	remaining	lifetime(hours)	lba_of_first_error
# 1	short offline	aborted by host	90%	2392	-
# 2	short offline	completed: read failure	10%	2298	6915943
# 3	short offline	completed: read failure	10%	2297	6915943
# 4	short offline	completed without error	00%	0	-

smart selective self-test log data structure revision number 1

span	min_lba	max_lba	current_test_status
1	0	0	not_testing
2	0	0	not_testing
3	0	0	not_testing
4	0	0	not_testing
5	0	0	not_testing

selective self-test flags (0x0):

after scanning selected spans, do not read-scan remainder of disk.
if selective self-test is pending on power-up, resume after 0 minute delay.