Adarsh Saurabh

+91 7004428313 adarshsaurabh1396@gmail.com LinkedIn GitHub Devpost LeetCode

Education

National Institute Of Technology, Rourkela **2025 – 2027**
Master of Technology in Signal and Image Processing, CGPA: 8.28 *Rourkela, India*

Guru Ghasidas University, Bilaspur **2020 – 2024**
Bachelor of Technology in Computer Science and Engineering, CGPA: 8.5 *Bilaspur, India*

Jawahar Navodaya Vidyalaya, Sitamarhi **2017**
Matriculation CBSE, CGPA: 8.8 *Sitamarhi, India*

Relevant Coursework

- Data Structures
- Algorithms Analysis
- Operating Systems
- Database Management
- Software Methodology
- Computer Architecture
- Artificial Intelligence
- Computer Vision

Experience

Autobot Robotics **May 2023 – Aug 2023**
Machine Learning Intern *Remote*

- Mentored and guided a junior intern, imparting mastery in ML fundamentals, Data Manipulation, Numpy, and Pandas.
- Developed and deployed (Django) 4 ML/DL projects with models that may be integrated into company robots.

Ziroh Labs Source Link **Jan 2022 – Feb 2022**
Team Leader - Academic Alliance Program *Remote*

- Fostered strong mentor-team connections, facilitating seamless communication and collaboration.
- Successfully led a team of 5 to achieve project completion ahead of schedule, consistently meeting deadlines.

Key Projects

Uplan — Adversarial Document Intelligence Pipeline Source Link | *Python, Gemini API, LangGraph, Streamlit* **2025**

- Architected an adversarial multi-agent workflow in LangGraph using modern AI tools (Gemini 2.5 Pro specialists) to check visa document coherence; reduced manual verification workload by 85% with detailed failure rebuttal generation.
- Designed structural encoding system using Gemini 2.0 Flash to compile page-level document metadata into a typed semantic graph (98% token compression) and integrated a zero-hallucination mathematical rule check engine.

Alternative Data Radar Source Link | *Python, Next.js, SQL, REST APIs, Bright Data, LLM APIs* **2026**

- Engineered an automated data collection backend in Next.js to gather public web signals (careers and pricing data), routing requests via Bright Data Web Unlocker to bypass anti-scraping mechanisms.
- Implemented AI-driven analysis to calculate a 0–100 corporate health score stored in a SQL database, presenting pre-earnings intelligence and warning alerts in a responsive Recharts dashboard.

IBYD Technology — Warehouse PathMapper Source Link | *Python, Algorithms, Data Structures* **2023**

- Delivered a dynamic warehouse mapping solution as a freelance engagement, working directly with the client to translate their operational pathfinding needs into a heuristic-based routing system.
- Scaled the routing engine to warehouses as large as 10,000×10,000 units, computing optimal paths through 10,000+ locations simultaneously in under 0.5 seconds on a standard i5 laptop CPU.

Achievements

Intermediate Winner — Awaiken Hacks 2023 Source Link: Innovative tool using Mediapipe for real-time action analysis in education with precise feedback on posture and motion

Rank 1 — Girlscript Bilaspur Hackathon "Hack4CG" Source Link: Won top honors for Facial Emotion Recognition project addressing depression vulnerability in modern society

Leadership / Extracurricular

Google Developers Student Club **3rd Year**
Vice President *Guru Ghasidas University*

- Organized technical workshops and hackathons on Machine Learning, Cloud, and Web technologies for 500+ students.

Technical Skills

Languages: Python, C++, C, SQL, JavaScript, HTML, CSS
Core CS & Software Engineering: Data Structures & Algorithms, Object-Oriented Programming, Database Management, REST APIs, Software Methodology, Git, GitHub
Machine Learning & AI: Machine Learning, Deep Learning, Natural Language Processing, Large Language Models, Computer Vision, Multi-Agent Systems, LangGraph, Gemini API, TensorFlow, Scikit-learn, OpenCV, NumPy, Pandas
Tools & Frameworks: VS Code, Anaconda, Django, Flask, Next.js, React Vite, Streamlit

SOFTWARE DEVELOPMENT ENGINEER INTERN

About Media.net

Media.net is a leading online ad-tech company that develops innovative products for advertisers and publishers. Media.net has one of the most comprehensive portfolios of advertising technology in the industry across search, native, display, mobile, local, products and video. Media.net manages high-quality ad supply on over 500,000 websites and its platform and products are licensed by some of the largest publishers, ad networks and other ad tech companies worldwide.

Media.net is one of the largest contextual advertising company worldwide. Media.net has key operation centers across - North America, Europe and Asia. Media.net's US HQ is based in New York, and Global HQ in Dubai.

What you'll do

- Work with engineers and product teams to understand requirements, break down problems and translate them into scalable technical solutions.
- Design, develop, test and maintain clean, readable and production-quality code.
- Use AI coding assistants and developer tools responsibly to accelerate development, debugging, testing and documentation-while independently validating the output and maintaining code quality.
- Explore how AI/ML and intelligent automation can be applied to improve ad-tech products, engineering workflows, system performance and user experiences.
- Contribute across the software development lifecycle, including solution design, architecture, coding, testing, deployment and iteration.
- Debug issues, investigate root causes and improve system performance, reliability, scalability and usability.
- Participate in code reviews and technical discussions, and learn from experienced engineers and peers.
- Build a strong understanding of engineering trade-offs involved in high-scale, real-time systems.

.

What We're Looking For:

- Strong fundamentals in data structures, algorithms, computer science and problem-solving.
- Strong programming skills in at least one language such as Java, C++, C#, Python, JavaScript or similar.
- Understanding of core software engineering concepts such as object-oriented programming, databases, APIs and operating systems.
- Curiosity about AI and a willingness to adopt AI-powered development tools and workflows.
- Ability to use AI tools as an engineering accelerator-not as a substitute for understanding, reasoning, testing or code ownership.
- Interest in building scalable, reliable and high-performance software and solving complex technical problems.
- Ability to learn quickly, take ownership and work effectively in a collaborative environment.
- Strong analytical thinking and the ability to communicate technical ideas clearly.

Good to Have:

- Exposure to AI/ML concepts, generative AI, LLMs, APIs, prompt engineering or AI-enabled developer tools.
- Experience building projects that use AI/ML or integrating third-party APIs and services.
- Exposure to web technologies, distributed systems, networking, concurrency or cloud technologies.
- Experience with SQL/relational databases, caching, REST APIs or other backend technologies.
- Familiarity with Git and software development practices such as Agile, Scrum or Test-Driven Development.
- Personal projects, hackathons, open-source contributions, technical blogs or competitive programming experience.

Interview Round

- Online assessment (90 mins) DSA + Coding
- Technical Round 1 (60 mins) Problem Solving + Coding + Tech
- Technical Round 2 (60 mins) CS fundamentals + Project deep-dive + Engineering Judgement + AI/ML Scope
- HR Round (20 mins)

Note - Interviews and the online assessment evaluate unassisted problem-solving. Your fluency with AI tools is assessed separately, through how you talk about the projects you've built with them.

Why Join Us?

- Work on industry-leading ad-tech products that impact millions of users worldwide.
- Solve interesting engineering problems involving scale, performance, distributed systems and real-time technology.
- Work in an environment that embraces modern engineering practices and the adoption of AI across the software development lifecycle.
- Learn directly from experienced engineers and collaborate with talented technologists.
- Get exposure to problems where technology, data and AI can create meaningful product and business impact.

Other Benefits

- Flexible work hours and leaves
- Butler and concierge services
- And many more....

Internship Stipend - One Lakh Per Month

1. Executive Intelligence & Recruitment Blueprint

Company Heritage, Scale & Ad-Tech Dominance

Media.net is one of the world's largest contextual advertising companies and sell-side programmatic platforms (Directi heritage, founded by Divyank Turakhia; acquired by Miteno / Starry Media for $900M).

- **Yahoo! Bing Network Partnership**: Media.net exclusively powers the Yahoo! Bing Network contextual ads program, connecting high-intent search advertisers to premium publishers worldwide.
- **Global Footprint**: Manages ad supply on **over 500,000 publisher websites** across North America, Europe, and Asia (e.g., Forbes, CNN, Reuters, USA Today).
- **Engineering Constraint**: Real-Time Bidding (RTB) auctions execute under a **strict sub-50ms SLA**.
- **Core Stack**: High-performance Java, C++, Python, Scala microservices; Apache Kafka (millions of events/sec), Redis, Aerospike, MySQL, Elasticsearch, Kubernetes edge clusters.

Candidate Placement Profile & Compensation Details

- **Role**: Software Development Engineer (SDE) Intern (6-Month Internship + Pre-Placement Offer).
- **Monthly Stipend**: **¥1,00,000 / month** (1 LPM).
- **CTC on PPO Conversion**: **¥38.00 LPA Total Package**:
  - **Fixed Base Salary**: ¥18.00 Lakhs
  - **One-Time Joining Bonus**: ¥4.00 Lakhs
  - **Additional Performance / Retention Bonus**: ¥16.00 Lakhs
- **Eligible Degree & Branch**: B.Tech / M.Tech / Dual / Int MSc — All Branches (CGPA $\geq$ 6.0).

The 4 Recruitment Stages & Exact Expectations

1. **Online Assessment (90 Mins)**: 3 CP-level coding problems (InterviewBit / HackerEarth). Focus: DP, Graphs, Heaps, Binary Search, String Tries. Extremely strict automated AST plagiarism filtering.
2. **Technical Round 1 (60 Mins)**: Live Problem Solving & Unassisted Coding on Google Docs / Codeshare. Evaluates problem-solving agility, edge-case coverage, and clean modular code without IDE assistance.
3. **Technical Round 2 (60 Mins)**: Core CS Fundamentals (Operating Systems, Computer Networks, Database Internals) + Deep Resume Project Grilling + System Architecture Judgement.
4. **HR & Managerial Round (20 Mins)**: Cultural alignment with Directi values: high ownership, technical curiosity, meritocracy, resilience, and trade-off justification.

The Unassisted Problem-Solving Directive (Crucial JD Clause)

The official Media.net JD states:

> *"Interviews and the online assessment evaluate unassisted problem-solving. Your fluency with AI tools is assessed separately, through how you talk about the projects you've built with them."*

In technical rounds, the interviewer expects you to derive algorithms from first principles. If asked about AI, frame tools as an accelerator for test harness generation, fuzzing, or boilerplate drafting, while demonstrating 100% personal ownership of the architecture, memory layout, and deterministic mathematical validation.

2. Live Coding Protocol & Most Expected Algorithmic Problems

The 5-Step Unassisted Live Coding Protocol

When coding on Google Docs or Codeshare, execute this exact sequence:

1. **Clarify Constraints Immediately**: Ask about input bounds ($N \leq 10^5 \implies O(N \log N)$), memory constraints, negative values, and empty inputs.
2. **State the Brute-Force Baseline First**: Explicitly state the $O(N^2)$ or $O(2^N)$ approach to prove correctness before jumping to optimizations.
3. **Derive the Optimal Algorithm**: Explain the optimized data structure (Heap, Trie, DP, DSU) and wait for the interviewer's acknowledgment before typing.
4. **Dry-Run with Edge Cases**: Manually trace sample inputs and corner cases (empty array, single element, duplicates, extreme boundaries) before declaring completion.
5. **State Complexities Explicitly**: State Time and Space Big-O without prompting.

Problem 1: Top-K Generalized Second-Price (GSP) Vickrey Auction Engine

Problem Statement: In an ad exchange, N DSPs submit bids for K slots ($1 \leq K \leq N$). Each bid contains `dsp_id`, `bid_price`, and `timestamp_ms`. The top K bidders win. Ties are broken by earliest timestamp. The i-th winner pays the $(i+1)$-th bid price (or reserve price R). Determine the winning DSPs and clearing prices in $O(N \log K)$ time.

```cpp
#include <iostream>
#include <vector>
#include <string>
#include <queue>
#include <algorithm>

struct Bid {
    std::string dsp_id;
    double price;
    int64_t timestamp_ms;

    // Min-heap ordering: lowest priority evicted first
    bool operator>(const Bid& other) const {
        if (std::abs(price - other.price) > 1e-6) return price > other.price;
        if (timestamp_ms != other.timestamp_ms) return timestamp_ms < other.timestamp_ms;
        return dsp_id < other.dsp_id;
    }
};

struct Result { int rank; std::string dsp_id; double bid_price; double clearing_price; };

std::vector<Result> resolveGSPAuction(const std::vector<Bid>& bids, int K, double reserve) {
    std::priority_queue<Bid, std::vector<Bid>, std::greater<Bid>> min_heap;

    for (const auto& b : bids) {
        if (b.price < reserve) continue;
        min_heap.push(b);
        if (min_heap.size() > static_cast<size_t>(K + 1)) min_heap.pop();
    }

    std::vector<Bid> sorted;
    while (!min_heap.empty()) { sorted.push_back(min_heap.top()); min_heap.pop(); }
    std::reverse(sorted.begin(), sorted.end());

    std::vector<Result> res;
    int winners = std::min(K, static_cast<int>(sorted.size()));
    for (int i = 0; i < winners; ++i) {
        double clear = (i + 1 < static_cast<int>(sorted.size())) ? std::max(sorted[i + 1].price, reserve) :
            reserve;
        res.push_back({i + 1, sorted[i].dsp_id, sorted[i].price, clear});
    }
    return res;
}
```

Complexity: Time $O(N \log K)$, Auxiliary Space $O(K)$.

Problem 2: Contextual Keyword Wildcard Trie Matcher

Problem Statement: Advertisers register target keywords containing wildcards: `?` matches any single character; `*` matches zero or more characters. Given a publisher article token, return all matching campaign IDs.

```python
class TrieNode:
    def __init__(self):
        self.children = {}
        self.campaign_ids = []

class ContextualPatternMatcher:
    def __init__(self):
```

```
        self.root = TrieNode()

    def insert(self, pattern: str, campaign_id: int):
        node = self.root
        for char in pattern:
            if char not in node.children: node.children[char] = TrieNode()
            node = node.children[char]
        node.campaign_ids.append(campaign_id)

    def search(self, word: str) -> list:
        res = set()
        def dfs(node, idx):
            if idx == len(word):
                for cid in node.campaign_ids: res.add(cid)
                if '*' in node.children: dfs(node.children['*'], idx)
                return
            char = word[idx]
            if char in node.children: dfs(node.children[char], idx + 1)
            if '?' in node.children: dfs(node.children['?'], idx + 1)
            if '*' in node.children:
                star = node.children['*']
                dfs(star, idx)      # match 0 chars
                dfs(star, idx + 1)  # match 1+ chars
        dfs(self.root, 0)
        return sorted(list(res))
```

Problem 3: Weighted Interval Scheduling DP (Ad Slot Revenue Maximization)

Problem Statement: An online publisher has N ad campaigns, each with $[start_i, end_i, revenue_i]$. No two campaigns can run simultaneously on the same slot. Find the maximum revenue achievable in $O(N \log N)$ time.

```
import bisect

def max_campaign_revenue(campaigns: list) -> int:
    # campaigns: list of (start, end, revenue)
    if not campaigns: return 0
    sorted_c = sorted(campaigns, key=lambda x: x[1])
    n = len(sorted_c)
    end_times = [c[1] for c in sorted_c]
    dp = [0] * (n + 1)

    for i in range(1, n + 1):
        start, end, val = sorted_c[i - 1]
        # Binary search for latest campaign ending <= start
        idx = bisect.bisect_right(end_times, start)
        dp[i] = max(dp[i - 1], val + dp[idx])

    return dp[n]
```

Recurrence: $DP[i] = \max(DP[i-1], \text{revenue}_i + DP[p(i)])$. Complexity: Time $O(N \log N)$, Space $O(N)$.

Problem 4: DAG Pipeline Cycle Detection & Critical Path Latency

Problem Statement: Ad rendering requires executing N tasks with latencies L_i. Dependencies form a directed graph. Detect cycles (which cause SLA violations) and compute the critical path latency in $O(V + E)$ time using Kahn's algorithm.

```
#include <vector>
#include <queue>
#include <algorithm>

std::pair<bool, int> analyzePipeline(int n, const std::vector<int>& lat, const std::vector<std::pair<int, int>>&
    deps) {
    std::vector<std::vector<int>> adj(n);
    std::vector<int> in_deg(n, 0), comp_time = lat;

    for (const auto& [u, v] : deps) { adj[u].push_back(v); in_deg[v]++; }

    std::queue<int> q;
    for (int i = 0; i < n; ++i) if (in_deg[i] == 0) q.push(i);

    int visited = 0, critical_path = 0;
    while (!q.empty()) {
        int u = q.front(); q.pop(); visited++;
        for (int v : adj[u]) {
            comp_time[v] = std::max(comp_time[v], comp_time[u] + lat[v]);
            if (--in_deg[v] == 0) q.push(v);
        }
    }
    if (visited < n) return {true, -1}; // Cycle detected!
    for (int t : comp_time) critical_path = std::max(critical_path, t);
    return {false, critical_path};
}
```

Problem 5: Median of Streaming Bid Prices (Two Heaps Pattern)

Problem Statement: In an ad exchange, bid values arrive continuously in a stream. Maintain the running median in $O(\log N)$ insert time and $O(1)$ query time.

```cpp
#include <queue>

class StreamingMedian {
    std::priority_queue<int> max_heap; // Lower half
    std::priority_queue<int, std::vector<int>, std::greater<int>> min_heap; // Upper half

public:
    void addBid(int price) {
        if (max_heap.empty() || price <= max_heap.top()) max_heap.push(price);
        else min_heap.push(price);

        // Rebalance: max_heap can have at most 1 more element than min_heap
        if (max_heap.size() > min_heap.size() + 1) {
            min_heap.push(max_heap.top()); max_heap.pop();
        } else if (min_heap.size() > max_heap.size()) {
            max_heap.push(min_heap.top()); min_heap.pop();
        }
    }

    double getMedian() const {
        if (max_heap.size() > min_heap.size()) return max_heap.top();
        return (max_heap.top() + min_heap.top()) / 2.0;
    }
};
```

Problem 6: Trapping Rain Water (Two Pointers Pattern)

Problem Statement: Given N non-negative integers representing elevation map widths, compute how much water is trapped after raining.

```cpp
int trapWater(const std::vector<int>& height) {
    int left = 0, right = height.size() - 1, left_max = 0, right_max = 0, water = 0;
    while (left < right) {
        if (height[left] < height[right]) {
            if (height[left] >= left_max) left_max = height[left];
            else water += (left_max - height[left]);
            left++;
        } else {
            if (height[right] >= right_max) right_max = height[right];
            else water += (right_max - height[right]);
            right--;
        }
    }
    return water;
}
```

Complexity: Time $O(N)$, Auxiliary Space $O(1)$.

3. Operating Systems Deep Dive

Process vs. Thread Architecture & Low-Level Reality

- **Process**: An independent address space managed by the OS kernel. Has its own virtual page table hierarchy (PML4 on x86-64), file descriptor tables, signal handlers, and Process Control Block (PCB).
  - *Context Switch Mechanics*: Switches memory map via CR3 register reload. Forces invalidation of the CPU Translation Lookaside Buffer (TLB), triggering cold cache misses across L1/L2 and pipeline stalls (≈ 1–$3\,\mu$s).
- **Thread**: An independent execution flow within a process. Threads share the text, data/BSS, heap segments, and open socket descriptors, but maintain private **Stacks**, **Program Counters**, and registers in a Thread Control Block (TCB).
  - *Context Switch Mechanics*: Registers and stack pointers swapped; page table remains mapped. TLB entries remain valid ($\approx$ 100–300 ns).
- **`fork()` vs. `clone()` vs. Copy-on-Write (COW)**: Modern Linux implements `fork()` via `clone()` with Copy-on-Write. Memory pages are not duplicated immediately; page table entries are marked read-only. A physical copy occurs only when a process attempts a write.

Concurrency Primitives: Mutex vs. Spinlock vs. Semaphore

Primitive	Blocking / Waiting Behavior	Ad-Tech Low-Latency Use Case
Mutex	Sleeps waiting thread via OS kernel (`futex`); yields CPU slice.	Critical sections > 500 ns, disk I/O, network socket calls.
Spinlock	Busy-waits in user space burning CPU cycles (`PAUSE` instruction).	In-memory RTB locks lasting < 50 ns (e.g., metric counters).
Semaphore	Maintains an atomic counter allowing up to N concurrent threads.	Resource pool throttling (e.g., max 50 concurrent DSP connections).
Shared Mutex	Multiple concurrent readers, single exclusive writer.	In-memory routing tables and read-heavy campaign caches.

Condition Variables & The Spurious Wakeup Problem

In multi-threaded producer-consumer queues, a thread waking from a condition variable must **always** verify the condition inside a `while` loop, never an `if` statement:

```
std::unique_lock<std::mutex> lock(mtx);
// Correct: while loop guards against spurious wakeups and race conditions
while (queue.empty()) {
    cv.wait(lock); // Atomically unlocks mtx and puts thread to sleep
}
auto item = queue.front(); queue.pop();
```

Why?: POSIX allows threads to wake up without a signal (spurious wakeup), or another thread might consume the item between notification and lock acquisition.

Deadlocks: The 4 Coffman Conditions & Hierarchical Prevention

A deadlock occurs **if and only if** all four conditions hold simultaneously:

1. **Mutual Exclusion**: Non-shareable resource allocation.
2. **Hold and Wait**: A process holding resource A requests resource B.
3. **No Preemption**: Allocated resources cannot be forcibly revoked.
4. **Circular Wait**: P_0 waits for P_1, ..., P_n waits for P_0.

Production Prevention: Enforce a strict **global lock acquisition hierarchy** (always acquire Lock A before Lock B; never in reverse order).

Virtual Memory, Multi-Level Paging & TLB Shootdown

- **Address Translation**: Virtual address split into page directory offsets and page offset. The MMU traverses PML4 $\rightarrow$ PDP $\rightarrow$ PD $\rightarrow$ PT $\rightarrow$ Physical Frame.
- **Translation Lookaside Buffer (TLB)**: High-speed associative hardware cache. TLB Hit: < 1 ns. TLB Miss: 10–50 ns page table walk.

- **TLB Shootdown**: When a page table entry is modified (e.g., unmapping shared memory), the modifying core sends an Inter-Processor Interrupt (IPI) to all other cores to flush their local TLBs, causing inter-core latency spikes.
- **Thrashing & Working Set**: When aggregate memory demand exceeds physical RAM, the system spends more time servicing page faults than executing user instructions. Mitigated by increasing RAM or reducing thread working set size.

Cache Coherency, False Sharing & Memory Alignment

- **False Sharing**: Occurs when two independent variables accessed by different CPU cores reside on the same 64-byte cache line. Modifying one variable invalidates the entire cache line on other cores (MESI protocol), causing bus contention.
- **Fix**: Align independent variables to 64-byte boundaries using C++ `alignas(64)`.

4. Computer Networks & SRE at Scale

TCP Deep Dive: 3-Way Handshake, Teardown & SRE Mechanics

- **The 3-Way Handshake**: Client sends `SYN` → Server replies with `SYN-ACK` → Client sends `ACK`.
- **SYN Flood Attack & SYN Cookies**: Attackers send thousands of `SYN` packets from spoofed IPs without completing the handshake, exhausting the server's SYN backlog queue. Mitigation: **SYN Cookies** encode connection parameters into the initial sequence number, avoiding allocating memory until the client's final `ACK` arrives.
- **The 4-Way Teardown & `TIME_WAIT` Socket Exhaustion**:
  1. Client sends `FIN` → Server replies `ACK` → Server sends `FIN` → Client replies `ACK` → Client enters `TIME_WAIT`.
  2. *Duration*: $2 \times$ MSL (≈ 60 seconds) to absorb lingering packets.
  3. *The Production Hazard*: In an SSP processing 50,000 req/sec, opening and closing ephemeral connections creates tens of thousands of sockets in `TIME_WAIT`, exhausting port range (1024–65535) and throwing `EADDRNOTAVAIL`.
  4. *Production Resolution*: Implement persistent connection pooling, enable `SO_REUSEADDR`, and tune kernel `net.ipv4.tcp_tw_ = 1`.

TCP Flow Control vs. Congestion Control

- **Flow Control**: Protects the receiver from buffer overflow. Receiver advertises its available buffer space via the TCP Receive Window (`rwnd`). If `rwnd = 0`, sender pauses and emits zero-window probes.
- **Congestion Control**: Protects the intermediate network from packet collapse. Sender maintains a Congestion Window (`cwnd`):
  - *Slow Start*: `cwnd` doubles every RTT until Slow Start Threshold (`ssthresh`).
  - *Congestion Avoidance*: Increases `cwnd` linearly (+1 MSS per RTT).
  - *Fast Retransmit & Fast Recovery*: On 3 duplicate ACKs, retransmits lost segment immediately without waiting for timeout, cutting `cwnd` in half (Reno/CUBIC).
- **Nagle's Algorithm vs. Delayed ACK (The 40ms Hazard)**: Nagle buffers small packets until an ACK arrives; Delayed ACK waits 40ms before sending an ACK. When combined in low-latency systems, they introduce a catastrophic 40ms pause. **Fix**: Disable Nagle via `TCP_NODELAY`.

HTTP/1.1 vs. HTTP/2 vs. HTTP/3 (QUIC)

Feature	HTTP/1.1	HTTP/2	HTTP/3 (QUIC)
Transport	Single TCP connection per request (or pipelining).	Single TCP connection with binary framing.	UDP-based QUIC protocol.
Multiplexing	None (suffers from Application Head-of-Line blocking).	Stream multiplexing (interleaves frames over 1 TCP socket).	True independent stream multiplexing over UDP.
HoL Blocking	Severe at Application layer.	Solved at App layer; persists at TCP packet loss level.	Completely eliminated: packet loss on stream A does not stall stream B.
Handshake	1-RTT TCP + 2-RTT TLS 1.2 = 3 RTT.	1-RTT TCP + 1-RTT TLS 1.3 = 2 RTT.	0-RTT / 1-RTT connection setup with built-in TLS 1.3.

DNS Resolution Lifecycle: What Happens When You Type a URL

1. **Browser Cache & OS Hosts**: Checks browser cache, OS DNS cache, and local `/etc/hosts`.
2. **Recursive Resolver**: Queries ISP / local resolver (e.g., 8.8.8.8).
3. **Root Name Server**: Returns referral to the Top-Level Domain (TLD) server (`.com`).
4. **TLD Name Server**: Returns referral to the Authoritative Name Server (e.g., Cloudflare, AWS Route53).
5. **Authoritative Server**: Returns the final IP address (A / AAAA record).
6. **TCP / TLS Handshake**: Browser initiates TCP 3-way handshake + TLS 1.3 cryptographic session key exchange.
7. **HTTP GET & Rendering**: Browser requests HTML, parses DOM/CSSOM, constructs render tree, paints page.

Socket Programming: `select()` vs. `poll()` vs. `epoll()`

- `select()`: Limited to `FD_SETSIZE` (1024 descriptors). Checks ready sockets via $O(N)$ linear scan.
- `poll()`: Removes 1024 limit using an array of pollfds, but still requires $O(N)$ linear scanning across all descriptors on each event.

- `epoll()`: Uses an in-kernel Red-Black Tree to track descriptors and a Ready List linked list. When an I/O event fires, hardware interrupts append the ready socket to the list. `epoll_wait()` returns only active sockets in $O(1)$ **time**, powering high-concurrency event loops (Nginx, Envoy, Node.js).

5. Database Management Systems (DBMS) & SQL Mastery

Storage Engine Internals: B+ Tree Indexing

Media.net relies heavily on MySQL (InnoDB) and distributed NoSQL databases.

- **Why B+ Trees Beat B-Trees**:
  1. *Higher Fan-Out*: Internal nodes store only search keys and child pointers (no data payloads). Thousands of keys fit inside a single 16KB disk page, keeping tree height shallow ($h \leq 3$ for 10^7 rows).
  2. *Sequential Doubly-Linked Leaves*: All leaf nodes form a bidirectional doubly-linked list. Range scans (`WHERE date BETWEEN d1 AND d2`) require one $O(\log N)$ tree traversal to locate the start key, followed by linear linked-list scanning, eliminating random disk head seeks.
- **Clustered vs. Secondary (Non-Clustered) Index**:
  - *Clustered Index*: The leaf nodes *are* the actual physical table pages sorted by Primary Key. Every table has exactly 1 clustered index.
  - *Secondary Index*: Leaf nodes store the indexed key plus the primary key pointer.
  - *Bookmark Lookup*: Querying via secondary index requires two lookups: secondary index → primary key → row data.
  - *Covering Index*: If all columns requested in `SELECT` reside in the secondary index, the engine skips the second lookup entirely, providing a 10× speedup.
- **Composite Index Leftmost Prefix Rule**: An index on `(A, B, C)` can serve queries on `(A)`, `(A, B)`, and `(A, B, C)`, but **cannot** serve queries filtering only on `(B)` or `(C)`.

ACID Transactions & The 4 SQL Isolation Levels

Isolation Level	Dirty Read	Non-Repeatable	Phantom Read	Underlying Mechanism
Read Uncommitted	Yes	Yes	Yes	Reads raw uncommitted memory buffers; no shared locks.
Read Committed	No	Yes	Yes	MVCC: fresh consistent snapshot generated per statement.
Repeatable Read	No	No	No (in InnoDB)	MVCC: snapshot read created at first statement; Next-Key locks.
Serializable	No	No	No	Strict 2-Phase Locking (2PL); shared locks on read ranges.

10 Most Frequently Asked SQL Interview Queries

```sql
-- 1. N-th Highest Salary / Bid using DENSE_RANK()
WITH Ranked AS (
    SELECT bidder_id, bid_price, DENSE_RANK() OVER (ORDER BY bid_price DESC) as rk
    FROM dsp_bids
)
SELECT DISTINCT bid_price FROM Ranked WHERE rk = 2; -- 2nd Highest

-- 2. Second Highest Salary without Window Functions
SELECT MAX(bid_price) FROM dsp_bids WHERE bid_price < (SELECT MAX(bid_price) FROM dsp_bids);

-- 3. Department-Wise Highest Earner
SELECT dept_id, emp_name, salary FROM (
    SELECT dept_id, emp_name, salary,
           ROW_NUMBER() OVER (PARTITION BY dept_id ORDER BY salary DESC) as rn
    FROM employees
) t WHERE rn = 1;

-- 4. Delete Duplicate Records keeping only the lowest ID
DELETE FROM users
WHERE id NOT IN (
    SELECT min_id FROM (SELECT MIN(id) AS min_id FROM users GROUP BY email) t
);

-- 5. Self-Join: Employees earning more than their Managers
SELECT e.emp_name FROM employees e
JOIN employees m ON e.manager_id = m.id
WHERE e.salary > m.salary;

-- 6. Rolling 7-Day Average Ad Revenue
SELECT date, revenue,
       AVG(revenue) OVER (ORDER BY date ROWS BETWEEN 6 PRECEDING AND CURRENT ROW) as rolling_7d_avg
FROM publisher_revenue;

-- 7. Cumulative Running Total of Clicks per Campaign
```

```sql
SELECT campaign_id, event_time, clicks,
       SUM(clicks) OVER (PARTITION BY campaign_id ORDER BY event_time) as running_total
FROM ad_events;

-- 8. Find Consecutive Active Days / Logins (Gaps and Islands Pattern)
WITH RankedDays AS (
    SELECT user_id, login_date,
           DATE_SUB(login_date, INTERVAL ROW_NUMBER() OVER (PARTITION BY user_id ORDER BY login_date) DAY) as grp
    FROM user_logins
)
SELECT user_id, COUNT(*) as consecutive_days FROM RankedDays
GROUP BY user_id, grp HAVING COUNT(*) >= 3;

-- 9. Find Publishers who never served video ads (Left Join vs NOT EXISTS)
SELECT p.id, p.name FROM publishers p
WHERE NOT EXISTS (
    SELECT 1 FROM ad_impressions i WHERE i.publisher_id = p.id AND i.format = 'video'
);

-- 10. Pivot Table: Convert Formats into Columns
SELECT publisher_id,
       SUM(CASE WHEN format = 'banner' THEN revenue ELSE 0 END) AS banner_rev,
       SUM(CASE WHEN format = 'native' THEN revenue ELSE 0 END) AS native_rev,
       SUM(CASE WHEN format = 'video'  THEN revenue ELSE 0 END) AS video_rev
FROM ad_logs GROUP BY publisher_id;
```

6. Ad-Tech Domain Architecture & System Design

The Sub-50ms Real-Time Bidding (RTB) Latency Budget

When a user opens an article on Forbes, an auction request triggers across hundreds of DSPs before the page renders:

Step	Pipeline Operation	Budget	Underlying Mechanism / Technology
1	Browser → Edge SSP Request	10 ms	HTTP/2, Anycast DNS routing to closest edge PoP
2	Contextual NLP & Keyword Extraction	5 ms	In-memory Trie matcher, cached URL semantic vector
3	OpenRTB Serialization & DSP Dispatch	2 ms	Zero-copy JSON / Protocol Buffers serialization
4	DSP Bid Computation (Parallel Wait)	25 ms	Hard deadline timeout; non-responding DSPs dropped
5	Auction Resolution (Second-Price Vickrey)	3 ms	Min-Heap / QuickSelect top-K selection & pricing
6	Ad Markup Rendering & Async Logging	5 ms	Asynchronous logging to Kafka; return ad markup HTML
Total	**End-to-End Auction Pipeline**	**50 ms**	**Hard Sub-50ms SLA Guarantee**

Header Bidding (`Prebid.js`) vs. Traditional Waterfall

- **Waterfall (Legacy)**: Sequential daisy-chaining where requests cascaded down through SSPs. Caused 500ms–1500ms latency and left money on the table.
- **Header Bidding**: Lightweight JavaScript (`Prebid.js`) in the publisher's page `<head>` makes **concurrent asynchronous calls** to multiple SSPs before calling the ad server, running a transparent, unified auction that maximizes yield by 30–50%.

High-Scale Data Structures in Ad-Tech

- **Frequency Capping**: Restricts how often an ad is shown to a user. Stored efficiently using **Redis Bitmaps** and sliding window deques.
- **HyperLogLog (HLL)**: Estimates unique audience cardinality across billions of impressions using only **1.5 KB of memory** with $\approx 0.81\%$ standard error.
- **Bloom Filters**: In-memory probabilistic filters used at edge proxies to drop known click-fraud bot traffic in $< 10\,\mu s$.

Machine Coding (LLD): Thread-Safe In-Memory Cache with TTL & LRU

```cpp
#include <unordered_map>
#include <list>
#include <mutex>
#include <chrono>
#include <optional>

template <typename K, typename V>
class LRUCacheWithTTL {
    struct Item { K key; V val; std::chrono::steady_clock::time_point exp; };
    size_t cap_;
    std::list<Item> list_; // Front = MRU, Back = LRU
    std::unordered_map<K, typename std::list<Item>::iterator> map_;
    mutable std::mutex mtx_;

public:
    explicit LRUCacheWithTTL(size_t cap) : cap_(cap) {}

    std::optional<V> get(const K& key) {
        std::lock_guard<std::mutex> lock(mtx_);
        auto it = map_.find(key);
        if (it == map_.end()) return std::nullopt;
        if (std::chrono::steady_clock::now() > it->second->exp) {
            list_.erase(it->second); map_.erase(it); return std::nullopt;
        }
        list_.splice(list_.begin(), list_, it->second); // Move to MRU
        return it->second->val;
    }

    void put(const K& key, const V& val, int64_t ttl_ms) {
        std::lock_guard<std::mutex> lock(mtx_);
        auto exp = std::chrono::steady_clock::now() + std::chrono::milliseconds(ttl_ms);
        auto it = map_.find(key);
        if (it != map_.end()) {
            it->second->val = val; it->second->exp = exp;
            list_.splice(list_.begin(), list_, it->second);
            return;
        }
        if (map_.size() >= cap_) {
            map_.erase(list_.back().key); list_.pop_back(); // Evict LRU
        }
        list_.push_front({key, val, exp});
        map_[key] = list_.begin();
```

```
    }
};
```

High-Level Design (HLD): Scalable Real-Time Ad Matching Engine

- **Ingestion Edge Gateway**: Terminated via Envoy / Nginx proxy with Anycast DNS routing and persistent HTTP/2 connection pooling with registered DSPs.
- **Contextual Tokenizer**: Caches semantic keyword vectors for popular publisher URLs in Redis with sub-millisecond lookup.
- **Auction Coordinator**: Emits parallel OpenRTB bid requests to matching DSPs with a **hard 25ms timeout**. Non-responding DSPs are dropped.
- **Second-Price Clearing Engine**: Computes highest bidder and sets clearing price to (2nd_highest_bid + \$0.01).
- **Decoupled Event Streaming**: Winning impressions and click tracking beacons are published asynchronously to an Apache Kafka topic, isolating analytical ingestion from real-time auction latency.

7. Candidate Resume Defense & Grilling Traps

Project 1: Warehouse PathMapper (IBYD Technology)

Interviewer Question: *"You claim optimal pathfinding on a* $10,000 \times 10,000$ *grid in* $< 0.5\,s$*. On* 10^8 *cells, Dijkstra will timeout. How did you achieve this?"*

- **The Master Defense**:

1. *Topological Waypoint Abstraction*: In real warehouses, 95% of space consists of fixed rack walls. Rather than searching 10^8 cells, I precomputed a hierarchical topological waypoint graph connecting aisle intersections and picking bays ($\approx 1,500$ nodes).
2. *Bidirectional A**: Used Manhattan distance heuristic $h(n) = |x_1 - x_2| + |y_1 - y_2|$ running from both start and target simultaneously, terminating when search frontiers met.
3. *Contiguous Cache Locality*: Coordinates were stored in flat 1D array buffers, eliminating pointer chasing and L1/L2 CPU cache misses.
4. *Ad-Tech Analogy*: Directly parallels ad exchange routing: instead of evaluating every DSP linearly, we prune target criteria using topological clustering.

Project 2: Uplan — Adversarial Document Intelligence Pipeline

Interviewer Question: *"The Media.net JD explicitly tests unassisted problem-solving. Did you write the logic, or did LLMs do the thinking?"*

- **The Master Defense**:

1. *Deterministic Rule Engine First*: LLMs are non-deterministic and hallucinate when validating numbers. I engineered a zero-hallucination mathematical verification engine in Python that checks bank balances, tax credits, and salary figures against deterministic Boolean rules.
2. *Structural Encoding*: Used Gemini Flash strictly as a compilation extractor to compress page metadata into a typed semantic JSON graph, cutting prompt tokens by 98%.
3. *Adversarial LangGraph Topology*: Created Proposer and Adversary roles orchestrated over a deterministic Directed Acyclic Graph (DAG).
4. *AI as Accelerator*: I designed the state graphs, type definitions, and rule engines; AI was used for synthetic edge-case test generation.

Project 3: Alternative Data Radar

Interviewer Question: *"How did you handle anti-scraping, rate limits, and SQL concurrency?"*

- **The Master Defense**:

1. *Proxy Rotation*: Routed traffic via Bright Data Web Unlocker, managing TLS fingerprint rotation and exponential backoff with jitter on HTTP 429/503.
2. *Async Worker Architecture*: Used Python `asyncio` worker pools to stream parsed signals asynchronously into the database.
3. *SQL Optimization*: Created composite indexes on `(company_id, metric_date DESC)` to ensure constant-time dashboard reads.

Defending Your Dual Background: M.Tech Signal Processing + B.Tech CSE

Interviewer Question: *"Why apply for Core SDE at Media.net with a Master's in Signal Processing?"*

- **The Winning Narrative**:

1. *B.Tech in CSE*: Provided rock-solid foundations in Data Structures, Algorithms, OS, Networks, and Databases.
2. *M.Tech at NIT Rourkela*: Trained me in high-dimensional linear algebra, statistical signal filtering, and real-time streaming pipelines.
3. *Direct Ad-Tech Application*: Programmatic ad bidding is fundamentally a real-time digital signal stream. Click fraud detection relies on statistical anomaly filtering (Kalman filtering); contextual matching uses high-dimensional vector embeddings; and sub-50ms RTB requires microsecond timing budgeting.

8. Behavioral Scenarios & Directi Culture

Directi / Media.net Engineering Values

Media.net inherits the Directi engineering ethos:

- **Extreme Ownership**: You own your code from architecture through production deployment and monitoring.
- **Debate by Data**: In technical arguments, seniority does not win; empirical benchmarks and rigorous complexity proofs win.
- **First-Principles Thinking**: Reject "industry best practices" unless backed by technical trade-off justification.

6 High-Impact STAR Behavioral Responses

1. **Production Outage / High-Pressure Bug**:
   - *Situation*: Warehouse PathMapper crashed on $10,000 \times 10,000$ grids 48 hours before client demo due to memory allocation spikes.
   - *Action*: Profiled allocations with Valgrind; identified tuple instantiation thrashing garbage collection. Refactored into contiguous 1D array buffers and topological waypoint graphs.
   - *Result*: Scaled to 10k grid in 0.48s with zero memory leaks.
2. **Technical Disagreement with Peer**:
   - *Situation*: At Ziroh Labs, team debated using ResNet-50 vs. lightweight unsupervised HOG for video keyframes.
   - *Action*: Instituted an objective 24-hour benchmark spike comparing inference FPS, CPU RAM, and precision.
   - *Result*: HOG ran $11\times$ faster with comparable 96.45% accuracy; data-driven consensus achieved.
3. **Handling Technical Debt vs. Shipping Speed**:
   - *Action*: Delivered minimum viable feature with strict interface abstraction boundaries, isolating fast-shipped logic so modular refactoring did not break consumers.
4. **Why Media.net?**:
   - *Answer*: Scale (500k+ publishers, billions of daily requests), pure engineering meritocracy, and distributed systems operating under sub-50ms latency SLAs aligning with my dual background in CSE and Signal Processing.

9. Rapid Recall CheatSheet & Last-Minute Formulas

High-Yield Systems & Queueing Formulas

- **Amdahl's Law (Speedup Limit)**: $S_{\text{latency}} = \frac{1}{(1-p)+\frac{p}{s}}$ (If 10% is serial, speedup cannot exceed 10× even with ∞ cores).
- **Little's Law**: $L = \lambda \times W$ (Average requests in system L = Throughput λ× Latency W. For $50,000$ req/s at 50 ms, the system holds $50000 \times 0.05 = 2,500$ in-flight requests).
- **Bandwidth-Delay Product (BDP)**: BDP = Bandwidth (bits/s) × RTT (s) (Determines socket buffer size).

C++ Concurrency & Syntax Quick-Ref

```cpp
// 1. Min-Heap for Top-K
std::priority_queue<int, std::vector<int>, std::greater<int>> min_pq;

// 2. Custom Comparator Heap
auto cmp = [](const auto& a, const auto& b) { return a.price > b.price; };
std::priority_queue<Bid, std::vector<Bid>, decltype(cmp)> pq(cmp);

// 3. Binary Search
int idx = std::upper_bound(arr.begin(), arr.end(), target) - arr.begin();

// 4. Thread-Safe Mutex Lock
std::mutex mtx;
{ std::lock_guard<std::mutex> lock(mtx); }

// 5. Condition Variable
std::condition_variable cv;
std::unique_lock<std::mutex> ulock(mtx);
cv.wait(ulock, []{ return !queue.empty(); });
```

Key Ad-Tech Business Metrics

- **CPM**: Cost Per Mille = Cost per 1,000 ad impressions.
- **eCPM**: $\frac{\text{Total Earnings}}{\text{Total Impressions}} \times 1000$.
- **CTR**: $\frac{\text{Total Clicks}}{\text{Total Impressions}} \times 100\%$.
- **Vickrey Auction (Second-Price)**: Highest bidder wins, pays second-highest bid +$0.01. Dominant strategy for truthful bidding.