

CS3431 – Database Systems I

Project Overview

Murali Mani

CS3431



One continuous course project

- **Description:** Envision a database application, and implement it fully.
- **Teaming :** Teams of 2 students each
- **Grading :** Collect points over the phases

CS3431



Phases

- Phase 0: (due Sep 10, 7:59 am)
 - Decide on your team and project. Send an email to cs3431-ta@cs.wpi.edu with (a) the people in the team (b) project title and a short one para description of what you will work on for this project
- Phase 1: (due Sep 21, 7:59 am via turnin)
 - Represent the application requirements as an ER schema, translate the ER to relational, analyze the relational design using normalization theory, come up with DDL statements for the relational schema, test the DDL statements.
- Phase 2: (due Oct 12, 7:59 am via turnin)
 - Analyze the operations needed for your application, represent them in SQL DML, build an interface for the end-user. Demonstrate your working project to the TA/instructor.

CS3431



What DBMS to use?

- Oracle
 - Accounts already created, Server version 10.2.0.3.0
 - Documentation: <http://otn.oracle.com>
- MySQL: Version 5.0. 45
 - To create an account, visit <http://www.wpi.edu/Academics/CCC>
 - Documentation: <http://www.mysql.com>

CS3431



How to set up Oracle



- Check the type of shell that you are using.
For this from your unix prompt, type:
`echo $SHELL`
- Most of you will get for above “ /bin/tcsh “
– this means you are using turbo c-shell
- From your shell prompt, type :
`echo $PATH`
- Set environment variables based on if path is empty or not (next slide)

CS3431



How to set up Oracle



- Add following to your .cshrc at the end – if your path is not empty

```
setenv ORACLE_BASE /usr/local/oracle/  
setenv ORACLE_HOME /usr/local/oracle/product/11.1.0/db_1  
setenv PATH ${PATH}:${ORACLE_HOME}/bin  
setenv ORACLE_SID WPIDBR2  
setenv TWO_TASK ${ORACLE_SID}
```

CS3431



How to set up Oracle (contd...)



- Add to .cshrc – if your path is empty

setenv PATH .

```
setenv ORACLE_BASE /usr/local/oracle
setenv ORACLE_HOME
    /usr/local/oracle/product/11.1.0/db_1
setenv PATH ${PATH}:${ORACLE_HOME}/bin
setenv ORACLE_SID WPIDBR2
setenv TWO_TASK ${ORACLE_SID}
```



How to set up Oracle (contd...)



- After editing file .cshrc
- Please run :

```
source ~/.cshrc
```

CS3431



Problems while setting up Oracle



- Important – Set up Oracle immediately and see that it is working
- Many of you will run into problems, typically due to simple typos (be careful !! Have an extra “shell” open and working – so even if you make mistakes, you can undo changes from the working shell).
- If you have identified a project partner, start working with him/her on this !

CS3431



Oracle introduction



- Connecting
 - `sqlplus <userName>/<passwd>`
 - For example,
 - `sqlplus myname/myname`
 - Change passwd using password command
 - You will end up submitting your passwd; therefore don't use password that you use for other purposes.

CS3431



Oracle useful commands



These commands can be executed from the SQL shell

```
SELECT * FROM cat; -- lists tables you have created
SELECT table_name FROM user_tables; -- as above.
```

```
DESCRIBE <tableName>; -- describes the schema for
the table with name tableName
```

```
help index; -- shows list of help topics;
```

```
help start; -- illustrates how to use command start
```

```
exit; -- exit from the SQL shell
```

CS3431



Using Oracle from Windows



- Multiple ways:
 - Use aquastudio software from aquafold.com (NOT free).
 - Use DreamCoder for Oracle 4.2 (FREE !!)

Connect as:

```
server: oracle.wpi.edu
port: 1521 (this is the default)
SID: WPIDBR2
```

- Download oracle client for windows. Connect using sqlplus client or other tools:

```
sqlplus mmani/mmani@//oracle.wpi.edu:1521/WPIDBR2
```

CS3431



MySQL introduction



- Connecting

- `mysql -h<host> -u<user> -p<passwd>
<dbname>`

- Useful commands

- `show tables;`
- `describe <tableName>;`
- `exit;`
- Look at manual for other commands.

CS3431



Working with the Data Server



CS3431



Testing that you are set

```
CREATE TABLE student(sNum INTEGER,sName VARCHAR (30));
-- creates table student      with two columns

INSERT INTO student VALUES (1, 'Joe');
-- insert one row into the student table

SELECT * FROM student;
-- select all rows from student table

DELETE FROM student;
-- delete all rows in the student table

DROP TABLE student;
-- drop student table

Purge recyclebin;
-- purge recyclebin tables that get created.
```

CS3431



Running scripts in SQLPlus

To enter OS environment, use sqlplus command:
Host

Now you can execute OS commands, like :
cd.. , **exit** , **etc.**

- Create a file in your file system in the current directory called createTable.sql
 - @createTable -- executes the script
 - start createTable -- also executes the script
- If you want to save your output to a file (similar to **script** in Unix)
 - spool <fileName>
 - <executeCmds...>
 - spool off;

CS3431



Loading data from a text file (SQLldr utility)



- `CREATE TABLE myTable1 (a int, b int);`

- Create data file, say: sample.dat
- Put data into the file :

```
1,11  
2,22  
3,33  
4,44
```

CS3431



Loading from text file (Contd)



- Create control file, say load.ctl

```
LOAD DATA  
INFILE sample.dat  
INTO TABLE myTable1  
FIELDS TERMINATED BY ','  
(a,b)
```

- Invoke SQL Loader (from your UNIX shell):

- `$ sqlldr <user/password> control=load.ctl`

CS3431



Building Interfaces



- Call Level Interface
 - Perl – to build web interfaces
 - JDBC – Java, servlets etc
- Embedded SQL
 - C API (Pro*C)
 - C++API (Pro*C++)
 - Java API (SQLJ) [Oracle]

CS3431



Get Started Now ...



- Pick project partner (feel free to use mywpi to recruit partner)
- Jointly toss around ideas about cool project
- Try out basics – to assure you have access to oracle (or mysql)

CS3431

