Employee Management System

Full Stack Developer Intern - Technical Assessment
Solution Report

Name	Adarsh Singh
Email	adarshx68@gmail.com
Date	30 October 2026
Stack	React 19 + Vite, ASP.NET Core 8 Web API, SQL Server 2022 Express
GitHub	https://github.com/Adarsh041-arch/EMPLOYEE_MANAGEMENT_SYSTEM
Google Drive	https://drive.google.com/drive/folders/17aUOIJAy5_ITs9ubIAa_XphRhDtlz_IC

Contents

1. Overview
2. Technology stack
3. Architecture
4. Database design
5. Employee code generation and transfers
6. API
7. Validation rules
8. Security
9. Frontend and screenshots
10. Testing
11. Setup steps
12. Dependencies
13. Assumptions

1. Overview


The application lets a company manage its employees. Admins and managers can register employees, edit them, transfer them between departments and deactivate them. Every employee gets a code based on their department (for example `I0001` for the first IT employee). When someone is transferred, they get the next free code in the new department, while their internal ID stays the same and the move is recorded in a transfer history.

The employee list supports a global search, six filters, sorting on every column and pagination with 5, 10 or 20 rows. All of this runs on the server, so it works the same however many employees there are. Everything in the brief is implemented: Task A (frontend), Task B (REST API) and Task C (database).

2. Technology stack

Layer	Technology	Why
Frontend	React 19, Vite 6, React Router 6, react-hook-form + zod, axios, plain CSS	Small and fast to build. zod lets the form use the same rules as the backend.
Backend	ASP.NET Core 8 Web API, EF Core 8, FluentValidation, JWT Bearer, Swashbuckle	8.0 is the current LTS. EF Core migrations give a repeatable schema.
Database	SQL Server 2022 Express	Free, and it supports the transaction isolation and row locking the code generator needs.
Testing	xUnit + WebApplicationFactory, Vitest	The API tests run against a real SQL Server database, not an in-memory fake.


3. Architecture



The API has three layers. Controllers deal only with HTTP (routes, roles, status codes). Services hold the business rules: code generation, transfers, masking and query building. EF Core does the data access. Validation runs before a controller is called (FluentValidation), and one middleware turns every error into a ProblemDetails response with the correct status code, so the controllers contain no try/catch blocks.

In development, Vite forwards `/api` to the API, so the browser sees a single origin. CORS is also set up for `http://localhost:5173`.

4. Database design



- **Primary and foreign keys** on every table. Personal details and code sequences share the primary key of their parent (1:1).
- **Unique constraints** on `EmployeeCode`, `Email`, department name and prefix, role name and username.
- **Check constraints** on salary (> 0), status and gender.
- **Indexes** on the columns used for filtering and sorting, so searches and paging stay fast.
- **Delete rules:** deleting an employee removes their personal details (cascade), but transfer history is protected (restrict), so an employee who has been transferred can only be deactivated. Departments and roles can't be deleted while employees use them (restrict).

The schema is created by the EF Core migration (`backend/EmployeeManagement.Api/Migrations`). The same thing is available as a plain script in `database/schema.sql`. Sample data is in `database/seed.sql`: 5 departments, 5 roles, 22 employees spread over every department, role, salary band and status, 3 users and 4 transfer history rows. I checked that both scripts run on an empty database.

5. Employee code generation and transfers

Code generation

Each department has one row in `EmployeeCodeSequences`. To get the next code, the service runs this statement inside the transaction that creates the employee:

```
UPDATE EmployeeCodeSequences WITH (ROWLOCK)
SET LastNumber = LastNumber + 1
OUTPUT inserted.LastNumber
WHERE DepartmentId = @departmentId
```

The update holds an exclusive lock on that department's row until the transaction commits. A second request for the same department waits, then sees the new number, so no two employees can get the

same code. Departments don't block each other. The final code is the prefix plus four digits (`F0004`). The unique index on `EmployeeCode` is a final safety net. One test fires 10 create requests in parallel for one department and checks that all 10 codes are different.

Transfer

1. Begin a **serializable** transaction.
2. Load the employee (404 if missing) and the target department (400 if it doesn't exist).
3. Reject a transfer to the same department (400).
4. Get the next code from the target department's sequence (same lock as above).
5. Insert a history row with the old/new department, old/new code, date, reason and the user who made the transfer.
6. Update the employee's department and code. The internal `Id` stays the same.
7. Commit. Any exception rolls back all of it, including the sequence increment.

Example from the sample data: Rahul Sharma joined IT as `I0001` and was transferred to HR, so his code became the next free HR code (`H0005`). The history table shows both codes.

6. API

Method	Endpoint	Roles	Description
POST	/api/auth/login	public	Returns a JWT (8 hours) with the role and employee id
GET	/api/employees	all	Search, filter, sort, page. Employee role only gets their own record
GET	/api/employees/{id}	all	Full details, including personal details
GET	/api/employees/{id}/personal-details	all	Aadhaar/PAN masked unless Admin
POST	/api/employees	Admin, Manager	Create; returns 201 with the generated code
PUT	/api/employees/{id}	Admin, Manager	Update; blank Aadhaar/PAN keeps the stored values
DELETE	/api/employees/{id}	Admin	Deactivate; `?hard=true` deletes permanently if there is no transfer history (otherwise 409)
POST	/api/employees/{id}/transfer	Admin, Manager	Transfer to another department
GET	/api/employees/{id}/transfers	all	Transfer history
GET	/api/departments, /api/roles	all	Dropdown data

List parameters: `search, departmentId, roleId, status, gender, joiningFrom, joiningTo, minSalary, maxSalary, sortBy, sortDir, pageNumber, pageSize`. The response is `{ items, totalCount, pageNumber, pageSize, totalPages }`. Sorting is only allowed on whitelisted columns, with the Id as a tie-breaker so paging is stable.

Status codes: 200/201/204 on success; 400 for validation errors (with a per-field `errors` object); 401 for a missing or invalid token or wrong login; 403 when the role isn't allowed; 404 for an unknown employee; 409 for a duplicate email or code; 500 for anything unexpected (logged, with a generic message returned).

Documentation: Swagger UI at `/swagger` (with an "Authorize" button for the token), `docs/swagger.json`, and a Postman collection at `docs/EmployeeManagement.postman_collection.json`. Its login request saves the token automatically.

7. Validation rules

The same rules are checked in the browser (zod) and on the server (FluentValidation), so the API is safe even when it's called directly.

Field	Rule
Full name	Required, letters and spaces only, max 100
Email	Required, valid format, unique (409 if taken; stored in lower case)


Mobile	Exactly 10 digits
Aadhaar	Exactly 12 digits; the form formats it as XXXX-XXXX-XXXX while typing; dashes or spaces are accepted by the API
PAN	`^[A-Z]{5}[0-9]{4}[A-Z]$` (ABCDE1234F); the form changes it to upper case while typing
Date of birth	Required, not in the future, at least 18 years old, not before 1900
Gender / Status	Required, must be one of the allowed values
Department / Role	Required, must exist
Joining date	Required, after the date of birth, at most one year from today
Address	Required, max 300
Annual salary	Greater than zero
Transfer	New department, date and reason required; new department must differ from the current one; transfer date can't be before the joining date
List query	pageSize 5/10/20, pageNumber ≥ 1, minSalary ≤ maxSalary, known sortBy/sortDir

8. Security


- **Authentication:** JWT (HMAC-SHA256) checked for signature, issuer, audience and expiry. Passwords are stored as BCrypt hashes. A failed login gives the same message for an unknown user and a wrong password.
- **Authorization:** role checks on each endpoint (Admin / Manager / Employee). Users with the Employee role can only read their own record, and the API enforces this, not just the UI. Managers cannot deactivate employees (not even by setting the status in Edit) and cannot edit their own record.
- **Sensitive data:** Aadhaar and PAN are encrypted with AES-256-GCM (random nonce per value) using a key from configuration. Only Admins see the decrypted values; everyone else sees `XXXX-XXXX-1234` / `ABXXXXX34F`. The global search does not include Aadhaar or PAN at all.
- **SQL injection:** all queries go through EF Core with parameters, including the one raw SQL statement (an interpolated `SqlQuery` becomes a parameterised query).
- **Secrets:** keys go in `appsettings.Development.json`, which is git-ignored. The connection string uses Windows authentication, so the repository and ZIP contain no passwords.
- **Errors:** unexpected exceptions are logged on the server, and the client only gets a generic message without stack traces.

9. Frontend and screenshots


The frontend has five screens. Search, filters, sorting, page size and page number are all stored in the URL. They combine with each other, survive a page refresh, and the browser back button works as expected. Search waits until the user stops typing (400 ms). Buttons the current role can't use are hidden. On phones, the table switches to a stacked card layout.




Employee list (admin), 10 rows per page, sorted by code




Status = Active combined with the ₹3–5 LPA salary range, 5 rows per page, sorted by salary (descending)




Registration form showing validation messages (Aadhaar is being formatted as it is typed)




Details page right after creating an employee (code I0007 generated)




Transfer form: the current department is read-only and is left out of the "New department" options




After the transfer: the code changed from I0007 to H0006, and the history row was added




The list shows the new code



Logged in with the Employee role: only their own record, no edit actions



Phone width (390px): the table switches to cards



Swagger UI

10. Testing

- **Backend: 68 xUnit tests** (`cd backend && dotnet test`). 35 are unit tests for the validators and the encryption/masking helper. 33 are API tests that start the real API in memory against a separate SQL Server database (`EmployeeManagement_Test`, re-created on each run). They cover code generation, 10 parallel creates in one department, transfers (new code, same Id, history row, same-department rejection, two parallel transfers of one employee, transfer date before joining), duplicate email (409), validation errors (400), unknown id (404), role restrictions (401/403), masking, search fields (including the check that Aadhaar/PAN are *not* searched), filter combinations, paging consistency and sorting.
- **Frontend: 33 Vitest tests** (`cd frontend && npm test`) for the zod form rules (including the date checks and local-time "today"), Aadhaar formatting and the salary presets.
- **End-to-end:** I also drove the running app with a headless browser through login, sorting, filters, a refresh with filters set, the form errors, create, duplicate email, transfer, editing as a manager, the Employee role view, phone width and Swagger. The screenshots above come from that run.

11. Setup steps

1. Install the .NET 8 SDK, SQL Server 2022 Express and Node.js 20 or newer.
2. `cd backend/EmployeeManagement.Api` and copy `appsettings.example.json` to `appsettings.Development.json` (it contains sample keys).
3. If your SQL Server instance isn't `.\SQLEXPRESS`, change the connection string in `appsettings.json`.

4. `cd backend`, `dotnet restore`, then `dotnet run --project EmployeeManagement.Api --launch-profile http`. On first run this creates the database and loads the sample data. The API is at http://localhost:5005/swagger.
5. `cd frontend`, `npm ci`, then `npm run dev`, and open http://localhost:5173.
6. Log in as `admin / Admin@123`, `manager / Manager@123` or `employee / Employee@123`.

Alternatively, run `database/schema.sql` and then `database/seed.sql` on an empty database. The README covers both options in more detail.

12. Dependencies

Backend NuGet package	Version
Microsoft.EntityFrameworkCore.SqlServer	8.0.11
Microsoft.EntityFrameworkCore.Design	8.0.11
Microsoft.AspNetCore.Authentication.JwtBearer	8.0.11
Swashbuckle.AspNetCore	6.6.2
FluentValidation.AspNetCore	11.3.0
BCrypt.Net-Next	4.0.3
Tests: xunit / xunit.runner.visualstudio / Microsoft.NET.Test.Sdk / Microsoft.AspNetCore.Mvc.Testing / coverlet.collector	2.5.3 / 2.5.3 / 17.8.0 / 8.0.11 / 6.0.0
Tool: dotnet-ef	8.0.11

Frontend npm package	Version
react, react-dom	19.3.1
react-router-dom	6.28.0
axios	1.7.9
react-hook-form / @hookform/resolvers / zod	7.54.2 / 3.9.1 / 3.24.1
Dev: vite / @vitejs/plugin-react / vitest / eslint	6.4.5 / 4.7.0 / 2.1.8 / 9.39.5

Restore with `dotnet restore` and `dotnet tool restore` (nuget.org, configured in `nuget.config`) and `npm ci` (exact versions from `package-lock.json`).

13. Assumptions

- "Delete" deactivates an employee so their history isn't lost. Admins can still delete permanently, but only employees who have never been transferred.
- A department can only change through a transfer, never through Edit, so the code and history always match.
- Salary presets are lower-inclusive and upper-exclusive, as in the brief (₹3,00,000 belongs to "3–5 LPA"). The API's min/max filters are inclusive, so the UI sends ₹2,99,999.99 as the upper limit for "1–3 LPA".

- The Employee role is linked to one employee record and can only read that record.
- Codes are never reused. If an employee leaves a department, their old code is not handed out again.