CYCLOPROP | CP-RB-231 | REV B | PROTOTYPE

NOT RELEASED FOR FABRICATION - NOMINAL DIMENSIONS IN mm

MODEL: RB_Socket_Eye_D7_Sphere5p05_PROTOTYPE

MODEL SHA256: 7a893a0440386394aaeadfecc09a10f49ab5c0e6f002502e521369e09fbaa078







DIMENSION / INTERFACE DEFINITION

Machined7075-T6 proposed, quantity8. Socket ball centre is local origin.
Main eye OD7, thickness4.40, lower/side spherical cavityD5.05; axial mouthD4.40.
Female M6x0.35 cap interface: major envelopeD6, from localZ0.80 to2.20. Cap flange seats atZ2.20.
Open D6 body top admits D5 ball before cap installation. Thread fit, runout, tap-drill and full physical thread geometry need release.
Neck approx4x4, reaches7.50 from ball centre. Bond boreD2.10x2.70; nominal tube insertion2.50.
Qualified lubrication, wear, locking torque/process, pullout proof and cyclic tests required. Geometry is not a strength release.

DO NOT SCALE. Individual model-view scales may differ. Nominal dimensions in mm.
Release holds apply: fits, loaded clearances, locking, fatigue and supplied material.
Thread solids show major envelopes; DO NOT use as tap-drill sizes.

SOLIDWORKS Educational Product. For Instructional Use Only.