

CYCLOPROP | CP-RB-227 | REV B | PROTOTYPE


NOT RELEASED FOR FABRICATION - NOMINAL DIMENSIONS IN mm

MODEL: RB_ISO8750_D1x8_INSTALLED_REFERENCE

MODEL SHA256: 9d69947e967479a1c38dbd1bd65f76e22bd3035fb836fecba7abe5f24c009126







View scale 8.0:1. All dimensions nominal unless a limit is explicitly stated.
Release holds apply: fits, loaded clearances, locking, fatigue and supplied material.
Thread solids show major envelopes; DO NOT use as tap-drill sizes.

DIMENSION / INTERFACE DEFINITION

Quantity4. Assigned material: AISI 4340 Steel, normalized.
SPIROL standard-duty metric ISO8750 coiled pin1x8 installed envelope D1x8.
Free OD1.05..1.15 and recommended hole1.00..1.04 from manufacturer guide p17.
Proposed line-ream1.00..1.02.
Coils/chamfers omitted; steel density proxy only, no supplied grade, fit retention, fatigue or physical proof inferred.
For METAL trunnion only.
Supplier/application approval required.
RELEASE HOLD: supplied material, fits, finish, tolerances and approved loads/locking require review. Nominal thread envelopes are not tap-drill geometry.
Use model identified by SHA for referenced contour; this prototype inspection sheet does not release undimensioned manufacturing features.

SOLIDWORKS Educational Product. For Instructional Use Only.