

Gate Assignment 2

Adarsh Sai - AI20BTECH11001

Download all python codes from

<https://github.com/Adarsh541/EE3900/blob/main/Gate2/codes/Gate2.py>

Download latex-tikz codes from

<https://github.com/Adarsh541/EE3900/blob/main/Gate2/Gate2.tex>

1 PROBLEM(GATE EC 2010 Q.41)

A continuous time LTI system is described by

$$\frac{d^2y(t)}{dt^2} + 4\frac{dy(t)}{dt} + 3y(t) = 2\frac{dx(t)}{dt} + 4x(t) \quad (1.0.1)$$

Assuming zero initial conditions, the response $y(t)$ of the above system for the input $x(t) = e^{-2t}u(t)$ is given by

- 1) $(e^t - e^{3t})u(t)$
- 2) $(e^{-t} - e^{-3t})u(t)$
- 3) $(e^{-t} + e^{-3t})u(t)$
- 4) $(e^t + e^{3t})u(t)$

2 SOLUTION

Lemma 2.1 (Table of Laplace Transforms).

Time Function $f(t) = \mathcal{L}^{-1}\{F(s)\}$	Laplace transform of $f(t)$ $F(s) = \mathcal{L}\{f(t)\}$
$u(t)$	$\frac{1}{s}, s > 0$
$g'(t)$	$sG(s) - g(0)$
$g''(t)$	$s^2G(s) - sg(0) - g'(0)$
$e^{-at}u(t)$	$\frac{1}{s+a}, s+a > 0$

Lemma 2.2. Linearity of Laplace Transform

$$\mathcal{L}\{af(t) + bg(t)\} = a\mathcal{L}\{f(t)\} + b\mathcal{L}\{g(t)\} \quad (2.0.1)$$

From Lemma-2.1 Laplace transform of $x(t) = e^{-2t}u(t)$ is given by

$$X(s) = \frac{1}{s+2} \quad (2.0.2)$$

Since initial conditions are zero. Laplace Transform of (1.0.1) gives

$$s^2Y(s) + 4sY(s) + 3Y(s) = 2sX(s) + 4X(s) \quad (2.0.3)$$

$$Y(s) = \frac{2(s+2)}{s^2+4s+3}X(s) \quad (2.0.4)$$

$$= \frac{1}{s+1} - \frac{1}{s+3} \quad (2.0.5)$$

From Lemma-2.1. Inverse Laplace transform of $Y(s)$ is given by

$$y(t) = e^{-t}u(t) - e^{-3t}u(t) \quad (2.0.6)$$

$$= (e^{-t} - e^{-3t})u(t) \quad (2.0.7)$$

∴ The required option is B.




Fig. 4: Plot of input and output responses in time domain.