

SEJONG TABLET PRESS REPORT

(1/2)

Software version (2.0)

PRODUCTION REPORT

Product Information

Station No :	Station 2		
Machine Name :	MC081 SEJONG 49D	Product Name :	Amisulpride 200mg
User ID :	pk8943	Batch NO. :	ADNC26011
Print Interval :	125000 Tabs	Running Time :	02 Hour 48 Min59 Sec
Total Counter :	Tabs	Total Running Time :	206 Hour 13 Min

Setting Value

Feeder :	Auto ; 90 %	Manual ; 13 RPM	
Filling Cam :	Cam C 8.5-14mm	Target Quantity :	500000 Tabs
Air Pressure Low Limit :	400 Kpa	Hydraulic High Limit :	15 Mpa (Low: 0.1 Mpa)
Oil Lubrication S1 :	Interval: 300 Min	Supply: 3 Sec	Upper Punch
Oil Lubrication S2 :	Interval: 300 Min	Supply: 3 Sec	Lower Punch
Oil Lubrication S3 :	Interval: 999 Min	Supply: 0 Sec	Lower Head
Powder Supply Time :	30 Sec	Initial Reject Time :	8.3 Sec

Control Limits & Stop Conditions

Parameter	% Setting	kN Limit	Stop Condition
HSP (High Stop Pressure)	45 %	32.9 kN	Stop: Yes
HEP (High Error Pressure)	30 %	29.49 kN	10 Rot / 10 Tabs
HCP (High Control Pressure)	3 %	23.37 kN	5 Times
Ref (Reference Pressure)	-	22.69 kN	-
LCP (Low Control Pressure)	3 %	22.01 kN	5 Times
LEP (Low Error Pressure)	29 %	16.11 kN	10 Rot / 10 Tabs
LSP (Low Stop Pressure)	45 %	12.48 kN	Stop: Yes
SD Limit	15 %	-	Stop: Yes
Pre HSP	-	37.08 kN	Stop: Yes

Pressure Data

Section	Mean (kN)	SD (%)	Min (kN) [Punch]	Max (kN) [Punch]
Pre Pressure	2.3 kN	0.9 %	2.25 kN [#4]	2.35 kN [#48]
Main Pressure	20.03 kN	3.5 %	18.26 kN [#44]	21.68 kN [#9]
Filling Depth Adjustments	Increase: 21 times			

Date: 2026-09-01 00:00:00

Operator: p.s.krishna murthy

Signature: _____

SEJONG TABLET PRESS REPORT

(2/2)

Software version (2.0)

PRODUCTION REPORT - OPERATIONS & TABLET DATA

Operation Value

Disk Speed :	15 RPM	Capacity :	88200 Tabs/hour
Feeder Status :	AUTO	Feeder Speed :	13 RPM
Pre-Pressure Thickness :	10.43 mm	Lower Punch Position :	12.43 mm (Penet: 2 mm)
Main-Pressure Thickness :	3.49 mm	Lower Punch Position :	6.49 mm (Penet: 3 mm)
Filling Depth :	12.3 mm	Current Cam :	Cam C 8.5-14mm
Main Air Pressure :	606 Kpa	Hydraulic Pressure :	7.5 Mpa
Oil S1 Remain Time :	11 Min	Oil S2 / S3 Remain :	S2: 11 Min S3: 512 Min
Powder Status :	Enable	Dust Collector :	ON
Initial Reject :	ON	Buzzer :	ON

Tablet Data & Production Counters

Metric	Value / Count (Tabs)	Percentage / Details
Total Counter	250,026 Tabs	100% Machine Processed
A.W.C. Counter	242,991 Tabs	Automatic Weight Controlled
HEP (High Error Punch Reject)	7 Tabs	7 (0.0%)
LEP (Low Error Punch Reject)	1 Tabs	1 (0.0%)
GOOD Tablets	242,983 Tabs	242983 (100.0%)

Date: 2026-09-01 00:00:00

Operator: p.s.krishna murthy

Signature: _____