

SEJONG TABLET PRESS REPORT

(1/2)

Software version (2.0)

PRODUCTION REPORT

Product Information

Station No :	Station 1		
Machine Name :	MC081 SEJONG 49D	Product Name :	Amisulpride 200mg
User ID :	ts11401	Batch NO. :	ADNC26015
Print Interval :	125000 Tabs	Running Time :	04 Hour 12 Min52 Sec
Total Counter :	Tabs	Total Running Time :	229 Hour 53 Min

Setting Value

Feeder :	Auto ; 90 %	Manual ; 13 RPM	
Filling Cam :	Cam C 8.5-14mm	Target Quantity :	500000 Tabs
Air Pressure Low Limit :	400 Kpa	Hydraulic High Limit :	15 Mpa (Low: 0.1 Mpa)
Oil Lubrication S1 :	Interval: 300 Min	Supply: 3 Sec	Upper Punch
Oil Lubrication S2 :	Interval: 300 Min	Supply: 3 Sec	Lower Punch
Oil Lubrication S3 :	Interval: 999 Min	Supply: 0 Sec	Lower Head
Powder Supply Time :	30 Sec	Initial Reject Time :	8.3 Sec

Control Limits & Stop Conditions

Parameter	% Setting	kN Limit	Stop Condition
HSP (High Stop Pressure)	45 %	29.35 kN	Stop: Yes
HEP (High Error Pressure)	30 %	26.32 kN	10 Rot / 10 Tabs
HCP (High Control Pressure)	3 %	20.85 kN	5 Times
Ref (Reference Pressure)	-	20.24 kN	-
LCP (Low Control Pressure)	3 %	19.64 kN	5 Times
LEP (Low Error Pressure)	29 %	14.37 kN	10 Rot / 10 Tabs
LSP (Low Stop Pressure)	45 %	11.13 kN	Stop: Yes
SD Limit	15 %	-	Stop: Yes
Pre HSP	-	33.22 kN	Stop: Yes

Pressure Data

Section	Mean (kN)	SD (%)	Min (kN) [Punch]	Max (kN) [Punch]
Pre Pressure	2.32 kN	0.8 %	2.28 kN [#10]	2.39 kN [#25]
Main Pressure	20.07 kN	4.6 %	17.71 kN [#24]	22.35 kN [#3]
Filling Depth Adjustments	Increase: 45 times			

Date: 2026-09-04 00:00:00

Operator: t.sudheer babu

Signature: _____

SEJONG TABLET PRESS REPORT

(2/2)

Software version (2.0)

PRODUCTION REPORT - OPERATIONS & TABLET DATA

Operation Value

Disk Speed :	15 RPM	Capacity :	88200 Tabs/hour
Feeder Status :	AUTO	Feeder Speed :	13 RPM
Pre-Pressure Thickness :	11.14 mm	Lower Punch Position :	13.14 mm (Penet: 2 mm)
Main-Pressure Thickness :	3.46 mm	Lower Punch Position :	6.46 mm (Penet: 3 mm)
Filling Depth :	11.99 mm	Current Cam :	Cam C 8.5-14mm
Main Air Pressure :	619 Kpa	Hydraulic Pressure :	7.5 Mpa
Oil S1 Remain Time :	94 Min	Oil S2 / S3 Remain :	S2: 94 Min S3: 94 Min
Powder Status :	Enable	Dust Collector :	ON
Initial Reject :	ON	Buzzer :	ON

Tablet Data & Production Counters

Metric	Value / Count (Tabs)	Percentage / Details
Total Counter	375,056 Tabs	100% Machine Processed
A.W.C. Counter	367,304 Tabs	Automatic Weight Controlled
HEP (High Error Punch Reject)	4 Tabs	4 (0.0%)
LEP (Low Error Punch Reject)	0 Tabs	0 (0%)
GOOD Tablets	367,300 Tabs	367300 (100.0%)

Date: 2026-09-04 00:00:00

Operator: t.sudheer babu

Signature: _____