

SEJONG TABLET PRESS REPORT

(1/2)

Software version (2.0)

PRODUCTION REPORT

Product Information

Station No :	Station 2		
Machine Name :	MC081 SEJONG 49D	Product Name :	Amisulpride 100mg
User ID :	mr11358	Batch NO. :	ADNB26004
Print Interval :	250000 Tabs	Running Time :	07 Hour 00 Min25 Sec
Total Counter :	Tabs	Total Running Time :	243 Hour 49 Min

Setting Value

Feeder :	Auto ; 90 %	Manual ; 13 RPM	
Filling Cam :	Cam C 8.5-14mm	Target Quantity :	1000000 Tabs
Air Pressure Low Limit :	400 Kpa	Hydraulic High Limit :	15 Mpa (Low: 0.1 Mpa)
Oil Lubrication S1 :	Interval: 300 Min	Supply: 3 Sec	Upper Punch
Oil Lubrication S2 :	Interval: 300 Min	Supply: 3 Sec	Lower Punch
Oil Lubrication S3 :	Interval: 999 Min	Supply: 0 Sec	Lower Head
Powder Supply Time :	30 Sec	Initial Reject Time :	7.1 Sec

Control Limits & Stop Conditions

Parameter	% Setting	kN Limit	Stop Condition
HSP (High Stop Pressure)	45 %	18.86 kN	Stop: Yes
HEP (High Error Pressure)	30 %	16.91 kN	10 Rot / 10 Tabs
HCP (High Control Pressure)	3 %	13.4 kN	5 Times
Ref (Reference Pressure)	-	13.01 kN	-
LCP (Low Control Pressure)	3 %	12.62 kN	5 Times
LEP (Low Error Pressure)	29 %	9.23 kN	10 Rot / 10 Tabs
LSP (Low Stop Pressure)	45 %	7.15 kN	Stop: Yes
SD Limit	15 %	-	Stop: Yes
Pre HSP	-	21.05 kN	Stop: Yes

Pressure Data

Section	Mean (kN)	SD (%)	Min (kN) [Punch]	Max (kN) [Punch]
Pre Pressure	2.42 kN	0.7 %	2.37 kN [#4]	2.47 kN [#29]
Main Pressure	14.22 kN	4.9 %	12.25 kN [#29]	16.7 kN [#8]
Filling Depth Adjustments	Increase: 140 times			

Date: 2026-09-06 00:00:00

Operator: mahaboob ramzan

Signature: _____

SEJONG TABLET PRESS REPORT

(2/2)

Software version (2.0)

PRODUCTION REPORT - OPERATIONS & TABLET DATA

Operation Value

Disk Speed :	18 RPM	Capacity :	105840 Tabs/hour
Feeder Status :	AUTO	Feeder Speed :	16 RPM
Pre-Pressure Thickness :	10.78 mm	Lower Punch Position :	12.78 mm (Penet: 2 mm)
Main-Pressure Thickness :	3.26 mm	Lower Punch Position :	6.26 mm (Penet: 3 mm)
Filling Depth :	10.84 mm	Current Cam :	Cam C 8.5-14mm
Main Air Pressure :	655 Kpa	Hydraulic Pressure :	7.5 Mpa
Oil S1 Remain Time :	160 Min	Oil S2 / S3 Remain :	S2: 160 Min S3: 259 Min
Powder Status :	Enable	Dust Collector :	ON
Initial Reject :	ON	Buzzer :	ON

Tablet Data & Production Counters

Metric	Value / Count (Tabs)	Percentage / Details
Total Counter	750,104 Tabs	100% Machine Processed
A.W.C. Counter	726,523 Tabs	Automatic Weight Controlled
HEP (High Error Punch Reject)	2,113 Tabs	2113 (0.3%)
LEP (Low Error Punch Reject)	22 Tabs	22 (0.0%)
GOOD Tablets	724,388 Tabs	724388 (99.7%)

Date: 2026-09-06 00:00:00

Operator: mahaboob ramzan

Signature: _____