

Scan Firewall

Report generated by Nessus™

Sat, 03 Jun 2023 07:34:10 EDT

TABLE OF CONTENTS
Vulnerabilities by Host
• 192.168.100.150

192.168.100.150



Scan Information

Start time: Sat Jun 3 07:24:03 2023

End time: Sat Jun 3 07:34:10 2023

Host Information

Netbios Name: METASPLOITABLE

IP: 192.168.100.150
OS: Linux Kernel 2.6

Vulnerabilities

136769 - ISC BIND Service Downgrade / Reflected DoS

Synopsis

The remote name server is affected by Service Downgrade / Reflected DoS vulnerabilities.

Description

According to its self-reported version, the instance of ISC BIND 9 running on the remote name server is affected by performance downgrade and Reflected DoS vulnerabilities. This is due to BIND DNS not sufficiently limiting the number fetches which may be performed while processing a referral response.

An unauthenticated, remote attacker can exploit this to cause degrade the service of the recursive server or to use the affected server as a reflector in a reflection attack.

See Also

https://kb.isc.org/docs/cve-2020-8616

Solution

Upgrade to the ISC BIND version referenced in the vendor advisory.

Risk Factor

Medium

CVSS v3.0 Base Score

8.6 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

7.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.2

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

ı

References

CVE CVE-2020-8616 XREF IAVA:2020-A-0217-S

Plugin Information

Published: 2020/05/22, Modified: 2020/06/26

Plugin Output

udp/53/dns

Installed version : 9.4.2
Fixed version : 9.11.19

90509 - Samba Badlock Vulnerability

Synopsis

An SMB server running on the remote host is affected by the Badlock vulnerability.

Description

The version of Samba, a CIFS/SMB server for Linux and Unix, running on the remote host is affected by a flaw, known as Badlock, that exists in the Security Account Manager (SAM) and Local Security Authority (Domain Policy) (LSAD) protocols due to improper authentication level negotiation over Remote Procedure Call (RPC) channels. A man-in-the-middle attacker who is able to able to intercept the traffic between a client and a server hosting a SAM database can exploit this flaw to force a downgrade of the authentication level, which allows the execution of arbitrary Samba network calls in the context of the intercepted user, such as viewing or modifying sensitive security data in the Active Directory (AD) database or disabling critical services.

See Also

http://badlock.org

https://www.samba.org/samba/security/CVE-2016-2118.html

Solution

Upgrade to Samba version 4.2.11 / 4.3.8 / 4.4.2 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:U/RL:OF/RC:C)

References

BID 86002

CVE CVE-2016-2118 XREF CERT:813296

Plugin Information

Published: 2016/04/13, Modified: 2019/11/20

Plugin Output

tcp/445/cifs

Nessus detected that the Samba Badlock patch has not been applied.

139915 - ISC BIND 9.x < 9.11.22, 9.12.x < 9.16.6, 9.17.x < 9.17.4 DoS

Synopsis The remote name server is affected by a denial of service vulnerability. Description According to its self-reported version number, the installation of ISC BIND running on the remote name server is version 9.x prior to 9.11.22, 9.12.x prior to 9.16.6 or 9.17.x prior to 9.17.4. It is, therefore, affected by a denial of service (DoS) vulnerability due to an assertion failure when attempting to verify a truncated response to a TSIG-signed request. An authenticated, remote attacker can exploit this issue by sending a truncated response to a TSIG-signed request to trigger an assertion failure, causing the server to exit. Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number. See Also https://kb.isc.org/docs/cve-2020-8622 Solution Upgrade to BIND 9.11.22, 9.16.6, 9.17.4 or later. Risk Factor Medium CVSS v3.0 Base Score 6.5 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:N/I:N/A:H) CVSS v3.0 Temporal Score 5.7 (CVSS:3.0/E:U/RL:O/RC:C) **VPR** Score 3.6 CVSS v2.0 Base Score 4.0 (CVSS2#AV:N/AC:L/Au:S/C:N/I:N/A:P) CVSS v2.0 Temporal Score 3.0 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

ı

References

CVE CVE-2020-8622 XREF IAVA:2020-A-0385-S

Plugin Information

Published: 2020/08/27, Modified: 2021/06/03

Plugin Output

udp/53/dns

Installed version: 9.4.2

Fixed version : 9.11.22, 9.16.6, 9.17.4 or later

136808 - ISC BIND Denial of Service

Synopsis The remote name server is affected by an assertion failure vulnerability. Description A denial of service (DoS) vulnerability exists in ISC BIND versions 9.11.18 / 9.11.18-S1 / 9.12.4-P2 / 9.13 / 9.14.11 / 9.15 / 9.16.2 / 9.17 / 9.17.1 and earlier. An unauthenticated, remote attacker can exploit this issue, via a specially-crafted message, to cause the service to stop responding. Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number. See Also https://kb.isc.org/docs/cve-2020-8617 Solution Upgrade to the patched release most closely related to your current version of BIND. Risk Factor Medium CVSS v3.0 Base Score 5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:N/A:H) CVSS v3.0 Temporal Score 5.3 (CVSS:3.0/E:P/RL:O/RC:C) **VPR Score** 5.1 CVSS v2.0 Base Score 4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:N/A:P) CVSS v2.0 Temporal Score 3.4 (CVSS2#E:POC/RL:OF/RC:C) STIG Severity

References

CVE CVE-2020-8617 XREF IAVA:2020-A-0217-S

Plugin Information

Published: 2020/05/22, Modified: 2023/03/23

Plugin Output

udp/53/dns

Installed version : 9.4.2
Fixed version : 9.11.19

57608 - SMB Signing not required

Synopsis

Signing is not required on the remote SMB server.

Description

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

See Also

http://www.nessus.org/u?df39b8b3

http://technet.microsoft.com/en-us/library/cc731957.aspx

http://www.nessus.org/u?74b80723

https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html

http://www.nessus.org/u?a3cac4ea

Solution

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

Plugin Information

Published: 2012/01/19, Modified: 2022/10/05

Plugin Output

tcp/445/cifs

10407 - X Server Detection

Synopsis

An X11 server is listening on the remote host

Description

The remote host is running an X11 server. X11 is a client-server protocol that can be used to display graphical applications running on a given host on a remote client.

Since the X11 traffic is not ciphered, it is possible for an attacker to eavesdrop on the connection.

Solution

Restrict access to this port. If the X11 client/server facility is not used, disable TCP support in X11 entirely (nolisten tcp).

Risk Factor

Low

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2000/05/12, Modified: 2019/03/05

Plugin Output

tcp/6000/x11

X11 Version : 11.0