

Methods 3: Multilevel Statistical Modeling and Machine Learning

Week 6: *Mid-way evaluation and Machine Learning Intro*

November 2, 2021

by: Lau Møller Andersen

These slides are distributed according to the CC
BY 4.0 licence:

<https://creativecommons.org/licenses/by/4.0/>



Study Café

how is it going?

Reminder:
Office hours
(If assignments are hard, why is
no one coming?)

Python book in Stakbogladden

<https://www.stakbogladden.dk/soegning.asp?phrase=9781783555130>

Also available online at the
Royal Library (thanks, Emil!)



BOG

Python machine learning : unlock deeper insights into machine learning with this vital guide to cutting-edge predictive analytics

Sebastian Raschka author; Randal S Olson author of foreword
2015; 1st edition

[Tilgængelig online >](#)

Practical exercise tomorrow

To make sure that *Python* runs within *R Markdown*, make sure you have the *reticulate* package installed



```
install.packages('reticulate')
```

Also create a text file that is called *.Renviron* (remember the dot) placed in the folder where your *RProj* file is. It should have a single line: `RETICULATE_PYTHON=PATH` where `PATH` is the path to your *methods3* conda environment. Use the commands below to find the paths:

```
library(reticulate)
print(conda_list())
```

```
##           name                               python
## 1  miniconda3          /home/lau/miniconda3/bin/python
## 2   methods3    /home/lau/miniconda3/envs/methods3/bin/python
## 3      mne          /home/lau/miniconda3/envs/mne/bin/python
## 4  mne_0.17    /home/lau/miniconda3/envs/mne_0.17/bin/python
## 5 mne_func_sig /home/lau/miniconda3/envs/mne_func_sig/bin/python
## 6   mnedev      /home/lau/miniconda3/envs/mnedev/bin/python
## 7  psychopy      /home/lau/miniconda3/envs/psychopy/bin/python
## 8  fslpython      /usr/local/fsl/fslpython/bin/python
## 9  fslpython /usr/local/fsl/fslpython/envs/fslpython/bin/python
```

Practical exercise tomorrow



NB! No spaces around equals sign!

Practical exercise tomorrow

Update environment

```
conda env create --force -f methods3_environment.yml
```

Overwrite old environment

Update environment (new packages have been added). Run this command from the folder *week_06*

Mid-way evaluation

Mid-way evaluation

- 1) Write something you liked about the course so far
- 2) Write something you did not like about the course so far
- 3) What would you change?

Next time: I'll summarise the feedback on the three points and what I'll change

Learning goals

Evaluating and comparing models

1) Learning tools for comparing models

- 1) Variance explained

- 2) Likelihood ratio tests

- 3) Information criteria

2) Bridging to out-of-sample

Why are we modelling?

Remember Emil's slides from week 03

- To be able to understand the world
- To be able to predict and manipulate the world

$$F = G \frac{m_1 m_2}{r^2}$$

EXPLANATION



NASA/Bill Ingalls

PREDICTION

What constitutes a good model?

Remember Emil's slides from week 03

- Accurate estimation of the underlying parameters of the population distribution
- Generalisation to new data

EXPLANATION

PREDICTION

Within an **explanatory** framework, how can we assess whether we have done a good job?

Variance explained

- Pros
 - R^2 is intuitive
- Cons
 - More complex models will always explain more variance
 - Hard to interpret in the case of collinearity
 - R^2 doesn't give us what we want

Likelihood ratio

- Pros
 - Models can be compared in a principled way by reference to a theoretical distribution, χ^2 . (In the single level case, F can be calculated)
- Cons
 - Models have to be nested in one another
 - Maximum likelihood fitting may be biased for complex models
 - Requires large sample sizes
 - Be careful if collinearity is high

Information criteria

- Pros
 - Models can be compared even though one is not nested within the other (response data has to be the same though)
- Cons
 - Number of effective parameters not well defined for multilevel models
 - Maximum likelihood fitting may be biased for complex models

Did you learn? (it's not easy)

Evaluating and comparing models

1) Learning tools for comparing models

- 1) Variance explained

- 2) Likelihood ratio tests

- 3) Information criteria

2) Bridging to out-of-sample

Learning goals

Explanation and prediction

- 1) Understanding that fitting (explaining) often leads to overfitting
- 2) Learning methods to prevent overfitting by introducing *bias*
- 3) Understanding how the error can be decomposed into *bias* and *variance*

To fit is to overfit

(Yarkoni and Westfall, 2017)

Overfitting: fitting sample-specific noise,
which is thus not representative of the
population






Fig. 1. Training and test error produced by fitting either a linear regression (left) or a 10th-order polynomial regression (right) when the true relationship in the population (red line) is linear. In both cases, the test data (green) deviate more from the model's predictions (blue line) than the training data (blue). However, the flexibility of the 10th-order polynomial model facilitates much greater overfitting, resulting in lower training error but much higher test error than the linear model. MSE = mean squared error.

(Yarkoni and Westfall, 2017)


A sample of 10 linear or quadratic?




A sample of 10 linear or quadratic?




A sample of 10 linear or quadratic?



Residuals (linear)



Residuals (quadratic)



Quadratic:

$$ax^2 + bx + c$$

Linear:

$$bx + c$$


Estimates

$a = 0,6184; b = 3,0201$




$b = 3,020$

Now a sample of 100



$$b = 1,650$$



$$a = -0,03074 \approx 0; b = 1,650$$




Fig. 2. An estimator's predictions can deviate from the desired outcome (or true scores) in two ways. First, the predictions may display a systematic tendency (or *bias*) to deviate from the central tendency of the true scores (compare right panels with left panels). Second, the predictions may show a high degree of *variance*, or imprecision (compare bottom panels with top panels).

(Yarkoni and Westfall, 2017)

Which two of these does our least-squares solution prefer?




FIGURE 3.7. Accuracy versus precision. A schematic illustration of the differences between accuracy and precision of source localization. After left median-nerve stimulation, activations is expected in the right-hemisphere hand region of the primary somatosensory cortex. The foot area is shown at the top of the head. See text for further explanation.

(Hari and Puce, 2017)




Fig. 3. Schematic illustration of the bias-variance decomposition. (Left) Under the classical error model, prediction error is defined as the sum of squared differences between true scores and observed scores (black lines). (Right) The bias-variance decomposition partitions the total sum of squared errors into two separate components: a bias term that captures a model's systematic tendency to deviate from the true scores in a predictable way (black line) and a variance term that represents the deviations of the individual observations from the model's expected prediction (gray lines).

Bias variance decomposition

$$E[(y_0 - \hat{f}(x_0))^2] = \text{bias}(\hat{f}(x_0))^2 + \text{var}(\hat{f}(x_0)) + \sigma^2$$

$$\text{bias}(\hat{f}(x_0)) = E[\hat{f}(x_0)] - f(x_0)$$

is the *expected* squared error between the true value y_0 and its estimates based on fits $\hat{f}(x_0)$

We'll look more into this during tomorrow's exercise

Multilevel modelling as a *bias* introducer

“For example, some readers may be surprised to learn that multilevel modeling approaches to analyzing clustered data—which have recently seen a dramatic increase in adoption in psychology—improve on ordinary least squares (OLS) approaches to estimating individual cluster effects by deliberately biasing (through “shrinking” or “pooling”) the cluster estimates toward the estimated population average”

(Yarkoni and Westfall, 2017)

Introducing *bias*

“In a widely used form of penalized regression called lasso regression (Tibshirani, 1996, 2011), this leastsquares criterion is retained, but the overall cost function that the estimation seeks to minimize now includes an additional penalty term that is proportional to the sum of the absolute values of the coefficients.”

(Yarkoni and Westfall, 2017)

Penalised regression

$$\text{RSS} = \sum (y_i - \hat{y}_i)^2 \text{ (minimise to obtain least squares solution)}$$

$$\text{lasso regression: } \text{RSS} + \lambda \sum_{j=1}^p |\beta_j| \text{ (minimise this sum)}$$

$$\text{ridge regression: } \text{RSS} + \lambda \sum_{j=1}^p (\beta_j^2) \text{ (minimise this sum)}$$

i : observations

p : predictor variables

λ : a constant

Penalised regression

$RSS = \sum (y_i - \hat{y}_i)^2$ (minimise to obtain least squares solution)

lasso regression : $RSS + \lambda \sum_{j=1}^p |\beta_j|$ (minimise this sum)

ridge regression : $RSS + \lambda \sum_{j=1}^p (\beta_j^2)$ (minimise this sum)

i : observations

p : predictor variables

λ : a constant

Group discussion

In each case: what happens when?

1. λ increases?
2. λ decreases?
3. λ is 0?
4. λ goes towards infinity?

Penalised regression

$$\text{RSS} = \sum (y_i - \hat{y}_i)^2 \text{ (minimise to obtain least squares solution)}$$

$$\underset{\lambda}{\text{argmin}} = \text{RSS} + \lambda \sum_{j=1}^p |\beta_j|$$

$$\underset{\lambda}{\text{argmin}} = \text{RSS} + \lambda \sum_{j=1}^p (\beta_j^2)$$

i : observations

p : predictor variables

λ : a constant

How to choose λ ?

```
##  
## Call:  
## lm(formula = hp ~ mpg + wt + drat + qsec, data = mtcars)  
##  
## Coefficients:  
## (Intercept)          mpg           wt          drat          qsec  
##      473.779       -2.877       26.037        4.819       -20.751
```

What is λ equal to here?


```
sum.of.squares.total <- sum((y - mean(y))^2)  
sum.of.squared.errors.lm <- sum(residuals(linear_model)^2)  
print(r.squared.lm <- 1 - sum.of.squared.errors.lm/sum.of.squares.total)
```

```
## [1] 0.8072553
```

How to choose $\lambda_{(lasso)}$?

```
##  
## Call:  glmnet(x = x, y = y, alpha = 1, lambda = c(0, 0.2, 2, 4, 20,  
100))  
##  
##          lambda          RSS      penalty          sum  
## Df    %Dev Lambda          lambda          RSS      penalty          sum  
## 1    0 0.0000  100.0          100.0 145726.9          0.0          145726.9  
## 2    2 0.6567   20.0        20.00000 50025.64218        14.05496 50039.69714  
## 3    3 0.8004    4.0         4.00000 29082.92003        41.34363 29124.26366  
## 4    3 0.8051    2.0         2.00000 28408.50683        44.99057 28453.49740  
## 5    4 0.8072    0.2         0.20000 28097.60764        52.47741 28150.08505  
## 6    4 0.8073    0.0         0.00000 28088.09951        54.46997 28142.56948
```

How to choose λ ?



What does λ do (ridge)?

$$\hat{\beta}_{ridge} = (X^T X + \lambda I)^{-1} X^T y$$

I : an identity matrix with p predictor variables

λ : a constant (small)

What is $X^T X$?

```
head(X)
```

```
##                (Intercept)  mpg    wt drat  qsec
## Mazda RX4                1 21.0 2.620 3.90 16.46
## Mazda RX4 Wag            1 21.0 2.875 3.90 17.02
## Datsun 710                1 22.8 2.320 3.85 18.61
## Hornet 4 Drive            1 21.4 3.215 3.08 19.44
## Hornet Sportabout         1 18.7 3.440 3.15 17.02
## Valiant                   1 18.1 3.460 2.76 20.22
```


```
print(cov.X)
```

$$X_{COV} = X^T X$$

```
##                mpg          wt          drat          qsec
## mpg  14042.310 1909.7528 2380.2770 11614.745
## wt   1909.753  360.9011  358.7190  1828.095
## drat 2380.277  358.7190  422.7907  2056.914
## qsec 11614.745 1828.0946 2056.9140 10293.480
```

$$X_{COV} = X^T X$$

Covariance matrix



The fact that the off-diagonal > 0 , indicates that there is **collinearity**


Collinearity can be bad

```
##  
## Call:  
## lm(formula = hp ~ mpg + wt + drat + qsec, data = mtcars)  
##  
## Coefficients:  
## (Intercept)          mpg           wt          drat          qsec  
##      473.779       -2.877       26.037        4.819       -20.751
```

Assuming no collinearity, what is the interpretation of the coefficients?
With collinearity, is that interpretation possible?


$$\hat{\beta}_{ridge} = (X^T X + \lambda I)^{-1} X^T y$$

Inverted Covariance matrix, regularized:(lambda= 0)




$$\hat{\beta}_{ridge} = (X^T X + \lambda I)^{-1} X^T y$$

Inverted Covariance matrix, regularized:(lambda= 1)




$$\hat{\beta}_{ridge} = (X^T X + \lambda I)^{-1} X^T y$$

Inverted Covariance matrix, regularized:(lambda= 10)




$$\hat{\beta}_{ridge} = \left(X^T X + \lambda I \right)^{-1} X^T y$$

Inverted Covariance matrix, regularized:(lambda= 100)



$$\hat{\beta}_{ridge} = (X^T X + \lambda I)^{-1} X^T y$$

Inverted Covariance matrix, regularized:(lambda= 1000)



**So why is it called
regularisation?**

Two notes about the inverted matrix:

with increase of λ

1. Diagonal shrinks (bias is added)
2. Off-diagonal shrinks (collinearity is reduced, which improves the stability of the model)

In a stable model:

Feeding new data or adding new predictor variables will not change the parameter estimates a lot

We have succeeded in finding a λ making our model more stable (improved **in-sample** validity), but we haven't found a λ that optimises predictive power – (**out-of-sample**)

Out-of-sample as validity check



```
mtcars.1 <- mtcars[1:10, ]
```



Out-of-sample as validity check

Call:

```
lm(formula = hp ~ mpg + wt + drat + qsec, data = mtcars.1)
```

Coefficients:

(Intercept)	mpg	wt	drat	qsec
414.541	-13.638	12.753	11.263	-5.042

Call:

```
lm(formula = hp ~ mpg + wt + drat + qsec, data = mtcars)
```

Coefficients:

(Intercept)	mpg	wt	drat	qsec
473.779	-2.877	26.037	4.819	-20.751


Suddenly, someone shows up with



Let's check
our model


```
mtcars.2 <- mtcars[11:32, ]
```

Predictions based on mtcars.1



Finding optimal lambda

Ridge Regression



$$MSE = \text{mean}((y - \hat{y})^2)$$

Which dataset is the MSE calculated on?

Call:

```
lm(formula = hp ~ mpg + wt + drat + qsec + 0, data = mtcars.1)
```

Coefficients:


mpg	wt	drat	qsec
-8.379	76.588	45.705	-5.850

```
print(beta.hat.ridge <- ridge.regression(X, y, mtcars.1, min.lambda))
```

```
##           mpg      wt      drat      qsec  
## [1,] -7.421887 33.637 22.0378 4.70691
```

What has happened to the coefficients?


Predictions based on mtcars.1; $\lambda=3.53$




Prediction on mtcars.2

$$\lambda=0$$

Predictions based on mtcars.1




Predictions based on mtcars.1; lambda=3,53



“Prediction” on mtcars.1

$$\lambda = 0$$

Predictions based on mtcars.1; lambda=0



Nomenclature


- mtcars.1 -> training set
- mtcars.2 -> test set
 - NB! Normally, we prefer that our training set is bigger than our test set
- By introducing *bias* in our training set, we at the same time reduce the *variance* of our training set, increasing the reliability of our predictions on a test set

“Testing” on training set


greater bias
lesser variance

smallest bias
greater variance (of \hat{y})

Predictions based on mtcars.1; lambda=3,53



Predictions based on mtcars.1; lambda=0




Optimal λ


lesser bias
lesser variance

more bias
greater variance (of \hat{y})

Predictions based on mtcars.1; lambda=3,53



Predictions based on mtcars.1



Did you learn?

Explanation and prediction

- 1) Understanding that fitting (explaining) often leads to overfitting
- 2) Learning methods to prevent overfitting by introducing *bias*
- 3) Understanding that the error can be decomposed into *bias* and *variance*

Next time

- The Perceptron
- Adaline
- Linear regression

References

- Bolker, B.M., Brooks, M.E., Clark, C.J., Geange, S.W., Poulsen, J.R., Stevens, M.H.H., White, J.-S.S., 2009. Generalized linear mixed models: a practical guide for ecology and evolution. *Trends in Ecology & Evolution* 24, 127–135.
<https://doi.org/10.1016/j.tree.2008.10.008>
- Gelman, A., Hill, J., 2006. *Data Analysis Using Regression and Multilevel/Hierarchical Models*. Cambridge University Press.
- Hari, R., Puce, A., 2017. *MEG-EEG Primer*. Oxford University Press, New York, NY, US.
- Yarkoni, T., Westfall, J., 2017. Choosing Prediction Over Explanation in Psychology: Lessons From Machine Learning. *Perspect Psychol Sci* 12, 1100–1122. <https://doi.org/10.1177/1745691617693393>