Deutsche Power

ELEKTRA ONE

ONLINE UPS

M000VA~6000VA

Mission Critical
Online UPS

TECHNICAL SPECIFICATION

Elektra One 1KVA, 2KVA, 3KVA & 6KVA - 24/36/48V UPS

- True double-conversion
- Pure Sine-wave output
- Output Power Factor 0.9
- Configurable charging current via LCD setting
- Compatible with Generator
- Cold Start capability
- Overload and short circuit protection
- Very powerful AC charger at 60A
- Optional parallel operation up to 9 units for Single Phase and Three Phase application
- Common 48Vdc battery pack for the parallel system
- Full Bridge inverter design to support half-wave load and unbalanced load



Model		ONE-ES101	ONE-ES102	ONE-ES103	ONE-ES106
CAPACITY		900W	1800W	2400W	5400W
INPUT					
Voltage		220/230/240 VAC			
Voltage Range		110-280 VAC @ 50% load ; 176-280 VAC @ 100% load			
Frequency Range		46~54 Hz or 56~64 Hz			
Power Factor		≧ 0.98 @ Nominal Voltage (100% Load)			
THDi		≦ 8%			
OUTPUT					
Output Voltage		220/230/240 VAC			
AC Voltage Regulation (Batt. Mode)		± 1%			
Frequency Range (Synchronized Range)		46~54 Hz or 56~64 Hz			
Frequency Range (Batt. Mode)		50 Hz ± 0.1 Hz or 60Hz ± 0.1 Hz			
Current Crest Ratio		3:1			
Harmonic Distortion		≦ 3% THD (Linear Load), ≦ 5 % THD (Non-linear Load)			
Transfer Time	AC Mode to Batt. Mode	Zero			
	Inverter to Bypass	4 ms (Typical)			
Waveform		Pure Sinewave			
EFFICIENCY					
Line Mode		93.0%			
ECO Mode		99.5%			
Battery Mode		91.0%			
BATTERY					
Battery Voltage		24/36VDC	48VDC		
Floating Charge Voltage		24.3~40.95VDC	54.6 VDC		
Overcharge Protection		32~48 VDC	66 VDC		
Charging Current (max.)		10A		60A	
INDICATORS					
LCD Panel		Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicator Via LCD			
PHYSICAL					
Dimension, D x W x H(mm)		440 x 325x 86.5	465 x 190 x 318 440 x 621.5 x 86.5 (2U) 1140 x 621.5 x 175 (4U)		
Net Weight (kgs)		15.5 ~ 20			
Communication Interface		USB, RS232,SNMP, Dry Contact Card (Alarm Generation) optional			
OPERATING ENVIRONMENT					
Humidity		0 to 95% Relative Humidity(Non-condensing)			
Operating Temperature		0°C to 50°C			
Storage Temperature		-15°C to 60°C			

Product specifications are subject to change without further notice

DP ELECTRONICS (DEUTSCHE POWER CO., LIMITED)

Germany Head Office

DP electronics (Deutsche Power Co., Limited) Klon, Germany.
Phone: +49-221-26016266
Fax: +49-221-26016267
Email: enquiries@deutschepower.de

Hong Kong Office

RM 1701(057), 17/F, HeNan Building No90, Wan Chai, Hong Kong.
Phone: +86-755-82610239
Fax: +86-755-82610233
helenlong@deutschepower.de