SOLO SINE

SOLO SINEWAVE HYBRID INVERTER
WITH BUILT-IN AVR
1KVA/2KVA

Solar MPPT Inverter
Home & Small Office Loads

SOLO SINE WITH SOLAR MPPT

SOLO SINE Series with Solar MPPT

Smart House With SOLO SINE With Solar MPPT & Built-In AVR

Deutsche Power SOLO SINE Series is a solar hybrid Inverter system with built-in AVR for home and office appliances. With Pure SInewave its selectable wide and narrow input voltage switch features flexibility for users. It is perfect to connect either domestic and office appliances or computer-related devices. Its a green substitution for generator without air pollution.



Features

- Pure Sine Wave Inverter
- 4 Step AVR
- Selectable input voltage range for home appliances or personal computers
- Selectable battery types of gel. lead-acid and open lead acid (optional)
- Selectable charging current : 10A or 20A
- Auto restart while AC is recovering
- Overload and short circuit protection
- Generators & Computer-related devices compatible
- Cold start function

Applications

- Tube Light
- TV
- Computers
- Fan
- Stereo
- PABX
- Router
- Switch etc.

TECHNICAL SPECIFICATION

MODEL	SOLO 1000	SOLO 1500	SOLO 2000
RANGE	1000VA	1500VA	2000VA
INPUT			
Phase	Single Phase In & Single Phase Out		
Voltage	220V/230/240±25%		
Frequency	50Hz±5%		
OUTPUT			
Wave from	Pure Sine Wave		
Voltage	220V/230V/240±10%		
Frequency	50Hz±1% (Battery Mode)		
Transfer Time	<10msec		
Sockets	Universal		
BATTERY			
Voltage	12VDC		24VDC
Charging Current	10A or 20A		
Communication	SNMP (Optional)		

Solar MPPT Specification

SOLAR MPPT CHARGER	12V	24V
MIN. OPEN CIRCUIT VOLTAGE	30V	60A
MAX. OPEN CIRCUIT VOLTAGE	110V	110V
MAX. INPUT CURRENT	17A	34A
MAX. PV POWER	1400V	2800V
LOW BATTERY CUTOFF VOLTAGE	<10.0V	<20.0V
DC LOAD OUTPUT	OFF	
MAX. OUTPUT CURRENT	70A	
EFFICIENCY	0.8& - 0.9%	
MANUAL SETTING	12V / 24V	
MAX. OPERATING TEMP.	80℃	
DC LOAD CUTOFF ON LOW BATTERY	CUTOFF ON LOW BATTERY	

DP Electronics (Deutsche Power Co., Limited)