Deutsche Power

XL SINE SERIES

LINE INTERACTIVE PURE SINE WAVE UPS

1000VA ~ 3000VA (1/1)

SOHO &
I.T Grade UPS

LINE INTERACTIVE UPS

DP Electronics (Deutsche Power Co., Limited)

XL-Sine Series (1000VA~3000VA)

XL Sine Series is an improved Line-Interactive UPS with Pure Sine Wave out put.

A mini-tower UPS with line interactive topology XL Sine is a microprocessor Control Series with most advance technology short back up built-In battery with high durability and advanced features . Ideal for servers, storage, network closets, business VoIP & desktops, retail POS, An advanced multifunction control panel with a color LCD clearly communicates UPS status

LCD

XL- Sine Series has LCD in its front panel for easily LCD displays input /output voltages, faults and many others features can be viewed.

Salient Features are as follows

- Automatic Voltage Regulation helps correct utility voltage
- Graceful shutdown using serial or USB
- Surge Protection
- Excellent microprocessor control guarantees high reliability.

Internal self-diagnostic technology

- Data Line Protection :Prevents power surges that travel through coaxial and Ethernet lines from causing damage to electronics.
- Ultra Quiet Design Minimizes noise during operation for a quieter work environment.



Application

- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Cold start function
- Off-mode charging
- Fast intelligent battery recharge function
- Generator compatible
- Optional USB/RS232 communication port and RJ45 protection





LINE INTERACTIVE UPS

TECHNICAL SPECIFICATION FOR XL-PLUS SERIES

MODEL				
Rating	XLS-1000	XLS-1500	XLS-2000	XLS-3000
VA	1000	1500	2000	3000
INPUT				
Phase	110/120 VAC or 220/230/240 VAC			
Voltage Range (Buck & Boost AVR)	81-145 VAC / 162-290 VAC			
Frequency Range	60/50 Hz (Auto sensing)			
OUTPUT				
Output Voltage	110/120 VAC or 220/230/240 VAC			
Power Factor	0.7 (standard), 0.8 Available on request			
AC voltage Regulation	± 10%			
Frequency Range	60 Hz or 50 Hz ± 1 Hz			
Transfer Time	Typicle 2-6 ms			
Waveform (Batt. Mode)	Pure Sinewave			
BATTERY				
Battery Type & Number	12V/7Ah-9Ahx2			12V/7Ahx4
Typical Recharge Time	4-6 hours to recover 90% capacity		4-8 hours to recover 90% capacity	
PROTECTION				
Full Protection	Surge, overload, discharge and overcharge. IP20|ROHS|REACH Contains SVHCs|Battery Disconneter			
Surge Energy Rating	156 Joules			
INDICATORS				
LED / LCD Display LCD Display (optional)	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage Overload, Fault, and Low Battery			
PHYSICAL				
Dimension	353x149x162	380 x 158 x 198		440x600x86
Net Weight (kgs)	8.6	12.3		15.5
Thermal (Input/Output)	Power Cord / IEC 320 C14 Universal receptacle			
Safety	IEC/EN62040-1;IEC/EN60950-1			
EMC	IEC/EN62040-2;IEC61000-4-2;IEC61000-4-3;IEC61000-4-4;IEC61000-4-5;IEC61000-4-6;IEC61000-4-8			
ENVIRONMENT				
Humidity	0-90% RH @ 0-40 C (Non-condensing)			
Noise Level	Less then 40db			
MANAGEMENT				
Communication	USB/RS-232 Port (optional)			

DP Electronics (Deutsche Power Co. Limited) has a policy of continuous product development and improvement and therefore reserve the right to vary any information without prior notes.

DP Electronics (Deutsche Power Co., Limited)

DP ELECTRONICS (DEUTSCHE POWER CO., LIMITED)

Germany Head Office

DP electronics (Deutsche Power Co., Limited) Klon, Germany.
Phone: +49-221-26016266
Fax: +49-221-26016267
Email: enquiries@deutschepower.de

Hong Kong Office

RM 1701(057), 17/F, HeNan Building No90, Wan Chai, Hong Kong.
Phone: +86-755-82610239
Fax: +86-755-82610233
helenlong@deutschepower.de